

NCKU Programming Contest Training Course

2013/05/18

Pinchieh Huang (free999)

Pinchieh.huang@gmail.com

<http://myweb.ncku.edu.tw/~p76014143/20130508.rar>

Department of Computer Science and Information Engineering
National Cheng Kung University
Tainan, Taiwan



Outline

Chinese Postman Problem





Difference Constraint



Chinese Postman Problem

- Problem Definition
 - Given a (weighted) graph $G(V, E)$. Start from a given vertex, finding the shortest route that cover each **at least once** and back to the origin vertex.




Chinese Postman Problem

- Euler Path (Circuit)
 - **Eulerian trail** (or **Eulerian path**) is a trail in a graph which visits every edge exactly once. Similarly, an **Eulerian circuit** or **Eulerian cycle** is an Eulerian trail which starts and ends on the same vertex.



Chinese Postman Problem


- How to determine whether a Euler Path (Circuit) can be found?




Seven Bridges of Königsberg

Chinese Postman Problem


- Lemma
 - A Euler Path can be found in a graph if the number of vertexes with odd degree are **less or equal than two**. A Euler Circuit can be found in a graph if the number of vertexes with odd degree is **equal to 0**.



number of V_{odd}
=



number of V_{odd}
=



number of V_{odd}
=




Chinese Postman Problem


- Lets return the original problem..
 - (1) If we can found an **Euler circuit** in the given graph, the answer is obvious the summation of all edges' weight.
 - (2) If we can't.... ??




Chinese Postman Problem




Chinese Postman Problem




Chinese Postman Problem




Chinese Postman Problem



Chinese Postman Problem




Chinese Postman Problem




made by free999



Chinese Postman Problem




Chinese Postman Problem




made by free999




Chinese Postman Problem




Chinese Postman Problem




Chinese Postman Problem




Chinese Postman Problem



Chinese Postman Problem



Chinese Postman Problem




match

$dp[bit]$ = 走過 bit 上的點的最短距離

求 $dp[(1 \ll N) - 1]$

枚舉任兩個拜訪過的點



made by free999



Example

- UVa 10296



Outline

Chinese Postman Problem



Difference Constraint



Difference Constraint

Given :

$$X1 - X2 \leq 0$$

$$X1 - X5 \leq -1$$

$$X2 - X5 \leq 1$$

$$X3 - X1 \leq 5$$

$$X4 - X1 \leq 4$$

$$X4 - X3 \leq -1$$

$$X5 - X3 \leq -3$$


$$X5 - X4 \leq -3$$

Find :

A feasible solution of $X1, X2, \dots, X5$



Difference Constraint



example

Uva 515



K-shortest Path



Homework

Uva

515,

POJ

1201, 2983, 1364, 1275

