
Quiz 6

Deadline	Friday, 24 July 2020 at 11:59PM
Latest Submission	Friday, 24 July 2020 at 3:41PM
Raw Mark	4.00/4.00 (100.00%)
Late Penalty	N/A
Final Mark	4.00/4.00 (100.00%)


Question 1 (1 mark)

Consider the following heap and its array representation



[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]	[8]
not used	8	7	6	4	5	2	,	,

If the value 9 is inserted into this heap, what does the updated array look like?



✓ Your response was correct.

Mark: 1.00


Easy to work out if you insert 9 into the tree and then shift it up (fixUp()).


Question 2 (1 mark)


What is the trie resulting from inserting the following keys into an initially empty trie, in the order given?

ants pants panda dog an pan don

Finishing nodes are shown in the tree in **red**.







(e) None of the above

✓ Your response was correct.

Mark: 1.00

Question 3 (1 mark)

If we have an initially empty linear-probed hash table with 7 slots, and a with a hash function


int hash(int n) { return (n % 7); }


what is the final state of the table after the following values:

10 5 7 3 14 12

are inserted in the order given?

Empty entries in the hash table are indicated by a value of '-'.





✓ Your response was correct.

Mark: 1.00

Question 4 (1 mark)

What has value is returned by the following hash function

```
int hash(char *key, int N) {
   int i; char *c;
   unsigned int h = 127;
   for (i = 0, c = key; *c != '\0'; i++, c++)
      h *= (*c + i);
   return h % N;
}
```

if it is invoked as

```
hash("2521", 42)
```

Assume that unsigned int values are 32-bits long.

(a)	0	
(b)	1	

(c)	14
(d)	24
(e)	None of the above is correct

✓ Your response was correct.

Mark: 1.00