

# TWISTER USER GUIDE



---

Subject: [Twister User Guide](#)  
Issue: 0.1

date: August 30, 2013  
Author: Andrei Toma  
[atoma@luxoft.com](mailto:atoma@luxoft.com)

# TWISTER USER GUIDE

## Change History

Issue	Date		Modified by
0.1	05 September 2013	1 <sup>st</sup> draft document	Andrei Toma, Cristian Constantin,

# TWISTER USER GUIDE

## TABLE OF CONTENTS

### Contents

Change History .....	2
1 Introduction .....	4
2 Definitions, acronyms and abbreviations .....	4
3 What is Twister ?.....	5
3.1 High Level Description.....	7
4 How to install the framework .....	8
4.1 Dependencies list.....	10
5 Twister services.....	12
5.1 Central engine web interface .....	13
6 How to compile the Java GUI .....	16
7 Overview of the Java GUI .....	17
8 How to define the suites and add the tests .....	24
9 How to run the test files .....	27
10 Command line interface .....	28
11 Twister configuration .....	36
11.1 Twister configuration files .....	36
11.2 Configure the paths .....	38
11.3 Configure the e-mail .....	39
11.4 Configure the database .....	41
11.5 Configure the devices(testbed) .....	49
11.6 Configure the SUTs.....	51
11.7 Configure the global parameters .....	53
11.8 Configure 'panic detect' .....	54
11.9 Services and Plugins .....	55
11.10 Changing users.....	57
11.11 Set-up and Tear-down controls.....	58
11.12 Connection management (SSH implementation) .....	59
11.13 Test case/Suites management .....	61
11.14 User levels .....	62
11.15 Configuration management .....	67
11.16 Email notification .....	67
11.17 Test case details descriptors.....	67
11.18 Library management.....	68
11.19 Log customization.....	68
11.20 EP start-up.....	69
12 How to write tests .....	70
13 Performance and troubleshooting .....	71

# TWISTER USER GUIDE

## 1 Introduction

A test automation framework is a set of assumptions, concepts and tools that provide support for automated software testing.

Twister is a test automation framework that helps user in building functional, regression and load test suites.

## 2 Definitions, acronyms and abbreviations

**APPLET** - the GUI of the Twister Framework. It's written in Java and can be accessed in the browser. Its role is to create projects (group suites and files), edit tests, run and stop the test-cases execution, view logs and configure the framework (paths, e-mail, database, test-bed, global parameters, plug-ins).

**CE**- Central Engine. It's a collection of services that form the Twister server. A lot of functions are exposed via XML-RPC. Its role is to send files and libraries to User EEs, collect statistics and logs from each file executed, send e-mail and save to database after each Project execution and run plug-ins

**CLI** – command line interface

**CLIENT MACHINE** – this is the machine where the execution engines are installed

**EE/EP** - Execution Engine. It's a script that waits the Start signal from CE and sends the logs to CE. When the Start is detected, the EE launches the Runner. If the Stop signal is detected, the EE instantly kills the Runner. EE is basically a simple service, designed to start and stop the Runner. One EE belongs to one User and has a unique name for that particular user. One EE cannot be shared between more users;

**PROJECT FILE** - XML file that contains a set of test files, grouped inside suites. One Project can run on multiple test-beds, that have defined a number of EEs;

**RA** - Resource Allocator is a service included in CE. All functions are exposed via XML-RPC. Its role is to manage nodes that represent test-beds and real devices;

**REPORTING** - the Reporting Server, is used to view the results of the test executions. The reports can be fully customized;

**WEB INTERFACE** - the Central Engine web interface, is used mostly for debugging. Its role is to view statistics, logs and the connected users. A user can also start and stop the

# TWISTER USER GUIDE

EEs. For more complex operations, the user must use the *applet*,

**RUNNER** - Test-case Runner has the following roles:

- connects to CE to receive the libraries that must be executed in this project;
- reads the START/ STOP/ PAUSE/ RESUME status and if it's PAUSE, it waits for RESUME;
- checks for current file dependencies, if there are any, it waits for the dependency to be executed;
- skips the files that have status Skip;
- downloads the files that are not Runnable, without executing them;
- downloads and executes the files that must be executed;
- the files that must be executed can be in many formats, ex: Python, TCL, Perl and Java; the Runner detects them by extension and starts the appropriate ScriptRunner;

**SERVER MACHINE** – this is the machine where the central engine is installed

**TWISTER\_SERVER\_PATH** - when running the installer, the user can choose the path to the servers. This path can be anywhere on a Linux server machine. By default, the path is ``/opt/twister``.

**TWISTER\_CLIENT\_PATH** - when running the installer, the client path is always the **\$HOME\_PATH** of the user running the installer + ``/twister/``. This cannot be changed.

**USER** - one client that uses Twister. Each user can define a number of EEs, which are used to run test-cases, simultaneously. The test-cases are grouped into suites and can be saved for later use, into Projects;

**USER MACHINE** – this is the machine where the user uses a browser to access the framework GUI

## 3 What is Twister ?

Twister is an open source test automation framework.

The code can be downloaded from: <https://github.com/Luxoft/Twister>.


Twister helps building functional, regression and load test suites.

# TWISTER USER GUIDE

Key features of Twister:

- web based GUI intuitive & user friendly interface ;
- easy to manage tests/ suites/ projects ;
- multi-user architecture, users have groups and roles ;
- real time monitoring of execution ;
- distributed execution: SUT's can be tested in parallel ;
- against same or different set of tests ;
- flexible reporting mechanism: DB schema is not fixed and there is no need to change framework to fit with a new DB schema ;
- support for different scripting languages and for record & play GUI tools ;
- support for Continuous Integration, Source Revision Control, Bug tracking ;
- support for GUI/ backend plugins: specific functionality loaded dynamically ;
- OpenFlow 1.0 and 1.3 modules available for conformance testing.

## Concept



# TWISTER USER GUIDE

## 3.1 High Level Description

Twister framework is based on a client/server architecture. In the same time, Twister has a multi-tenant architecture that allows execution of test cases for multiple users in the same time without any interference between processes. Twister has a component referred as **Central Engine** (CE) that serves and manages the test-cases and libraries for many **users**, each user having one or multiple **EEs**. The users interact with the framework through a Java applet.

Aside from the Java applet interface, the Twister framework is developed in Python programming language.

All servers run on top of CherryPy library, which means that the exposed functions can be accessed from a browser, or via XML-RPC.

**Error! Not a valid bookmark self-reference.** picture depicts the high level architecture of the framework and it's interactions with other parties.




Figure 1 High Level Architecture

# TWISTER USER GUIDE

The main components of the framework are the graphical user Interface (GUI), the central engine (CE) and the execution engines (EE).

The GUI represents the interface of the user to the framework. The user uses the interface to configure the framework, to define the details of the systems under test, to define the suite(s) of test cases that are executed against the systems under test, to run the test cases and to view the reports.

The central engine represents the core of the framework. It assures the link with the GUI, the execution engines and other parties ( e.g. database server ). It manages all the information defined in the configuration files, manages the suite of test case, delivers the right test cases to the right execution engines and save the execution results into the database. The central engine ensures the interaction with different modules integrated into framework and makes the link between different plugins and the framework.

The execution engine(s) represents the interface of system(s) under test with the framework. It executes the test cases that it receives from the central engine, collects the output from system under test to send it to the central engine and reports back to the central engine the status of every test case that is executed.

## 4 How to install the framework

In order to install the Twister Framework, a few requirements must be met:

- **A Linux machine.** All the services must run on **Linux** (tested on *Ubuntu* and *OpenSuse*);
- **Python 2.7.** Python is installed by default, on most Linux systems; the framework is written and tested in Python 2.7;
- **Python Tkinter.** **Required only if you need to run TCL tests.** This is included by default in Python, but some Linux distributions don't have the ``python-tk`` lib, so it has to be installed with: ``sudo apt-get install python-tk``;
- **TCL Expect libraries.** **Required only if you need to run TCL tests with Expect.** To test the functionality, open a Python 2.7 interpreter, then type:

```
from Tkinter import Tcl
t = Tcl()
t.eval('package require Expect')
```



# TWISTER USER GUIDE

```
# If this fails, you must install Expect from your package manager, or compile it from
sources
# The sources are at: sf.net/projects/expect; download, extract, ./configure, sudo
make install
exit()
```

- **Perl Inline Python**. This is required only if you need to run Perl scripts.

The Twister repository is located at: <https://github.com/luxoft/twister>.

The installer is located in the folder ``installer`` and it's also written in Python. **It works only in Linux.**

It has 3 options that user can select:

- install dependencies
- install Twister server ( central engine )
- install Twister client

When installing the dependencies, the script must be executed as **ROOT** or as a user with root privileges. In this stage, all the dependencies (see chapter 3 for a list) are installed on the machine. At this stage, it is **STRONGLY RECOMMENDED** to have an internet connection to allow the setup of all the dependencies; otherwise, you have to install the dependencies manually.

You might need to configure the **proxy** to access the internet. In this case, edit the file ``installer.py``, locate the line with **HTTP\_PROXY** and type: **HTTP\_PROXY =** `'http://UserName:PassWord@http-proxy:3128'`. If the username and password are not required for your proxy, you can omit them.

When installing the server, it is recommended to run as **ROOT**, but is not mandatory.

In order to serve the Java applet, you will also need **Apache** or **Lighttpd** server and **Open-SSH** server.

The recommended command for starting the installer:

```
sudo python2.7 installer.py
```

The *Twister Client* doesn't have any required dependencies. ``Scapy`` is optional, used only if you need to run the packet sniffer. **Some tests and libraries will require additional dependencies!**

# TWISTER USER GUIDE

For example: ``paramiko``, ``pExpect``, ``RpcLib``, ``Suds``, ``Requests``, or ``Gevent``. If you need to run these tests or libraries, you can install ``pip`` (tool for installing and managing Python packages - [www.pip-installer.org](http://www.pip-installer.org)) and use ``sudo pip install <package>``.

The installer will guide you through all the steps:

1. Select what you wish to install (*dependencies*, *client*, or *server*);
2. If the ``twister`` folder is already present, you are asked to back up your data in order to continue, because everything is DELETED, except for the ``config`` folder. The backup has to be done manually.

Twister Client will be installed in the home of your user, in the folder ``twister``; this folder cannot be changed. The server will be installed by default in ``/opt/twister``, but it can be changed.

**NOTE: The Twister framework cannot be installed on Windows OS because of Python dependencies. However, some specialized EP's can be used on Windows OS for specific test cases type (e.g. Selenium, Sikuli and Test Complete).**

## 4.1 Dependencies list

The dependencies will be installed automatically when you first install Twister. If an internet connection is not available, the installer will use the packages from ``installer/packages`` folder.

- **LXML**: ([www.lxml.de/](http://www.lxml.de/))

- XML and HTML documents parser;
- LXML is included in Ubuntu by default. The other Linux distributions must install it;

- **MySQL-python**: ([mysql-python.sourceforge.net/](http://mysql-python.sourceforge.net/))

- Connects to MySQL databases. It is only used by the Central Engine;
- MySQL-python requires the *python2.7-dev* headers in order to compile;

- **CherryPy**: ([www.cherrypy.org/](http://www.cherrypy.org/))

- High performance, minimalist Python web framework;
- CherryPy is used to serve the Central Engine, Resource Allocator and Reports;

- **Mako**: ([www.makotemplates.org/](http://www.makotemplates.org/))

- Hyperfast and lightweight templating for the Python platform;
- Mako is used for templating the Central Engine REST and Report pages;

# TWISTER USER GUIDE

- **PyCrypto**: ([dlitz.net/software/pycrypto/](http://dlitz.net/software/pycrypto/))
  - The Python Cryptography Toolkit;
  - PyCrypto is used to encrypt and decrypt sensitive data, for example user passwords;
- **Paramiko**: ([github.com/paramiko/paramiko/](https://github.com/paramiko/paramiko/))
  - Native Python SSHv2 protocol library;
  - Paramiko is used by the Central Engine to check the user and by the Twister SSH Lib to connect to remote machines;

## ~ Optional ~

- **Scapy**: ([pypi.python.org/pypi/scapy-real/](http://pypi.python.org/pypi/scapy-real/))
  - Interactive packet manipulation tool;
  - **Scapy**, is used by the Execution Process to capture packets and send them to the applet;
- **pExpect**: ([sourceforge.net/projects/pexpect/](http://sourceforge.net/projects/pexpect/))
  - Spawn child applications, control them, respond to expected patterns in their output;
  - **pExpect** is *optional*; it is used by some Python test cases to connect to FTP/Telnet;
- **RpcLib**: (<https://github.com/arskom/rpclib/>)
  - Create web services in Python (soap, rpc, rest servers);
  - **RpcLib** is *optional*; it is used by some Python test cases;
- **Suds**: (<https://fedorahosted.org/suds/>)
  - Lightweight SOAP python client for consuming Web Services;
  - **Suds** is *optional*; it is used by some Python test cases;
- **Requests**: (<http://docs.python-requests.org/>)
  - Elegant and simple HTTP library for Python, built for human beings;
  - **Requests** is *optional*; it is used by some Python test cases to connect to HTTP servers;
- **Gevent**: (<http://www.gevent.org/>)
  - Co-routine-based Python networking library that provides a high-level synchronous API;
  - **Gevent** is *optional*; it is used by some Python test cases to create sockets and threads;

# TWISTER USER GUIDE

## 5 Twister services

Twister framework has 2 services:

1. The **Central Engine** = central server for script and library files. It includes the Resource Allocator, Service Manager and Reporting Server. This can be run as a normal user, but the recommendation is to be run as **ROOT** in order to have read/ write access to all files.
2. The **Execution Process Manager** = client service that manages the EPs that have to be started for execution of test cases. This can be run as normal user, but for some functionality (packet sniffer) it has to be run as **ROOT**.

The executable script for central engine is located in `/opt/twister/bin/start_server`. The script doesn't require an input parameter, it has to be executed as is and it will launch the server in the background.

The executable script for execution process(s) manager is located in ``${USER_HOME}/twister/bin/start_client``.

If your default Python executable is NOT Python2.7, you must edit the `start_server` and `start_client` files manually, locate the line: `PYTHON_PATH=/usr/bin/python` and replace the value with the path to Python2.7, for example `/usr/local/bin/python2.7`.

This script can take the following parameters:

- start – to start the service;
- start silent – start the service and no messages are printed
- stop – to stop the service
- restart – to restart the service
- status – to display the status of the service and what EPs are running

The execution process manager service must be configured before run. You have to edit the file `epname.ini` from `twister/config/` folder; it contains the **name** of the available EPs, the **IP** and the **port** of the CE instance that it will run on. For every EP, there is an optional tag `EP_HOST` that can be set by the user to restrict the machine where that EP can be started. By default, if this tag is not set, the EP can be started. Otherwise, the comparison between the `EP_HOST` and the local machine is done and if there is a match, the EP is allowed to be started.

When the `start_client` script with `start` option is executed, a client service is started. This service is used to manage the start and stop of available execution processes on demand. The list of available EPs is obtained from the `epname.ini` file.

# TWISTER USER GUIDE

The `start_client` script reads this file and registers all the available EPs to the central engine so the user is able to select EPs from GUI when execution is needed. When testing is started, the CE send the list of selected EPs to the EP manager and this one starts on demand all the EPs requested by the user. When execution of the test cases is completed, the EPs are stopped automatically by the EP manager.

The `start` option can be used in conjunction with `silent` to stop printing messages in terminal.

To stop the EP manager, the `stop` option must be used.

To restart the EP manager, the `restart` option must be used. Restart of the EP manager must occur when the list of available EPs is changed in the `epname.ini` file.

The status of the client and the list of started EPs is obtained using `status` option. The started EPs are listed only when the testing is in progress.



If needed, the EP manager can be started automatically at system boot, by adding it into the rc files. Given the EP manager is user specific, it must be added for every user that has Twister client installed and it has to be started as that user.

## 5.1 Central engine web interface

While the **Central Engine** service is running, you can access a web interface that allows viewing some statistics, logs and users connected. You can also start and stop the processes.

*Management interface Home;*

## Central Engine interface

IP and Port	127.0.0.1:8000
Machine	user-VirtualBox
System	Ubuntu 13.04 raring
Server Type	no_type
Server Version	2.024
Processor	
Memory	

*Central Engine Logs;*

## Central Engine Log

Refresh 

```

13-08-01 13:22:18  DEBUG  __init__: CE: Starting Twister Server version `2.016`...
13-08-01 13:22:18  DEBUG  __init__: CE: Running server type `no_type`.
13-08-01 13:22:18  DEBUG  __init__: CE: Initialization took 0.0000 seconds.
13-08-01 13:22:18  DEBUG  __init__: SM: Starting Service Manager...
13-08-01 13:22:18  DEBUG  __init__: SM: Found `5` services: `controller, controller_1, controller_2,
13-08-01 13:22:18  DEBUG  _load: RA: Resources loaded successfully.
13-08-01 13:22:18  INFO    [01/Aug/2013:13:22:18] ENGINE Listening for SIGHUP.
13-08-01 13:22:18  INFO    [01/Aug/2013:13:22:18] ENGINE Listening for SIGTERM.
13-08-01 13:22:18  INFO    [01/Aug/2013:13:22:18] ENGINE Listening for SIGUSR1.
13-08-01 13:22:18  INFO    [01/Aug/2013:13:22:18] ENGINE Bus STARTING
13-08-01 13:22:18  INFO    [01/Aug/2013:13:22:18] ENGINE Started monitor thread '_TimeoutMonitor'.
13-08-01 13:22:18  INFO    [01/Aug/2013:13:22:18] ENGINE Serving on 0.0.0.0:8000
13-08-01 13:22:18  INFO    [01/Aug/2013:13:22:18] ENGINE Bus STARTED
13-08-01 13:22:18  INFO    [01/Aug/2013:13:22:18] ENGINE Started monitor thread 'Session cleanup'.
13-08-01 13:22:18  DEBUG  createUser: Project: Created user `nisuser` ...

```

# TWISTER USER GUIDE

User interface;

## User `user`

Status	stopped ( ▶ start   ■ stop   ⚠ reset! )
Master config	/home/user/twister/config/fwmconfig.xml
Project config	/home/user/twister/config/testsuites.xml
DB config path	/home/user/twister/config/db.xml
E-mail config path	/home/user/twister/config/email.xml
EPs file	/home/user/twister/config/epname.ini
Logs path	/home/user/twister/logs
Tests path	/home/user/twister/demo
User groups	user, admin
User roles	CHANGE_DB_CFG, CHANGE_EML_CFG, CHANGE_FWM_CFG, CHANGE_GLOBALS, CHANGE_PLUGINS, CHANGE_PROJECT, CHANGE_SERVICES, CHANGE_TESTBED, CREATE_PROJECT, DELETE_PROJECT, EDIT_TC, RUN_TESTS

Control the processes;

Home Processes Logs

## Processes for `tscquest`

EP-1001

EP-1002

EP-1003

EP-1004

EP-1005

Actions: ▶ | || ■ | ✎

Suite1

- /home/tscquest/twister/demo/testsuite-python/init.py
- /home/tscquest/twister/demo/testsuite-python/test002.py
- /home/tscquest/twister/demo/testsuite-python/test001.py
- /home/tscquest/twister/demo/testsuite-python/test003.py

# TWISTER USER GUIDE

Check all user logs;



The screenshot displays a web interface titled "Logs for `tscquest`". On the left, there is a sidebar with a list of log categories: logCli EP-1001, logCli EP-1002, logDebug, logRunning, logSummary, and logTest. The main content area shows the log for logCli EP-1001. The log text includes: "Py debug: For EP EP-1001, CE Server returned a new status: running.", "EP debug: Received start signal from CE!", "TC debug: TestCaseRunner started with User: tscquest ; EP: EP-1001.", "TC debug: Connected to proxy, running tests!", "Downloading library `/home/tscquest/twister/.twister\_cache/EP-1001/ce\_libs/ExposedLibraries.py` ...", "Downloading library `/home/tscquest/twister/.twister\_cache/EP-1001/ce\_libs/TscFtp.py` ...", "Downloading library `/home/tscquest/twister/.twister\_cache/EP-1001/ce\_libs/TscTelnnet.py` ...", "====", "Starting suite `100:Suite1`", "====", "Downloading library `/home/tscquest/twister/.twister\_cache/EP-1001/ce\_libs/TscFtp.py` ...", and "Downloading library `/home/tscquest/twister/.twister\_cache/EP-1001/ce\_libs/TscTelnnet.py` ...".

This web service can be accessed in a browser, by going to: [`http://central-engine-IP:PORT/`](http://central-engine-IP:PORT/),

for **example**: [`http://localhost:8000/`](http://localhost:8000/).

## 6 How to compile the Java GUI

The Java Graphical User interface compiled version can be found at ``twister/binaries/applet``. You have to copy the ``applet`` folder in ``/var/www`` and if you have an *Apache* or *Lighttpd* Server, you will be able to access it in the browser.

If you have changed the sources, or you want to compile the JAR files yourself, the sources are located at ``twister/client/userinterface/java``. Some binary JAR files are already included in folders ``target`` and ``extlibs``, respectively.

After compilation, you have to move the JAR files, so that a server can serve them.

Steps 1-2 require **Oracle JDK 1.7** (*Oracle Java Development Kit*).

Step 5 requires **Apache** or **Lighttpd** Server and your machine must have **OpenSSH Server** enabled on port 22.



# TWISTER USER GUIDE

Here are the steps:

1. Generate a key store, or import a certificate (*this is done only **the first time!***);

```
PATH_TO_JDK/bin/keytool -genkey -keyalg rsa -validity 360000 -alias Twister -  
keypass password -storepass password
```

OR

```
PATH_TO_JDK/bin/keytool -import -alias Twister -file certificate_file.cer
```

2. Go in ``client/userinterface/java``. Then, if you are on **Windows**, run ``pack.bat``, on **Linux** run ``./build.sh``. You might need to edit these files, to change the path to **JDK\_PATH**;
3. Move all files from ``target`` and ``extlibs`` in ``/var/www/twister`` (path for Apache, or other web servers);
4. Copy ``jquery.min.js`` from ``/opt/twister/server/static/js`` also in ``/var/www/twister``;
5. Open a browser that supports Java Applets and go to: ``http://localhost/twister``.


## 7 Overview of the Java GUI

The **first tab (Suites)** is split in four panes:

- **Top left**, is where the test suites are defined. Any file from the right can be dragged in here. The files can be checked/ unchecked; the files that are not checked will not run;
- **Top right**, is where the test files are located. These files can be used in the suites;
- **Bottom left**, is where the project, suite and test information is added. The suite information is defined in the file ``DB.xml``, section name ``field_section`` (*more about this in the configuration section*);
- **Bottom right**, you can see the title and description of the currently selected test file.


# TWISTER USER GUIDE

*A configuration, with Python scripts:*



# TWISTER USER GUIDE

*A different configuration, with TCL scripts:*




# TWISTER USER GUIDE

## While running:

- You can check test lists with their statuses. By default, all tests are in pending, unless they recently ran, in which case the most recent status is displayed;
- Logs for the tests. The logs can be cleaned, exported, or searched for keywords.

*Here the Central engine is stopped; in this case you can see the most recent statuses:*




At the top, there are two buttons, which control the Central Engine: **Run/ Pause** and **Stop**.

Also at the top, is the status of the Central Engine, the time of the last start, time elapsed and the user that started it.

*While the Central engine is running:*

# TWISTER USER GUIDE




# TWISTER USER GUIDE


## The Reports Tab

When clicking on it, the reports page will open in a new tab.

*Reporting home* (this will look different, depending on the configuration!)



*A report with user chosen fields;*



*The same report, after the user chose the build;*

# TWISTER USER GUIDE

[Home](#)

**Details (build)**

[Details \(suite\)](#)

[History](#)

[Summary](#)

[Pass Rate](#)

[goto Yahoo](#)

[goto Google](#)

[Help](#)

## Details (build) Report

for Build="V06\_05.190"

10 records per page

Search:

no_regression	suite_name	test_name	status	date	build	run_no	logfilename
45999	RETRIEVE	RETRIEVE_001	PASS	2008-10-18 12:43:44	V06_05.190	1	V06_05.190_2007_10_18_12_36
46000	BO	T-001	PASS	2008-10-18 12:59:54	V06_05.190	1	V06_05.190_2007_10_18_12_36
46001	BO	T-002	PASS	2008-10-18 13:01:10	V06_05.190	1	V06_05.190_2007_10_18_12_36
46002	BO	T-003	PASS	2008-10-18 13:02:24	V06_05.190	1	V06_05.190_2007_10_18_12_36
46003	BO	T-007	PASS	2008-10-18 13:02:56	V06_05.190	1	V06_05.190_2007_10_18_12_36
46004	BO	T-008	PASS	2008-10-18 13:03:28	V06_05.190	1	V06_05.190_2007_10_18_12_36
46005	BO	T-009	PASS	2008-10-18 13:04:02	V06_05.190	1	V06_05.190_2007_10_18_12_36
46006	BO	T-012	PASS	2008-10-18 13:05:13	V06_05.190	1	V06_05.190_2007_10_18_12_36
46007	BO	T-013	PASS	2008-10-18 13:06:27	V06_05.190	1	V06_05.190_2007_10_18_12_36
46008	BO	T-014	PASS	2008-10-18 13:07:43	V06_05.190	1	V06_05.190_2007_10_18_12_36
no_regression	suite_name	test_name	status	date	build	run_no	logfilename

Showing 1 to 10 of 739 entries

← Previous 1 2 3 4 5 Next →

# TWISTER USER GUIDE

## The **configuration tab**

Here, you can configure:

- Central Engine port (*default 8000*). This is the port the applet will use for connection;
- the path of the test files, logs files, project files
- the path of the database xml, e-mail xml, EP names;
- additional path for python library files, and the path for predefined suite files
- the names of the log files;
- e-mail configuration, database configuration;
- devices configuration for Test Bed;
- global variables, injected in all Twister test files;
- services configuration
- panic-detect: checks errors in CLI logs.

More about this in **`Configure the framework`** section.

## 8 How to define the suites and add the tests

When starting the interface, you must first *select* or *create* a **project file**. This file will save your suites, script files and suites configurations.

Each project has a set of global settings:

Global options

☐ Stop on fail   ☐ DB autosave   TC delay    Libraries

Pre execution script:  ...   ☒ Stop on fail

Post execution script:  ...


- **Stop on fail** = if a test that is mandatory will fail, or will crash, all the project will fail ;
- **DB Autosave** = after all the tests from all suites finish execution, the Central Engine will automatically save the results into database, without asking the user ;
- **TC Delay** = after each test, the EP will wait X seconds, before starting to execute the next test ;
- **Pre execution script** = this defines a script that can be executed in command line interface; the script from this path will be executed by the Central Engine **before** running any test. The script can be written in any language (Perl, TCL, binary executable, etc.). You cannot use a normal Twister test as a Pre/ Post exec script! If you write a script in an interpreted language, don't forget to add




# TWISTER USER GUIDE

`#!/usr/bin/env ... *your language*` on the first line. If the file is not executable, CE will automatically run `chmod +x` on the file ;

- **Post execution script** = this defines a script that can be executed in command line interface; the script from this path will be executed by the Central Engine **after** running all tests. It has the same specifications as the Pre execution script ;




After setting the project file, click on **Add Suite** (Add suite). The required fields are: **the name** of the suite and **one or Test beds** (the workstation(s) where the tests from this suite will run).



In order to save the **project file**, use the *File menu* :

You can download the project file locally, to share it with your team members.

A suite is basically a folder, where one or more script/ test files can be added, that will be executed by one or more Test Beds, and implicitly by one or more Execution Processes.

A dialog box titled "Suite options". It contains a "Suite name:" field with "Suite-1" entered. Below it is a "Run on TB:" section with a list box containing "tb3", "tb2", and "tb1", where "tb1" is selected. At the bottom left, there is a "Panic Detect" checkbox (unchecked) and a "Libraries" button. At the bottom right, there is a "Run Number:" field with "4" entered.

## TWISTER USER GUIDE

Each suite can also have some properties attached to it, like ``release``, ``build``, ``comments``, etc. These fields are defined in ``DB.xml`` file (*more about this in the database configuration section*) and will look different, depending on the configuration (text box, drop down list, path to a script, etc.) ; these ``meta`` properties are used while saving the results into database.

A suite can be exported for later usage by right clicking it and selecting *Export*:




The content of the suite, including the test cases and its sub suites, is saved in an xml file in the *Predefined Suites* path. These exported suites can be loaded in other project using drag & drop from the *Predefined Suites* tab into the suite definition window.

The script/ test files and the suites can be re-arranged anytime, using drag & drop, or can be deleted.

# TWISTER USER GUIDE

Each script/ test file has a few properties too:



- A test that is not *Runnable* will be sent to **EP**, but will never execute. You can use this option to transfer configuration files on the EP, without executing them ;
- *Optional* tests that fail, will not stop the execution when the global *Stop on Fail* checkbox is active ;
- *Setup* tests are executed at all times (they have to be runnable) and if they *fail*, the entire Suite is considered *Failed*. Setup files are NOT saved into the database!
- *Teardown* tests are executed at all times (they have to be runnable). They are used to clean-up a suite, even if the suite was aborted because of a failed Setup. Teardown files are NOT saved into the database!

The user can define a list of parameters and properties for every test case. Both the parameters and the properties are sent to the tests and can be accessed during execution.

The properties: ``type``, ``suite``, ``file``, ``config_files``, ``dependency``, ``status``, ``Runnable``, ``Optional``, ``setup_file``, ``teardown_file`` and ``param`` are reserved for internal use and must NOT be used; more about this in **'How to write Twister tests'** section.

## 9 How to run the test files


After all the suites and scripts are set, click on , to start the execution.

What will happen is that, all **checked** scripts from all suites will run, in order. The execution doesn't stop if one of the scripts fails, excepting the case when the test that fails is *mandatory* and the *Stop on Fail* checkbox is checked.

# TWISTER USER GUIDE

If the **Run** button is disabled, it means that the Central Engine service is not running, so the execution cannot start.









If the **Run** button is enabled, you can start the execution. When you start the execution, the **Stop** button will activate, to allow stopping the Central Engine and killing all the running processes and the **Run** button will become **Pause**, allowing to pause after the current tests finishes its execution.

If the Central Engine was started recently, by default all the files will be in  state *pending*.

If a previous run was completed, the most recent status is displayed (*pass, failed, etc.*).

If the execution is stopped prematurely, all files that did not execute (were pending), have status NOT EXECUTED.

The states for the files and their respective icons are:

-  (running) while the file is running;
-  (pause) if the test is paused;
-  (success) if the execution was successful;
-  (failure) if the execution failed;
-  (skip) if the file was marked as skip (*runnable=false*);
-  (abort) if the file was stopped while running;
-  (not executed) if the file was paused and was stopped instead of being resumed;
-  (dependency) is the file depends on another file and the dependency didn't finish its execution, so this file is waiting.

While the tests are running, the logs from the left will update, showing the live output.

When a test is completed, the icon will change to Pass or Fail. All the history of result can be seen in the ``log_summary.log``.

The logs can be cleaned, exported, or searched for keywords, by clicking the buttons from the bottom.

After all the tests are run, if the e-mail is configured, CE sends an e-mail with the report and then, all tests are saved into the database, excepting the *Setup* and *Teardown* files.

## 10 Command line interface

The Command-line script can be found in `twister/bin`, both on server and client side.

This script can be used to:

# TWISTER USER GUIDE

- start, stop, pause the execution;
- show all users that are running tests;
- display what EPs are enabled for your user;
- show what is the start time for this run, suites list and tests list;
- show execution summary status: how many test cases are planned for execution, how many were executed, how many passed, how many failed;
- show execution details status: the same, plus status per test case;
- queue tests during run time (the user is not forced to stop the execution in order to add more files for execution). Queuing a file while the execution is stopped has no effect - it will be discarded when the execution is started. Instead, the project file has to be updated in order to include that file.
- dequeue tests during run time, before they are executed. Dequeueing a file while the execution is stopped has no effect.

You can use `./cli.py --help` anytime, to see the usage information.

```
Usage: cli.py --server <ip:port> --command [...parameters]

Options:
  --version            show program's version number and exit
  -h, --help          show this help message and exit
  --server=SERVER      Your user and password @ central engine IP and port
                        (default: http://user:password@127.0.0.1:8000/)
  -u, --users          Show active and inactive users.
  --eps               Show active and inactive Eps.
  --stats             Show stats.
  --details           Show detailed status for All files.
  --status-details=STATUS_DETAILS
                        Show detailed status for running, finished, pending,
                        or all files.
  -q QUEUE, --queue=QUEUE
                        Queue a file at the end of a suite. Specify queue like
                        'Suite:file_path'.
  -d DEQUEUE, --dequeue=DEQUEUE
                        Un-Queue 1 or more files. Specify like 'EP,
                        EP:suite_id, EP:Suite, or EP:file_id'.
  -s SET, --set=SET    Set status: start/ stop/ pause. (Must also specify a
                        config and a project)
  -c CONFIG, --config=CONFIG
                        Path to FWMCONFIG.XML file.
  -p PROJECT, --project=PROJECT
                        Path to PROJECT.XML file.
```

Commands:

- `./cli.py -u` - Show active and inactive users ;
- `./cli.py -eps` - Show active and inactive Eps ;
- `./cli.py -stats` - Show minimal stats ;
- `./cli.py -details` - Show detailed stats, per ep + suite + test ;
- `./cli.py --status-details <running| finished| pending| all>` ;
- `./cli.py --queue <Suite1:some_path/some_file.py>`

# TWISTER USER GUIDE

- Queue a file at the end of a suite. Must specify queue in the form of `suite:file\_path` ;
- **./cli.py --dequeue** <EP | EP:suite\_id | EP:Suite | EP:file\_id>
- - Un-queue a file from a project, before it is executed ;
- **./cli.py -s stop** | **./cli.py -s start** -p ~/twister/config/testsuites.xml --config ~/twister/config/fwmconfig.xml
- start, pause, or stop the central engine.

## Examples:

### **./cli.py --version**

Showing cli.py version:

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py --version
cli.py 2.014
```

```
tscguest@tsc-server:/opt/twister/bin$
```

### **./cli.py --server**

It must be used with other command:

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py --server
http://tscguest:tscguest@tsc-server:8000/
```

Hello, user `tscguest`.

You didn't specify a command ! Exiting !

```
tscguest@tsc-server:/opt/twister/bin$
```

You can see below how it is used with other commands.

### **./cli.py -u, --users**

It will show you the users that have Twister installed and active/inactive users.

If you don't specify a server it will use the default value for server

(user:password@127.0.0.1:8000/).

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py -u --server
http://tscguest:tscguest@tsc-server:8000/
```

Hello, user `tscguest`.

All users that have installed Twister: `bogdan, croq, nisuser, nisuser2, tscguest`.

All active users: `croq, nisuser, tscguest`.

```
tscguest@tsc-server:/opt/twister/bin$
```

### **./cli.py --eps**

## TWISTER USER GUIDE

It will show you a status of the EPs and their state(active/inactive)

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py --eps --server  
http://tscguest:tscguest@tsc-server:8000/
```

Hello, user `tscguest`.

Your Execution-Processes are:

EP-1001 : service not running

EP-1002 : service not running

EP-1003 : service not running

```
tscguest@tsc-server:/opt/twister/bin$
```

### **./cli.py --stats**

It will show you the status of the tests executed on the server:

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py --stats --server  
http://tscguest:tscguest@tsc-server:8000/
```

Hello, user `tscguest`.

User status : stopped

Last started: 2013-08-29 11:35:45

Time elapsed: 0:00:56

Passed : 5

Failed : 2

Pending : 0

Working : 0

Aborted : 0

No Exec : 0

Other : 0

> Total : 7

Pass rate: 71.43%

```
tscguest@tsc-server:/opt/twister/bin$
```

### **./cli.py --details**

It will show you detailed status of all tests:

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py --details --server  
http://tscguest:tscguest@tsc-server:8000/
```

Hello, user `tscguest`.

## TWISTER USER GUIDE

```
User status : stopped
Last started: 2013-08-29 13:13:10
Time elapsed: 0:00:09
```

Your Suites are:

- on EP-1001 :
  - (id 101) S1
    - [pass] (id 1001) /home/tscguest/twister/demo/testsuite-python/init.py
    - [pass] (id 1002) /home/tscguest/twister/demo/testsuite-python/init.py
    - [pass] (id 1003) /home/tscguest/twister/demo/testsuite-python/init.py
- on EP-1002 :
  - nothing here
- on EP-1003 :
  - nothing here

```
tscguest@tsc-server:/opt/twister/bin$
```

### **./cli.py --status-details**

It will show you the detailed status of the tests based on a filter(all, running, finished, pending)

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py --status-details all --server
http://tscguest:tscguest@tsc-server:8000/
```

```
Hello, user `tscguest`.
```

```
User status : stopped
Last started: 2013-08-29 13:13:10
Time elapsed: 0:00:09
```

Your Suites are:

- on EP-1001 :
  - (id 101) S1
    - [pass] (id 1001) /home/tscguest/twister/demo/testsuite-python/init.py
    - [pass] (id 1002) /home/tscguest/twister/demo/testsuite-python/init.py
    - [pass] (id 1003) /home/tscguest/twister/demo/testsuite-python/init.py
- on EP-1002 :
  - nothing here
- on EP-1003 :
  - nothing here



# TWISTER USER GUIDE

```
tscguest@tsc-server:/opt/twister/bin$
```

## **./cli.py -q**

It will add/queue a test at the end of a specified suite.

This command it's working only when the tests are already running.

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py -q
S1:/home/tscguest/twister/demo/testsuite-python/test_py_printnlogs.py --server
http://tscguest:tscguest@tsc-server:8000/
```

```
Hello, user `tscguest`.
```

```
Test `/home/tscguest/twister/demo/testsuite-python/test_py_printnlogs.py` was queued
in suite `S1`.
```

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py --details --server
http://tscguest:tscguest@tsc-server:8000/
Hello, user `tscguest`.
```

```
User status : running
Last started: 2013-08-29 13:40:37
Time elapsed: 0:00:27
```

Your Suites are:

- on EP-1001 :
  - (id 101) S1
    - [pass] (id 1001) /home/tscguest/twister/demo/testsuite-python/init.py
    - [pass] (id 1002) /home/tscguest/twister/demo/testsuite-python/test\_py\_globals1.py
    - [pass] (id 1003) /home/tscguest/twister/demo/testsuite-python/test\_py\_globals2.py
    - [pass] (id 1004) /home/tscguest/twister/demo/testsuite-python/test\_py\_globals3.py
    - [pass] (id 1005) /home/tscguest/twister/demo/testsuite-python/test\_py\_printnlogs.py
    - [working] (id 1006) /home/tscguest/twister/demo/testsuite-python/test\_pexpect\_ftp.py
    - [pending] (id 1007) /home/tscguest/twister/demo/testsuite-python/test\_py\_printnlogs.py
- on EP-1002 :
  - nothing here
- on EP-1003 :

## TWISTER USER GUIDE

- nothing here

```
tscguest@tsc-server:/opt/twister/bin$
```

### **./cli.py -d**

It will delete/de queue a test, a suite or all of the tests from a suite or EP.

This command it's working only when the tests are already running.

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py --details --server
http://tscguest:tscguest@tsc-server:8000/
Hello, user `tscguest`.
```

```
User status : running
Last started: 2013-08-29 14:04:41
Time elapsed: 0:00:07
```

Your Suites are:

```
- on EP-1001 :
- (id 101) S1
  - [pass] (id 1001) /home/tscguest/twister/demo/testsuite-python/init.py
  - [pass] (id 1002) /home/tscguest/twister/demo/testsuite-python/test_py_globals1.py
  - [pass] (id 1003) /home/tscguest/twister/demo/testsuite-python/test_py_globals2.py
  - [pending] (id 1004) /home/tscguest/twister/demo/testsuite-
python/test_py_globals3.py
  - [pending] (id 1005) /home/tscguest/twister/demo//testsuite-
python/test_py_printnlogs.py
  - [pending] (id 1006) /home/tscguest/twister/demo//testsuite-
python/test_pexpect_ftp.py

- on EP-1002 :
- nothing here

- on EP-1003 :
- nothing here
```

```
tscguest@tsc-server:/opt/twister/bin$
tscguest@tsc-server:/opt/twister/bin$
tscguest@tsc-server:/opt/twister/bin$ python cli.py -d EP-1001:1006 --server
http://tscguest:tscguest@tsc-server:8000/
Hello, user `tscguest`.
```

```
Test `1006` was removed from the project.
```

## TWISTER USER GUIDE

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py --details --server
http://tscguest:tscguest@tsc-server:8000/
```

Hello, user `tscguest`.

User status : running  
Last started: 2013-08-29 14:04:41  
Time elapsed: 0:00:17

Your Suites are:

- on EP-1001 :
  - (id 101) S1
    - [pass] (id 1001) /home/tscguest/twister/demo/testsuite-python/init.py
    - [pass] (id 1002) /home/tscguest/twister/demo/testsuite-python/test\_py\_globals1.py
    - [pass] (id 1003) /home/tscguest/twister/demo/testsuite-python/test\_py\_globals2.py
    - [pass] (id 1004) /home/tscguest/twister/demo/testsuite-python/test\_py\_globals3.py
    - [working] (id 1005) /home/tscguest/twister/demo/testsuite-python/test\_py\_printnlogs.py
- on EP-1002 :
  - nothing here
- on EP-1003 :
  - nothing here

```
tscguest@tsc-server:/opt/twister/bin$
```

### **./cli.py -s, --set**

It will start/stop/pause the execution of a project file.

You will have to specify the config and the project file you will be using.

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py -s start --server
http://tscguest:tscguest@tsc-server:8000/ -c ~/twister/config/fwmconfig.xml -p
~/twister/config/testsuites.xml
```

Hello, user `tscguest`.

Starting...  
running

```
tscguest@tsc-server:/opt/twister/bin$ python cli.py --details --server
http://tscguest:tscguest@tsc-server:8000/
Hello, user `tscguest`.
```

# TWISTER USER GUIDE

User status : running  
Last started: 2013-08-29 11:35:45  
Time elapsed: 0:00:08

Your Suites are:

- on EP-1001 :
  - (id 101) S1
    - [pass] (id 1001) /home/tscguest/twister/demo//testsuite-python/init.py
    - [working] (id 1002) /home/tscguest/twister/demo//testsuite-python/test\_pexpect\_ftp.py
    - [pending] (id 1003) /home/tscguest/twister/demo//testsuite-python/test\_pexpect\_ssh.py
    - [pending] (id 1004) /home/tscguest/twister/demo//testsuite-python/test\_py\_globals1.py
    - [pending] (id 1005) /home/tscguest/twister/demo//testsuite-python/test\_py\_globals2.py
    - [pending] (id 1006) /home/tscguest/twister/demo//testsuite-python/test\_py\_globals3.py
    - [pending] (id 1007) /home/tscguest/twister/demo/testsuite-python/init.py
- on EP-1002 :
  - nothing here
- on EP-1003 :
  - nothing here

## 11 Twister configuration

### 11.1 Twister configuration files

Twister has a few configuration files, in XML, ini and Json format.

There are 2 types of configurations: per user (located at */\$USER\_HOME/twister/config*) and global for all users (by default located at */opt/twister/config*).

- **fwmconfig.xml**: the **master framework config**. Contains the paths to all the other config files. Config saved per user;
- **epname.ini**: contains all the EPs for the current user. **This must be edited**

## TWISTER USER GUIDE

**manually.** Config saved per user;

- **email.xml**: contains all the information necessary to send an e-mail from Twister. Config saved per user;
- **db.xml**: contains all the information about saving and reading from the MySQL database. Config saved per user;
- **globals.xml**: contains all global variables, per user;
- **plugins.xml**: contains information about all plugins, per user;
- **testsuites.xml**: contains all suites and all files for the current run. Saved per user;
- **resources.json**: contains all the resources from Resource Allocator server, all testbeds and devices. It's a global config;
- **services.ini**: contains all the services from Service Manager. It's a global config;
- **server\_init.ini**: contains the current server type: **no\_type**, **development**, or **production**. In *`production`* mode, all user roles are enabled. In *`no\_type`* mode, all roles are enabled, but changing users is disabled. It also contains the server location description;
- **users\_and\_groups.ini**: contains all users, groups and roles;

Most of the files are generated automatically from the Java applet. They **should not** be edited manually, unless specified otherwise.

# TWISTER USER GUIDE

## 11.2 Configure the paths

The screenshot shows the 'Configuration' tab of the Twister application. On the left, there is a sidebar with buttons for 'Paths', 'Email', 'Database', 'Test Beds', 'Global Parameters', 'Panic Detect', 'Services', and 'Plugins'. The main configuration area contains the following sections:

- TestCase Source Path**: Master directory with the test cases that can be run by the framework. Path:  ...
- Projects Path**: Location of projects XML files. Path:  ...
- EP name File**: Location of the file that contains the Ep name list. Path:  ...
- Logs Path**: Location of the directory that stores the logs that will be monitored. Path:  ...
- Log Files**: All the log files that will be monitored.

Running:	<input type="text" value="log_running.log"/>
Debug:	<input type="text" value="log_debug.log"/>
Summary:	<input type="text" value="log_summary.log"/>
Info:	<input type="text" value="log_test.log"/>
Cli:	<input type="text" value="CLI.log"/>

★ All the paths below refer to the computer where the **Central Engine** is running.

**Test case source path** represents the folder where all test files are located. The files here can be dragged inside suites, in the first tab (suites).

**Projects path** is the folder where the profiles are saved in the first tab; usually this doesn't need to be changed.

**EP Name** file stores the list of EPs (the workstations where tests will run). An `EP` is just a name to uniquely identify a computer, it can be any string.

**Logs path** is the folder where all the logs are written. There are 5 major logs: log running, log debug, log summary, log info, and log CLI. Each of the logs will be saved in the logs path, with the name defined in the configuration. Usually, the logs don't need to be changed.

**E-mail XML path**, **Database XML path** and **Globals XML path** are the files that store the information for the next 3 tabs. You can have multiple files, and switch between configurations.


# TWISTER USER GUIDE

The **Central Engine port** is, of course, the port where the applet connects to the server. The default value is *8000*.

**Library path** defines a path where user defined python libraries can be found. The user libraries will be used together with the system libraries, stored in */opt/twister/lib*, to execute the test cases.

**Predefined suites path** this defines a path where user can save suites (different from project files) for future usage. The user can export a suite from a project file and import it in another project file

## 11.3 Configure the e-mail



The screenshot shows a configuration window for email settings. It contains several sections: 'SMTP server' with fields for 'IP/Name' (smtp.email.com) and 'Port' (25); 'Authentication' with fields for 'User' (MyUser), 'Password' (masked with dots), and 'From' (MyUser@email.com); 'Email List' with a text area containing 'OtherUser@email.com'; 'Subject' with a text area containing 'Test1'; and 'Message' with a text area containing 'Test2'. At the bottom, there is a 'Disabled' checkbox, and two buttons labeled 'Test' and 'Save'.

Here you can configure the parameters required to connect to a SMTP server and send an e-mail.

The Central Engine will send the e-mail every time the execution finishes for ALL the test files.

The most important fields are: SMTP *IP* and *port*, *username*, *password*, *from* and the *e-mail list*.

## TWISTER USER GUIDE

Optionally, you can change the subject and add a few lines in the message body.

In order to test the connection to the SMTP server, using the user and password, you can send a test e-mail, using the button `Test` in the applet.

Both the subject and the message, can contain insert fields from `DB.xml`, from `*insert\_section*` tag.

*For example*, if you defined the fields with IDs `release\_id`, `build\_id`, `suite`, you can write the subject like :

E-mail report for R{*release\_id*} B{*build\_id*} - {*suite*} [{*date*}]

If your release number is `2`, build number is `15` and suite is `Branch Test1`, the subject will be generated like:

E-mail report for R2 B15 – Branch Test1 [2012.03.23 13:24]



# TWISTER USER GUIDE

## 11.4 Configure the database

Paths

Email

Database

Test Beds

Global Parameters

Panic Detect

Services

Plugins

About

Database

Database: TestDb

Server: 127.0.0.1

User: user

Password: ●●●

Field Section

Insert Section

Reports Section

Field Section

ID: res id	Field Name: id	From Table: result	SQL Query: select MAX(id)+1	Label:	Type: DbSelect	<input type="checkbox"/> GUI Defined	<input checked="" type="checkbox"/> Ma
ID: loq id	Field Name: id	From Table: loqs	SQL Query: select MAX(id)+1	Label:	Type: DbSelect	<input type="checkbox"/> GUI Defined	<input checked="" type="checkbox"/> Ma
ID: relea	Field Name: id	From Table: sites	SQL Query: select DISTINCT i	Label: Relea	Type: UserSelect	<input checked="" type="checkbox"/> GUI Defined	<input checked="" type="checkbox"/> Ma
ID: build	Field Name: id	From Table: suite	SQL Query: select DISTINCT i	Label: Build	Type: UserSelect	<input checked="" type="checkbox"/> GUI Defined	<input checked="" type="checkbox"/> Ma
ID: suite	Field Name: id	From Table: pri	SQL Query: select DISTINCT i	Label: Suite	Type: UserSelect	<input checked="" type="checkbox"/> GUI Defined	<input checked="" type="checkbox"/> Ma
ID: static	Field Name: id	From Table: suts	SQL Query: select DISTINCT i	Label: Static	Type: UserSelect	<input checked="" type="checkbox"/> GUI Defined	<input checked="" type="checkbox"/> Ma
ID: comr	Field Name:	From Table:	SQL Query:	Label: Set c	Type: UserText	<input checked="" type="checkbox"/> GUI Defined	<input type="checkbox"/> Ma

Add

Save File

Paths

Email

Database

Test Beds

Global Parameters

Panic Detect

Services

Plugins

About

Database

Database: TestDb

Server: 127.0.0.1

User: user

Password: ●●●

Field Section

Insert Section

Reports Section

Insert Section

SQL Statement: INSERT INTO repo test view VALUES( @res id@, \$release id, \$build id, \$suite id, \$station id, \$twist

Add

Save File

# TWISTER USER GUIDE

Paths

Email

Database

Test Beds

Global Parameters

Panic Detect

Services

Plugins

About

Database

Database:TestDb

Server:127.0.0.1

User:user

Password:●●●

Field Section

Insert Section

Reports Section

Reports Section

ID: Other	SQL Query	Label: Other filters	Type: UserText	Remove
ID: Date	SQL Query SELECT DISTINCT tdate FROM repo test vi	Label: Select date	Type: UserSelect	Remove
ID: DateStart	SQL Query SELECT DISTINCT tdate FROM repo test vi	Label: Select date St	Type: UserSelect	Remove
ID: zDateEnd	SQL Query SELECT DISTINCT tdate FROM repo test vi	Label: Select date Er	Type: UserSelect	Remove
ID: TestStatus	SQL Query SELECT DISTINCT status FROM repo test vi	Label: Select test sta	Type: UserSelect	Remove
ID: Release	SQL Query SELECT id.name FROM repo release	Label: Select release	Type: UserSelect	Remove
ID: Build	SQL Query SELECT id.name FROM repo build	Label: Select build	Type: UserSelect	Remove
ID: Suite	SQL Query SELECT id.name FROM repo suite	Label: Select suite	Type: UserSelect	Remove
ID: Station	SQL Query SELECT id.name FROM repo station	Label: Select station	Type: UserSelect	Remove
ID: Total	SQL Query SELECT * FROM repo test view	SQL Total:	Type: Table	Remove
ID: Details	SQL Query SELECT * FROM repo test view	SQL Total:	Type: Table	Remove
ID: History	SQL Query SELECT build id AS 'Build', sta	SQL Total: SELECT build id AS 'Build', sta	Type: BarChart	Remove
ID: Summary	SQL Query SELECT status AS 'Status',COU	SQL Total:	Type: PieChart	Remove

Save File

# TWISTER USER GUIDE

All the database information is stored in `DB.xml` file, by default. This file can be changed from the interface, in the **Paths tab**. You can have multiple configurations and switch between them.

The **field section** contains all the information that was defined in the **Suites tab** for each and every suite, things like: release, build, station, logs, comments, etc.

This information is used when saving the execution results into the database and when sending the report e-mail.

Each field must contain the following tags:

- **ID**: represents the name of the field and MUST be unique;
- **Type**: there are 4 types of fields: **UserSelect**, **DbSelect** (where you must define an SQL query that will generate a list of value in the interface; the user will select 1 value and that will be saved; the difference between them is that DbSelect will never appear in the interface), **UserScript** (when specifying this field, for each Suite defined in the **Suites tab**, the user must provide the path to a script that will run for each file that is inserted in the database. This script can be written in any programming language and all the output printed on the screen *stdout* will be captured and written in the database) and **UserText** (free text, can be any text);
- **SQLQuery**: this is required only for *UserSelect* and *DbSelect* fields. The query must be defined in such a way that the values will be unique (eg: by using SELECT DISTINCT id, name FROM ...) and should select 2 columns. The first column will be the **ID** and second will be the **description** of the respective ID;
- **GUIDefined**: if a field is not GUI defined, it will not appear in the **Suites tab**, when editing suites. DbSelect fields are never visible in the interface;
- **Mandatory**: if a field is mandatory, each suite from the **Suites tab** must have a value for this field. If the user doesn't choose a value, he will not be able to save the profile, or start the execution of the project. Mandatory fields must be GuiDefined;
- **Label**: a short text that describes the field and will appear in the interface; labels are not necessary for DbSelect fields, because they are not visible in the interface.

**Examples of fields:**

```
<field ID="res_id" Type="DbSelect"
SQLQuery="select MAX(id)+1 from repo_test_view"
Label="-" GUIDefined="false" Mandatory="true" />
```

## TWISTER USER GUIDE

```
<field ID="release_id" Type="UserSelect"
SQLQuery="select DISTINCT id, release_name from t_releases"
GUIDefined="true" Mandatory="true" Label="Release:" />

<field ID="build_id" Type="UserSelect"
SQLQuery="select DISTINCT id, build_name from t_builds"
Label="Build:" GUIDefined="true" Mandatory="true" />

<field ID="comments" Type="UserText" SQLQuery=""
Label="Set comments:" GUIDefined="true" Mandatory="false" />
```

The **insert section** defines a list of SQL queries that will execute every time the execution finishes for ALL the test files. All queries are executed for each and every test file.

The insert queries use the information from the fields described above. A file can only access the fields defined in his parent suite.

Other than that, the queries can access a list of variables passed from the Central Engine, which describe how the execution was completed. Here are the variables:

- **\$twister\_user** = the name of the user that ran the tests;
- **\$twister\_ce\_os** = the operating system of the computer where Central Engine runs;
- **\$twister\_ep\_os** = the operating system of the computer where Execution Process runs;
- **\$twister\_ce\_ip** = the IP of the Central Engine;
- **\$twister\_ce\_hostname** = the host name of the Central Engine;
- **\$twister\_ep\_ip** = the IP of the Execution Process;
- **\$twister\_ep\_hostname** = the host name of the Execution Process;
- **\$twister\_ce\_type** = server type can be *development*, *production*, or *no\_type*, as defined in *server\_init.ini*.
- **\$twister\_server\_location** = a description for the current server location, as defined in *server\_init.ini*.
- **\$twister\_ep\_name** = EP name, defined in **Suites tab**;
- **\$twister\_rf\_fname** = the path to Twister resources file (default is ``resources.json``);
- **\$twister\_pf\_fname** = the path to Twister project file (default is ``project_users.json``);
- **\$twister\_ce\_python\_revision** = python version from Central Engine;
- **\$twister\_ep\_python\_revision** = python version from Execution Process;
- **\$twister\_suite\_name** = suite name, defined in **Suites tab**;

## TWISTER USER GUIDE

- **\$twister\_tc\_name** = the file name of the current test;
- **\$twister\_tc\_full\_path** = the path + file name of the current test;
- **\$twister\_tc\_title** = the title, from the **Suites tab**;
- **\$twister\_tc\_description** = the description, from the **Suites tab**;
- **\$twister\_tc\_status** = the final status of the test: pass, fail, skip, abort, etc;
- **\$twister\_tc\_crash\_detected** = if the file had a fatal error that prematurely stopped the execution;
- **\$twister\_tc\_time\_elapsed** = time elapsed;
- **\$twister\_tc\_date\_started** = date and time when the running started;
- **\$twister\_tc\_date\_finished** = date and time when the running finished;
- **\$twister\_tc\_log** = the complete log from execution.

These variables can be used in the query like ``$variable_name``, or ``@dbselect_field_name@``.

Only the fields of type **DbSelect** are surrounded by **@**.

# TWISTER USER GUIDE

**Examples of database inserts:**

```
<sql_statement>
INSERT INTO gg_regression
(suite_name, test_name, status, date_start, date_end, build, machine)
VALUES
( '$twister_suite_name', '$twister_tc_name', '$twister_tc_status',
'$twister_tc_date_started', '$twister_tc_date_finished', '$release.$build',
'$twister_ep_name' )
</sql_statement>
```

Or:

```
<sql_statement>
INSERT INTO results_table1
VALUES
( @res_id@, $release_id, $build_id, $suite_id, $station_id, '$twister_tc_date_finished',
'$twister_tc_status', '$comments' )
</sql_statement>
```

★ In this last example, `res\_id` is a **DbSelect** field with the query defined as:  
`SELECT MAX(id)+1 FROM results\_table1`.

The **reports section** defines all the information exposed to the reporting framework.

In this section you can define the *fields*, the *reports* and the *redirects*.

The **fields** must have the following properties:

- **ID**: represents the name of the field and **MUST** be unique;
- **Type**: there are 2 types of fields: **UserSelect** (where you must define an SQL query) and **UserText** (free text, you can write anything);
- **SQLQuery**: this is required only for UserSelect fields. The query should select two columns: the first is the ID and the second is a name, or a description of the respective ID. If the table where you have the data doesn't have any description associated with the ID, you can use only the ID;
- **Label**: a short text that describes the field, when the user is asked to select a value.

**Examples of report fields:**

```
<field ID="Dates" Type="UserSelect" Label="Select date:"
SQLQuery="SELECT DISTINCT date FROM results_table1 ORDER BY date" />
```

## TWISTER USER GUIDE

```
<field ID="Statuses" Label="Select test status:" Type="UserSelect"  
SQLQuery="SELECT DISTINCT status FROM results_table1 ORDER BY status" />
```

```
<field ID="Releases" Label="Select release" Type="UserSelect"  
SQLQuery="SELECT DISTINCT SUBSTRING(build, 1, 6) AS R FROM results_table1  
ORDER BY R" />
```

```
<field ID="Other" Type="UserText" Label="Type other filters:" SQLQuery="" />
```

# TWISTER USER GUIDE

The **reports** must have the properties:

- **ID**: represents the name of the report and MUST be unique;
- **Type**: there are 4 types of reports: **Table** (an interactive table is generated; the table can be sorted and filtered dynamically), **PieChart**, **BarChart** and **LineChart** (they show both the chart and the table; for PieChart report, the SQL query must be defined in such a way that the first column is a string describing the data, and the second column is an integer or float data; BarChart and LineChart must also have the query generate 2 columns, the first is a number and the second is a label or another number);
- **SQLQuery**: all reports must define an SQL query. If the type of report is Table, it can select any number of fields (although it's recommended to use a maximum of 10, to fit on the screen without having to scroll to the right). If the report is a chart, you must select only 2 columns. The query can use any, or none of the fields described above. Each field name **must be surrounded by `@`**. When a field is used in the query, the reporting framework will require the user to choose a value, before displaying the report.

*Examples or reports:*

```
<report ID="Details (build)" Type="Table"
SQLQuery="SELECT * FROM results_table1 WHERE build='@Build@' ORDER BY id"
/>

<report ID="Details (suite)" Type="Table"
SQLQuery="SELECT * FROM results_table1 WHERE build='@Build@' AND
suite_name='@Suite@' " />

<report ID="Summary" Type="PieChart"
SQLQuery="SELECT status AS 'Status', COUNT(status) AS 'Count' FROM
results_table1 WHERE build= '@Build@' group by status " />

<report ID="Pass Rate" Type="LineChart"
SQLQuery="SELECT Build, COUNT(status) AS 'Pass Rate (%)' FROM results_table1
WHERE Build LIKE '@Release@%' AND status='Pass' GROUP BY Build"
SQLTotal="SELECT Build, COUNT(status) AS 'Pass Rate (%)' FROM results_table1
WHERE Build LIKE '@Release@%' GROUP BY Build" />
```

The **redirects** must have the properties:

- **ID**: represents the name of the redirect and MUST be unique. Ideally, the ID should start with the word ``goto``;



# TWISTER USER GUIDE

- **Path:** is the full path to a HTML page. It can be a link to a static page, to PhpMyAdmin for the current database, or a user web page served by any web server.

*Examples of redirects:*

```
<redirect ID="goto PhpMyAdmin" Path="http://my-server/phpmyadmin" />  
<redirect ID="goto PHP Report" Path="http://my-server/some-report.php" />
```

## 11.5 Configure the devices(testbed)

The screenshot shows a web interface for configuring testbeds. On the left, a list of testbeds (TB) is displayed: tb3, tb2, and tb1. Below this list are two buttons: 'Add Component' and 'Remove'. On the right, a detailed configuration panel for a selected testbed (tb1) is shown. It includes a 'Run on EP:' dropdown menu with options EP-1001, EP-1002, EP-1003, and EP-1004. Below this are input fields for 'Name:' (tb1), 'ID:' (f119f3cf8f), and 'Path:' (tb1). At the bottom of the configuration panel is a 'Properties' section with an 'Add' button.

The Resource Allocator server is used to view and edit the Testbed and SUT properties.

**The testbed is global for all users.**

Each device == node == resource must have a name and some properties in the form of **{key : value}**.

The name of a resource must be unique in its parent. For example you cannot have more nodes called `Device1` in parent `Testbed1`, but you can have nodes called `Device1` for both `Testbed1` and `Testbed2`.

This is important, because each resource can be accessed using its ID, or its full path (just like a Unix file system).

# TWISTER USER GUIDE

The Resource Allocator server exposes a simple API inside the Twister tests, for accessing the resources:

- **getResource**( ID or full path ) - returns a dictionary containing all the node properties;
- **setResource**( name, parent ID or full path, properties in dictionary or JSON string)

- This function is used to CREATE and MODIFY nodes. If the resource is created, the ID of the new resource is returned. If the resource is updated, the function returns True.

Example: **setResource**('module1', '/tb1/device2', '{"ip":"10.0.0.1", "port":"80"}') ;

- **renameResource**( ID or full path, new name ) - renames resources or their properties;
- **deleteResource**( ID or full path ) - deletes resources or their properties;
- **getResourceStatus**( ID or full path ) - obsolete.

## Examples:

Let's say there are 3 testbeds: *tb1*, *tb2*, *tb3*. Each testbed has 2 devices: *dev1* and *dev2*. Each device has 3 modules: *mod1*, *mod2*, *mod3*.

To access module 2 from device 1 from testbed 3, you can use: **getResource**('/tb3/dev1/mod2').

To access testbed 1, you can use: **getResource**('/tb1').


To rename device 2 from testbed 2, you can use: **renResource**('/tb2/dev2', 'dev\_x2').

Note that the new name is just a string, not the full path.

In **production mode**, to be able to Set, Rename or Delete a resource, a user must have the *CHANGE\_TESTBED* role.

# TWISTER USER GUIDE

## 11.6 Configure the SUTs



This is where you can edit the SUTs (systems under test). A SUT is a collection of TestBeds or devices, linked together in a system that will be tested as a whole.

**The SUT is global for all users.**

In order to create a SUT, press on `Add SUT` button in the applet. You will be asked to type a name and select an execution process for the SUT. The name **MUST** be unique; you cannot have more SUTs with the same name.

After the SUT is create, to add TestBeds or devices drag & drop resources from the TestBeds tree in the right.

You can rename a SUT by selecting it and using the `Modify SUT` button and you can delete it with `Remove`.

The Resource Allocator server exposes a simple API inside the Twister tests, for accessing the SUTs:

- `getSut( ID or full path )` - returns a dictionary containing all the SUT properties;
- When you use the `getSut` function, for example `getSut('SUT1')`, you will receive a hash-map like this:

## TWISTER USER GUIDE

```
{'path':'SUT1', 'meta':{'epnames': 'EP-1001'}, 'id':'a322908eab', 'children':['5cae3abaef', 'c76db917e6']}
```

Each child is the ID of a node from the SUT, and the node name is an ID of a TestBed or device.

Use getSut of the child ID, to see the ID of a TestBed or device, in the path of the SUT.

```
getSut('5cae3abaef') # {'path': 'SUT1/f119f3cf8f', 'meta': {}, 'id': '5cae3abaef', 'children': []}
```

```
getSut('c76db917e6') # {'path': 'SUT1/f7a32d31cf', 'meta': {}, 'id': 'c76db917e6', 'children': []}
```

```
getResource('f119f3cf8f') # {'path': 'tb1', 'meta': {}, 'id': 'f119f3cf8f', 'children': ['6f1bf6a142']}
```

```
getResource('f7a32d31cf') # {'path': 'tb2/device1', 'meta': {}, 'id': 'f7a32d31cf', 'children': []}
```

- setSut( name, parent ID or full path, properties in dictionary or JSON string)

- This function is used to CREATE and MODIFY SUTs. If the SUT did not exist before, the ID of the new SUT is returned. If the SUT is updated, the function returns True.


Example: setSut('SUT11', '/', '{"epnames":"EP-1001;EP-1002"}') ;

- renameSut( ID or full path, new name ) - renames SUTs or their properties;
- deleteSut( ID or full path ) - deletes SUTs or their properties.

In **production mode**, to be able to Set, Rename or Delete a SUT, a user must have the *CHANGE\_TESTBED* role.

# TWISTER USER GUIDE

## 11.7 Configure the global parameters



Global parameters are variables available in all test files. There is no need to import any library.

### The parameters are stored per user!

The API is very simple: in any test, use **getGlobal**( name ) and **setGlobal**( name, value ). You don't need to import anything.

If the **name** is a folder (not a variable with a value), instead of a value, getGlobal returns a dictionary. If the parameter **name** doesn't exist, getGlobal returns *False*.

The setGlobal function will update, create or delete parameters. If the name exists, it is updated. If it doesn't exist, it is created. If you use **setGlobal** (name, False), the parameter is deleted.

The changes made by setGlobal are temporary and will RESET every time the tests start running.

# TWISTER USER GUIDE

There are 3 types of parameters:

1. the default parameters stored in the configuration, that are saved in globals.xml file ;
2. the serializable parameters saved by the test files are shared between all Eps from a user ;
3. the complex, not serializable parameters are stored on the EP that is running the tests.

## 11.8 Configure 'panic detect'

The screenshot shows the 'Configuration' tab of the Twister interface. On the left is a sidebar with buttons for 'Paths', 'Email', 'Database', 'Test Beds', 'Global Parameters', 'Panic Detect', 'Services', and 'Plugins'. The 'Panic Detect' button is highlighted. The main area displays a table of regular expressions for panic detection:

RegEx:			
RegEx:	CORE-DUMP	<input checked="" type="checkbox"/> Enabled	Remove
RegEx:	has CRASHED	<input checked="" type="checkbox"/> Enabled	Remove
RegEx:	CRITICAL ERROR	<input type="checkbox"/> Enabled	Remove
			Add

Panic detect is a mechanism that allows the users to add `expressions` that will be searched in the test logs. If any of the expressions is detected, the execution STOPS.


An `expression` can be a normal string, or a regex.

# TWISTER USER GUIDE

This is useful to check for core dumps and critical errors; in these extreme cases, it's useless to continue the execution of any test.

## 11.9 Services and Plugins

*Print screen with Services* (in production mode, using Services requires the `CHANGE_SERVICES` role)



*Print screen with Plug-ins* (in production mode, using Plug-ins requires the `CHANGE_PLUGINS` role)

# TWISTER USER GUIDE

Project

Reports

Configuration

Paths

Email

Database

Test Beds

Global Parameters

Panic Detect

Services

Plugins

Local

Local installed plugins

ServiceManagement.jar

Remove

UserName.jar

Remove

Scheduler.jar

Remove

Remote

Remote plugins found on server

PacketsTwistPlugin.jar

Download

GITPlugin.jar

Download

JiraPlugin.jar

Download

SVNPlugin.jar

Download

JenkinsPlugin.jar

Download

☐ Activate

**Scheduler.jar**

Scheduler

Read more

☐ Activate

**ServiceManagement.jar**

ServiceManagement plugin

Read more

☐ Activate

**UserName.jar**

Plugin to display user name

Read more

More about this in the **`Twister Libraries, Plugins, Services`** help file.



# TWISTER USER GUIDE

## 11.10 Changing users

*Print screen with Users Management*

Users

User Name	Timeout	User Groups	User Roles
tscguest	05	admin	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGIN_S,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS
nisuser	00	developer,admin	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGIN_S,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS
admin	01	admin,user	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGIN_S,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS
developer	01	tester,developer	CHANGE_DB_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PROJECT,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS
boqdan	01	admin	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGIN_S,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS

Add User Remove User

User properties

User name: tscguest

Timeout: 05

Groups

- tester
- developer
- admin
- guest
- user

Groups

Group Name	Group Roles
tester	CHANGE_DB_CFG,RUN_TESTS
developer	CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_DB_CFG,RUN_TESTS,EDIT_TC,CREATE_PROJECT,CHANGE_PROJECT,DELETE_PROJECT
admin	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGIN_S,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS
guest	CHANGE_GLOBALS
user	CREATE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED

Edit Group Roles

Control Panel

Since *version 2.020*, every user that connects to the Central Engine must be registered in Twister, must be part of a group, and implicitly has a set of roles.

When installing **Twister Server** for the first time, you must go in the server install folder and edit the ``config/users_and_groups.ini`` file. In the section `[users]`, the first user by default is `[[admin]]`; this name must be replaced with **your system user**. This way, you will become a Twister Administrator and will be able to create, edit, or delete other Twister users.

This manual edit must be done only the first time, the rest of the users should be changed using the GUI (the applet). You should also make sure that no one can view the `users_and_groups` file except for the ROOT user and make sure that Central Engine runs as ROOT, so it will be able to read the file (or if you plan to update the users using the GUI, Central Engine must also be able to write).

# TWISTER USER GUIDE

The roles are enabled only when the server type is **`production`**, in the file **`config/server\_init.ini`**. If the server type is **`development`**, users have all the roles, except for CHANGE\_USERS.

If a user cannot be found in *users\_and\_groups* file, **he CANNOT** use Twister. In *users\_and\_groups.ini* file, a Twister user has a title (his own name) and 3 fields:

- **groups** (a list of groups that this user belongs to. The groups will give him a set of Roles. The group can be 0 zero, which means zero Roles);
- **timeout** (the amount of seconds until the applet automatically logs out the user);
- a unique **key** (used to encrypt the passwords from DB.xml and EMAIL.xml. The passwords from the files cannot be decrypted without the key; it's important that only the ROOT can view the settings and see the user keys).

The timeout and key are very important in any server mode (development or production).


The groups have a set of unique roles. This is the complete list:

- RUN\_TESTS - Can run tests (server + applet)
- EDIT\_TC - Can edit test files (applet)
- CREATE\_PROJECT - Can create new projects (applet)
- CHANGE\_PROJECT - Can change defined projects (applet)
- DELETE\_PROJECT - Can delete projects (applet)
- VIEW\_REPORTS - Can open the reports (server + applet)
- CHANGE\_FWM\_CFG - Can change his main config (applet)
- CHANGE\_GLOBALS - Can change global parameters (applet)
- CHANGE\_DB\_CFG - Can change database config (applet)
- CHANGE\_EML\_CFG - Can change e-mail config (applet)
- CHANGE\_PLUGINS - Can load/ unload plugins (applet)
- CHANGE\_TESTBED - Can change the global testbed (server + applet)
- CHANGE\_SERVICES - Can start/ stop services (server + applet)
- CHANGE\_USERS - Can create, change and delete users (server + applet)

## 11.11 Set-up and Tear-down controls

Setup and Teardown controls are used to mark scripts as setup or teardown scripts.

# TWISTER USER GUIDE



TC options

TC name:

☒ Runnable ☐ Optional ☒ setup file ☐ teardown file

Properties

Parameters

The setup scripts can be used to setup a configuration on a network and the teardown to clear the configuration.

- *Setup* scripts are executed at all times (they have to be runnable) and if they *fail*, the entire Suite is considered *Failed*. Setup files are NOT saved into the database!
- *Teardown* scripts are executed at all times (they have to be runnable). They are used to clean-up a suite, even if the suite was aborted because of a failed Setup. Teardown files are NOT saved into the database!

## 11.12 Connection management (SSH implementation)

The SSH library is a file that is downloaded by the Execution Process, before executing the tests.

It is a library that wraps python paramiko library and offers the user a manager for custom ssh connections.

The manager allows the user to open, list and close ssh connections and the other basic operations as read, write.

The test files can import the libraries like this:

```
from ce_libs import SshManager
```

Following are the parameters available for the Ssh library.

You can find an example of how to use it in `~/twister/demo/testsuite-python/test_py_ssh_twist.py`

### - parameters:

name = connection name;  
host = connection host;  
user = username for connection login;  
password = username password for connection login;

# TWISTER USER GUIDE

port = connection port is default 22;  
command = string command to pass on telnet connection;  
timeout = connection timeout;

## - **open\_connection:**

- mandatory parameters: name, host;
- optional parameters: user, password, port;

## - **write:**

- mandatory parameters: command;
- optional parameters: name;

If no name is supplied it will try to use the active connection otherwise returns False. If success returns the connection output.

## - **read:**

- mandatory parameters: None;
- optional parameters: name;

If no name is supplied it will try to use the active connection otherwise returns False. If success returns the connection output.

## - **set\_timeout:**

- mandatory parameters: timeout;
- optional parameters: name;

If no name is supplied it will try to use the active connection otherwise returns False. If success returns True.

## - **get\_connection:**

- mandatory parameters: None;
- optional parameters: name;

If no name is supplied it will try to use the active connection otherwise returns False. If success returns a SshConnection instance (custom ssh connection).

## - **set\_active\_connection:**

- mandatory parameters: name;
- optional parameters: None;

If success returns True otherwise False.

## - **list\_connections:**

- mandatory parameters: None;
- optional parameters: None;

Returns a list of connection names.

## - **close\_connection:**

- mandatory parameters: None;
- optional parameters: name;

# TWISTER USER GUIDE

If no name is supplied it will try to use the active connection otherwise returns False. If success returns True.

## - close\_all\_connections:


- mandatory parameters: None;
- optional parameters: None;

If success returns True otherwise False.


## 11.13 Test case/Suites management

You can save your suites for a later use as predefined suites.

Before using this feature you must define the path where the predefined suites will be saved. To do that go to Configuration->Paths tab.




After you define your suite you can save it by right clicking on the suite that you want to save and enter a name for it.



# TWISTER USER GUIDE

The saved suites can be found in the **Predefined Suites** tab. You can drag and drop them in the main window where you define your tests to be run.



## 11.14 User levels

This feature is an enhanced user management with CE typing and multiple user groups: "developer" and "tester", and session management.

### A. CE server typing

Twister is supporting two types of servers: production and development. This information is displayed on GUI to allow the user to find out on what server types he's connected.

- i. The information is stored in a CE configuration file (server\_init.ini)
- ii. The default value of ce\_server\_type is no\_type. If you use "no\_type" you will have access to all the Twister features
- iii. As administrator you can change control of the file through unix group permissions.
- iv. After the ce\_server\_type is changed, a full restart of CE is required.

Example of server\_init.ini:

```
# Valid types: no_type, production, development
ce_server_type = "production"
# The server location can be any string
ce_server_location = "NeverLand"
```

# TWISTER USER GUIDE

## B. User groups

The twister GUI, it's providing a panel where the groups are managed. There are 3 twister user groups: admin, developer, tester.

- i. The twister admin is created by the Unix/NIS admin.
- ii. The twister admin can add, delete users (identified by unix\_name such as ttfisher), and set the users group.
- iii. The users can be moved from one group to another by the twister admin.
- iv. If a user belongs to the tester group, there will be some parts of the GUI that are greyed out and the user doesn't have access to that functionality.
- v. The GUI login credentials ( username/password ) are exported to the test cases as internal variables.

The screenshot displays the Twister GUI's user management interface. It is divided into two main sections: 'Users' and 'Groups'.

**Users Section:**

User Name	Timeout	User Groups	User Roles
tscgquest	05	admin	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGINS,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS
nisuser	00	developer,admin	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGINS,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS

Buttons: Add User, Remove User

**User properties (Left Panel):**

User name: tscgquest  
Timeout: 05  
Groups: tester, developer, admin (selected), guest, user

**Groups Section:**

Group Name	Group Roles
tester	CHANGE_DB_CFG,RUN_TESTS
developer	CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_DB_CFG,RUN_TESTS,EDIT_TC,CREATE_PROJECT,CHANGE_PROJECT,DELETE_PROJECT
admin	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGINS,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS
guest	CHANGE_GLOBALS
user	CREATE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED

Buttons: Edit Group Roles, Control Panel

The Unix/NIS users will be created by the IT team and not from Twister GUI. Once a user has a Unix/NIS account, the Twister admin will be able to get the list of Unix/NIS accounts and select which one can be added into a group. If a Unix/NIS account is not present in any Twister groups, he'll not be able to run tests even if he has a Unix system/NIS account.

## TWISTER USER GUIDE

### C. About screen.

The Twister framework is providing a CE configuration file to allow enterprise-specific information to be displayed in the Welcome and About screens.

To configure what it is displayed in the About screen you have to create/edit a logo.txt file which must be placed in the main directory where the GUI is loaded from (ex: /var/www/twister).

You can also add an image to the About screen which must be placed in the same directory as logo.txt and must be named logo.png. The image will be resized automatically by the GUI applet and displayed at this dimension W=230px, H=100px.

Logo example:



**Figure 7 FNC logo**

### D. User Information

Twister is showing in GUI who are the activated users and the groups they belong to.



# TWISTER USER GUIDE

Users

User Name	Timeout	User Groups	User Roles
tscguest	05	admin	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGINS,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS
nisuser	00	developer,admin	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGINS,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS

Add User

Remove User

User properties

User name: tscguest

Timeout: 05

Groups

tester

developer

admin

guest

user

Groups

Group Name	Group Roles
tester	CHANGE_DB_CFG,RUN_TESTS
developer	CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_DB_CFG,RUN_TESTS,EDIT_TC,CREATE_PROJECT,CHANGE_PROJECT,DELETE_PROJECT
admin	CHANGE_DB_CFG,CHANGE_EML_CFG,CHANGE_FWM_CFG,CHANGE_GLOBALS,CHANGE_PLUGINS,CHANGE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED,CHANGE_USERS,CREATE_PROJECT,DELETE_PROJECT,EDIT_TC,RUN_TESTS,VIEW_REPORTS
guest	CHANGE_GLOBALS
user	CREATE_PROJECT,CHANGE_SERVICES,CHANGE_TESTBED

Edit Group Roles

Control Panel


## E. Welcome Screen

Twister is providing a welcome screen same as the About screen from Configuration -> About screen, and indicates that the user should “Press any Key to Logon” Doing that the login pop-up is presented. The welcome screen is also presented when post-logout, Timeout, Cancel, and login failure.

# TWISTER USER GUIDE



After you login the Control Panel screen will be shown.



# TWISTER USER GUIDE

## F. Session Termination

- i. Twister have a Logout button which returns you to the Welcome screen.
- ii. Twister have an inactivity timer - User is logged off if no activity for programmed time. (Off, 15 min, 30 min) set by the admin.

## 11.15 Configuration management

A suite of global params compatible .XML files

You can have hundreds of configuration files organized in folders or subfolders.

In the project tab where you define your suites and tests to be run you can assign one or more configuration files to each test individually.

## 11.16 Email notification

Twister is providing a test button so the user can verify if the system can generate the email with the configured parameters. Activating the test button sends the email. The button is working regardless of the Enable/Disable checkbox. The user can disable email, send a test email, and then later enable email.

When you press the Test button, in case you entered wrong parameters/info the CE will pass through the SMTP error messages from the email server to an alert (pop-up in the GUI).

The email password is stored in a non-human readable format and it's encrypted with the user key from users\_and\_groups config file.

## 11.17 Test case details descriptors

In a testcase you can define any numbers of meta tags.

For example:

```
# <title>This is the title.</title>
```

```
# <description>This test prints and sends some logs.</description>
```

```
# <tag></tag> displays Tag:<stuff>
```

```
# <meta></meta> displays Meta:<stuff>
```

```
#<setup></setup> displays Setup:<stuff>
```

# TWISTER USER GUIDE

An example of how it can be used you can find it in `~/twister/demo/testsuites-python/init.py` file.

## 11.18 Library management

When you install Twister the default path where the libraries are stored is `/opt/twister/lib`. Besides this path every user can define a custom library path. You can use the both locations in the same time.

To define the custom path location go to Configuration -> Paths and set the path to the library location.

In a python test to import a library you must add the following line:

```
from ce_libs import <library_file>
```

The CE will first search for this library in the default library location and then in the custom library path.

## 11.19 Log customization

The client log files are reset every time a new execution is started. This overwrites the logs.

Details:

- i. In Log Path in the Configuration Paths window, allow specification of a secondary (archive) /path for log files.
- ii. The use of this secondary /path can be Enabled/Disabled by checkbox. Disabled is the default setting and makes Twister operate in the current fashion.
- iii. When the secondary folder is Enabled: Prior to starting a new execution, the logs are closed, and moved to the secondary /path.
- iv. With the move, all file\_names will have the same unix timestamp appended such as:

```
log_running.log.1370288853  
through
```

```
log_CLI.log. 1370288853
```

- v. The user can specify the same /path for both primary and backup.

# TWISTER USER GUIDE

## 11.20 EP start-up

This feature is providing a mechanism to allow start of EP's on demand when they are needed by the user for testing. This feature is providing a registration mechanism between the EP's and the CE. The registration is for EP's to CE, so the CE will know what are the available EP's for an user.

To manage the client you will need to run *start\_client* script which is installed in client path.

The script will be started manually by the user or automatically at system boot. Another mechanism to start automatically the script, is to set this in a *.profile* file that is executed automatically when the user log in into that machine. In the same time, the *.profile* file is executed automatically when a user logs into Twister GUI.

The *start\_client* script will read the available EP's from *epname.ini* file and register them to the configured CE. When the registration information is passed to the CE, the IP address of the EP, the name of the EP and the name of the user are passed to the CE. In this way, the EP where to run the test cases is identified by the CE.

The *start\_client* script is accepting the following options:

- Start – to start the client process
- Start silent - to start the client process and to disable printing of messages
- Stop – to stop the client process
- Restart – to restart the client process
- Status – to show the status of the client process

The *epname.ini* file is containing a tag called *EP\_HOST* for every EP set for the user. This tag is used to indicate the host machine where that EP can be started and it is used to allow the user to control on what machine the EP is started. In this way, the user can have a common *epname.ini* file for many machines and he can control what EP's to be started on what machines.

Example:

```
[EP-1001]
CE_IP = 11.126.32.20
CE_PORT = 8000
EP_HOST = 11.126.32.20
```

The *EP\_HOST* can be entered as a hostname or as an IP address.

If the *EP\_HOST* is commented out, the EP can be started on any machine. Same behaviour is present if there is no information set for *EP\_HOST* (IP or hostname).

If the user changes the *epname.ini* file, the client process and the GUI must be restarted so the user can get the latest changes. CE restart is not needed, since the registration mechanism will update the available EP's .

If the CE is stopped, the client process will try continuously to register EP's with the CE and it will succeed that once the CE is up and running.

# TWISTER USER GUIDE

## 12 How to write tests

Twister framework can run **Python**, **TCL** and **Perl** (limited) tests.

Writing a **Twister test** is just like writing a normal Python 2.7 test, or TCL 8.5 test, or Perl test, with a few exceptions.

Twister tests are most likely **incompatible** with the original language; for example a Twister Python test will not run with Python by default, because Twister inserts a few helper variables and functions, which are not available in the usual environment. So **if the a test uses the helper variables and functions**, the script will become incompatible with the original Python/ TCL/ Perl language and will be executed only from Twister.

Variables inserted in all Twister tests:

- **USER** : the username running the current test ;
- **PASSWD** : the password of the current user;
- **EP** : the name of the Execution Process running the current test ;
- **SUITE\_NAME** : the name of the suite that contains the current test ;
- **FILE\_NAME** : the full path of the test file from the machine that runs the Central Engine ;
- **currentTB** : the current test bed ;
- **PROXY** : this is a pointer to the Central Engine XML-RPC server. It is used for development.

And a few functions:

- **logMsg( logType, message )** : this function sends a message in a special log and will not appear in the CLI. Valid log types are : *logRunning*, *logDebug* and *logTest*. It is used for sending debug messages from the tests.
- **getGlobal( path )** : get a global parameter;
- **setGlobal( path, new\_value )** : set a global parameter;
- **getResource( ID or full path )** : get a resource;
- **setResource( ID or full path, new name )** : create, or update a resource;
- **renameResource( ID or full path, new name )** : rename one resource or property of a resource;
- **deleteResource( ID or full path )** : delete one resource or property of a resource;

# TWISTER USER GUIDE

- **getSut**( ID or full path ) : get a SUT properties;
- **setSut**( ID or full path, new name ) : create, or update a SUT;
- **renameSut**( ID or full path, new name ) : rename one SUT or property of a SUT;
- **deleteSut**( ID or full path ) : delete one SUT or property of a SUT;
- **getResourceStatus**( ID or full path ) : get the status of a resource: free, busy, or reserved;
- **reserveResource**( ID or full path ) : reserve one resource;
- **py\_exec** *some\_python\_command* : this function works **only in TCL** tests and allows running Python commands, or calling functions and objects from global parameters, defined in the previous tests.

In order to access the parameters sent from the interface, a Python test can use ``import sys ; sys.argv``.

The parameters are passed as a list and can be accessed using usual python variable arguments mechanism (using `sys.argv`).

To access a property called ``var1``, a Python test can use the following syntax (it returns the value of property):

PROPERTIES['*var1*']

The properties: ``type``, ``suite``, ``file``, ``dependency``, ``status``, ``Runnable``, ``Optional``, ``setup_file``, ``teardown_file`` and ``param`` are reserved for internal use and must NOT be used.

## 13 Performance and troubleshooting

The Central Engine and the Reporting Server are instances of Python CherryPy and were tested with 750+ simultaneous connections, without crashing, or losing connection.

★An article concerning python web servers: <http://nichol.as/benchmark-of-python-web-servers>.

Even if the Central Engine is fast enough, for a smooth experience, it's not recommended to run more than 100 Execution Processes on one Central Engine

## TWISTER USER GUIDE

instance. If you need more, you can simply open another instance of CE, on a different port and connect the rest of the clients on the new one.

The Execution Processes should be running on different workstations and their performance depends on the hardware of the respective machine.

All services have logs that describe every operation that is being executed. If something fails, it will be easy to know where exactly the error was produced.

On the server side, you can check the logs from `/opt/twister/server_log.log`, or `/opt/twister/logs/` folder.

On the client side, you can check the logs from `/$USER_HOME/twister/.twister_cache/`. Every EP has its own log.

If you notice a crash, or wish to report a bug, you can use the ``create_bug_report.py`` script from twister repo folder.