

# **Twister framework guide**

## **Contents**

- 1** - What is Twister
- 2** - How to install the framework
- 3** - Dependencies list
- 4** - Twister services
- 5** - How to compile the Java GUI
- 6** - Overview of the Java GUI
- 7** - How to define the suites and add tests
- 8** - How to run the test files
- 9** - How to configure the framework
- 10** - Performance and troubleshooting

# 1 - What is Twister?

Twister is an **open source** test automation framework.


The code can be downloaded from: <https://github.com/Luxoft/Twister>.

Twister helps building functional, regression and load test suites. It was developed taking in account the specific needs of the enterprise telecommunication market to help in testing telecommunication devices like switches, routers or PBXs.

Key features of Twister:

- web based GUI intuitive & user friendly interface ;
- easy to manage tests/ suites/ projects ;
- multi-user architecture ;
- real time monitoring of execution ;
- distributed execution: SUT's can be tested in parallel ;
- against same or different set of tests ;
- flexible reporting mechanism: DB schema is not fixed and there is no need to change framework to fit with a new DB schema ;
- support for different scripting languages and for record & play GUI tools ;
- support for Continuous Integration, Source Revision Control, Bug tracking ;
- support for GUI/ backend plugins: specific functionality loaded dynamically ;
- OpenFlow 1.3 module available for conformance testing.

## Concept



## 2 - How to install the framework

In order to install the Twister Framework, a few requirements must be met:

- **A Linux machine.** All the services must run on **Linux** (tested on *Ubuntu* and *OpenSuse*). Only the Execution Process can also run on Windows (with limited features);
- **Python 2.7.** Python is installed by default, on most Linux systems; the framework is written and tested in Python 2.7;
- **Python Tkinter.** Required only if you need to run TCL tests. This is included by default in Python, but some Linux distributions don't have the ``python-tk`` lib, so it has to be installed: ``sudo apt-get install python-tk``;
- **TCL Expect libraries.** Required only if you need to run TCL tests with Expect. To test the functionality, open a Python 2.7 interpreter, then type:

```
from Tkinter import Tcl
t = Tcl()
t.eval('package require Expect')
# If this fails, you must install Expect from your package manager, or compile it from sources
# The sources are at: sf.net/projects/expect; download, extract, ./configure, sudo make install
exit()
```

- **Perl Inline Python.** This is required only if you need to run Perl scripts.

The Twister repository is located at: <https://github.com/luxoft/twister>.

The installer is located in the folder ``installer`` and is also written in Python. It works only in Linux and must run as **ROOT**, because it will try to automatically install all the necessary Python libraries.

The recommended command for starting the installer:

```
sudo python2.7 installer.py
```

If you are installing the *Twister Server*, you should be connected to internet, or else, before running the installer, you must also install ``Python-DEV`` and then ``python-MySQL``.

In order to serve the Java applet, you will also need **Apache** or **Lighttpd** server and **Open-SSH** server.

You might need to configure the **proxy** to access the internet. In this case, edit the file ``installer.py``, locate the line with **HTTP\_PROXY** and type: `HTTP_PROXY = 'http://UserName:PassWord@http-proxy:3128'`. If the username and password are not required, you can omit them.

The *Twister Client* doesn't have any required dependencies. Some tests will require additional dependencies, for example: ``pExpect``, ``RpcLib``, ``Suds``, ``Requests``, or ``Gevent``.

The installer will guide you through all the steps:

1. Select what you wish to install (*client* or *server*);
2. If the ``twister`` folder is already present, you are asked to backup your data in order to continue, because everything is DELETED, except for the ``config`` folder.

Twister Client will be installed in the home of your user, in the folder ``twister``.

Any dependencies that are old, or missing, will be automatically downloaded and installed. If all the requirements are met, the client or server files are copied, nothing else is installed.

### **3 - Dependencies list**

The dependencies will be installed automatically when you first install Twister, if you have a connection on the internet.

- **LXML:** ([www.lxml.de/](http://www.lxml.de/))
  - XML and HTML documents parser;
  - LXML is included in Ubuntu by default. The other Linux distributions must install it;
- **MySQL-python:** ([mysql-python.sourceforge.net/](http://mysql-python.sourceforge.net/))
  - Connects to MySQL databases. It is only used by the Central Engine;
  - MySQL-python requires the *python2.7-dev* headers in order to compile;
- **CherryPy:** ([www.cherrypy.org/](http://www.cherrypy.org/))
  - High performance, minimalist Python web framework;
  - CherryPy is used to serve the Central Engine, Resource Allocator and Reports;
- **Mako:** ([www.makotemplates.org/](http://www.makotemplates.org/))
  - Hyperfast and lightweight templating for the Python platform;
  - Mako is used for templating the Central Engine REST and Report pages;
- **Beaker:** ([beaker.readthedocs.org/](http://beaker.readthedocs.org/))
  - Library for caching and sessions, in web applications and stand-alone Python scripts;
  - *Beaker is optional*; it is used by Mako, to cache the pages for better performance;
- **Scapy:** ([pypi.python.org/pypi/scapy-real/](http://pypi.python.org/pypi/scapy-real/))
  - Interactive packet manipulation tool;
  - *Scapy*, is used by the Execution Process to capture packets and send them to the applet;
- **pExpect:** ([sourceforge.net/projects/pexpect/](http://sourceforge.net/projects/pexpect/))
  - Spawn child applications, control them, respond to expected patterns in their output;
  - *pExpect is optional*; it is used by some Python test cases to connect to FTP/ Telnet;
- **RpcLib:** (<https://github.com/arskom/rpclib/>)
  - Create web services in Python (soap, rpc, rest servers);
  - *RpcLib is optional*; it is used by some Python test cases;
- **Suds:** (<https://fedorahosted.org/suds/>)
  - Lightweight SOAP python client for consuming Web Services;
  - *Suds is optional*; it is used by some Python test cases;
- **Requests:** (<http://docs.python-requests.org/>)
  - Elegant and simple HTTP library for Python, built for human beings;
  - *Requests is optional*; it is used by some Python test cases to connect to HTTP servers;
- **Gevent:** (<http://www.gevent.org/>)
  - Co-routine-based Python networking library that provides a high-level synchronous API;
  - *Gevent is optional*; it is used by some Python test cases to create sockets and threads;

## 4 - Twister services

Twister framework has 3 services:

1. The **Central Engine** = central server for script and library files. It includes the Resource Allocator and Service Manager servers. Must run as ROOT;
2. The **HTTP Server** = server for reporting framework and java applet GUI;
3. The **Execution Process** = client service that runs the script files (Python, TCL, Perl).

The executable scripts for starting the services are located in the ``bin`` folder:

- CE and Http Server are located in ``/opt/twister/bin``;
- Execution Process is located in ``/$USER_HOME/twister/bin``.

The first 2 services should run on the same machine, because they depend on the same configuration files.

The Linux EP service must be configured before run. You have to edit the file ``epname.ini`` from ``twister/config/`` folder; it contains the **name** of the EP, the **IP** and the **port** of the CE instance that it will run on.

To start the services, execute one of the following commands:

```
# Central Engine (ROOT!)
/opt/twister/bin/start_ce
# HTTP Server
/opt/twister/bin/start_http

# For Linux Execution Process
python /home/your_user/twister/bin/start_ep.py
```

### 4.1 - Central Engine REST interface

While the **Central Engine** service is running, you can access a web interface that allows viewing some statistics, logs and users connected. You can also start and stop the processes.

*REST interface Home;*

[Main](#) [Users](#) [Log](#)

## Central Engine REST interface

IP and Port	11.126.32.9:8000
Machine	tsc-server
System	Ubuntu 11.10 oneiric
Processor	---
Memory	■■■

Central Engine Logs;

⌂ Main

👤 Users

☰ Log

# Central Engine Log

Refresh ↻

13-01-09 11:14:40

DEBUG

\_\_init\_\_: CE: Starting Central Engine...

13-01-09 11:14:40

DEBUG

\_\_init\_\_: CE: Initialization took 0.0000 seconds.

13-01-09 11:14:40

INFO

[09/Jan/2013:11:14:40] ENGINE Listening for SIGHUP.

13-01-09 11:14:40

INFO

[09/Jan/2013:11:14:40] ENGINE Listening for SIGTERM.

13-01-09 11:14:40

INFO

[09/Jan/2013:11:14:40] ENGINE Listening for SIGUSR1.

13-01-09 11:14:40

INFO

[09/Jan/2013:11:14:40] ENGINE Bus STARTING

13-01-09 11:14:40

INFO

[09/Jan/2013:11:14:40] ENGINE Started monitor thread '\_TimeoutMonitor'.

13-01-09 11:14:41

INFO

[09/Jan/2013:11:14:41] ENGINE Serving on 0.0.0.0:8000

13-01-09 11:14:41

INFO

[09/Jan/2013:11:14:41] ENGINE Bus STARTED

User interface;

👤 Home

☰ Processes

☰ Logs

# User `tscguest`

Status	running (▶ start   ■ stop   ⚠ reset! )
Master config	/home/tscguest/twister/config/fwmconfig.xml
Project config	/home/tscguest/twister/config/testsuites.xml
DB config path	/home/tscguest/twister/config/db.contivity.xml
E-mail config path	/home/tscguest/twister/config/email.xml
EPs file	/home/tscguest/twister/config/epname.txt
Logs path	/home/tscguest/twister/logs

Control the processes;

The screenshot shows a web interface titled "Processes for `tscgquest`". At the top, there are navigation links: "Home", "Processes" (highlighted in blue), and "Logs". On the left, a sidebar lists five processes: "EP-1001", "EP-1002", "EP-1003", "EP-1004", and "EP-1005". Each process has a status icon (a circle with a square inside) and a play button icon. The "EP-1001" process is selected. To the right of the sidebar, there is an "Actions" bar with icons for play, pause, stop, and refresh. Below the actions bar, a tree view shows the structure of the selected process: "Suite1" containing four files: "/home/tscgquest/twister/demo/testsuite-python/init.py", "/home/tscgquest/twister/demo/testsuite-python/test002.py", "/home/tscgquest/twister/demo/testsuite-python/test001.py", and "/home/tscgquest/twister/demo/testsuite-python/test003.py".

Check all user logs;

The screenshot shows a web interface titled "Logs for `tscgquest`". On the left, a sidebar lists six log categories: "logCli EP-1001", "logCli EP-1002", "logDebug", "logRunning", "logSummary", and "logTest". The "logCli EP-1001" category is selected. The main area displays a log stream with the following content:

```
Py debug: For EP EP-1001, CE Server returned a new status: running.
EP debug: Received start signal from CE!
TC debug: TestCaseRunner started with User: tscgquest ; EP: EP-1001.
TC debug: Connected to proxy, running tests!
Downloading library `/home/tscgquest//twister/.twister_cache/EP-1001/ce_libs/ExposedLibraries.py` ...
Downloading library `/home/tscgquest//twister/.twister_cache/EP-1001/ce_libs/TscFtp.py` ...
Downloading library `/home/tscgquest//twister/.twister_cache/EP-1001/ce_libs/TscTelnet.py` ...

=====
Starting suite `100:Suite1`
=====

Downloading library `/home/tscgquest//twister/.twister_cache/EP-1001/ce_libs/TscFtp.py` ...
Downloading library `/home/tscgquest//twister/.twister_cache/EP-1001/ce_libs/TscTelnet.py` ...
```

This web service can be accessed in a browser, by going to: ``http://central-engine-IP:PORT/rest``,  
For **example**: ``http://localhost:8000/rest``.

## 5 - How to compile the Java GUI

The Java Graphical User interface compiled version can be found at ``twister/binaries/applet``. You have to copy the ``applet`` folder in ``/var/www`` and you will be able to access it in the browser.

If you have changed the sources, or you want to compile the JAR files yourself, the sources are located at ``twister/client/userinterface/java``. Some binary JAR files are already included in folders ``target`` and ``extlibs``, respectively.

After compilation, you have to move the JAR files so that a server can serve them (ex: Apache or Lighttpd).

Steps **1-2** require **Oracle JDK** (Oracle Java Development Kit).

Step **5** requires **Apache** or **Lighttpd** Server and your machine must have **OpenSSH Server** enabled.

Here are the steps:

1. Generate a key store, or import a certificate (*this is done only **the first time!***);

```
PATH_TO_JDK/bin/keytool -genkey -keyalg rsa -validity 360000 -alias Twister -keypass password -storepass password
```

OR

```
PATH_TO_JDK/bin/keytool -import -alias Twister -file certificate_file.cer
```

2. Go in ``client/userinterface/java``. Then, if you are on **Windows**, run ``pack.bat``, on **Linux** run ``.`/build.sh``.  
You might need to edit these files, to change the path to JDK\_PATH;
3. Move all files from ``target`` and ``extlibs`` in ``/var/www/twister`` (path for Apache, or other web servers);
4. Copy ``jquery.min.js`` from ``/opt/twister/server/httpserver/static/js`` also in ``/var/www/twister``;
5. Open a browser that supports Java Applets and go to: [http://localhost/twister`](http://localhost/twister).


## 6 - Overview of the Java GUI

The **first tab (Suites)** is split in four panes:


- **Top left**, is where the test suites are defined. Any file from the right can be dragged in here. The files can be checked/ unchecked; the files that are not checked will not run;
- **Top right**, is where the test files are located. These files can be used in the suites;
- **Bottom left**, is where the project, suite and test information is added. The suite information is defined in the file ``DB.xml``, section name ``field_section`` (*more about this in the configuration section*);
- **Bottom right**, you can see the title and description of the currently selected test file.



A configuration, with Python scripts:




A different configuration, with TCL scripts:



## While running:

- You can check test lists with their statuses. By default, all tests are in pending, unless they recently ran, in which case the most recent status is displayed;
- Logs for the tests. The logs can be cleaned, exported, or searched for keywords.


Here the Central engine is stopped; in this case you can see the most recent statuses:



At the top, there are two buttons, which control the Central Engine: **Run/ Pause** and **Stop**.

Also at the top, is the status of the Central Engine, the time of the last start, time elapsed and the user that started it.

While the Central engine is running:



The **Reports Tab**

When clicking on it, the reports page will open in a new tab.

*Reporting home* (this will look different, depending on the configuration)

Home

Details (build)

Details (suite)

History

Summary

Pass Rate

goto Yahoo

goto Google

Help

Twister reporting

Welcome !  
Please choose a report from the left.

*A report with user chosen fields;*

Home

Details (build)

Details (suite)

History

Summary

Pass Rate

goto Yahoo

goto Google

Help

Required fields

Select build V06\_05.190

Select Cancel

*The same report, after the user chose the build;*

Home

Details (build)

Details (suite)

History

Summary

Pass Rate

goto Yahoo

goto Google

Help

Details (build) Report

for Build="V06\_05.190"

10 records per page

Search:

no_regression	suite_name	test_name	status	date	build	run_no	logfilename
45999	RETRIEVE	RETRIEVE_001	PASS	2008-10-18 12:43:44	V06_05.190	1	V06_05.190_2007_10_18_12_36
46000	BO	T-001	PASS	2008-10-18 12:59:54	V06_05.190	1	V06_05.190_2007_10_18_12_36
46001	BO	T-002	PASS	2008-10-18 13:01:10	V06_05.190	1	V06_05.190_2007_10_18_12_36
46002	BO	T-003	PASS	2008-10-18 13:02:24	V06_05.190	1	V06_05.190_2007_10_18_12_36
46003	BO	T-007	PASS	2008-10-18 13:02:56	V06_05.190	1	V06_05.190_2007_10_18_12_36
46004	BO	T-008	PASS	2008-10-18 13:03:28	V06_05.190	1	V06_05.190_2007_10_18_12_36
46005	BO	T-009	PASS	2008-10-18 13:04:02	V06_05.190	1	V06_05.190_2007_10_18_12_36
46006	BO	T-012	PASS	2008-10-18 13:05:13	V06_05.190	1	V06_05.190_2007_10_18_12_36
46007	BO	T-013	PASS	2008-10-18 13:06:27	V06_05.190	1	V06_05.190_2007_10_18_12_36
46008	BO	T-014	PASS	2008-10-18 13:07:43	V06_05.190	1	V06_05.190_2007_10_18_12_36

no\_regression suite\_name test\_name status date build run\_no logfilename

Showing 1 to 10 of 739 entries

Previous

1

2

3

4

5

Next

## The **configuration tab**

Here, you can configure:


- Central Engine port (*default 8000*). This is the port the applet will use for connection;
- the path of the test files, logs files, user files;
- the path of the database xml, e-mail xml, EP names;
- the names of the log files;
- e-mail configuration;
- database configuration;
- devices configuration for Test Bed;
- global variables, injected in all Twister test files;
- panic detect: checks errors in CLI logs.

More about this in **Configure the framework** section.


## 7 - How to define the suites and add tests

When starting the interface, you must first *select or create* a **project file**. This file will save your suites, script files and suites configurations.

Each project has a set of global settings:



- **Stop on fail** = if a test that is mandatory will not run successfully, or will crash, all the project will fail ;
- **DB Autosave** = after all the tests from all suites finish execution, the Central Engine will save the results into database, without asking the user ;
- **TC Delay** = after each test, the EP will wait X seconds, before starting to execute the next test ;
- **Pre execution script** = the script from this path will be executed by the Central Engine **before** running any test. The script can be written in any language (Perl, TCL, binary executable, etc). You cannot use a normal Twister test as a Pre/ Post exec script! If you write a script in an interpreted language, don't forget to add ``#!/usr/bin/env ...your_language`` on the first line. If the file is not executable, CE will automatically run ``chmod +x`` on the file ;
- **Post execution script** = the script from this path will be executed by the Central Engine **after** running all tests. It has the same specifications as the Pre execution script ;



After setting the project file, click on **Add Suite** (Add suite). The required fields are: **the name** of the suite and **one or Test beds** (the workstation(s) where the tests from this suite will run).


A suite is basically a folder, where one or more script/ test files can be added, that will be executed by Execution Processes.

Each suite can also have some properties attached to it, like ``release``, ``build``, ``comments``, etc. These fields are defined in ``DB.xml`` file (*more about this in the database configuration section*) and will look different, depending on the configuration (text box, drop down list, path to a script, etc.).

These ``meta`` properties are used while saving the results into database.

The script/ test files and the suites can be re-arranged anytime, using drag & drop, or can be deleted.

Each script/ test file has a few properties too:




TC options

TC name:

☒ Runnable ☐ Optional ☐ pre-requisites

- a test that is not *Runnable* will be sent to **EP**, but will never execute ;
- *Optional* tests that fail, will not stop the EP when *Stop on Fail* checkbox is active ;
- *Pre-requisite* tests are always mandatory and if they *fail*, the entire Suite is considered *Failed*.




New project file  
Open project file  
Save project file  
Save project as  
Delete project file  
Open from local  
Save to local

In order to save the **project file**, use the *File menu*:


You can download the project file locally, to share it with the team members.

## 8 - How to run the test files









After all the suites and scripts are set, click on: , to start the execution.

What will happen is that, all **checked** scripts from all suites will run, in order. The execution doesn't stop if one of the scripts fails, excepting the case when the test that fails is *mandatory* and the *Stop on Fail* checkbox is checked.

If the **Run** button is disabled, it means that the Central Engine service is not running, so the execution cannot start. If the **Run** button is enabled, you can start the execution. At the same time, the **Stop** button will activate, allowing to stop the Central Engine and kill all the running processes and the **Run** button will become **Pause**, allowing to pause after the current tests finishes its execution.

If the Central Engine was started recently, by default all the files will be in state *pending*  . If a previous run was completed, the most recent status is displayed (*pass, failed, etc.*).

The states for the files and their respective icons are:

-  (running) while the file is running;
-  (pause) if the test is paused;
-  (success) if the execution was successful;
-  (failure) if the execution failed;
-  (skip) if the file was marked as skip (*runnable=false*);
-  (abort) if the file was stopped while running;
-  (not executed) if the file was paused and was stopped instead of being resumed;
-  (dependency) is the file depends on another file and the dependency didn't finish its execution, so this file is waiting.

While the tests are running, the logs from the left will update, showing the live output.

When a test is completed, the icon will change to Pass or Fail. All the history of result can be seen in the ``log_summary.log``.

The logs can be cleaned, exported, or searched for keywords, by clicking the buttons from the bottom.

## 9.0 - Twister configuration files

Twister has a few configuration files: XML, ini, or Json.

There are 2 types of configurations: per user (located at `/$USER_HOME/twister/config`) and global for all users (located at `/opt/twister/config`).

- **fwmconfig.xml**: the **master framework config**. Contains the paths to all the other config files. Config saved per user;
- **epname.ini**: contains all the EPs for the current user. **This must be edited manually**. Config saved per user;
- **email.xml**: contains all the information necessary to send an e-mail from Twister. Config saved per user;
- **db.xml**: contains all the information about saving and reading from the MySQL database. **This must be edited manually**. Config saved per user;
- **globals.xml**: contains all global variables, per user;
- **plugins.xml**: contains information about all plugins, per user;
- **testsuites.xml**: contains all suites and all files for the current run. Saved per user;
- **resources.json**: contains all the resources from Resource Allocator server, all testbeds and devices. It's a global config;
- **services.ini**: contains all the services from Service Manager. It's a global config;

Most of the files are generated automatically from the Java applet. They **should not** be edited manually, unless specified otherwise.

## 9.1 - Configure the paths

The screenshot shows a web-based configuration interface with three tabs: 'Project', 'Reports', and 'Configuration'. The 'Configuration' tab is active. On the left side of the 'Configuration' tab, there is a vertical menu with buttons for 'Paths', 'Email', 'Database', 'Test Beds', 'Global Parameters', 'Panic Detect', 'Services', and 'Plugins'. The main area of the 'Configuration' tab contains several sections for setting paths and log files:

- TestCase Source Path**: Master directory with the test cases that can be run by the framework. The path is `/home/tscquest/twister/demo`.
- Projects Path**: Location of projects XML files. The path is `/home/tscquest/twister/config/users`.
- EP name File**: Location of the file that contains the Ep name list. The path is `/home/tscquest/twister/config/epname.ini`.
- Logs Path**: Location of the directory that stores the logs that will be monitored. The path is `/home/tscquest/twister/logs/`.
- Log Files**: All the log files that will be monitored. This section contains five input fields:
  - Running: `log_running.log`
  - Debug: `log_debug.log`
  - Summary: `log_summary.log`
  - Info: `log_test.log`
  - CLI: `CLI.log`

★ All the paths below refer to the computer where the **Central Engine** is running.

**Test case source path** represents the folder where all test files are located. The files here can be dragged inside suites, in the first tab (suites).

**User's path** is the folder where the profiles are saved, in the first tab. Usually, this doesn't need to be changed.

**EP Names** file stores the list of EPs (the workstations where tests will run). An `EP` is just a name to uniquely identify a computer, it can be any string.

**Logs path** is the folder where all the logs are written. There are 5 major logs: log running, log debug, log summary, log info, and log CLI. Each of the logs will be saved in the logs path, with the name defined in the configuration. Usually, the logs don't need to be changed.

**E-mail XML path**, **Database XML path** and **Globals XML path** are the files that store the information for the next 3 tabs. You can have multiple files, and switch between configurations.

**The Central Engine port** and **HTTP Server port** are, of course, the ports where the applet connects to the respective servers. The default values are: 8000 and 8080.



## 9.2 - Configure the e-mail

Project Reports Configuration

Paths  
Email  
Database  
Test Beds  
Global Parameters  
Panic Detect  
Services  
Plugins

SMTP server  
IP/Name: smtp.itcnetworks  
Port: 25

Authentication  
User: MyUser  
Password: ••••  
From: MyUser@luxoft.com

Email List  
Xxx@luxoft.com

Subject  
Report for \$release\_id \$build\_id [\$date]

Message

Enabled ☒  
Save

Here you can configure the parameters required to connect to a SMTP server and send an e-mail.

The Central Engine will send the e-mail every time the execution finishes for ALL the test files.

The most important fields are: SMTP *IP* and *port*, *username*, *password*, *from* and the *e-mail list*.

Optionally, you can change the subject and add a few lines in the message body.

Both the subject and the message, can contain template variables from `DB.xml`, section name `field\_section`.

For example, if you defined the fields with IDs `release\_id`, `build\_id`, `suite`, you can write the subject like :

```
E-mail report for R{release_id} B{build_id} - {suite} [{date}]
```

If your release number is `2`, build number is `15` and suite is `Branch Test1`, the subject will be generated like:

```
E-mail report for R2 B15 - Branch Test1 [2012.03.23 13:24]
```

## 9.3 - Configure the database

The screenshot shows a web-based configuration interface. At the top, there are three tabs: 'Project', 'Reports', and 'Configuration'. The 'Configuration' tab is active. On the left side, there is a vertical menu with buttons for 'Paths', 'Email', 'Database', 'Test Beds', 'Global Parameters', 'Panic Detect', 'Services', and 'Plugins'. The main content area is titled 'Configuration' and contains a form for database settings. The form has the following fields and controls:

- File:** A text input field with a 'Browse' button and an 'Upload' button.
- Database:** A text input field containing the value 'TestDB'.
- Server:** A text input field containing the value 'tsc-server'.
- User:** A text input field containing the value 'tsc'.
- Password:** A text input field with masked characters (dots).
- Save:** A button located below the Password field.

All the database information is stored in `DB.xml` file, by default. This file can be changed from the interface, in the **Paths tab**. You can have multiple configurations and switch between them.

**Most of this file must be edited manually.** In the root of the XML file, there are 2 sections: `**db\_config**`, that is written by the interface and `**twister\_user\_defined**`.

The section `**twister\_user\_defined**` has 3 sub-sections: `**field\_section**`, `**insert\_section**` and `**reports\_section**`.

The **field section** contains all the information that was defined in the **Suites tab** for each and every suite, things like: release, build, station, comments, etc.

This information is used when saving the execution results into the database and when sending the report e-mail.

Each field must contain the following tags:

- **ID**: represents the name of the field and MUST be unique;
- **Type**: there are 3 types of fields: **UserSelect**, **DbSelect** (where you must define an SQL query that will generate a list of value in the interface; the user will select 1 value and that will be saved; the difference between them is that DbSelect will not be shown in the interface) and **UserText** (free text, you can write anything);
- **SQLQuery**: this is required for UserSelect and DbSelect fields. The query must be defined in such a way that the values will be unique (eg: by using SELECT DISTINCT id, name FROM ...) and should select 2 columns. The first column will be the ID and second will be the description of the respective ID;
- **GUIDefined**: if a field is not GUI defined, it will be visible in the **Suites tab**, when editing suites;
- **Mandatory**: if a field is mandatory, each suite from the **Suites tab** must have a value for this field. If the user doesn't choose a value, he will not be able to save the profile, or generate the Suites XML;
- **Label**: a short text that describes the field, in the interface; it's not necessary for DbSelect fields, because they are not visible in the interface.

### Examples of fields:

```
<field ID="res_id" Type="DbSelect"
SQLQuery="select MAX(id)+1 from repo_test_view"
Label="-" GUIDefined="false" Mandatory="true" />

<field ID="release_id" Type="UserSelect"
SQLQuery="select DISTINCT id, release_name from t_releases"
GUIDefined="true" Mandatory="true" Label="Release:" />

<field ID="build_id" Type="UserSelect"
SQLQuery="select DISTINCT id, build_name from t_builds"
Label="Build:" GUIDefined="true" Mandatory="true" />

<field ID="comments" Type="UserText" SQLQuery=""
Label="Set comments:" GUIDefined="true" Mandatory="false" />
```

The **insert section** defines a list of SQL queries that will execute every time the execution finishes for ALL the test files. All queries are executed for each and every test file.

The insert queries use the information from the fields described above. A file can only access the fields defined in his parent suite.

Other than that, the queries can access a list of variables passed from the Central Engine, which describe how the execution was completed. Here are the variables:

- **\$twister\_ce\_os** = the operating system of the computer where Central Engine runs;
- **\$twister\_ep\_os** = the operating system of the computer where Execution Process runs;
- **\$twister\_ce\_ip** = the IP of the Central Engine;
- **\$twister\_ce\_hostname** = the host name of the Central Engine;
- **\$twister\_ep\_ip** = the IP of the Execution Process;
- **\$twister\_ep\_hostname** = the host name of the Execution Process;
- **\$twister\_ep\_name** = EP name, defined in **Suites tab**;
- **\$twister\_rf\_fname** = the path to Twister resources file (default is `resources.json`);
- **\$twister\_pf\_fname** = the path to Twister project file (default is `project\_users.json`);
- **\$twister\_suite\_name** = suite name, defined in **Suites tab**;
- **\$twister\_tc\_name** = the file name of the current test;
- **\$twister\_tc\_full\_path** = the path + file name of the current test;
- **\$twister\_tc\_title** = the title, from the **Suites tab**;
- **\$twister\_tc\_description** = the description, from the **Suites tab**;
- **\$twister\_tc\_status** = the final status of the test: pass, fail, skip, abort, etc;
- **\$twister\_tc\_crash\_detected** = if the file had a fatal error that prematurely stopped the execution;
- **\$twister\_tc\_time\_elapsed** = time elapsed;
- **\$twister\_tc\_date\_started** = date and time when the running started;
- **\$twister\_tc\_date\_finished** = date and time when the running finished;
- **\$twister\_tc\_log** = the complete log from execution.

These variables can be used in the query like ` \$variable\_name `, or ` @dbselect\_field\_name@ `.

Only the fields of type **DbSelect** are surrounded by @.

### Examples of database inserts:

```
<sql_statement>
INSERT INTO gg_regression
(suite_name, test_name, status, date_start, date_end, build, machine)
VALUES
( '$twister_suite_name', '$twister_tc_name', '$twister_tc_status',
'$twister_tc_date_started', '$twister_tc_date_finished', '$release.$build',
'$twister_ep_name' )
</sql_statement>
```

Or:

```
<sql_statement>
INSERT INTO results_table1
VALUES
( @res_id@, $release_id, $build_id, $suite_id, $station_id, '$twister_tc_date_finished',
'$twister_tc_status', '$comments' )
</sql_statement>
```

★ In this last example, `res\_id` is a DbSelect field with the query defined as:  
`SELECT MAX(id)+1 FROM results\_table1`.

The **reports section** defines all the information exposed to the reporting framework.

In this section you can define the *fields*, the *reports* and the *redirects*.

The **fields** must have the following properties:

- **ID**: represents the name of the field and MUST be unique;
- **Type**: there are 2 types of fields: **UserSelect** (where you must define an SQL query) and **UserText** (free text, you can write anything);
- **SQLQuery**: this is required only for UserSelect fields. The query should select two columns: the first is the ID and the second is a name, or a description of the respective ID. If the table where you have the data doesn't have any description associated with the ID, you can use only the ID;
- **Label**: a short text that describes the field, when the user is asked to select a value.

### Examples of report fields:

```
<field ID="Dates" Type="UserSelect" Label="Select date:"
SQLQuery="SELECT DISTINCT date FROM results_table1 ORDER BY date" />

<field ID="Statuses" Label="Select test status:" Type="UserSelect"
SQLQuery="SELECT DISTINCT status FROM results_table1 ORDER BY status" />

<field ID="Releases" Label="Select release" Type="UserSelect"
SQLQuery="SELECT DISTINCT SUBSTRING(build, 1, 6) AS R FROM results_table1 ORDER BY R" />

<field ID="Other" Type="UserText" Label="Type other filters:" SQLQuery="" />
```

The **reports** must have the properties:

- **ID**: represents the name of the report and MUST be unique;
- **Type**: there are 4 types of reports: **Table** (an interactive table is generated; the table can be sorted and filtered dynamically), **PieChart**, **BarChart** and **LineChart** (they show both the chart and the table; for PieChart report, the SQL query must be defined in such a way that the first column is a string describing the data, and the second column is an integer or float data; BarChart and LineChart must also have the query generate 2 columns, the first is a number and the second is a label or another number);
- **SQLQuery**: all reports must define an SQL query. If the type of report is Table, it can select any number of fields (although it's recommended to use a maximum of 10, to fit on the screen without having to scroll to the right). If the report is a chart, you must select only 2 columns. The query can use any, or none of the fields described above. When a field is used in the query, the reporting framework will require the user to choose a value, before displaying the report.

*Examples or reports:*

```
<report ID="Details (build)" Type="Table"
SQLQuery="SELECT * FROM results_table1 WHERE build='@Build@' ORDER BY id" />

<report ID="Details (suite)" Type="Table"
SQLQuery="SELECT * FROM results_table1 WHERE build='@Build@' AND suite_name='@Suite@' " />

<report ID="Summary" Type="PieChart"
SQLQuery="SELECT status AS 'Status', COUNT(status) AS 'Count' FROM results_table1 WHERE build=
'@Build@' group by status " />

<report ID="Pass Rate" Type="LineChart"
SQLQuery="SELECT Build, COUNT(status) AS 'Pass Rate (%)' FROM results_table1 WHERE Build LIKE
'@Release@%' AND status='Pass' GROUP BY Build"
SQLTotal="SELECT Build, COUNT(status) AS 'Pass Rate (%)' FROM results_table1 WHERE Build LIKE
'@Release@%' GROUP BY Build" />
```

The **redirects** must have the properties:


- **ID**: represents the name of the redirect and MUST be unique. Ideally, the ID should start with the word ``goto``;
- **Path**: is the full path to a HTML page. It can be a link to a static page, to PhpMyAdmin for the current database, or a user web page served by any web server.

*Examples of redirects:*

```
<redirect ID="goto PhpMyAdmin" Path="http://my-server/phpmyadmin" />

<redirect ID="goto PHP Report" Path="http://my-server/some-report.php" />
```

## 9.4 - Config the devices (testbed)



The Resource Allocator server is integrated inside Central Engine. It is used to view and edit the testbed properties.  
**The testbed is global for all users.**

Each device == node == resource must have a name and some properties in the form of : `{key: value}`.

The name of a resource must be unique in its parent. For example you cannot have more nodes called `Device1` in parent `Testbed1`, but you can have nodes called `Device1` for both `Testbed1` and `Testbed2`. This is important, because each resource can be accessed using its ID, or its full path (just like a unix filesystem).

The Resource Allocator server exposes a simple API for accessing the resources:

- **getResource**( ID or full path ) - returns a dictionary containing all the node properties
- **setResource**( name, parent ID or full path, properties in dictionary or JSON string)

- This function is used to CREATE and MODIFY nodes. If the resource is created, the ID of the new resource is returned. If the resource is updated, the function returns True.

Example: `setResource('module1', '/tb1/device2', '{"ip":"10.0.0.1", "port":"80"}')`;

- **renResource**( ID or full path, new name ) - renames resources or properties
- **deleteResource**( ID or full path ) - deletes resources or properties
- **getResourceStatus**( ID or full path ) - obsolete

### Examples:


Let's say there are 3 testbeds: *tb1*, *tb2*, *tb3*. Each testbed has 2 devices: *dev1* and *dev2*. Each device has 3 modules: *mod1*, *mod2*, *mod3*.

To access module 2 from device 1 from testbed 3, you can use: `getResource('/tb3/dev1/mod2')`.

To access testbed 1, you can use: `getResource('/tb1')`.

To rename device 2 from testbed 2, you can use: `renResource('/tb2/dev2', 'dev_x2')`. Note that the new name is just a string, not the full path.

## 9.5 - Config the global parameters



Global parameters are variables available in all test files. There is no need to import any library.

**The parameters are stored per user.**

The API is very simple: **getGlobal**( name ) and **setGlobal**( name, value ).

If the *name* is a folder (not a variable with a value), instead of a value, **getGlobal** returns a dictionary. If the parameter *name* doesn't exist, **getGlobal** returns *False*.

The **setGlobal** function will update, create or delete parameters. If the name exists, it is updated. If it doesn't exist, it is created. If you use **setGlobal**( name, False), the parameter is deleted.

The changes made by **setGlobal** are temporary and RESET every time the tests start running.

There are 3 types of parameters:

1. the default parameters stored in the configuration, that are saved in globals.xml file ;
2. the serializable parameters saved by the test files are shared between all Eps from a user ;
3. the complex, not serializable parameters are stored on the EP that is running the tests.

## 9.6 - Config `panic detect`

Project

Reports

Configuration

Paths

Email

Database

Test Beds

Global Parameters

Panic Detect

Services

Plugins

Regex: CORE-DUMP☒ EnabledRemove

Regex: has CRASHED☒ EnabledRemove

Regex: CRITICAL ERROR☐ EnabledRemove

Add

Panic detect is a mechanism that allows the users to add `expressions` that will be searched in the test logs. If any of the expressions is detected, the execution STOPS.

An `expression` can be a normal string, or a regex.

This is useful to check for core dumps and critical errors; in these extreme cases, it's useless to run any test.



## 9.7 - Services and Plug-ins

Print screen with Services

ProjectReportsConfiguration

PathsEmailDatabaseTest BedsGlobal ParametersPanic DetectServicesPlugins

ofcontroller 1

Openflow controller 1

stopped

Start

Stop

Configuration

ofcontroller 2

Openflow controller 2

stopped

Start

Stop

Configuration

ofcontroller 3

Openflow controller 3

stopped

Start

Stop

Configuration

Scheduler

Scheduler Server

stopped

Start

Stop

Configuration

Print screen with Plug-ins

ProjectReportsConfiguration

PathsEmailDatabaseTest BedsGlobal ParametersPanic DetectServicesPlugins

Local

Local installed plugins

ServiceManagement.jar

Remove

UserName.jar

Remove

Scheduler.jar

Remove

Remote

Remote plugins found on server

PacketsTwistPlugin.jar

Download

GITPlugin.jar

Download

JiraPlugin.jar

Download

SVNPlugin.jar

Download

JenkinsPlugin.jar

Download

☐ Activate

Scheduler.jar

Scheduler

Read more

☐ Activate

ServiceManagement.jar

ServiceManagement plugin

Read more

☐ Activate

UserName.jar

Plugin to display user name

Read more

More about this in the **`Twister Libraries, Plugins, Services`** help file.

## How to write Twister tests

Twister framework can run **Python**, **TCL** and **Perl** (limited) tests.

Writing a **Twister test** is just like writing a normal Python 2.7 test, or TCL 8.5 test, or Perl test, with a few exceptions.

Twister tests are most likely **incompatible** with the original language; for example a Twister Python test will not run with Python by default, because Twister inserts a few helper variables and functions, which are not available in the usual environment. So if the a test uses the helper variables and functions, the script will become incompatible with the original Python/ TCL/ Perl language and will be executed only from Twister.

Variables inserted in all Twister tests:

- **USER** : the username running the current test ;
- **EP** : the name of the Execution Process running the current test ;
- **SUITE\_NAME** : the name of the suite that contains the current test ;
- **FILE\_NAME** : the full path of the test file from the machine that runs the Central Engine ;
- **currentTB** : the current test bed ;
- **PROXY** : this is a pointer to the Central Engine XML-RPC server. It is used for development.

And a few functions:

- **logMsg**( logType, message ) : this function sends a message in a special log and will not appear in the CLI. Valid log types are : *logRunning*, *logDebug* and *logTest*. It is used for sending debug messages from the tests.
- **getGlobal**( path ) : get a global parameter;
- **setGlobal**( path, new\_value ) : set a global parameter;
- **py\_exec** some\_python\_command : this function works **only in TCL** tests and allows running Python commands, or calling functions and objects from global parameters, defined in the previous tests.

## **10 – Performance and troubleshooting**

The Central Engine and the Reporting Server are instances of Python CherryPy and were tested with 750+ simultaneous connections, without crashing, or losing connection.

★An article concerning python web servers: <http://nichol.as/benchmark-of-python-web-servers>.

Even if the Central Engine is fast enough, for a smooth experience, it's not recommended to run more than 50 Execution Processes on one Central Engine instance. If you need more, you can simply open another instance of CE, on a different port and connect the rest of the clients on the new one.

The Execution Processes are running on different workstations and their performance depends on the hardware of the respective machine.

All services have logs that describe every operation that is being executed. If something fails, it will be easy to know where exactly the error was produced.

On the server side, you can check the logs from `/opt/twister/ce_log.log` and `/opt/twister/http_log.log`, or `/opt/twister/logs/` folder.

On the client side, you can check the logs from `/$USER_HOME/twister/.twister_cache/`. Every EP has its own log.