

Table of Contents:

| | |
|--------------------------------------|----------|
| Moving Exercise | 1 |
| Introduction | 1 |
| Data - Input File | 1 |
| Data - Output File | 2 |
| Processing Required | 2 |
| Arithmetic Exercise | 3 |
| Introduction | 3 |
| Data - Input File | 3 |
| Data - Good Output File | 3 |
| Data - Bad Output File | 4 |
| Processing Required | 4 |
| Validation Required | 4 |
| Input JCL | 5 |
| Subscribing/Indexing Exercise | 6 |
| Introduction | 6 |
| Data - Input File | 6 |
| Processing | 6 |
| Extraction Exercise | 7 |
| Introduction | 7 |
| Data - Good Input File | 7 |
| Data - Extracted Good Output File | 8 |
| Processing | 8 |
| Update Exercise | 9 |
| Data - Extracted Good Input File | 9 |
| Data - Master Input File | 10 |
| Data - New Master Output File | 10 |
| Data - Control Report File Format | 11 |
| Processing | 11 |

Moving Exercise

Introduction

An input file is provided with 2 records per customer. Information will be taken from each record to produce one output file with the selected data.

Data - Input File

This is for **Record A**

| Field | Type | Size |
|-----------------|--------------|------|
| Account Number | Alphanumeric | 8 |
| Account Name. | | |
| Title | Alphanumeric | 3 |
| Initials. | | |
| First initial | Alphanumeric | 1 |
| Middle initial | Alphanumeric | 1 |
| Surname | Alphanumeric | 30 |
| Date of Issue | Alphanumeric | 8 |
| Date of receipt | Alphanumeric | 8 |
| Balance | Numeric | 10 |
| Filler | Alphanumeric | 10 |
| Type | Alphanumeric | 1 |

This is for **Record B**

| Field | Type | Size |
|----------------|--------------|------|
| Account Number | Alphanumeric | 8 |
| Address. | | |
| Number | Numeric | 4 |
| Street | Alphanumeric | 20 |
| Town | Alphanumeric | 20 |
| County | Alphanumeric | 10 |
| Postcode | Alphanumeric | 10 |
| Filler | Alphanumeric | 7 |
| Type | Alphanumeric | 1 |

Data - Output File

| Field | Type | Size |
|----------------|--------------|------|
| Account number | Alphanumeric | 8 |
| County | Alphanumeric | 10 |
| Balance | Numeric | 9 |
| Unused | Alphanumeric | 51 |
| Type | Alphanumeric | 1 |

Processing Required

Records will be in order in the input file, record A followed by B followed by A etc. Output file should consist of the account number and balance taken from record A and the county taken from record B as well as an unused field of spaces and type containing a 0.

- The input file is NDRD0.GDVD181.CBLPROG1.INPUT1
- You can write your own JCL or use NDRD0.GDVD181.JCLLIB.TEST(PROG1JCL)
- Write this is DTB – it'll be fun.

The COBOL version of the program is NDRD0.GDVD181.SOURCE.TEST(CBLPROG1), if it were me I'd start with re-writing the main proc logic, the moves.

Arithmetic Exercise

Introduction

In a department store that may or may not be running a sale on a particular day, a record is created for every item that is sold in any of its five departments. The records are input over a monthly period, in no particular sequence.

Data - Input File

| | | |
|----------------|--------------|---|
| Department | Numeric | 1 |
| Quantity | Numeric | 4 |
| Retail Price | Numeric | 5 |
| Sale Price | Numeric | 5 |
| Invoice Number | Alphanumeric | 5 |
| Sale indicator | Alphanumeric | 1 |

Data - Good Output File

| | | |
|--------------|--------------|----|
| Department 1 | Numeric | 1 |
| Total 1 | Comp-3 | 7 |
| Department 2 | Numeric | 1 |
| Total 2 | Comp-3 | 7 |
| Department 3 | Numeric | 1 |
| Total 3 | Comp-3 | 7 |
| Department 4 | Numeric | 1 |
| Total 4 | Comp-3 | 7 |
| Department 5 | Numeric | 1 |
| Total 5 | Comp-3 | 7 |
| Filler | Alphanumeric | 55 |

Data - Bad Output File

| | | |
|----------------|--------------|------------------------|
| Department | Numeric | 1 |
| Error | Alphanumeric | 5 (value always Error) |
| Invoice Number | Alphanumeric | 4 |
| Filler | Alphanumeric | 70 |

Processing Required

Each input record is to be validated as required in the section below.

Any invalid records will generate an error record on output file B, you can also add displays to identify which validation lead to the error being written. Valid records are to be accumulated into 1 of 5 department totals, the value being determined by multiplying the quantity by the appropriate price.

At the end of the input file, one record is to be produced on output file A with the department number and the total sales for each department.

Validation Required

1. The department number is in the range of 1-5
2. The indicator field can only contain the letter S or a space
3. Quantity, retail price and sale price are all numeric
4. Quantity and retail price are greater than 0
5. The first character of the invoice is A through R inclusive and the rest of the field is numeric
6. If the indicator field is blank then the sale price is 0
7. If the indicator field contains the letter 'S' then the sale price is present with the sale price less than the retail price.

Input JCL

NDRD0.GDVD181.CBLPROG2.GOOD1 is a file that contains perfectly correct data – write yourself a test plan of what you think you need to check (the 7 points above are a clue) and then you can edit the file to create these scenarios e.g. changing one of the department numbers to 6 should fail – that would be a test.

NDRD0.GDVD181.CBLPROG2.BAD1 is a file that already has errors in and will test your validation, if you're having problems testing it yourself you can use this file to hopefully narrow down where the issue is. *Jamie/Carl and Yvette will have the results from this.*

You can write your own JCL to execute the program but if you get stuck then you can use NDRD0.GDVD181.JCLLIB.TEST(PROG2JCL).

I've created a linkparm member for you in NDRD0.GDVD***.LINKPARM – it's based on you naming your program CBLPROG2 so if you don't then you'll have to change the linkparm accordingly. The linkparm is used for when you TSO BIND.

Subscribing/Indexing Exercise

Introduction

The way people have voted is recorded on records – the file should consist of one constituency (indicated by a four-character identifier). Each column holds a person's vote as a single digit in the range of 0-6 to indicate the party voted for.

The parties are as follows:

- 0 – Raving Loony Party
- 1 – Conservative
- 2 – Plaid Cymru
- 3 – Free Cleethorpes
- 4 – Labour
- 5 – Liberal
- 6 – Scottish National
- 7 – Spoilt votes

Data - Input File

Cols 1-4 is for the Constituency Identifier

Cols 5-76 is for the Votes

Each column could contain a vote in the range of 0-6. Consecutive columns are used, but a record could finish before column 76 with a space character which is not a spoilt vote)

Cols 77-80 is for Spaces

Processing

Count all the votes for each party.


The constituency ID will be input as a parameter in JCL. Any record that does not match the identifier will have its total number of votes added to Spoilt votes.

Any vote not in the range of 0-6 should also be in Spoilt votes. Produce, on a print file, a single page listing at the end of the run showing each party, Spoilt votes, the number of votes achieved and the winning party with *** next to the name.

Extraction Exercise

Introduction

In this exercise, you'll need to create an extract program based on the diagram below. This exercise precedes the next one.



Data - Good Input File

The records are input into the program in no particular sequence. It is **NOT** possible to have 2 or more input records with the same account number.

| | | |
|---------------------|--------------|----|
| Account Number | Numeric | 5 |
| Initial | Alphanumeric | 1 |
| Surname | Alphanumeric | 20 |
| Credit/Debit Marker | Alphanumeric | 1 |
| Transaction Amount | Numeric | 5 |
| Transaction Date | Numeric | 8 |
| Transaction Details | Alphanumeric | 20 |
| Not Used | Alphanumeric | 20 |

Data - Extracted Good Output File

The records are output from the program in no particular sequence. It is **NOT** possible to have 2 or more extracted good records with the same number.

| | | |
|---------------------|----------------|----|
| Account Number | Alphanumeric | 5 |
| Credit/Debit Marker | Alphanumeric | 1 |
| Transaction Amount | Packed Decimal | 5 |
| Transaction Date | Numeric | 8 |
| Initial | Alphanumeric | 1 |
| Surname | Alphanumeric | 20 |
| Not Used | Alphanumeric | 20 |

Processing

Each input record on the Good File will produce an output record on the Extracted Good File.


When the Credit/Debit Marker has the value 'D' then the Transaction Amount must be held as a negative value.

The Transaction Date must be held in the format - YYYYMMDD.

Blanks must be held in the Not Used field.

Update Exercise

In this exercise, you'll need to create an update program based on the diagram below.



Data - Extracted Good Input File

The records are input into the program in **ascending** account number sequence. It is **NOT** possible to have 2 or more input records with the same account number.

| | | |
|---------------------|----------------|----|
| Account Number | Alphanumeric | 5 |
| Credit/Debit Marker | Alphanumeric | 1 |
| Transaction Amount | Packed Decimal | 5 |
| Transaction Date | Numeric | 8 |
| Initial | Alphanumeric | 1 |
| Surname | Alphanumeric | 20 |
| Not Used | Alphanumeric | 20 |

Data - Master Input File

The records are input into the program in **ascending** account number sequence. It is **NOT** possible to have 2 or more input records with the same account number.

| | | |
|-------------------------|----------------|----|
| Account Number | Alphanumeric | 5 |
| Initial | Alphanumeric | 1 |
| Surname | Alphanumeric | 20 |
| Balance | Packed Decimal | 5 |
| Historical Transactions | Occurs 5 Times | |
| Credit/Debit Marker | Alphanumeric | 1 |
| Transaction Amount | Numeric | 5 |
| Not Used | Alphanumeric | 19 |

Data - New Master Output File

The records are output from the program in **ascending** account number sequence. It is **NOT** possible to have 2 or more output records with the same account number.

| | | |
|-------------------------|----------------|----|
| Account Number | Alphanumeric | 5 |
| Initial | Alphanumeric | 1 |
| Surname | Alphanumeric | 20 |
| Balance | Packed Decimal | 5 |
| Historical Transactions | Occurs 5 Times | |
| Credit/Debit Marker | Alphanumeric | 1 |
| Transaction Amount | Numeric | 5 |
| Not Used | Alphanumeric | 19 |

Data - Control Report File Format

| Type of Record | Total | Percentage |
|-------------------|-------|------------|
| Unchanged Records | 999 | 999.99 |
| New Records | 999 | 999.99 |
| Updated Records | 999 | 999.99 |
| All Record Types | 999 | 999.99 |

Processing

The records on the Extracted Good File and the Master File are to be processed together as a two file match program.

For each account number record on the Master File that does not have a matching record on the Extracted Good File will produce an unchanged record to be written out to the New Master File.

For each account number record on the Extracted Good File that does not have a matching record on the Master File will produce a new record to be written out to the New Master File.

- The Balance will hold the Transaction Amount.
- The Credit/Debit Marker and Transaction Amount will be held in the first occurrence of the Historical Transactions.
- Other occurrences of Historical Transactions must be held as spaces and zeroes respectively.
- Blanks must be held in the Not Used field.

For each matching account number record will produce an updated record to be written out to the New Master File.

- The Transaction Amount must be used to update the Balance
- The Credit/Debit Marker and Transaction Amount will be held in the first occurrence of the Historical Transactions.
- Other occurrences of Historical Transactions will be adjusted accordingly.

Finally, a control report will be produced as a summary.