

Table of Contents:

Table of Contents:	1
Introduction to Batch Processing	4
Enterprise Data Processing	4
Mainframe Data Processing	4
Data Types:	4
Online and Batch Processing	5
Benefits of Batch Processing	5
Working with Batch Processing	6
Examples:	6
Running a Batch Job	6
Other terminology:	6
Batch Job Automation	7
Batch Job Scheduling	7
Batch Processing Prerequisites	8
JCL z/OS 2.4 Update	8
Coding Requirements	9
JCL Coding Rules	9
Planning Processing Requirements	9
Reality of JCL Coding	9
How to copy JCL:	9
Identifying JCL code	10
The empty // curse	10
Uppercase Characters	11
Record Length	11
Continuing a statement	12
Statement Breakdown	13
Statement Names	13
Statement Types	13
Parameters	14
Positional Parameters	14
Example:	14
Keyword Parameters	15
Example:	15
Comments	15
JOB Statement Basics	16
Statement Requirements	16
JOB Statement Importance	16
JOB Name Standards	16
Running a JOB Multiple Times	17
Multiple JOB Statements	17

Incorrect JOB Name	18
Statement Positional Parameters	18
Accounting Information:	19
Programmer's Name:	20
Some or No Positional Parameters	20
Statement Keyword Parameters	21
CLASS Parameter	21
MSGCLASS Parameter	21
MSGLEVEL Parameter	23
REGION Parameter	25
NOTIFY Parameter	25
Additional JOB Statement Parameters	27
Popular Statement Parameters	27
TYPRUN Parameter	27
Scenario 1 - TYPRUN HOLD:	27
Scenario 2 - TYPRUN SCAN:	28
Scenario 3 - TYPRUN COPY:	28
Scenario 4 - TYPRUN JCLHOLD:	29
TIME Parameter	29
COND Parameter	30
PRTY Parameter	31
Other JOB Statement Parameters	32
RESTART Parameter	32
Memory-Related Parameters:	32
Output-Related Parameters:	33
SYSAFF Job Processing Environment Parameter	34
SYSTEM Job Processing Environment Parameter	35
SCHENV Job Processing Environment Parameter	35
Identification-Related Parameters	36
Running a Program using EXEC Statements	37
EXEC Statement Basics	37
No JOB without Steps	37
Statement Name - EXEC	38
EXEC Operation	38
Programs	39
JOBLIB and STEPLIB Statements	39
Program Referback	40
Procedures	40
Calling a Procedure	41
Locating a Procedure	41
EXEC Statement Parameters	42
REGION Parameter	42
COND Parameter	43

PARM Parameter	44
Syntax Rules:	44
PARMDD Parameter	45
Defining Symbol Values	46
TIME Parameter	46

Introduction to Batch Processing

Enterprise Data Processing

Mainframe Data Processing

Data on the mainframe does not come in one shape. For example, every record within a data set containing daily transactions will need to be processed, while other data sets provide the ability to update individual records only.


Data Types:

- Partitioned Data Set
 - Contains individual members.
 - An example of this is individual compiled programs residing in a production partitioned data set.
- Sequential Data Set
 - Contains data that is stored sequentially, one record following the next.
 - An example of this would be performance data that will later be printed or a list of transactions that will be applied to a master file.
- VSAM Data Set
 - There are several types of VSAM data set that can be created in a z/OS environment.
 - These are more complex than other types of data sets as they can consist of indexes or keys, to access and retrieve data records.
 - An example of data that would be stored in a VSAM structure would be system catalogs or customer data containing fields such as name, or ID that need to be referenced using that information as a key.
- z/OS UNIX File
 - JCL can be used to run shell scripts or z/OS UNIX application programs against z/OS UNIX data.
 - A wide range of data can be stored in several types of z/OS UNIX files.
- Database File
 - They provide many features and capabilities that can be applied to data stored within them.
 - They are generally used where there is a large amount of data and specific information needs to be accessed quickly.
 - An example of data that would be stored in a database table would be results of research experiments or records of organizational purchases.

Online and Batch Processing

Due to the mainframe containing several types of data with numerous people needing access to it the z/OS needs a way to manage this.

There are two methods for how this can be achieved - online and batch



With online processing you simply enter a request from a screen and press Enter, the relevant data is accessed, and a response is returned to your screen. Online processing is usually reserved for simple, quick tasks.

Batch processing is often used when large amounts of data need to be accessed and worked on, usually at a predetermined time, unlike online processing which is immediate. Batch processing uses JCL to identify the programs to be run, what is to be used as input data, and what needs to be produced as a result.

Benefits of Batch Processing

If online processing can perform tasks instantly, why is there a need for batch processing? This is due to how the cost to make resources available to that extent is not yet economically viable. Hence, batch processing is the perfect solution for situations where there is repetitious, high volume work.

- Updates to data can be performed at a time that is suitable to the organisation.
- It is suitable for large amounts of repeated work i.e. master file updates.
- Dollar costs per workload are significantly less because of the characteristics above.
- Less user interaction is required to schedule and run batch jobs.

Working with Batch Processing

Depending on one's role, our relationship to batch processing is likely to differ. However, regardless of its application if the JCL is not coded correctly, it can have some drastic consequences.


Examples:

- An incorrect version of a master file is being used as input, resulting in overpayment notices being sent to some customers.
- Some parameters that you passed to a sort program have accidentally deleted data that is normally used as input to a later program you have to run.
- The management report that is supposed to be created from your batch job is not being produced.

Running a Batch Job

Understanding how the process works allows one to better diagnose JCL error messages at a later stage.

- Submit the Job
 - JES interprets JCL and places it on an input queue, making it available to a z/OS initiator.
- z/OS manages each step of execution
 - Required resources are allocated - programs, memory, files
 - Resources are freed when the program is finished
- Output time
 - JES collects the output and information about the job
 - JES prints output
- User views and interprets output



Other terminology:

- ISPF - to access the JCL code that is used for a batch job
- JES - you will need some background on how JES, JES2, or JES3 is going to handle your submitted batch job
- SDSF or similar output viewing software - to display the results following the completion of your batch job

Batch Job Automation


Many larger organizations have implemented automated batch scheduling software that is capable of handling complex batch job scheduling requirements. For example, batch processing may need to run at a specific time, once other data has become available, when a resource becomes free, or simply triggered once another batch job has completed.

Some examples of scheduling products used:

- BMC Control-M Product
- IBM Workload Scheduler
- CA Workload Automation - CA 7 Edition

Batch Job Scheduling

Since z/OS 2.2, we can create simple scheduling for batch jobs within the batch job itself. The JCL code is referenced by JES which can run jobs at specific times or after other jobs have completed.



```
File Edit Edit Settings Menu Utilities Compilers Test Help
EDIT      IBMUSER.JCL(XRGRP) - 01.03      Columns 00001 00072
Command ==>                               Scroll ==> CSR
***** ***** Top of Data *****
000100 //XRGRP  JOBGROUP (MK112),HARRIS,ERROR=(ABEND),ONERROR=STOP
000200 //TRANAPY  GJOB
000300 //XTRCT    GJOB
000400 //        AFTER NAME=TRANAPY,WHEN=(RC=0)
000500 //XRSTORE  GJOB
000600 //        AFTER NAME=TRANAPY,WHEN=(RC=8)
000700 //XREPORT  GJOB
000800 //        AFTER NAME=XTRCT
000900 //        AFTER NAME=XRSTORE
001000 //XRGRP  ENDGROUP
001100 //TRANAPY  JOB MSGCLASS=X
001200 //        SCHEDULE JOBGROUP=XRGRP,
001300 //        HOLDUNTIL='+03:00'
001400 //APPLY    EXEC PGM=TRNASS
001500 //XTRCT    JOB MSGCLASS=X
001600 //        SCHEDULE JOBGROUP=XRGRP
001700 //EXTRACT EXEC PGM=TRNXRT
001800 //XRSTORE  JOB MSGCLASS=X
```

Batch Processing Prerequisites

The data set used for storing batch jobs is the partitioned data set (PDS) This is because it contains individual members, thus, making it an ideal location to store all batch jobs belonging to you or your group.

Job used to compile COBOL source code.

Job used to unload Db2 database records.

```
Menu  Functions  Confirm  Utilities  Help
-----
EDIT  IBMUSER.JCL                                     Row 0000035 of 0000066
Command ==>

Name      Prompt      Size  Created      Changed      ID
-----
ARUNREP   ARUNREP   3     2017/09/04   2017/09/07   20:11:09   IBMUSER
ASM1GH    ASM1GH    9     2017/09/04   2017/09/04   20:05:24   IBMUSER
COBCOMP   COBCOMP   38    2016/06/14   2017/09/06   20:34:02   IBMUSER
CSFSMFJ   CSFSMFJ   12    2017/09/03   2017/09/03   23:57:06   IBMUSER
DBRM      DBRM      10    2017/09/19   2017/09/19   20:34:22   IBMUSER
DBUNLOAD  DBUNLOAD  10    2017/09/19   2017/09/19   20:34:22   IBMUSER

Data Set Information
Command ==>
Data Set Name . . . . : IBMUSER.JCL
General Data
Data class . . . . . : **None**
Organization . . . . : PO
Record format . . . . : FB
Record length . . . . : 80
Block size . . . . . : 32720
Current utilization
Used pages . . . . . : 123
% Utilized . . . . . : 68
```

JCL z/OS 2.4 Update

There are only minor changes made to JCL with the introduction of z/OS 2.4, with one being included here.

A new NULLOVRD parameter can be used when performing overrides of DD * or DD DATA statements.

```
EDIT      IBMUSER.JCL.LIB(JIEBGNR2) - 01.04          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** ***** Top of Data *****
000100 //JIEBGNR2 JOB 'TEST RUN',MSGCLASS=X,CLASS=A,NOTIFY=&SYSUID
000110 //MYLIB   JCLLIB ORDER=IBMUSER.PROCLIB
000111 //STEP1    EXEC PROCGEN
000128 //PSTEP1.SYSUT1 DD *
000129 THIS WAS LINE 1
000130 /*
000140 //          DD NULLOVRD
000150 // DD *
000160 THIS WAS LINE 3
000170 /*
***** ***** Bottom of Data *****
```


Identifying JCL code

JCL statements begin with a double slash within columns 1 and 2. This is how the system is able to interpret the data that is submitted to the system as JCL. Do note that there are, however, some exceptions to this double slash rule.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(COPYSMF) - 01.05          Columns 00001 00072
Command ==> SUBMIT                               Scroll ==> CSR
=COLS> -----1-----2-----3-----4-----5-----6-----7--
***** ***** Top of Data *****
000100 COPYSMF JOB MSGCLASS=C,MSGLEVEL=(1,1),NOTIFY=IBMUSER
000200 //*
000300 //STEP1 EXEC PGM=ICEGENER
000400 //SYSPRINT DD SYSOUT=*
000500 //SYSUT1 DD DSN=MVS1.SMF.RECORDS(0),DISP=SHR
000600 //SYSUT2 DD DSN=IBMUSER.TEST.MVS.DATA,DISP=(,CATLG),
000700 //          SPACE=(TRK,(10,10),RLSE)
000800 //SYSIN DD DUMMY
***** ***** Bottom of Data *****

IKJ56700A ENTER JOBNAME CHARACTER(S) -
```

In the example above, the system cannot determine the name of the job because it does not recognise the first line due to the lack of double slash (//) at the beginning of the line.

```
IKJ56700A ENTER JOBNAME CHARACTER(S) -
COPYSMF
IKJ56254I JOBNAME TRUNCATED+
IKJ56250I JOB IBMUSERC(JOB09296) SUBMITTED
***
```

What the initial prompt did not mention was that it will use one's user ID (IBMUSER) as part of the job name and that one needs to add characters to append to it. Since the name of the job can only be eight characters, it has truncated the response using the C only.

The empty // curse

A common mistake for new JCL users is to submit a job that contains a line where the only data is //. This type of statement is called a null statement and indicates that this is the end of your JCL.

In the example here, the user wanted to remove the content from a JCL statement, but left // by itself on line 000500. Even though JCL statements appear after this line, the system will not recognize them.

```
000300 //
000400 // SET MEM=COMPUTE2
000500 //
000600 //COMP1 EXEC PGM=IGYCRCTL,REGION=0M,
000700 // PARM='LIST,XREF'
000800 //* SCHEDULE STARTBY='+00:05'
```

Uppercase Characters

JCL is coded in uppercase characters and you can use the PROF command in the CLI to check whether you have caps set to on or off.

- This can be fixed by using CAPS ON in the command line to automatically have your input converted to uppercase whenever you hit enter.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(CSFSMFJ) - 01.00                      Columns 00001 00072
Command ==> PROF                                           Scroll ==> CSR
***** ***** Top of Data *****
=PROF> ....JCL (FIXED - 80)....RECOVERY ON....NUMBER OFF.....
=PROF> ....CAPS OFF....HEX OFF....NULLS ON STD....TABS OFF.....
=PROF> ....AUTOSAVE ON....AUTONUM OFF....AUTOLIST OFF....STATS ON.....
=PROF> ....PROFILE UNLOCK....IMACRO NONE....PACK OFF....NOTE ON.....
=PROF> ....HILITE OFF CURSOR FIND.....
000001 //CSFSMFJ JOB (), 'GMH RUN', CLASS=A, MSGCLASS=X, NOTIFY=gh8ibm
000002 //*****
000003 //*-----*
000004 //* UNLOAD SMF RECORDS TO PRINT *
000005 //*-----*
000006 //SMFDMP EXEC PGM=IFASMFDP
000007 //DUMPIN DD DISP=SHR, DSN=SYS1.S0W1.MAN1.DATA
000008 //DUMPOUT DD SYSOUT=*
000009 //SYSPRINT DD SYSOUT=*
000010 //SYSIN DD *
000011 INDD(DUMPIN, OPTIONS(DUMP))
000012 OUTDD(DUMPOUT, TYPE(82))
***** ***** Bottom of Data *****
```

However, not everything has to be in uppercase; there are a few exceptions where you'll need to use lowercase characters enclosed within single quotes. The example shown below showcases this concept through a z/OS UNIX file being referenced.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(A#UX01) - 01.01                      Columns 00001 00072
Command ==>                                           Scroll ==> CSR
***** ***** Top of Data *****
000001 //A#UX01 JOB MSGCLASS=C, MSGLEVEL=(1,1), NOTIFY=IBMUSER, REGION=0M
000002 //STEP1 EXEC PGM=IEFBR14
000003 //DD1 DD PATH='/u/ibmuser/account2',
000004 // FILEDATA=BINARY,
000005 // PATHMODE=(SIRUSR, SIWUSR, SIRGRP, SIROTH),
000006 // PATHDISP=(KEEP, DELETE),
000007 // PATHOPTS=(OCREAT, ORDWR)
```

Record Length

Within the PDS member that stores one's JCL code, it has a record length of 80 - based on punch cards from the early days of computing. Columns 73 - 80 are ignored when a job is submitted as they were traditionally used for sequence numbers. Thus, avoid code that overruns into these columns to prevent errors popping up when the job is submitted.

Continuing a statement

Since you cannot extend your JCL statement past column 72, how do you handle a JCL statement that contains lots of information? To continue a statement, you code a comma at the end of the parameter being specified on that line, and on the following line the double slash (//) characters must be in columns 1 and 2, and your continued information can appear anywhere between columns 4 and 16 (inclusive).

Often you will see for readability purposes that continued line data is aligned with previous lines.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
EDIT IBMUSER.JCL(APDSE2) - 01.01 Columns 00001 00072
Command ==> Scroll ==> CSR
=COLS> -----1-----2-----3-----4-----5-----6-----7--
***** Top of Data *****
000100 //APDSE2 JOB MSGCLASS=X,CLASS=C
000200 //*
000300 //CREATE EXEC PGM=IEFBR14
000400 //PDSE2 DD DSN=IBMUSER.PDSE.GENS,
000500 // DSNTYPE=(LIBRARY,2),MAXGENS=10,
000600 // RECFM=FB,LRECL=80,
000700 // UNIT=SYSALLDA,SPACE=(CYL,(1,1,1)),
000800 // DISP=(,CATLG,DELETE)
***** Bottom of Data *****
```

Commas appear at the end of each line indicating to the system that the line that follows contains continuation information for that statement.

No comma is required here, signifying the end of information for this statement.







In this example, the continuation appears in column 12.

Additionally, one should avoid putting any code in column 72 itself as traditionally this column was used to indicate a continuation but today is generally no longer used for this purpose and needs to be blank.

Statement Breakdown

Statement Names

When creating JCL, you will need to tell the system the type of statement you are providing, and in most cases, provide a name for that statement. The name you provide for each statement is one to eight characters and appears immediately after the double slash (//) characters. This name must start with an alpha or national character (\$, #, @), while the remaining characters can also contain numbers.

Incorrect statement names		
	1STSTEP	Begins with a number 
	MYPROGSTEP	Too many characters 
	&BACKUP	Ampersand (&) is not a national or alpha character 

Statement Types

Associated with the name is the statement type. Common statements used include JOB, EXEC, and DD (as seen in the image below). At least one space must be coded following the name before this statement type is entered.

If you are working on an existing JCL you will often see several spaces between the name and the statement type. This is for readability purposes as it aligns important information.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL(FAMXTGH) - 01.00          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //FAMXTGH JOB MSGCLASS=C,MSGLEVEL=(1,1),NOTIFY=IBMUSER
000200 //*
000300 //STEP1 EXEC PGM=ICEGENER
000400 //SYSPRINT DD SYSOUT=*
000500 //SYSUT1 DD DSN=GHEMAST.FAMAPS.D256,DISP=OLD
000600 //SYSUT2 DD DSN=GHEMAST.FAMAPS.D256.BACKUP,
000700 //          DISP=(,CATLG)
000800 //SYSIN DD DUMMY
***** Bottom of Data *****
```

Parameters

Every statement will have some parameters that describe requirements, or attributes, to be associated with that statement. There may be many associated with that statement, though in reality you are only likely to use a subset of them regularly. If parameters are specified, at least one space must follow the statement type - JOB, EXEC, or DD - before they are entered.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(FAMXTGH) - 01.02                      Columns 00001 00072
Command ==>                                         Scroll ==> CSR
*****
***** Top of Data *****
000100 //FAMXTGH  JOB  MSGCLASS=C,MSGLEVEL=(1,1),NOTIFY=IBMUSER
000200 //*
000300 //STEP1   EXEC PGM=ICEGENER
000400 //SYSPRINT DD SYSOUT=*
000500 //SYSUT1    DD DSN=GHMAST.FAMAPS.D256,DISP=OLD
000600 //SYSUT2    DD DSN=GHMAST.FAMAPS.D256.BACKUP,
000700 //          DISP=(,CATLG)
000800 //SYSIN     DD DUMMY
*****
***** Bottom of Data *****
```

Where there are multiple parameters for a statement, they must be separated by commas, and if the parameter itself contains a space, it needs to be enclosed in single quotes.

Positional Parameters

The parameters for each statement are separated into positional and keyword. If used, a positional parameter must appear in a specific area of the code, and if it is not required, a comma is often used to indicate it being bypassed, although this is not always the case.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(FAMXTGH) - 01.03                      Columns 00001 00072
Command ==>                                         Scroll ==> CSR
*****
***** Top of Data *****
000100 //FAMXTGH  JOB  DEPT-118,'GREG HAMLYN',
000200 //          CLASS=K
000300 //          MSGCLASS=X,
000400 //          NOTIFY=IBMUSER
000500 //*
000600 //STEP1   EXEC PGM=ICEGENER
000700 //SYSPRINT DD SYSOUT=*
000800 //SYSUT1    DD DSN=GHMAST.FAMAPS.D256,DISP=OLD
000900 //SYSUT2    DD DSN=GHMAST.FAMAPS.D256.BACKUP,
001000 //          DISP=(,CATLG)
001100 //SYSIN     DD DUMMY
*****
***** Bottom of Data *****
```

Example:

- Left arrow: If this accounting information was not required but the programmer's name was, then a comma would need to be coded to signify that the accounting information was being bypassed.
- Right arrow: Even though this is a positional parameter, if it is not required and the accounting information is, then you do not need to code a comma to indicate its absence. Note that in this example, because the value contains a space, it needs to be encased in single quotes.

Keyword Parameters

Keyword parameters are more common and can appear in any order within the statement, following the statement type. Their name is followed by an equals (=) sign and then the value assigned to that keyword parameter.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL(FAMXTGH) - 01.04          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** ***** Top of Data *****
000100 //FAMXTGH  JOB 'GREG HAMLYN',
000200 //          CLASS=K,
000300 //          MSGCLASS=X,
000400 //          NOTIFY=IBMUSER
000500 //*
000600 //STEP1    EXEC PGM=ICEGENER
000700 //SYSPRINT  DD SYSOUT=*
000800 //SYSUT1    DD DISP=OLD,DSN=GHMAST.FAMAPS.D256
000900 //SYSUT2    DD DSN=GHMAST.FAMAPS.D256.BACKUP,DISP=(,CATLG)
001000 //SYSIN     DD DUMMY
***** ***** Bottom of Data *****
```

Example:

- Line 000800 shows a DISP parameter first, and then a DSN parameter. On the line after this, these two parameters appear in the opposite order. As DISP and DSN are keyword parameters this coding is acceptable.

Comments

There are two ways of coding comments in JCL. The more common method is to code a `/*` statement such as on lines 000500 to 000800. Any text that then appears after this is considered a comment. Another method is to leave at least one space at the end of a line and type your comment, such as on the end of line 001100.


```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL(FAMXTGH) - 01.04          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** ***** Top of Data *****
000100 //FAMXTGH  JOB 'GREG HAMLYN',
000200 //          CLASS=K,
000300 //          MSGCLASS=X,
000400 //          NOTIFY=IBMUSER
000500 /*
000600 /* THE FIRST STEP IS USED FOR RECOVERY PURPOSES
000700 /* CHANGE THE SYSUT1 AND SYSUT2 DATA SETS AS REQUIRED
000800 /*
000900 //STEP1    EXEC PGM=ICEGENER
001000 //SYSPRINT  DD SYSOUT=*
001100 //SYSUT1    DD DISP=OLD,DSN=GHMAST.FAMAPS.D256 * INPUT DATA SET *
001200 //SYSUT2    DD DSN=GHMAST.FAMAPS.D256.BACKUP,DISP=(,CATLG)
001300 //SYSIN     DD DUMMY
***** ***** Bottom of Data *****
```


JOB Statement Basics

Statement Requirements

JOB Statement Importance

The JOB statement is typically the first statement encountered in your job, it is used to specify attributes to be associated with your job when it is submitted to the system. The JOB statement is important and if not coded correctly, can have major ramifications on the success of your job.



```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(IBMJOB) - 01.06                      Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //GMHUN01 JOB (),'GMH',CLASS=A,MSGCLASS=X,NOTIFY=IBMUSER
000200 //*
000300 //STEP1 EXEC PGM=BPXBATCH,TIME=NOLIMIT,REGION=0M
000400 //STDIN DD PATH='/u/ibmuser/gethob',
000500 //      PATHOPTS=(ORDONLY)
000600 //STDOUT DD SYSOUT=*
000700 //STDERR DD SYSOUT=*
000800 //SYSPRINT DD SYSOUT=*
000900 //SYSUDUMP DD SYSOUT=*
001000 //SYSNDUMP DD SYSOUT=*
001100 //*
001200 //RCTEST IF (STEP1.RC = 0) THEN
001300 //      SET PARMEN=DAILY
001400 //STEP2 EXEC PGM=IEBGENER
001500 //SYSUT1 DD DSN=IBMUSER.SALESIN,DISP=OLD
001600 //SYSUT2 DD DSN=IBMUSER.PEN.TRANS.&PARMPEN,
001700 //      DCB=(RECFM=FB,LRECL=80,BLKSIZE=32720),
001800 //      SPACE=(CYL,(1,1),RLSE),UNIT=SYSDA,DISP=(,CATLG)
```

The name you specify on this statement is the one that the system uses to reference your job when it is submitted. The PDS member name you are using to store your JCL can be the same or different to the job name and has no relationship with it.

JOB Name Standards

Mentioned previously in a section above, a statement name needs to meet specific rules - it should be between one and eight characters in length and begin with an alpha or national character. It can contain a number as long as it is not the first character.

Each organization will probably have its own standards regarding job names. This allows the organization to more clearly identify to whoever is looking at the job, what group, or individual it belongs to.

Running a JOB Multiple Times

To submit a job several times, for testing purposes for example, you can code your user ID as the job's name. When you submit your job, it will prompt you for a character to be added to the end of this name before it is submitted.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(IDCAMS6) - 01.04      Columns 00001 00072
Command ==> SUBMIT      Scroll ==> CSR
***** ***** Top of Data *****
000100 //IBMUSER JOB MSGCLASS=X,CLASS=C
000200 //*
000300 //STEP1 EXEC PGM=IDCAMS
000400 //SYSPRINT DD SYSOUT=*
000500 //SYSIN DD *
000600 DEFINE GENERATIONDATAGROUP -
000700 (NAME(IBMUSER.SMF.S0A1.DATA) -
000800 EMPTY -
000900 EXTENDED -
001000 LIMIT(200) )
001100 /*
***** ***** Bottom of Data *****

IKJ56700A ENTER JOBNAME CHARACTER(S) -
A
IKJ56250I JOB IBMUSERA(JOB09357) SUBMITTED
***
```

The A character has been appended to IBMUSER, which was specified in the JOB statement, to create the job name that the system will use. You can now use the same job, changing the name of the generation data set to S0B1, and when you submit the job you can use B for the appended job name character. When you check the output from these jobs, it is easy to determine which output belongs to which job.

Note that to use this option, one's user ID needs to be a maximum of seven characters, because a maximum of eight characters are allowed for a job name.

Multiple JOB Statements

Normally, there is just a single JOB statement followed by one or more steps used to execute programs. However, in some situations there might be several JOB statements coded within a PDS member. When submitted to the system, it will detect the JOB statement and submit the statements following it as a separate job.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(SUPJOB5) - 01.01      Columns 00001 00072
Command ==> SUBMIT      Scroll ==> CSR
***** ***** Top of Data *****
000100 //SUPAPD05 JOB MSGCLASS=X,CLASS=C
000200 //APPLY EXEC PGM=TRANAPL
000300 //INPUT DD DSN=PRODD.D112Y17.PENTRANS,DISP=OLD
000400 //OUTPUT DD DSN=IBMUSER.TOTAL.PENTRANS,DISP=(,CATLG),
000500 // UNIT=SYSDA,SPACE=(CYL,(10,10,RLSE))
000600 //SYSPRINT DD SYSOUT=*
000700 //SYSOUT DD SYSOUT=*
000800 //SUPXTD10 JOB MSGCLASS=X,CLASS=C
000900 //EXTRACT EXEC PGM=TRANXCT
001000 //SYSPRINT DD SYSOUT=*
001100 //INDD1 DD DSN=IBMUSER.TOTAL.PENTRANS,DISP=SHR
001200 //SYSIN DD *
001300 RECORDS=10000
***** ***** Bottom of Data *****

IKJ56250I JOB SUPAPD05(JOB09358) SUBMITTED
IKJ56250I JOB SUPXTD10(JOB09359) SUBMITTED
***
```

Incorrect JOB Name

Depending on the problem, the system may prompt you for some input that it will use with system defaults, to build a JOB statement for you, or it may fail indicating that it has an invalid name. In this example it failed because the job name did not start with an alpha or national character.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(IBMJOB3) - 01.05      Columns 00001 00072
Command ==>      Scroll ==> CSR
***** ***** Top of Data *****
000100 //1DAYMOD JOB  , 'GMH', CLASS=C, MSGCLASS=X, NOTIFY=IBMUSER
000200 //*
000300 //      SET WDAY=THURS
000400 //STEP1 EXEC PGM=IEBGENER
000500 //SYSUT1 DD DSN=IBMUSER.JSODATA, DISP=SHR

SDSF OUTPUT DISPLAY 1DAYMOD JOB09360 DSID      2 LINE 0      COLUMNS 02- 81
COMMAND INPUT ==>      SCROLL ==> CSR
3.14.27 JOB09360 ---- MONDAY,      30 OCT 2017 ----
3.14.27 JOB09360 IRRO10I USERID IBMUSER IS ASSIGNED TO THIS JOB.
3.14.27 JOB09360 IEF452I INVALID - JOB NOT RUN - JCL ERROR 975
----- JES2 JOB STATISTICS -----
. . .
1 //1DAYMOD JOB  , 'GMH', CLASS=C, MSGCLASS=X, NOTIFY=IBMUSER
2 //*
      SET WDAY=THURS
. . .
STMT NO. MESSAGE
1 IEF452I INVALID LABEL
***** ***** BOTTOM OF DATA *****
```

Statement Positional Parameters

With a correct job name and type of statement defined, you now need to look at the types of parameters that can be coded on a JOB statement.

There are two positional parameters that can be specified on a JOB statement - **accounting information**, and the **programmer's name**. As discussed previously, positional parameters, if used, need to appear in a specific order.

The value for these two parameters may be enforced through organizational standards, therefore supplying them in the JOB statement could be optional or mandatory.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(FAMXTP15) - 01.07      Columns 00001 00072
Command ==>      Scroll ==> CSR
***** ***** Top of Data *****
000100 //FAMXTP15 JOB (170A80), 'GINA HARRIS',
000200 //      CLASS=K,
000300 //      MSGCLASS=X,
000400 //      NOTIFY=IBMUSER
000500 //*
000600 /* THE FIRST STEP IS USED FOR RECOVERY PURPOSES
000700 /* CHANGE THE SYSUT1 AND SYSUT2 DATA SETS AS REQUIRED
000800 /*
000900 //STEP1 EXEC PGM=ICEGENER
001000 //SYSPRINT DD SYSOUT=*
001100 //SYSUT1 DD DSN=GHEMAST.FAMAPS.D256, DISP=OLD
001200 //SYSUT2 DD DSN=GHEMAST.FAMAPS.D256, BACKUP, DISP=(,CATLG)
001300 //SYSIN DD DUMMY
***** ***** Bottom of Data *****
```


Accounting Information:

The accounting information parameter is used generally for billing, statistical, or performance-related purposes. The use of this parameter is likely to be dictated by an organization's standards. If used, this parameter must appear before any other JOB statement parameters.

The following are some rules when coding this parameter:

- If more than one subparameter is required, you must code the sub parameters within parentheses. You may also see a single parameter here enclosed in parentheses which is also acceptable.
- If sub parameters contain special characters, with the exception of hyphens, they must appear within apostrophes.
- It cannot exceed 143 characters in length.

The accounting information parameter can consist of two sub parameters - the account number, and more granular details associated with the account. You may also see JES2 accounting information supplied here, although this is not commonly used by organizations.



The three screenshots show JCL code in an editor window. Each window has a menu bar: File, Edit, Edit_Settings, Menu, Utilities, Compilers, Test, Help. The code is as follows:

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
EDIT IBMUSER.JCL(AASORT) - 01.02 Columns 00001 00072
Command ==> Scroll ==> CSR
***** Top of Data *****
000100 //AASORT JOB (6910-D112,'GINA HARRIS',
000200 // CLASS=C,MSGCLASS=X,NOTIFY=IBMUSER
000300 //
```

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
EDIT IBMUSER.JCL(SUPERJOB) - 01.02 Columns 00001 00072
Command ==> Scroll ==> CSR
***** Top of Data *****
000100 //SUPCHK JOB (67101,'DEPT/106',SECT04),'PAOLA MASONI',
000200 // MSGCLASS=X,CLASS=K
000300 //
```

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
EDIT IBMUSER.JCL(FAMXTP15) - 01.09 Columns 00001 00072
Command ==> Scroll ==> CSR
***** Top of Data *****
000100 //FAMXTP15 JOB (GMH1,R114,10,...,2),'GINA HARRIS',
000200 // CLASS=K,
000300 // MSGCLASS=X,
000400 // NOTIFY=IBMUSER
```

Examples:

- Image 1 - This is an example of an accounting code defined by the organisation. Even though it contains a hyphen, it does not need to be enclosed in parentheses or apostrophes, although syntactically this is allowed.
- Image 2 - This is an example wherein the organization has defined their accounting information for a job must contain a code, department number, and section name. As the department number contains a slash (/), it needs to be enclosed in apostrophes. As there are three sub parameters altogether, they are enclosed in parentheses.
- Image 3 - When using this parameter to supply JES2 accounting information, a range of sub parameters can be specified. These are positional sub parameters, in this example there are several commas entered to indicate values being bypassed.

Programmer's Name:

The programmer's name is another optional parameter that may be required by your organization. This field helps to provide identification about the owner of the job. This is often the name of an individual but could also be the name of your group. You can see here that the job's log at the bottom displays this information.

When coding the programmer's name parameter a maximum of 20 characters can be coded and single quotes are required if the name contains any special characters, other than hyphens (-) or periods (.).

Some or No Positional Parameters

If a positional parameter is not required, a comma is coded to signify its absence. This is required when another positional parameter immediately follows it. If no positional parameters are required at all for the statement, they can be omitted without any commas.

The example below is for when you omit the accounting information.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL(FAMXTP15) - 01.11          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //FAMXTP15 JOB , 'GINA HARRIS',
000200 //          CLASS=K,
000300 //          MSGCLASS=X,
000400 //          NOTIFY=IBMUSER
000500 //
000600 //* THE FIRST STEP IS USED FOR RECOVERY PURPOSES
000700 //* CHANGE THE SYSUT1 AND SYSUT2 DATA SETS AS REQUIRED
000800 //
000900 //STEP1      EXEC PGM=ICEGENER
001000 //SYSPRINT DD SYSOUT=*
001100 //SYSUT1      DD DSN=GHEMAST.FAMAPS.D256,DISP=OLD
001200 //SYSUT2      DD DSN=GHEMAST.FAMAPS.D256.BACKUP,DISP=(,CATLG),
001210 //          UNIT=SYSDA,SPACE=(CYL,(10,10),RLSE)
001300 //SYSIN       DD DUMMY
***** Bottom of Data *****
```

Statement Keyword Parameters

CLASS Parameter

During JES initialization, organizational job classes are defined with each containing their own characteristics. These classes can be a single number (0-9), letter (A-Z), or even a one to eight-character name. The example at the bottom of this page shows attributes assigned to K class jobs during JES initialization.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL(FAMXTP15) - 01.12          Columns 00001 00072
Command ==> SUBMIT                                   Scroll ==> CSR
***** Top of Data *****
000100 //FAMXTP15 JOB 6910-D112,'GINA HARRIS',
000200 //          CLASS=K
000300 //
000400 //* THE FIRST STEP IS USED FOR RECOVERY PURPOSES
000500 //* CHANGE THE SYSUT1 AND SYSUT2 DATA SETS AS REQUIRED
000600 //*
000700 //STEP1    EXEC PGM=ICEGENER

Display Filter View Print Options Search Help
-----
SDSF INPUT QUEUE DISPLAY ALL CLASSES          LINE 1-1 (1)
COMMAND INPUT ==>                               SCROLL ==> CSR
PREFIX=* DEST=(ALL) OWNER=* SYSNAME=
NP  JOBNAME JobID  Owner  JP  C  Pos PhaseName      Status
   FAMXTP15 JOB09417 IBMUSER    7  K    1 AWAIT MAIN SELECT
```

One of the items you would normally code on a JOB statement is a CLASS parameter and you can see in the screen at the top that the syntax is straightforward.

- If an invalid class is specified in the JOB statement the job will be flushed or cancelled and an error message will be displayed.

MSGCLASS Parameter

The MSGCLASS parameter is used to assign the job's log to an output class. This is what you look at in SDSF to determine whether your job ran successfully. Like the CLASS parameter, the attributes associated with output classes are defined during JES initialization.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL(FAMXTP15) - 01.12          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //FAMXTP15 JOB 6910-D112,'GINA HARRIS',
000200 //          CLASS=K,
000300 //          MSGCLASS=X
000400 //
000500 //* THE FIRST STEP IS USED FOR RECOVERY PURPOSES
000600 //* CHANGE THE SYSUT1 AND SYSUT2 DATA SETS AS REQUIRED

Display Filter View Print Options Search Help
-----
SDSF OUTPUT ALL CLASSES ALL FORMS          LINES 79          LINE 1-1 (1)
COMMAND INPUT ==>                               SCROLL ==> CSR
PREFIX=FAM* DEST=(ALL) OWNER=* SORT=CrDate/D SYSNAME=
NP  JOBNAME JobID  Owner  Prty C Forms  Dest      Rec-Cnt
   FAMXTP15 JOB09420 IBMUSER    144 X STD      LOCAL      79
```

Note that you will again be likely to have organizational standards that specify the output class you should use.

- MSGCLASS=Z is often configured to automatically purge job log output on completion of the job.

If you do not code a MSGCLASS parameter then installation defaults will be used, so it is usually good practice to code this parameter so that you can find your output easily.

In the example from the previous page, JES initialization statements defined that X class output is not held, and this is why you found it on the SDSF output screen rather than the held output screen. This is not always going to be the case.

```

File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(FAMXTP15) - 01.12      Columns 00001 00072
Command ==>                                Scroll ==> CSR
***** Top of Data *****
000100 //FAMXTP15 JOB 6910-D112,'GINA HARRIS',
000200 //          CLASS=K,
000300 //          MSGCLASS=Z
000400 //
000500 //* THE FIRST STEP IS USED FOR RECOVERY PURPOSES
000600 //* CHANGE THE SYSUT1 AND SYSUT2 DATA SETS AS REQUIRED

```

```

File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      VENDOR.PARMLIB(JES2420A) - 01.01      Columns 00001 00072
Command ==>                                Scroll ==> CSR
000481 OUTCLASS(K) OUTDISP=(HOLD,HOLD),OUTPUT=PUNCH
000482 OUTCLASS(R) OUTDISP=(HOLD,HOLD)
000483 OUTCLASS(Z) OUTDISP=(WRITE,WRITE),OUTPUT=DUMMY
000484 OUTDEF    COPIES=100,

```

In this example, a MSGCLASS of Z is specified in the JCL. In the JES initialization parameters, notice that for this class it displays OUTPUT=DUMMY, which means that the output will not be available for viewing. You might want to use this class for your job if you are running it many times and do not need to ever view its job log.

◀ Previous Next ▶

```

File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      VENDOR.PARMLIB(JES2420A) - 01.01      Columns 00001 00072
Command ==>                                Scroll ==> CSR
000481 OUTCLASS(K) OUTDISP=(HOLD,HOLD),OUTPUT=PUNCH
000482 OUTCLASS(R) OUTDISP=(HOLD,HOLD)
000483 OUTCLASS(Z) OUTDISP=(WRITE,WRITE),OUTPUT=DUMMY
000484 OUTDEF    COPIES=100,

```

```

Display Filter View Print Options Search Help
-----
SDSF HELD OUTPUT DISPLAY ALL CLASSES LINES 49      LINE 1-1 (1)
COMMAND INPUT ==>                                SCROLL ==> CSR
PREFIX=FAM* DEST=(ALL) OWNER=* SORT=CrDate/D SYSNAME=
NP  JOBNAME  JobID  Owner  Prty C ODisp Dest      REC-Cnt  PAGE
   FAMXTP15 JOB09423 IBMUSER 144 R HOLD  LOCAL          49

```

You can see in the JES initialization parameters at the top that R class output is assigned a HOLD status. If the job had a MSGCLASS of R you would have to search the SDSF held output screen to find it, not the normal output screens previously used.

◀ Previous Restart

MSGLEVEL Parameter

A job's log output, which was discussed on the previous page, consists of a number of separate output components including the following:

- JES job log
- JCL statements
- Job-related JES and operator messages - system messages

There may be times when you do not need all of this information to be made available because it can clutter the screen making it difficult for you to find what really matters to you.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(FAMXTP15) - 01.14                      Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //FAMXTP15 JOB 6910-D112,'GINA HARRIS',
000200 //          CLASS=K,
000300 //          MSGCLASS=X,
000400 //          MSGLEVEL=(0,1)
```

```
Display Filter View Print Options Search Help
-----
SDSF JOB DATA SET DISPLAY - JOB FAMXTP15 (JOB09428)      LINE 1-4 (4)
COMMAND INPUT ==>                                         SCROLL ==> CSR
PREFIX=FAM* DEST=(ALL) OWNER=* SYSNAME=
NP  DDNAME  StepName ProcStep DsID Owner  C Dest                      Rec-Cnt Page
   JESMSGLG JES2          2  IBMUSER  X LOCAL                      18
   JESJCL   JES2          3  IBMUSER  X LOCAL                      8
   JESYSMSG JES2          4  IBMUSER  X LOCAL                      21
```

The MSGLEVEL parameter consists of two sub parameters. The first indicates which statement images to produce. The second sub parameter indicates which system messages to produce. The default is usually MSGLEVEL=(1,1), which will show all JCL statements and messages. A MSGLEVEL default may also be defined for each JES JOBCCLASS definition.

In this example, specifying 0 for the first sub parameter will only produce the JOB statement and any comments that appear before the first step. You can see in the output produced that the number of records for the KCL messages have been reduced as a result of this.

```

Display Filter View Print Options Search Help
-----
SDSF JOB DATA SET DISPLAY - JOB ARUNREP (JOB09429) LINE 1-7 (7)
COMMAND INPUT ==> SCROLL ==> CSR
PREFIX=ARUN* DEST=(ALL) OWNER=* SYSNAME=
NP DDNAME StepName ProcStep DsID Owner C Dest Rec-Cnt Page
JESMSG LG JES2 2 IBMUSER C LOCAL 33
JESJCL JES2 3 IBMUSER C LOCAL 24
JESYSMSG JES2 4 IBMUSER C LOCAL 67

```

```

Display Filter View Print Options Search Help
-----
SDSF JOB DATA SET DISPLAY - JOB ARUNREP (JOB09430) LINE 1-7 (7)
COMMAND INPUT ==> SCROLL ==> CSR
PREFIX=ARUN* DEST=(ALL) OWNER=* SYSNAME=
NP DDNAME StepName ProcStep DsID Owner C Dest Rec-Cnt Page
JESMSG LG JES2 2 IBMUSER C LOCAL 33
JESJCL JES2 3 IBMUSER C LOCAL 3
JESYSMSG JES2 4 IBMUSER C LOCAL 67

```

Coding 2 for the first sub parameter will produce JCL and JES statements but not procedure statements. The output at the top did not have any MSGLEVEL parameter and you can see that it produced 24 records for the JESJCL part of the output. The same job when submitted with MSGLEVEL=(2,1) produced the output at the bottom showing only 3 records being produced.

```

Display Filter View Print Options Search Help
-----
SDSF JOB DATA SET DISPLAY - JOB FAMXTP15 (JOB09425) LINE 1-4 (4)
COMMAND INPUT ==> SCROLL ==> CSR
PREFIX=FAM* DEST=(ALL) OWNER=* SYSNAME=
NP DDNAME StepName ProcStep DsID Owner C Dest Rec-Cnt Page
JESMSG LG JES2 2 IBMUSER X LOCAL 18
JESJCL JES2 3 IBMUSER X LOCAL 13
JESYSMSG JES2 4 IBMUSER X LOCAL 21

```

```

Display Filter View Print Options Search Help
-----
SDSF JOB DATA SET DISPLAY - JOB FAMXTP15 (JOB09434) LINE 1-4 (4)
COMMAND INPUT ==> SCROLL ==> CSR
PREFIX=FAM* DEST=(ALL) OWNER=* SYSNAME=
NP DDNAME StepName ProcStep DsID Owner C Dest Rec-Cnt Page
JESMSG LG JES2 2 IBMUSER X LOCAL 18
JESJCL JES2 3 IBMUSER X LOCAL 13
JESYSMSG JES2 4 IBMUSER X LOCAL 11

```

Coding 0 for the second sub parameter will produce only JCL messages, unless the job fails, in which case JES and operator messages will also be produced. In this situation SMS messages will also be shown, if SMS has caused the job to fail. The example at the top is showing all job log output, while the one at the bottom is produced using MSGLEVEL=(1,0).

REGION Parameter

Every program you run is going to need a different amount of memory to run. Many organizations will use a REGION parameter to cap this requirement.

Coding REGION=0M or REGION=0K on the JOB statement provides every program specified in your job with as much virtual storage - memory - as it requires. Depending on your requirements, you can code a specific maximum amount of memory that can be used, in megabytes (M) or kilobytes (K). If REGION is not specified, then a JES initialization default will take effect.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(FAMXTP15) - 01.16          Columns 00001 00072
Command ==>                                     Scroll ==> CSR
***** Top of Data *****
000100 //FAMXTP15 JOB 6910-D112,'GINA HARRIS',
000200 //          CLASS=K,
000300 //          MSGCLASS=X,
000400 //          REGION=6M
000500 //
000600 //* THE FIRST STEP IS USED FOR RECOVERY PURPOSES
000700 //* CHANGE THE SYSUT1 AND SYSUT2 DATA SETS AS REQUIRED
000800 //*
000900 //STEP1 EXEC PGM=ICEGENER
001000 //SYSPRINT DD SYSOUT=*
001100 //SYSUT1 DD DSN=GHMAST.FAMAPS.D256,DISP=OLD
001200 //SYSUT2 DD DSN=GHMAST.FAMAPS.D256.BACKUP,DISP=(,CATLG),
001300 //          UNIT=SYSDA,SPACE=(CYL,(10,10),RLSE)
001400 //SYSIN DD DUMMY
***** Bottom of Data *****
```

NOTIFY Parameter

When you submit your job to the system, most people will want to be notified once the job has completed, so it can be checked. This task is achieved using the NOTIFY parameter.

The syntax of this command is relatively straightforward. The NOTIFY value is a TSO user ID, usually the person submitting the job.

Use &SYSUID - for anyone to use your JCL instead of specifying a specific TSO UserID.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(FAMXTP15) - 01.18          Columns 00001 00072
Command ==>                                     Scroll ==> CSR
***** Top of Data *****
000100 //FAMXTP15 JOB 6910-D112,'GINA HARRIS',
000200 //          CLASS=K,
000300 //          MSGCLASS=X,
000400 //          REGION=0M,
000500 //          NOTIFY=&SYSUID
000600 //
000700 //* THE FIRST STEP IS USED FOR RECOVERY PURPOSES
000800 //* CHANGE THE SYSUT1 AND SYSUT2 DATA SETS AS REQUIRED
000900 //*
001000 //STEP1 EXEC PGM=ICEGENER
001100 //SYSPRINT DD SYSOUT=*
001200 //SYSUT1 DD DSN=GHMAST.FAMAPS.D256,DISP=OLD
001300 //SYSUT2 DD DSN=GHMAST.FAMAPS.D256.BACKUP,DISP=(,CATLG),
001400 //          UNIT=SYSDA,SPACE=(CYL,(10,10),RLSE)
001500 //SYSIN DD DUMMY
***** Bottom of Data *****
```

The NOTIFY parameter is quite simple but has a few drawbacks, including the following:

- If the user that the message is to be sent to is not logged on, they will not receive a job completion message until they next log on
- The NOTIFY parameter can only be used to send a message to a single user
- There is no default, so if you forget to code this parameter you will need to monitor the job using other methods, to determine if it has finished

With z/OS 2.3 a new NOTIFY statement provides more flexibility in when and how job completion messages are sent. When specified, it must be placed after the JOB statement and before the first EXEC statement.

```
000100 //FAMXTP15 JOB 4467-D032,'LAYLA SHULZ',
000200 //      CLASS=K,
000300 //      MSGCLASS=X
000400 //*
000500 //NOT1      NOTIFY EMAIL='ghamlyn@bank.com',TYPE=EMAIL
```

This statement name follows the standard naming syntax for other statements, as discussed previously. This is followed by at least one blank and then the statement type: NOTIFY. All parameters used in this statement are keyword, so can be specified in any order. The EMAIL parameter is used to define the email address to whom job completion details will be sent. The TYPE parameter indicates that the message is to be sent as an email message and is the default when the EMAIL parameter is used.

```
000100 //FAMXTP15 JOB 4467-D032,'LAYLA SHULZ',
000200 //      CLASS=K,
000300 //      MSGCLASS=X
000400 //*
000500 //NOT1      NOTIFY USER=IBMUSER,TYPE=MSG
000600 //NOT2      NOTIFY USER=GTEDSWOT,TYPE=MSG
000700 //NOT3      NOTIFY USER=DZTPRD01,TYPE=MSG
```

A maximum of eight NOTIFY statements can be specified. In this example the USER parameter is used to identify the TSO user to whom a job completion message will be sent. The TYPE parameter indicates that the notification should be sent by using a TSO message, and is the default when the USER parameter is specified.

```
000100 //FAMXTP15 JOB 4467-D032,'LAYLA SHULZ',
000200 //      CLASS=K,
000300 //      MSGCLASS=X
000400 //*
000500 //NOT1      NOTIFY EMAIL='ghamlyn@bank.com',TYPE=EMAIL
000600 //      WHEN='(RC=4 | RC=8)'
000700 //*
000800 //NOT2      NOTIFY USER=LAYLA,TYPE=MSG,
000900 //      WHEN='(ABEND)'
001000 //*
001100 //NOT3      NOTIFY USER=SIMON,TYPE=MSG,
001200 //      WHEN='(ABENDCC=S0C4 OR ABENDCC=U1024)'
001300 //*
001400 //NOT4      NOTIFY USER=IBMUSER,TYPE=MSG,
001500 //      WHEN='(!RUN)'
```

The WHEN parameter can be used to define conditions under which notification will be performed. In the NOT1 statement, a confirmation email will be sent only if the job completes with a maximum condition code of 4 or 8. In the NOT2 statement, if an abend occurs then a message will be sent to TSO user LAYLA. The NOT3 statement is more specific as it indicates that either of the abend codes specified need to be produced before the message is sent. In the NOT4 statement if the job did not run - for example, it had a JCL syntax error - then a TSO message will be sent to TSO user IBMUSER. The exclamation mark (!) character indicates a not operation.

Additional JOB Statement Parameters

Popular Statement Parameters

TYPRUN Parameter

Normally when you submit a job, it will run immediately if the required resources are available. There may be situations though where you need the system to handle your job differently when it is submitted.

For example, the TYPRUN parameter can be used for the following purposes:

- Holding your job, pending a manual release, either by yourself or an operator.
- Scanning the syntax of your JCL. In this scenario, no actual job processing is performed.
- Sending a copy of your JCL directly to sysout, without performing any processing, in a JES2 environment only.

Scenario 1 - TYPRUN HOLD:

You are going to be detained all afternoon with meetings but need to submit a job that must be run when a file becomes available after 1:00pm. Rather than wait until you are back in the office later in the day to submit your job, you can submit it now and instruct an operator to release it.

The TYPRUN=HOLD parameter can be used for this purpose. You can see in the SDSF screen at the bottom of the page that the job has a HOLD status. Note that if your job contains syntax errors when it is submitted, it will fail immediately and not be held.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL(BLKJET01) - 01.01          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** ***** Top of Data *****
000100 //BLKJET01 JOB 6910-D112,'GINA HARRIS',
000200 //          CLASS=C,
000300 //          MSGCLASS=X,
000400 //          NOTIFY=IBMUSER,
000500 //          TYPRUN=HOLD
000600 //*=

Display Filter View Print Options Search Help
-----
SDSF INPUT QUEUE DISPLAY ALL CLASSES                LINE 1-1 (1)
COMMAND INPUT ==>                                     SCROLL ==> CSR
PREFIX=BL* DEST=(ALL) OWNER=* SYSNAME=
NP  JOBNAME JobID Owner JP C Pos PhaseName          Status
   BLKJET01 JOB09564 IBMUSER 7 K AWAIT MAIN SELECT    HOLD
```

Scenario 2 - TYPRUN SCAN:

You have been copying components of JCL from other sources to build your JCL. You still need to work on the programs that will be invoked but want to check your JCL to see whether it is syntactically correct.

The TYPRUN=SCAN parameter can be used for this purpose. You can see in the SDSF screen at the bottom that if the syntax is acceptable, there are no error-related messages. Note though that the job is not run, it is only scanned for syntax issues. Although you cannot see it here, at the bottom of the SDSF output, a copy of the JCL is also produced.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL(PENEDD12) - 01.01          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //PENEDD12 JOB SPEN1763,'E KARLSSON',
000110 //          TYPRUN=SCAN
000200 //*****
000300 //* THIS STEP WILL CONVERT THE PARTITIONED VB DATASET */
000400 //* INTO A SEQUENTIAL VBS DATASET TO BE READY FOR */
000500 //* IMPORT IN NEXT STEP. */
000600 //*****
000700 //STEP01 EXEC PGM=IEBGENER
000800 //SYSPRINT DD SYSOUT=Z

Display Filter View Print Options Search Help
-----
SDSF OUTPUT DISPLAY PENEDD12 JOB09565 DSID      2 LINE 0      COLUMNS 02- 81
COMMAND INPUT ==>                                         SCROLL ==> CSR
***** TOP OF DATA *****
              JES2 JOB LOG -- SYSTEM S0W1 -- NODE
18.39.19 JOB09565 ---- TUESDAY, 07 NOV 2017 ----
18.39.19 JOB09565 IRR010I USERID IBMUSER IS ASSIGNED TO THIS JOB.
----- JES2 JOB STATISTICS -----
              34 CARDS READ
              35 SYSOUT PRINT RECORDS
               0 SYSOUT PUNCH RECORDS
               3 SYSOUT SPOOL KBYTES
```

Scenario 3 - TYPRUN COPY:

TYPRUN=COPY can be used if you just need to copy your JCL directly to sysout - output that can be displayed through SDSF. If there are any syntax errors, this option will not pick them up.

```
Display Filter View Print Options Search Help
-----
SDSF OUTPUT DISPLAY PENEDD12 JOB09570 DSID      1 LINE 0      COLUMNS 02- 81
COMMAND INPUT ==>                                         SCROLL ==> CSR
***** TOP OF DATA *****
//PENEDD12 JOB SPEN1763,'E KARLSSON',                JOB09570
//          TYPRUN=COPY                                00011001
//*****                                              00020000
//* THIS STEP WILL CONVERT THE PARTITIONED VB DATASET */ 00030000
//* INTO A SEQUENTIAL VBS DATASET TO BE READY FOR */   00040000
//* IMPORT IN NEXT STEP. */                             00050000
//*****                                              00060000
//STEP01 EXEC PGM=IEBGENER                             00070000
```

Scenario 4 - TYPRUN JCLHOLD:

TYPRUN=JCLHOLD is similar to TYPRUN=HOLD except that the job is held prior to the JES2 conversion stage. You will see in a later course what happens during this stage and why this option may be useful. When the job is released by the operator, if there are any JCL syntax errors, similar output to that of the TYPRUN=SCAN will be produced, otherwise the job will begin executing if resources are available.

```
Display Filter View Print Options Search Help
-----
SDSF INPUT QUEUE DISPLAY ALL CLASSES          LINE 1-1 (1)
COMMAND INPUT ==>                          SCROLL ==> CSR
PREFIX=PEN*  DEST=(ALL)  OWNER=*  SYSNAME=
NP  JOBNAME  JobID  Owner  JP  C  Pos  PhaseName  Status
    PENEDD12  JOB09574  IBMUSER  7  *  AWAIT CONV  HOLD
```

If no TYPRUN parameter is specified, then the job is submitted and will run immediately if all required resources are available.

TIME Parameter

When testing any programs you are working on, you may want to ensure that they do not run longer than you think they should, for example in the case of a program looping. A TIME parameter can be coded on the JOB statement for this purpose. This is used to specify the maximum amount of CPU time, not elapsed time, that your job can execute for.

There are several values that can be specified for this parameter. In the example shown here, two positional sub parameters can be used to specify minutes and seconds.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(DISDEV05) - 01.02          Columns 00001 00072
Command ==>                                     Scroll ==> CSR
***** Top of Data *****
000100 //DISDEV05 JOB MSGCLASS=C,CLASS=K,
000200 //      TIME=(1,30)
000300 //*
000400 //STEP1  EXEC PGM=ICEGENER
000500 //SYSPRINT DD SYSOUT=*
000600 //SYSUT1  DD DSN=IBMUSER.CCF.REPORT,DISP=OLD
000700 //SYSUT2  DD DSN=IBMUSER.DIS.WKLY.REPTRNS(+1),
000800 //      DISP=(,CATLG)
000900 //SYSIN   DD DUMMY
001000 //STEP1  EXEC PGM=STRPDIS
001100 //INDD1   DD DSN=IBMUSER.CCF.REPORT,DISP=OLD
001200 //OUTDD1  DD DSN=IBMUSER.DIS.STRIPPED.REPDATA,
001300 //      DISP=(,CATLG),UNIT=SYSDA,
001400 //      SPACE=(CYL,(10,10),RLSE)
001500 //SYSPRINT DD SYSOUT=*
001600 //SYSIN   DD DUMMY
***** Bottom of Data *****
```

The first sub parameter in the TIME parameter refers to minutes. This value must be between 0 and 357913. The seconds sub parameter appears after the comma and must be a value between 0 and 59 - inclusive.

- If minutes are not required just put a comma in front of the seconds like with the accounting information and programmer name combo.
- If seconds are not required, just do TIME=2 or whatever value for the CPU minutes.
- It is possible for a job to take 1 hour to run but only consume a minute of CPU time so keep this in mind when using this parameter.

There may be several areas where your systems administrator has defined the maximum amount of time that a job can run. As well as specifying minutes and seconds as shown on the previous page, there are also several other values that can be used.

```
000100 //JETDEV01 JOB , 'B CORNES',
000200 //          CLASS=K,
000300 //          MSGCLASS=X,
000400 //          TIME=1440,
000500 //          NOTIFY=IBMUSER
000600 //S1          EXEC PGM=IEFBR14
```

```
000100 //FAMXTP15 JOB 6910-D112, 'GINA HARRIS',
000200 //          CLASS=K,
000300 //          MSGCLASS=X,
000400 //          TIME=NOLIMIT
000500 //*
```

```
000100 //PENEDD12 JOB SPEN1763, 'E KARLSSON',
000200 //          TIME=MAXIMUM
000300 //*****
```

COND Parameter

When your batch job runs, each step or program runs sequentially, and when it completes it produces a condition code. Following this, the next program sequentially in your JCL will be invoked, and so on. If for some reason a program completes unsuccessfully, then what usually occurs is that the job itself will fail at that point and no further processing for the job will occur.

JCL allows you to be more specific about the completion circumstances for each program and whether other programs that appear later in your job should run. One method used to achieve this is the JOB statement COND parameter.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(DISDEV05) - 01.04      Columns 00001 00072
Command ==>                                     Scroll ==> CSR
000100 //DISDEV05 JOB MSGCLASS=C,CLASS=K,
000200 //          COND=(4,LT)
000300 //*
000400 //STEP1      EXEC PGM=DISBKUP
000500 //*
000600 //STEP2      EXEC PGM=DISEXT
000700 //*
000800 //STEP3      EXEC PGM=DISSORT
000900 //*
001000 //STEP4      EXEC PGM=DISREP
001100 //*
***** Bottom of Data *****
```


PRTY Parameter

You saw earlier that when a job is submitted, if an initiator is available then the job will begin executing. Though what happens if there are several jobs waiting to be processed and you need yours to run first once an initiator becomes available?

One of the other tasks performed by JES is to set a priority for the job. In most cases as a general user, you will not have much control of job priority, because if you did then everyone would be promoting their job to the highest level. Having said that, there is a PRTY parameter that can be coded on the JOB statement that allows you, if authorized, to define a priority for your job. In the scenario here your job would appear as a higher order on the input queue than others.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(PLB#115) - 01.04                      Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** ***** Top of Data *****
000100 //PLB#115  JOB  CLASS=T,MSGCLASS=L,
000200 //                      PRTY=15
000300 //*
000400 //                      SET MEM=SEARCH
000500 //PLI      EXEC PGM=IBMZPLI,PARM=('SOURCE')
000600 //STEPLIB  DD DSN=IEL450.SIBMZCMP,DISP=SHR
000700 //                      DD DSN=CEE.SCEERUN,DISP=SHR
000800 //                      DD DSN=DSNB10.SDSNLOAD,DISP=SHR
000900 //OPTIONS DD DSN=IBMUSER.OPTIONS,DISP=SHR
001000 //DBRMLIB  DD DSN=IBMUSER.JCL(DBRM),DISP=SHR
001100 //SYSDEBUG DD DSN=IBMUSER.SYSDEBUG,DISP=SHR
001200 //SYSIN    DD DISP=SHR,DSN=IBMUSER.PL1.SRC(&MEM)
001300 //SYSLIB   DD DISP=SHR,DSN=IBMUSER.PL1.SRC
001400 //SYSPRINT DD SYSOUT=*
001500 //SYSOUT   DD SYSOUT=*
001600 //SYSLIN   DD DSN=&&LOADSET,DISP=(MOD,PASS),UNIT=SYSALLDA,
001700 //                      SPACE=(CYL,(1,1)),DCB=(LRECL=80,BLKSIZE=3200)
001800 //SYSUT1   DD DSN=&&SYSUT1,UNIT=SYSALLDA,
```

For a JES2 site, the value for this parameter is from 0 through 15, with the highest priority being 15. In a JES3 environment, the range is 0 through 14.

Depending on your organizational standards, if you have coded this parameter the system may just ignore it.

Other JOB Statement Parameters

RESTART Parameter

Normally when you submit a job, it will run from top to bottom, executing programs sequentially. However, what happens when your five-program job processes the first two programs successfully, and after 30 minutes of elapsed time processing them, fails in the third program because a data set you were trying to create already existed. To rerun it from the beginning would waste 30 minutes of previously successful processing. In this situation you may be able to use the JOB statement RESTART parameter.

In the example shown here, the RESTART parameter will begin from a step named STEP3. When the job is submitted, the DISBKUP and DISEXT programs will not be run, and processing will begin from STEP3, which invokes the DISSORT program.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL (DISDEV05) - 01.05      Columns 00001 00072
Command ==>                               Scroll ==> CSR
***** ***** Top of Data *****
000100 //DISDEV05 JOB MSGCLASS=C,CLASS=K,
000200 //          RESTART=STEP3
000300 //*
000400 //STEP1    EXEC PGM=DISBKUP
000500 //*
000600 //STEP2    EXEC PGM=DISEXT
000700 //*
000800 //STEP3    EXEC PGM=DISSORT
000900 //*
001000 //STEP4    EXEC PGM=DISREP
001100 //*
***** ***** Bottom of Data *****
```

Memory-Related Parameters:

The REGION parameter is used to specify the maximum amount of memory that can be used by programs within the job. However, there are several other memory-related parameters that can be used to further refine memory requirements.

```
000100 //PENEDD12 JOB SPEN1763,'E KARLSSON',
000200 //          REGIONX=(4M,256M)
000300 //*****
```

```
000100 //SUPAPD05 JOB T112-345,'ELIZA BROWN',
000200 //          ADDRSPC=REAL
000300 //STEP1    EXEC PGM=JEDDXX
```

```
000100 //A#PENXT  JOB MSGCLASS=C,
000200 //          MEMLIMIT=10000M
000300 //*
```

- REGIONX can be used if one already knows how much memory above and below the 16MB line is required
- By default, programs will utilize virtual storage which is pageable. This can be altered so all programs in the job use real, non-pageable storage.
- This last one places a limit on the total size of usable virtual storage above the bar in a single address space.

Output-Related Parameters:

Similar to MSGCLASS and MSGLEVEL parameters and how they are used when producing system output there are several other output-related parameters that can be used on the JOB statement to specifically control the maximum amount of output that should be produced. This is useful if your job creates more output than you expected. Note that like other parameters discussed, you will have an installation default for it, so coding this parameter is only useful if it varies from this value.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT IBMUSER.JCL(AASORT) - 01.03 Columns 00001 00072
Command ==> Scroll ==> CSR
***** Top of Data *****
000100 //AASORT JOB 6910-D112,'GINA HARRIS',
000200 // CLASS=C,MSGCLASS=X,
000300 // LINES=(10,WARNING)
000400 //*
000500 //STEP1 EXEC PGM=SORT
000600 //SYSOUT DD SYSOUT=*
000700 //SORTIN DD DSN=IBMUSER.PEN.DAILY.TRANS,DISP=OLD

Display Filter View Print Options Search Help
-----
SDSF OUTPUT DISPLAY AASORT JOB09610 DSID 2 LINE 0 COLUMNS 20- 99
COMMAND INPUT ==> SCROLL ==> CSR
***** TOP OF DATA *****
JES2 JOB LOG -- SYSTEM S0W1 -- NODE SVSCJES2

---- WEDNESDAY, 08 NOV 2017 ----
IRR010I USERID IBMUSER IS ASSIGNED TO THIS JOB.
ICH70001I IBMUSER LAST ACCESS AT 16:14:57 ON WEDNESDAY, NOVEMBER 8, 2017
$HASP373 AASORT STARTED - INIT 1 - CLASS K - SYS S0W1
$HASP375 AASORT ESTIMATED LINES EXCEEDED
$HASP375 AASORT ESTIMATE EXCEEDED BY 10,000 LINES
$HASP375 AASORT ESTIMATE EXCEEDED BY 20,000 LINES
$HASP375 AASORT ESTIMATE EXCEEDED BY 30,000 LINES
$HASP375 AASORT ESTIMATE EXCEEDED BY 40,000 LINES
```

The JCL at the top of this screen contains a LINES parameter, to indicate if more than ten (thousand) lines of output are produced, then a warning message will be sent to the operator. The job will continue to process the output for the job and an operator message will continue to be sent at regular intervals. The SDSF output for the job at the bottom of the screen shows these messages being produced, which are also sent to the operator.

- The warning parameter can be replaced with DUMP or CANCEL
 - DUMP will cancel the job once the maximum number of lines have been produced and request a system dump.
 - CANCEL will cancel the job without a dump.

```
000100 //BLKJET01 JOB 6910-D112,'GINA HARRIS',
000200 // CLASS=C,
000300 // MSGCLASS=X,
000400 // NOTIFY=IBMUSER,
000500 // PAGES=(20,WARNING)

000001 //CSFSMFJ JOB (D-117),'GMH RUN',
000002 // CLASS=A,
000003 // MSGCLASS=X,
000004 // BYTES=(5,DUMP)

000100 //DISDEV05 JOB MSGCLASS=C,
000200 // CLASS=K,
000300 // CARDS=(500,CANCEL)
```

The LINES parameter can be substituted with the following, using a different measurement to determine the maximum amount of output to be produced:

- PAGES is the maximum number of pages of output that can be produced before action is taken.
- BYTES is the maximum number of bytes, in thousands, that can be produced before action is taken.
- CARDS is the maximum number of cards that can be punched before action is taken.

SYSAFF Job Processing Environment Parameter

When the submit command is issued for a job, the system assumes that the job is to be run on the system where it is being submitted from. If resources are not available on that system, then the job may sit and wait a considerable time before it executes.

There are several JOB statement parameters that can be used to specify that the job is run on a more appropriate system within the organization. For example, the SYSAFF parameter shown here can be used to list the JES2 members, or JES3 systems, that are allowed to process this job.

```
Display Filter View Print Options Search Help
-----
SDSF OUTPUT DISPLAY PENEDD12 JOB09617 DSID      2 LINE  CHARS 'S0W1' FOUND
COMMAND INPUT ==>          SCROLL ==> CSR
5.37 JOB09617 $HASP373 PENEDD12 STARTED - INIT 1  - CLASS K  - SYS S0W1
5.37 JOB09617 -                                     -----TIMINGS (MINS.)-----
5.37 JOB09617 -STEPNAME PROCSTEP      RC  EXCP  CONN      TCB      SRB  CLOCK
5.37 JOB09617 -STEP01                  00   108    3      .00      .00   .0
5.37 JOB09617 -PENEDD12 ENDED.  NAME=E KARLSSON      TOTAL TCB CPU TIME=
5.37 JOB09617 $HASP395 PENEDD12 ENDED - RC=0000
-- JES2 JOB STATISTICS -----
NOV 2017 JOB EXECUTION DATE
  22 CARDS READ
  70 SYSOUT PRINT RECORDS
  0 SYSOUT PUNCH RECORDS
  8 SYSOUT SPOOL KBYTES
  0.00 MINUTES EXECUTION TIME
1 //PENEDD12 JOB SPEN1763,'E KARLSSON',          JO
  //          CLASS=K,                          00
  //          MSGCLASS=X,                       00
  //          SYSAFF=(S0W1,S0W2,S0W3)           00
  //=====
  // * THIS STEP WILL CONVERT THE PARTITIONED VB DATASET */ 00
```

As seen in the image above, this job output was eligible on JES2 members S0W1, S0W2 or S0W3. At the top of this output we can see that it was run on S0W1.

Several other types of values can be coded in the SYSAFF parameter such as:

- ~S0W3 which means the job can be processed on any member except S0W3
- All which means that any system can process the job

A maximum of 33 member names can be specified with this parameter.

SYSTEM Job Processing Environment Parameter

Similar to the SYSAFF parameter, the SYSTEM parameter defines the systems where the job can be processed. Up to 32 eight-character system names can be coded. A preceding hyphen (-) character can be used to identify that the job is not allowed to be processed on the specified system.

The ANY value indicates that it can run on any eligible system, while values of JGLOBAL - global processor only, and JLOCAL - local processor only, are used for JES3 environments.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(PLB#115) - 01.06                      Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //PLB#115  JOB CLASS=T,
000200 //      MSGCLASS=L,
000210 //      SYSTEM=(CHIGTEST,NEWYTEST,SEATTEST)
000300 //*
000400 //      SET MEM=SEARCH
000500 //PLI      EXEC PGM=IBMZPLI,PARM=('SOURCE')
000600 //STEPLIB DD DSN=IEL450.SIBMZCMP,DISP=SHR
000700 //      DD DSN=CEE.SCEERUN,DISP=SHR
000800 //      DD DSN=DSNB10.SDSNLOAD,DISP=SHR
000900 //OPTIONS DD DSN=IBMUSER.OPTIONS,DISP=SHR
001000 //DBRMLIB DD DSN=IBMUSER.JCL(DBRM),DISP=SHR
001100 //SYSDEBUG DD DSN=IBMUSER.SYSDEBUG,DISP=SHR
001200 //SYSIN    DD DISP=SHR,DSN=IBMUSER.PL1.SRC(&MEM)
001300 //SYSLIB   DD DISP=SHR,DSN=IBMUSER.PL1.SRC
001400 //SYSPRINT DD SYSOUT=*
001500 //SYSOUT   DD SYSOUT=*
001600 //SYSLIN   DD DSN=&&LOADSET,DISP=(MOD,PASS),UNIT=SYSALLDA,
001700 //          SPACE=(CYL,(1,1)),DCB=(LRECL=80,BLKSIZE=3200)
```

SCHENV Job Processing Environment Parameter

In your Workload Management (WLM) policy you may have defined a number of scheduling environments. A scheduling environment consists of a set of resources whose state can be set depending on the system they reside on. For example, you could have a scheduling environment named DBBAT that requires a resource representing the Db2 database being available to be set to OFF, and that a batch processing window resource be set to ON. When these resources meet this requirement, the DBBAT scheduling environment is available.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(DBBAT20) - 01.02                      Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000001 //DBBAT20  JOB CLASS=K,
000002 //      MSGCLASS=A,
000003 //      NOTIFY=IBMUSER,
000004 //      SCHENV=DBBAT
000005 //*
000006 //ALERTTAB EXEC PGM=IKJEFT01,DYNAMNBR=20
000007 //SYSTSPRT DD SYSOUT=*
000008 //SYSTSIN  DD *
000009 DSN SYSTEM(DB2)
000010 RUN  PROGRAM(DSNTIAD) -
000011 PLAN(DSNTIA31) -
000012 LIB('DB310.RUNLIB.LOAD')
000013 /*
000014 //SYSPRINT DD SYSOUT=*
000015 //SYSUDUMP DD SYSOUT=*
000016 //SYSIN    DD *
000017
000018 ALTER TABLE OLIBRARY ADD MEMBER CHAR(16) NOT NULL WITH DEFAULT;
```

When this batch job is submitted, JES will check the scheduling environment specified and then assign the work to a system that matches that scheduling environment.

Identification-Related Parameters

Normally, the system can identify the authorization requirements for a batch job as they are taken from the user submitting the job. However, there are several other lesser used JOB statement parameters that can be used for identification and authorization purposes.

USER=GREG, PASSWORD=*****

EMAIL='gham@bank.com'

GROUP=TESTER

SECLABEL=MGMT

Your organization may have a master ID and password in order to submit special jobs requiring authority. So that the job does not automatically use the submitter's ID, the USER parameter can define this ID. A PASSWORD parameter also needs to be supplied when using the USER parameter. The obvious problem here is that the password will need to be entered into the job, which may be visible for all who have access to it. The password itself is not displayed in the output of the job.

USER=GREG, PASSWORD=*****

EMAIL='gham@bank.com'

GROUP=TESTER

SECLABEL=MGMT

The EMAIL parameter can be used instead of the USER parameter to identify to the system the person that is submitting the job.

USER=GREG, PASSWORD=*****

EMAIL='gham@bank.com'

GROUP=TESTER

SECLABEL=MGMT

If you use RACF defined groups, then the GROUP parameter can be used to assign the TSO user to an alternate group rather than their default.

USER=GREG, PASSWORD=*****

EMAIL='gham@bank.com'

GROUP=TESTER

SECLABEL=MGMT

There may be some jobs that require additional security requirements in order to run. The SECLABEL parameter can be used to specify the security level at which the job is to run. This name represents a predefined RACF security level, defined by your security administrator. If you do not code this parameter, then the default security attributes will be used by the job, which is the norm for most people.

Running a Program using EXEC Statements

EXEC Statement Basics

Each EXEC statement marks the beginning of that step, which ends when another EXEC statement is encountered, or it is the end of the job. As well as informing the system of the programs to run, various parameters can be passed to the program in this statement.

A job can contain as many as 255 EXEC statements and must contain at least one, but it is rare today to see a large number of steps in a job. This is because it is more difficult to manage a job like this if a restart is required.

No JOB without Steps

A job must contain at least one step, otherwise it will fail. The SDSF output shown on the bottom screen indicates this exact problem, but it looks like there are steps in the JCL, which is shown at the top (it's the empty // curse).

```
EDIT          IBMUSER.JCL(FAMXTP15) - 01.21          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //FAMXTP15 JOB 6910-D112,'GINA HARRIS',
000200 //          CLASS=K,
000300 //          MSGCLASS=X
000400 //
000500 //* THE FIRST STEP IS USED FOR RECOVERY PURPOSES
000600 //* CHANGE THE SYSUT1 AND SYSUT2 DATA SETS AS REQUIRED
000700 //*
000800 //STEP1      EXEC PGM=ICEGENER
000900 //SYSPRINT DD SYSOUT=*
001000 //SYSUT1 DD DSN=GHEMAST.FAMAPS.D256,DISP=OLD
001100 //SYSUT2 DD DSN=GHEMAST.FAMAPS.D256.BACKUP,DISP=(,CATLG),
001200 //          UNIT=SYSDA,SPACE=(CYL,(10,10),RLSE)
001300 //SYSIN DD DUMMY
***** Bottom of Data *****
```

```
1 //FAMXTP15 JOB 6910-D112,'GREG HAMLYN',
  //          CLASS=K,
  //          MSGCLASS=X
STMT NO. MESSAGE
1 IEFC607I JOB HAS NO STEPS
***** BOTTOM OF DATA *****
```

Statement Name - EXEC

In the example below, the EXEC statements do not have a name. This is because it is optional, as this statement's only purpose is to invoke a program.

```
000300 // EXEC PGM=TRANAPL
000400 //INPUT DD DSN=PROD.D112Y17.PENTRANS,DISP=OLD
000500 //OUTPUT DD DSN=IBMUSER.TOTAL.PENTRANS,DISP=(,CATLG),
000600 // UNIT=SYSDA,SPACE=(CYL,(10,10,RLSE))
000700 //SYSPRINT DD SYSOUT=*
000800 //SYSOUT DD SYSOUT=*
000900 //*
001000 // EXEC PGM=TRANXCT
001100 //SYSPRINT DD SYSOUT=*
001200 //INDD1 DD DSN=IBMUSER.TOTAL.PENTRANS,DISP=SHR
001300 //SYSIN DD *
001400 RECORDS=10000
***** Bottom of Data *****
```

However, it is good practice to use them because:

- You need them for restart statements.
- It makes debugging easier.
- May have duplication issues in the long run.
- We are also able to refer back to certain statements in previous steps. To do this, we also need a statement name.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
EDIT IBMUSER.JCL(APENCHK) - 01.01 Columns 00001 00072
Command ==> Scroll ==> CSR
002000 //STEP3 EXEC PGM=IEBGENER
002100 //SYSUT1 DD DSN=IBMUSER.SALESIN,DISP=OLD
002200 //SYSUT2 DD DSN=IBMUSER.PEN.TRANS.PARMPEN,
002300 // DCB=(RECFM=FB,LRECL=80,BLKSIZE=32720),
002400 // SPACE=(CYL,(1,1),RLSE),UNIT=SYSDA,DISP=(,CATLG)
002500 //SYSPRINT DD SYSOUT=*
002600 //SYSIN DD DUMMY
002700 //*
002800 //STEP4 EXEC PGM=IEBGENER
002900 //SYSUT1 DD DSN=*STEP3.SYSUT2,DISP=SHR
003000 //SYSUT2 DD SYSOUT=*
003100 //SYSPRINT DD SYSOUT=*
003200 //SYSIN DD DUMMY
***** Bottom of Data *****
```

Although this has not yet been covered, you are also able to refer back to certain statements in previous steps. For example, to use the same data set created earlier in the job. In order to do this, you need to specify a step name. You can see in this example that on line 002900 the DSN parameter uses an asterisk (*) to indicate a referback, and what follows is the step name and DD statement name. It says to use the same data set used in STEP3 by DD statement SYSUT2. This is identified on line 002200. Do not worry too much about this parameter at this stage, it is just included here to highlight referencing of a step name.

EXEC Operation


Following the statement name, at least one space needs to be coded before entering the statement type EXEC. If the name is not specified, EXEC must appear at least one blank character after the // characters.

- If there's no EXEC for a statement, an error will appear.

Programs

The next step is to tell the system the program, or programs that it needs to run. This can be as easy as coding PGM=programname. This will instruct the system to look in the system program libraries for the program specified. These programs are stored as members in partitioned data sets. Once located, the program is then loaded into memory, and begins running.

- There must be a space between EXEC and PGM.



JOBLIB and STEPLIB Statements

If you are developing or testing programs there is a good chance that they will not reside in the default program libraries that the submitted JCL uses. In these situations, you can specify a JOBLIB or STEPLIB statement to instruct the system to begin the search for programs in these libraries.

- JOBLIB - When this job is run, the data specified in it - IBMUSER.LOAD will be searched first when there is any program request. If it is not located here, the default system libraries will then be searched.
- STEPLIB - this performs the same function as JOBLIB but only for a single step. In this scenario below, IGYCRCTL program will be searched for in the data set IBMUSER.MOD first. Other programs in this job will only use the default system libraries.

```
000100 //BLKJET01 JOB 6910-D112,'GINA HARRIS',
000200 //      CLASS=C,
000300 //      MSGCLASS=X
000400 //      JOBLIB DD DSN=IBMUSER.LOAD,DISP=SHR
000500 //
000600 //STEP1 EXEC PGM=BLKSRTIT
000700 //SRTIN DD DSN=IBMUSER.JET.DAILY.PAYMENTS,DISP=OLD
000800 //SRTOUT DD DSN=IBMUSER.SORTED.JET.DAILY.PAYMENTS,DISP=(,CATLG),
000900 //      SPACE=(CYL,(1,1),RLSE),UNIT=SYSDA
001000 //REPORT DD SYSOUT=R
001100 //
001200 //ALERTAB EXEC PGM=GHCHKDB,DYNAMNBR=20

000100 //OOCOMP JOB D227898,'COBOL COMPILE',CLASS=A,
000200 //      MSGCLASS=X
000300 //
000400 //      SET MEM=OOCBOOK
000500 //      EXEC PGM=IGYCRCTL,REGION=0M,
000600 //      PARM='LIST,MAP,SOURCE,XREF(SHORT),DLL,COMPILE,RENT,THREAD'
000700 //SYSIN DD DSN=IBMUSER.SRC(OOCBOOK),DISP=SHR
000800 //SYSLIB DD DISP=SHR,DSN=IBMUSER.SRC
000900 //      DD DISP=SHR,DSN=CEE.ACEEsrc1
001000 //STEPLIB DD DISP=SHR,DSN=IBMUSER.MOD
```


Program Referback

The method shown previously is the most common way that you will see a single program being invoked. There is a possibility though that your organization may use the PGM parameter for referring back to a JCL statement earlier in your job. A scenario might be that your first step creates a temporary program which then needs to be referred to in a later step.

- The '*' - in JCL the asterisk is used in several different ways; in this case it indicates a referback
- COMP - A period (.) is used to separate referback data. COMP indicates the name of the previous step that will be used to obtain the program name. If SYSLMOD had not been coded, the system would have used the program from the COMP step - IEWL.
- SYSLMOD - this is used to indicate the DD statement that contains the name of the program to be used - PROG.

```
001500 //COMP      EXEC PGM=IEWL,REGION=0M,COND=(5,LT,COMP1),
001600 //          PARM='LIST,XREF'
001700 //STEPLIB DD DSN=IGY520.SIGYCOMP,DISP=SHR
001800 //SYSLIB DD DISP=SHR,DSN=CEE.SCEELKED
001900 //SYSLIN DD DISP=(OLD,DELETE),DSN=**LOADSET
002000 //SYSLMOD DD DISP=OLD,DSN=IBMUER.MOD(&MEM)
002100 //SYSPRINT DD SYSOUT=A
002200 //SYSUT1 DD UNIT=SYSDA,SPACE=(1024,(200,20))
002300 //GO        EXEC PGM=*.COMP.SYSLMOD
```

Procedures

Another way of providing programs to be run is through a procedure. A procedure is a set of JCL statements, multiple steps usually, stored in a separate partitioned data set. They are useful if there is some common program processing that needs to be used by a number of users. In this way, the user only needs to code the name of the procedure on a single statement, rather than enter all of this code into their JCL.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
EDIT      IBMUSER.JCL(ARUNREP) - 01.05      Columns 00001 00072
Command ==>                                Scroll ==> CSR
***** Top of Data *****
000100 //ARUNREP JOB MSGCLASS=C,NOTIFY=IBMUSER,CLASS=M
000200 //*
000300 //RUNGH EXEC GHPROC
***** Bottom of Data *****
```



```
File Edit Edit_Settings Menu Utilities Compilers Test Help
EDIT      VENDOR.PROCLIB(GHPROC) - 01.05      Columns 00001 00072
Command ==>                                Scroll ==> CSR
***** Top of Data *****
000100 //STEP1 EXEC PGM=ALBKALL,REGION=4M
000200 //SYSPRINT DD SYSOUT=*
000300 //SYSIN DD DISP=SHR,DSN=VENDOR.PARMLIB(GHPCKS1)
000400 //OUTDD DD DSN=**VOLUMEUR,DISP=(,PASS),
000500 //          UNIT=SYSDA,
000600 //          SPACE=(TRK,(5,5),RLSE),
000700 //          DCB=(LRECL=80,RECFM=FB)
000800 //*
000900 //STEP2 EXEC PGM=IEBGENER
001000 //SYSIN DD DUMMY
001100 //SYSPRINT DD SYSOUT=*
```


Calling a Procedure

There are two ways of calling a procedure, using the PROC parameter and specifying the procedure name. Both of these methods perform the same task.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL (ARUNREP) - 01.05          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //ARUNREP JOB MSGCLASS=C,NOTIFY=IBMUSER,CLASS=K
000200 //*
000300 //RUNGH EXEC GHPROC
***** Bottom of Data *****
```

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL (ARUNREP) - 01.06          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //ARUNREP JOB MSGCLASS=C,NOTIFY=IBMUSER,CLASS=K
000200 //*
000300 //RUNGH EXEC PROC=GHPROC
***** Bottom of Data *****
```

Locating a Procedure

Just as programs are searched for in default system libraries when they are referenced, so too are procedures. But with these items, system procedure libraries are searched and if the procedure you are looking for is not found, then the messages highlighted here will be produced.

```
Display Filter View Print Options Search Help
-----
SDSF OUTPUT DISPLAY JNAPAN30 JOB09688 DSID      2 LINE 0      COLUMNS 02- 81
COMMAND INPUT ==>                                SCROLL ==> CSR
***** TOP OF DATA *****
JES2 JOB LOG -- SYSTEM S0W1 -- NODE

00.06.21 JOB09688 ---- MONDAY, 13 NOV 2017 ----
00.06.21 JOB09688 IRR010I USERID IBMUSER IS ASSIGNED TO THIS JOB.
00.06.21 JOB09688 IEF452I JNAPAN30 - JOB NOT RUN - JCL ERROR 770
----- JES2 JOB STATISTICS -----
      3 CARDS READ
     17 SYSOUT PRINT RECORDS
      0 SYSOUT PUNCH RECORDS
      1 SYSOUT SPOOL KBYTES
      0.00 MINUTES EXECUTION TIME
      1 //JNAPAN30 JOB MSGCLASS=C,NOTIFY=IBMUSER,CLASS=K
        //*
      2 //JNSTEP1 EXEC PROC=JNENG05
STMT NO. MESSAGE
      2 IEF612I PROCEDURE JNENG05 WAS NOT FOUND
***** BOTTOM OF DATA *****
```

EXEC Statement Parameters

REGION Parameter

As seen previously, the REGION parameter can be specified on the JOB statement, and how it defines the maximum amount of memory to be used by any program in your job. In some situations though, you may only need to specify a memory requirement for one of the programs in your job.

The REGION parameter can be used on the EXEC statement as shown here, and uses the same syntax as discussed previously

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
EDIT IBMUSER.JCL(CSFJ) - 01.04 Columns 00001 00072
Command ==> Scroll ==> CSR_
***** Top of Data *****
000100 //CSFJ JOB (D-117), 'GMH RUN',
000200 // CLASS=A,
000300 // MSGCLASS=X
000400 // *
000500 // * UNLOAD SMF RECORDS TO PRINT *
000600 // *
000700 //SMFDMP EXEC PGM=IFASMFDP,REGION=6M
000800 //DUMPIN DD DISP=SHR,DSN=SYS1.S0W1.MAN1.DATA
000900 //DUMPOUT DD SYSOUT=*
001000 //SYSPRINT DD SYSOUT=*
001100 //SYSIN DD * sub
001200 // INDD(DUMPIN,OPTIONS(DUMP))
001300 // OUTDD(DUMPOUT,TYPE(82))
***** Bottom of Data *****
```

- When using this parameter when specifying a procedure, then all programs within the procedure will use the REGION specification.
- If you only need to provide a memory requirement for a specific step within a procedure then this can be coded as shown below, it is rare to do this. In this example, the procedure step name is provided after coding a period (.) after REGION.

```
000300 //MYPROCS JCLLIB ORDER=IBMUSER.PROCLIB
000400 //JNSTEP1 EXEC PROC=JNENG05,REGION.STEP2=4M
***** Bottom of Data *****
```

- In the example below, a REGION parameter is coded on both JOB and EXEC statements. This could arise if parts of the JCL have been copied from different sources. If this scenario occurs, the JOB statement REGION parameter will override any EXEC statement equivalent.

```
000100 //SUPCHK JOB (67103, 'DEPT/106', SECT04), 'PAOLA MASONI',
000200 // MSGCLASS=X,
000300 // CLASS=K,
000400 // REGION=6M
000500 // *
000600 //SUPERC EXEC PGM=ISRSUPC,REGION=0M,
000700 // PARM=(DELTAL,LINECMP,'')
000800 //NEWDD DD DSN=IBMUSER.REPORT2,DISP=SHR
000900 //OLDD DD DSN=IBMUSER.REPORT4,DISP=SHR
001000 //OUTDD DD SYSOUT=A
```

COND Parameter

The COND parameter can also be used on the EXEC statement, but is used more specifically to identify whether the step should be run.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL(BLASTT05) - 01.11          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** ***** Top of Data *****
000100 //BLASTT05 JOB , 'JANE WILLIAMS',
000200 //          CLASS=K,
000300 //          MSGCLASS=X
000400 //          *
000500 //STEP1     EXEC PGM=BLSORT  Completion code of 0
000600 //          *
000700 //STEP2     EXEC PGM=BLSTRIP  Completion code of 0
000800 //          *
000900 //STEP3     EXEC PGM=BLREPORT,COND=(0,NE)
***** ***** Bottom of Data *****
```

The example displayed here shows how a simple COND parameter is used. There are three steps defined, with the last one containing a COND parameter. After the first two steps are run - assuming they both complete with a return code of zero, successful - your last step is a management report and should only run if all preceding steps have a zero-condition code.

The COND parameter can be quite confusing to determine sometimes how it is processing step condition codes. The example used on the previous page was a relatively simple one.

```
000700 //STEP2     EXEC PGM=BLSTRIP
000800 //          *
000900 //STEP3     EXEC PGM=BLREPORT,COND=(0,NE)
```

```
000700 //STEP2     EXEC PGM=BLSTRIP
000800 //          *
000900 // IF (RC=0) THEN
001000 //STEP3     EXEC PGM=BLREPORT
001100 // ENDIF
```

IBM have recognized the difficulty users have with interpreting this parameter, and recommend using an IF, THEN, ELSE, ENDIF structure, which will be more familiar to programmers.

PARM Parameter

There will be times when you need to pass additional information to the program in your EXEC statement. For example, a program you have written may perform several tasks with data that is input to it, but not necessarily every time the program is run. In this scenario some parameter information can be passed to the program, which the program will use in its processing.

The EXEC statement PARM parameter can be used for this purpose.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT      IBMUSER.JCL(COBCOMP) - 01.99                      Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** ***** Top of Data *****
000100 //IBMUCOB JOB 123,'COBOL COMPILE',CLASS=A,MSGCLASS=X,
000200 //      NOTIFY=IBMUSER
000300 //*
000400 //      SET MEM=COMPUTE2
000500 //COMP1 EXEC PGM=IGYCRCTL,
000600 //      PARM=LIST,XREF
000700 //STEPLIB DD DSN=IGY520.SIGYCOMP,DISP=SHR
000800 //SYSIN DD DISP=SHR.DSN=IBMUSER.COBOL.SRC(&MEM)
000900 //SYSLIB DD DISP=SHR.DSN=IBMUSER.COBOL.SRC
001000 // DD DISP=SHR.DSN=CEE.ACEE5SRC1
001100 //SYSPRINT DD SYSOUT=B
001200 //SYSLIN DD DISP=(MOD,PASS),DSN=&&LOADSET,SPACE=(80,(10,10)),
001300 //      UNIT=SYSDA
001400 //SYSUT1 DD SPACE=(CYL,(1,1)),UNIT=SYSDA
001500 //SYSUT2 DD SPACE=(CYL,(1,1)),UNIT=SYSDA
001600 //SYSUT3 DD SPACE=(CYL,(1,1)),UNIT=SYSDA
001700 //SYSUT4 DD SPACE=(CYL,(1,1)),UNIT=SYSDA
001800 //SYSUT5 DD SPACE=(CYL,(1,1)),UNIT=SYSDA
```

Note: The program must explicitly be written to accept and process the PARM information passed to it. As a result, the format and types of PARM data that can be passed must be documented.

Syntax Rules:

- What is the maximum length of PARM data?
 - Cannot exceed 100 characters
- What if PARM data will not fit entirely on one line?
 - You can extend the PARM data by ensuring that the sub parameters are enclosed in parentheses. At the end of a sub parameter definition, code a comma, and begin the continuation on the following line between columns 4 and 6, inclusive.

```
000400 //PLI      EXEC PGM=IBMZPLI,PARM=(SOURCE,ZZED,'JK;22',GLOBAL,
000500 //      'CULLDATE - 2018/02/11',KD30)
```

- How do you separate sub parameters that are required in PARM data?
 - Separate them using commas and they must be enclosed in parentheses or single quotes

```
000500 //COMP1 EXEC PGM=IGYCRCTL,
000600 //      PARM='LIST,XREF'
```

- What if you need to pass PARM data to one program within a procedure
 - The PARM.procedurestep can be used to specify that the PARM data is only passed to the specified step in that procedure. If the procedure step name is not used, then the PARM data will only be passed to the first step in the procedure.

```
000300 //INSTP01 EXEC PROC=STPOOLBK,
000400 //          PARM.STEP2=(LIST,XREF)
```

- What if PARM data contains special characters or blanks
 - It needs to be enclosed in single quotes
- What if you enter incorrect PARM data?
 - The program must be defined to interpret and act on the PARM data if it is specified. If you enter incorrect data, then often the program will be designed to just ignore it.

PARMDD Parameter

Rather than having to code your parameter information directly into the EXEC statement, you can also use a PARMDD parameter for this purpose. This instructs the system to obtain parameter information from another statement within the JCL. This statement may contain a reference to a data set that contains this data.

One benefit of using this in preference to the PARM parameter is that more than 100 characters can be specified. Note that the PARMDD parameter cannot be used with the PARM parameter on the same statement.

The screenshot shows an IBM JCL editor window titled 'IBMUUSER.JCL(OOCBKUP) - 01.05'. The window has a menu bar with 'File', 'Edit', 'Edit_Settings', 'Menu', 'Utilities', 'Compilers', 'Test', and 'Help'. The main text area displays a JCL program with the following lines:

```
000100 //OOCOMP JOB D22789B,'COBOL COMPILE',CLASS=A,
000200 //          MSGCLASS=X, TYPRUN=SCAN
000300 //          *
000400 //          SET MEM=OOCBOOK
000500 //COMP1 EXEC PGM=IGYCRCTL,PARMDD=OOCPARMS
000600 //STEPLIB DD DISP=SHR,DSN=IBMUUSER.MOD
000700 //          DD DISP=SHR,DSN=CEE.SCEERUN2
000800 //SYSIN DD DSN=IBMUUSER.COBOL.SRC(OOCBOOK),DISP=SHR
000900 //SYSLIB DD DISP=SHR,DSN=IBMUUSER.COBOL.SRC
001000 //          DD DISP=SHR,DSN=CEE.ACEE5SRC1
001100 //OOCPARMS DD DSN=VENDOR.PARMLIB(OOCPARMS),DISP=SHR
001200 //          *
001300 //SYSJAVA DD PATH='/u/ibmuser/java/elpsorttbl.java',
001400 //          PATHOPTS=(OWRONLY,OCREAT,OTRUNC),
001500 //          PATHMODE=SIRWXU,
001600 //          FILEDATA=TEXT
001700 //SYSPRINT DD SYSOUT=*
001800 //SYSLIN DD DSN=*&OBJECT(TSTOOC),UNIT=SYSALLDA,DISP=(MOD,PASS),
```

Defining Symbol Values

Another item you may encounter on an EXEC statement is a symbol. These are character strings that represent variable information within the JCL. The screen at the top shows a WORK variable being passed to a procedure. In the SDSF output for the job, you can see where this value has been substituted.

```
000100 //ARUNREP JOB MSGCLASS=C,NOTIFY=IBMUSER,CLASS=K
000200 //*
000300 //INSTP01 EXEC PROC=GHPENBK,WORK='5,5'
```

```
1 //ARUNREP JOB MSGCLASS=C,NOTIFY=IBMUSER,CLASS=K
  //*
2 //INSTP01 EXEC PROC=GHPENBK,WORK='5,5'
3 XXGHPENBK PROC
4 XXSTEP1 EXEC PGM=SORT
5 XXSYSOUT DD SYSOUT=*
6 XXSORTIN DD DSN=IBMUSER.PEN.TRANS.DAILY,DISP=OLD
7 XXSORTOUT DD DSN=IBMUSER.SORTED.PEN.TRANZ,DISP=(,CATLG),
  XX SPACE=(CYL,(10,10),RLSE),UNIT=SYSDA
8 XXSORTWK01 DD UNIT=SYSALLDA,SPACE=(CYL,(&WORK))
  IEFC653I SUBSTITUTION JCL - UNIT=SYSALLDA,SPACE=(CYL,(5,5))
9 XXSORTWK02 DD UNIT=SYSALLDA,SPACE=(CYL,(&WORK))
  IEFC653I SUBSTITUTION JCL - UNIT=SYSALLDA,SPACE=(CYL,(5,5))
```

TIME Parameter

This parameter can also be used on an EXEC statement, but only to specify the maximum amount of CPU time for that specific step.

```
File Edit Edit_Settings Menu Utilities Compilers Test Help
-----
EDIT          IBMUSER.JCL(PLB#115) - 01.08          Columns 00001 00072
Command ==>                                         Scroll ==> CSR
***** Top of Data *****
000100 //PLB#115 JOB CLASS=K,
000200 //          MSGCLASS=L
000300 //*
000400 //          SET MEM=SEARCH
000500 //PLI        EXEC PGM=IBMZPLI,PARM=(SOURCE,LIST),TIME=(,20)
000600 //STEPLIB    DD DSN=IEL450.SIBMZCMP,DISP=SHR
000700 //OPTIONS    DD DSN=IBMUSER.OPTIONS,DISP=SHR
000800 //DBRMLIB     DD DSN=IBMUSER.JCL(DBRM),DISP=SHR
000900 //SYSDEBUG    DD DSN=IBMUSER.SYSDEBUG,DISP=SHR
001000 //SYSIN       DD DISP=SHR,DSN=IBMUSER.PL1.SRC(&MEM)
001100 //SYSLIB      DD DISP=SHR,DSN=IBMUSER.PL1.SRC
001200 //SYSPRINT    DD SYSOUT=*
001300 //SYSOUT      DD SYSOUT=*
001400 //SYSLIN      DD DSN=&&LOADSET,DISP=(MOD,PASS),UNIT=SYSALLDA,
001500 //          SPACE=(CYL,(1,1)),DCB=(LRECL=80,BLKSIZE=3200)
001600 //SYSUT1      DD DSN=&&SYSUT1,UNIT=SYSALLDA,
001700 //          SPACE=(1024,(200,50),,CONTIG,ROUND),DCB=BLKSIZE=1024
001800 //*****
```