

Quantum Design-Program-Compilation (QuDPC) Tutorial TorchQuantum Library



Hanrui Wang¹, Jiaqi Gu², Zirui Li³, Zhiding Liang⁴, Weiwen Jiang⁵, Yiyu Shi⁴, David Z. Pan², Yongshan Ding⁶, Frederic T. Chong⁷, Song Han¹

¹MIT ²UT Austin ³SJTU ⁴University of Notre Dame ⁵George Mason University ⁶Yale University ⁷University of Chicago















- TorchQuantum An open-source library for differentiable quantum simulation and quantum machine learning
- https://github.com/mit-han-lab/torchquantum





Features

- Easy construction and simulation of quantum circuits in PyTorch
- Dynamic computation graph for easy debugging
- Gradient support via autograd
- Batch mode inference and training on CPU/GPU.
- Easy deployment on real quantum devices such as IBMQ
- Easy hybrid classical-quantum model construction
- (coming soon) **pulse-level** simulation
- Tutorials, videos and example projects of QML and using ML to optimize quantum computer system problems



Statevector

```
_state = torch.zeros(2 ** self.n_wires, dtype=C_DTYPE)
_state[0] = 1 + 0j
```

Quantum Gates




Quantum Gates

```
def crx matrix(params):
   theta = params.type(C_DTYPE)
   co = torch.cos(theta / 2)
   jsi = 1j * torch.sin(-theta / 2)
   matrix = torch.tensor([[1, 0, 0, 0],
                           [0, 1, 0, 0],
                           [0, 0, 0, 0],
                           [0, 0, 0, 0]], dtype=C_DTYPE, device=params.device
                          ).unsqueeze(0).repeat(co.shape[0], 1, 1)
   matrix[:, 2, 2] = co[:, 0]
   matrix[:, 2, 3] = jsi[:, 0]
   matrix[:, 3, 2] = jsi[:, 0]
   matrix[:, 3, 3] = co[:, 0]
    return matrix.squeeze(0)
```

Matrix-vector multiplication: torch.einsum and torch.bmm

Example of QNN





```
import torch.nn as nn
import torch.nn.functional as F
import torchquantum as tq
import torchquantum.functional as tqf

class QFCModel(nn.Module):
    def __init__(self):
        super().__init__()
        self.n_wires.=.4
        self.q_device = tq.QuantumDevice(n_wires=self.n_wires)
        self:measure = tq:MeasureAlt(tq:PauliZ)
```

Initialize a quantum device

```
Specify encoder gates
```

Specify trainable gates



```
# down-sample the image
                                               x = F.avg_pool2d(x, 6).view(bsz, 16)
                                                # reset qubit states
Reset statevector
                                               self.q_device.reset_states(bsz)
                                                 # encode the classical image to quantum domain
Encode classical pixels
                                               for k, gate in enumerate(self.encoder_gates):
                                                 gate(self.q device, wires=k % self.n wires, params=x[:, k])
                                                # add some trainable gates (need to instantiate ahead of time)
                                               self.rx0(self.q_device, wires=0)
Apply the trainable gates
                                               self.rv0(self.q device, wires=1)
                                               self.rz0(self.a device, wires=3)
                                               self.crx0(self.q device, wires=[0, 2])
                                                # add some more non-parameterized gates (add on-the-fly
                                               tqf.hadamard(self.q_device, wires=3)
                                               tqf.sx(self.q device, wires=2)
Apply some non-trainable gates
                                               tqf.cnot(self.q device, wires=[3, 0])
                                               tqf.qubitunitary(self.q device0, wires=[1, 2], params=[[1, 0, 0, 0],
                                                                                                 [0, 0, 0, 1i],
                                                                                                 [0, 0, -1i, 0])
                                               # perform measurement to get expectations (back to classical domain)
Measure to get classical values
                                               x = self.measure(self.q_device).reshape(bsz, 2, 2)
                                               # classification
                                               x = x.sum(-1).squeeze()
                                               x = F.\log_softmax(x, dim=1)
                                               return x
```

def forward(self, x):
 bsz = x.shape[0]

Tutorial Colab and videos

Quantum Convolution (Quanvolution) for MNIST image classification

Authors: Zirui Li, Hanrui Wang

Use Colab to run this example: Open in Colab

See this tutorial video for detailed explanations:





Zirui Li, Hanrui Wang MIT HAN Lab





Speedup over existing frameworks

- 2 orders of magnitude faster than other frameworks
 - Tensorized computation
 - Well optimized codes on CPU/GPU



WonJoon_YUN

Thanks! Mr. Wang!

Actually, our research team has studied quantum multi-agent reinforcement learning with leveraging torchquantum, which reduces 99% computational cost (6 days in other libraries but in <40 minutes in torchquantum). It enables feasibility studies on many existing QML research. Thank you and the torchquantum developers!!

Current status

- Users from around 20 research institutes/companies
- Over 250 stars on GitHub
- We will hold a full tutorial session on TorchQuantum in Quantum Week (QCE) this year



https://github.com/mit-han-lab/torchquantum



Quantum Computer Systems Lecture Series

A lecture series on quantum computer systems, software and cross-stack optimizations. Talks will cover quantum computing basics and state-of-the-art research topics.

Speakers

Prof. Yongshan Ding, Yale

Prof. Yufei Ding, UCSB

Prof. Weiwen Jiang, GMU

Prof. Gushu Li, UPenn

Prof. Tongvang Li, PKU.

Prof. Prineha Narang, Harvard

Prof. Tirthak Patel, Rice

Prof. Chen Qian, UCS

Prof. Sabre Kais, Purdue

Prof. Robert Wille, TUM

Dr. Junyu Liu, UChicago

Dr. Gokul Ravi, UChicago

Jinglei Cheng, USC

Siyuan Niu, Montpellier

Bochen Tan, UCLA

Wei Tang, *Princeton*Hanrui Wang, *MIT*Zhixin Song, *Gatech*

Topics

Quantum Basics

NISQ Algorithms

Quantum Compilation

Noise Mitigation

Quantum ML

Architecture Design

Program Debugging

Error Correction

Classical Simulation

Measurement

...

10:30AM ET

Thursdays

Website

Mailing-list





TorchQuantum library







To attend, visit sites.nd.edu/quantum

For TorchQuantum library, visit qmlsys.mit.edu/ or scan QC code

Organized by Zhiding Liang (Notre Dame), Hanrui Wang (MIT)