VP11 — Properties, traceability and model gaps

Revision: `e2a2f39e5c78476bb1bba08e406114367eb59953f02a63e952e435c880d24007`.

Declarations and all facts with source positions; support boundaries are retained.

Snapshot coverage

Counts describe this checked source snapshot, not implementation coverage or verification evidence. This inspection index contains no combined architecture diagram.

Inventory	Count
Declarations	312
Facts	1034
Explicit properties	195
Reported model gaps	1

Declaration kinds

Kind / verb	Count
actor	1
channel	40
container	1
contract	44
dataset	3
feature	10

field	14
functionality	28
interface	14
message	101
mode	1
scenario	22
unit	22
usecase	11

Fact verbs

Kind / verb	Count
allocated-to	28
consumes	24
contains	19
contributes-to	74
exercises	22
has	195
has-field	14
holds	3
owns	28
permits	101
pursues	11
replies-to	18
runs-in	22

step	116
supports	13
upholds	144
uses	202

Explicit properties

Property values, completeness and implementation-status are source assertions, not proof of implemented behavior or owner acceptance. Missing properties are unspecified, with no inferred defaults.

- AcceptCurrentFrame: message-kind = event. Source fact: f0000.
- AcceptCurrentModel: message-kind = event. Source fact: f0002.
- AcceptWorkerTicket: message-kind = event. Source fact: f0004.
- ActivateExternalTarget: message-kind = event. Source fact: f0006.
- ActivateRootAndHistory: message-kind = event. Source fact: f0008.
- AdmitDocument: message-kind = request. Source fact: f0010.
- AdmitGeneratedDocument: message-kind = request. Source fact: f0012.
- AdoptPreferencesDraft: message-kind = event. Source fact: f0014.
- AdvanceGenerationSequence: message-kind = event. Source fact: f0016.
- ApplyTextEdit: message-kind = event. Source fact: f0052.
- AttemptRelease: message-kind = event. Source fact: f0054.
- BeginPreferencesDraft: message-kind = event. Source fact: f0056.
- CacheCompatibleScene: message-kind = event. Source fact: f0059.
- CancelPdfRequest: message-kind = event. Source fact: f0061.
- CancelPreviousChild: message-kind = event. Source fact: f0063.
- CancelUnpublishedJob: message-kind = event. Source fact: f0065.
- CandidateRead: message-kind = result. Source fact: f0067.
- CandidateReadFailed: message-kind = result. Source fact: f0070.

- CaptureContextTarget: message-kind = event. Source fact: f0073.
- CheckCurrentMapping: message-kind = event. Source fact: f0076.
- CheckReferenceGeneration: message-kind = event. Source fact: f0078.
- ChooseCancel: message-kind = result. Source fact: f0080.
- ChooseInternalFile: message-kind = event. Source fact: f0083.
- ChooseSave: message-kind = result. Source fact: f0085.
- ChooseUnsaved: message-kind = request. Source fact: f0088.
- ChooserOpensThenChangesRoot: completeness = closed. Source fact: f0091.
- ClassifyExternalTarget: message-kind = event. Source fact: f0098.
- CommitPdfCandidate: message-kind = event. Source fact: f0100.
- CommitVisit: message-kind = event. Source fact: f0102.
- CompleteObsoleteWorker: message-kind = event. Source fact: f0104.
- ContextInteractionContract: completeness = closed. Source fact: f0109.
- ContextMenuDismissed: completeness = closed. Source fact: f0114.
- CurrentWritten: message-kind = result. Source fact: f0119.
- DebounceElapsed: message-kind = event. Source fact: f0122.
- DeliverGeneratedMain: message-kind = request. Source fact: f0124.
- DiagramInterpretationContract: completeness = closed. Source fact: f0127.
- DiagramLayoutCallsContract: completeness = closed. Source fact: f0132.
- DiagramScenePrepared: completeness = closed. Source fact: f0138.
- DirtyGeneratedDeliveryRejected: completeness = closed. Source fact: f0146.
- DirtyOpenCancelled: completeness = closed. Source fact: f0153.
- DiscardObsoleteCompletion: message-kind = event. Source fact: f0159.
- DiscardPdfCandidate: message-kind = event. Source fact: f0161.
- DismissContextMenu: message-kind = event. Source fact: f0163.
- DocumentBytes: presence = required. Source fact: f0165.
- DocumentBytes: value-type = bytes. Source fact: f0166.
- DocumentCallsContract: completeness = closed. Source fact: f0168.

- DocumentChanged: message-kind = event. Source fact: f0172.
- DocumentIdentity: presence = required. Source fact: f0174.
- DocumentIdentity: value-type = unsigned. Source fact: f0175.
- DocumentNotificationsContract: completeness = closed. Source fact: f0192.
- DocumentOpened: message-kind = result. Source fact: f0196.
- DocumentPath: presence = required. Source fact: f0199.
- DocumentPath: value-type = text. Source fact: f0200.
- DocumentRejected: message-kind = result. Source fact: f0202.
- DocumentRevision: presence = required. Source fact: f0205.
- DocumentRevision: value-type = unsigned. Source fact: f0206.
- DocumentStateChangesContract: completeness = closed. Source fact: f0213.
- DocumentStateShape: completeness = closed. Source fact: f0216.
- EditIntentsContract: completeness = closed. Source fact: f0258.
- EditedPreviewPublished: completeness = closed. Source fact: f0261.
- ExpandReference: message-kind = event. Source fact: f0282.
- ExportBytes: presence = required. Source fact: f0284.
- ExportBytes: value-type = bytes. Source fact: f0285.
- ExportDocument: presence = required. Source fact: f0286.
- ExportDocument: value-type = unsigned. Source fact: f0287.
- ExportInterpretationContract: completeness = closed. Source fact: f0289.
- ExportLayoutContract: completeness = closed. Source fact: f0293.
- ExportPagesLaidOut: message-kind = result. Source fact: f0296.
- ExportPath: presence = required. Source fact: f0299.
- ExportPath: value-type = text. Source fact: f0300.
- ExportRevision: presence = required. Source fact: f0301.
- ExportRevision: value-type = unsigned. Source fact: f0302.
- ExportSnapshotParsed: message-kind = result. Source fact: f0303.
- ExportSnapshotShape: completeness = closed. Source fact: f0306.

- ExternalOpeningContract: completeness = closed. Source fact: f0313.
- ExternalTargetHandedOff: completeness = closed. Source fact: f0316.
- FavoriteFileChosen: message-kind = event. Source fact: f0327.
- FavoriteFileOpens: completeness = closed. Source fact: f0330.
- FavoriteFolderChangesRoot: completeness = closed. Source fact: f0342.
- FavoriteFolderChosen: message-kind = event. Source fact: f0347.
- FreezeExportSnapshot: message-kind = event. Source fact: f0359.
- FullscreenChangesPresentation: completeness = closed. Source fact: f0363.
- GeneratedAdmissionContract: completeness = closed. Source fact: f0368.
- GeneratedDeliveryContract: completeness = closed. Source fact: f0374.
- GeneratedDocumentCallsContract: completeness = closed. Source fact: f0379.
- GeneratedDocumentChanged: message-kind = event. Source fact: f0382.
- GeneratedDocumentOpened: message-kind = result. Source fact: f0386.
- GeneratedIntentsContract: completeness = closed. Source fact: f0390.
- GeneratedMainAccepted: message-kind = result. Source fact: f0393.
- GeneratedMainRejected: message-kind = result. Source fact: f0396.
- GeneratedReplacementReleasesOldLease: completeness = closed. Source fact: f0400.
- GeneratedSelectionSupersedes: completeness = closed. Source fact: f0412.
- GenerationLifecycleContract: completeness = closed. Source fact: f0454.
- GenerationSequence: presence = required. Source fact: f0457.
- GenerationSequence: value-type = unsigned. Source fact: f0458.
- GenerationStateShape: completeness = closed. Source fact: f0459.
- IndexChangesContract: completeness = closed. Source fact: f0467.
- IndexIntentsContract: completeness = closed. Source fact: f0471.
- InspectDirtyMain: message-kind = event. Source fact: f0473.
- InstallNewLease: message-kind = event. Source fact: f0475.
- InteractionObservationShape: completeness = closed. Source fact: f0477.
- InterpretationCallsContract: completeness = closed. Source fact: f0480.

- InvalidSelectionRetainsChild: completeness = closed. Source fact: f0495.
- KeepUnsentRelease: message-kind = event. Source fact: f0499.
- LaunchConfiguredProgram: message-kind = event. Source fact: f0501.
- LayoutCallsContract: completeness = closed. Source fact: f0504.
- LayoutExportPages: message-kind = request. Source fact: f0507.
- LayoutModel: message-kind = request. Source fact: f0509.
- LayoutTypedDiagram: message-kind = request. Source fact: f0511.
- LeaseLifecycleContract: completeness = closed. Source fact: f0514.
- LeaseNotificationsContract: completeness = closed. Source fact: f0520.
- MapSourceAnchor: message-kind = event. Source fact: f0527.
- MarkCurrentSaved: message-kind = event. Source fact: f0529.
- ModelLaidOut: message-kind = result. Source fact: f0541.
- NavigationCallsContract: completeness = closed. Source fact: f0584.
- NotifyPreferenceChange: message-kind = event. Source fact: f0591.
- ObservationContext: presence = required. Source fact: f0593.
- ObservationContext: value-type = text. Source fact: f0594.
- OpenTarget: message-kind = request. Source fact: f0595.
- OpeningPolicyContract: completeness = closed. Source fact: f0598.
- PaintPdfCandidate: message-kind = event. Source fact: f0606.
- ParseExportSnapshot: message-kind = request. Source fact: f0608.
- ParseMermaidBlock: message-kind = event. Source fact: f0610.
- ParseReference: message-kind = request. Source fact: f0612.
- ParseSnapshot: message-kind = request. Source fact: f0614.
- ParsedSnapshot: message-kind = result. Source fact: f0616.
- PdfCancelledBeforePublication: completeness = closed. Source fact: f0620.
- PdfSnapshotPublished: completeness = closed. Source fact: f0629.
- PersistPreferencesDraft: message-kind = event. Source fact: f0640.
- PollReleaseQueue: message-kind = event. Source fact: f0642.

- PreferenceChangesContract: completeness = closed. Source fact: f0645.
- PreferencesPersistBeforeAdoption: completeness = closed. Source fact: f0662.
- PrepareDiagramScenes: message-kind = event. Source fact: f0669.
- PrepareEmbeddedResources: message-kind = event. Source fact: f0671.
- PrepareExportResources: message-kind = event. Source fact: f0673.
- PrepareTypedDiagram: message-kind = event. Source fact: f0675.
- PresentFrame: message-kind = event. Source fact: f0677.
- PresentationEventsContract: completeness = closed. Source fact: f0680.
- PreviewAdmissionContract: completeness = closed. Source fact: f0711.
- PreviewResourcesPrepared: completeness = closed. Source fact: f0723.
- PreviewScrollSynchronizesEditor: completeness = closed. Source fact: f0734.
- PublicationDrawingContract: completeness = closed. Source fact: f0764.
- PublicationInputsContract: completeness = closed. Source fact: f0767.
- PublicationIntentsContract: completeness = closed. Source fact: f0770.
- PublicationStateContract: completeness = closed. Source fact: f0774.
- PublishReferenceHeadings: message-kind = event. Source fact: f0778.
- QueuePreviousLease: message-kind = event. Source fact: f0780.
- ReadCandidate: message-kind = request. Source fact: f0782.
- ReadReference: message-kind = request. Source fact: f0784.
- ReferenceHeadingsLoaded: completeness = closed. Source fact: f0798.
- ReferenceInterpretationContract: completeness = closed. Source fact: f0808.
- ReferenceParsed: message-kind = result. Source fact: f0811.
- ReferenceRead: message-kind = result. Source fact: f0814.
- ReferenceStorageContract: completeness = closed. Source fact: f0818.
- RegisteredProject: presence = required. Source fact: f0821.
- RegisteredProject: value-type = text. Source fact: f0822.
- RejectInvalidSelection: message-kind = event. Source fact: f0823.
- ReleaseKeyboardGrab: message-kind = event. Source fact: f0825.

- ReleaseRetryAfterSendFailure: completeness = closed. Source fact: f0828.
- RemoveSentRelease: message-kind = event. Source fact: f0835.
- ReplaceDocument: message-kind = event. Source fact: f0853.
- RequestPdfExport: message-kind = event. Source fact: f0855.
- RequestTreeRefresh: message-kind = event. Source fact: f0857.
- ResourcePreparationContract: completeness = closed. Source fact: f0860.
- RestartDebounce: message-kind = event. Source fact: f0866.
- RetainDocumentAndAnchor: message-kind = event. Source fact: f0868.
- SaveThenReadFails: completeness = closed. Source fact: f0871.
- SavedBaselineBytes: presence = required. Source fact: f0882.
- SavedBaselineBytes: value-type = bytes. Source fact: f0883.
- ScheduledWorkContract: completeness = closed. Source fact: f0885.
- SelectInvalidView: message-kind = event. Source fact: f0897.
- SelectRegisteredView: message-kind = event. Source fact: f0899.
- SetChosenParentRoot: message-kind = event. Source fact: f0901.
- SetEditorAnchor: message-kind = event. Source fact: f0903.
- ShowDirtyRejection: message-kind = event. Source fact: f0905.
- StalePreviewDiscarded: completeness = closed. Source fact: f0915.
- StartGeneration: message-kind = event. Source fact: f0919.
- StorageCallsContract: completeness = closed. Source fact: f0922.
- TargetOpened: message-kind = result. Source fact: f0929.
- TargetPane: presence = required. Source fact: f0932.
- TargetPane: value-type = text. Source fact: f0933.
- TargetWindow: presence = required. Source fact: f0934.
- TargetWindow: value-type = text. Source fact: f0935.
- ToggleFullscreen: message-kind = event. Source fact: f0939.
- TypedDiagramLaidOut: message-kind = result. Source fact: f0941.
- UnsavedAdmissionContract: completeness = closed. Source fact: f0951.

- UserPreviewScroll: message-kind = event. Source fact: f0955.
- ValidatePreferencesDraft: message-kind = event. Source fact: f0957.
- ValidateProposedRoot: message-kind = event. Source fact: f0959.
- ValidateSelection: message-kind = event. Source fact: f0961.
- ViewportChangesContract: completeness = closed. Source fact: f0975.
- WindowPresentationContract: completeness = closed. Source fact: f0994.
- WorkspaceChangesContract: completeness = closed. Source fact: f1008.
- WorkspaceIntentsContract: completeness = closed. Source fact: f1024.
- WriteCurrent: message-kind = request. Source fact: f1029.

Reported model gaps

These are observations from the producer's current gap rules across viewpoints, not an exhaustive requirements audit. A missing modeled relation need not be a missing implementation or a required feature. An absence has no source statement; links identify declared context only. No reported gaps does not establish model completeness.

VP10 — Datagram encoding and packets

- NO_ENCODINGS — snapshot (no declared subject): No Encoding declared.

Declaration register

Every declaration is retained, including isolated definitions. Source links identify exact spans in the original checked files.

- AcceptCurrentFrame (message) — XfmdDesktop.design, line 2.
- AcceptCurrentModel (message) — XfmdDesktop.design, line 3.
- AcceptWorkerTicket (message) — XfmdDesktop.design, line 4.
- ActivateExternalTarget (message) — XfmdDesktop.design, line 5.
- ActivateRootAndHistory (message) — XfmdDesktop.design, line 6.
- AdmitDocument (message) — XfmdDesktop.design, line 7.

- AdmitGeneratedDocument (message) — XfmdDesktop.design, line 8.
- AdoptPreferencesDraft (message) — XfmdDesktop.design, line 9.
- AdvanceGenerationSequence (message) — XfmdDesktop.design, line 10.
- Application (unit) — XfmdDesktop.design, line 11.
- ApplicationIdentity (functionality) — XfmdDesktop.design, line 12.
- ApplicationPreferences (functionality) — XfmdDesktop.design, line 13.
- ApplyTextEdit (message) — XfmdDesktop.design, line 14.
- AttemptRelease (message) — XfmdDesktop.design, line 15.
- BeginPreferencesDraft (message) — XfmdDesktop.design, line 16.
- BrowseSdpProject (usecase) — XfmdDesktop.design, line 17.
- BrowseWorkspace (usecase) — XfmdDesktop.design, line 18.
- BuildIdentity (functionality) — XfmdDesktop.design, line 19.
- CacheCompatibleScene (message) — XfmdDesktop.design, line 20.
- CancelPdfRequest (message) — XfmdDesktop.design, line 21.
- CancelPreviousChild (message) — XfmdDesktop.design, line 22.
- CancelUnpublishedJob (message) — XfmdDesktop.design, line 23.
- CandidateRead (message) — XfmdDesktop.design, line 24.
- CandidateReadFailed (message) — XfmdDesktop.design, line 25.
- CaptureContextTarget (message) — XfmdDesktop.design, line 26.
- ChapterNavigation (feature) — XfmdDesktop.design, line 27.
- CheckCurrentMapping (message) — XfmdDesktop.design, line 28.
- CheckReferenceGeneration (message) — XfmdDesktop.design, line 29.
- ChooseCancel (message) — XfmdDesktop.design, line 30.
- ChooseInternalFile (message) — XfmdDesktop.design, line 31.
- ChooseSave (message) — XfmdDesktop.design, line 32.
- ChooseUnsaved (message) — XfmdDesktop.design, line 33.
- ChooserOpensThenChangesRoot (scenario) — XfmdDesktop.design, line 34.
- ClassifyExternalTarget (message) — XfmdDesktop.design, line 35.

- CommitPdfCandidate (message) — XfmdDesktop.design, line 36.
- CommitVisit (message) — XfmdDesktop.design, line 37.
- CompleteObsoleteWorker (message) — XfmdDesktop.design, line 38.
- ConfigurableScrolling (feature) — XfmdDesktop.design, line 39.
- ConfigurePreferences (usecase) — XfmdDesktop.design, line 40.
- ContextInteraction (channel) — XfmdDesktop.design, line 41.
- ContextInteractionContract (contract) — XfmdDesktop.design, line 42.
- ContextMenuDismissed (scenario) — XfmdDesktop.design, line 43.
- CurrentWritten (message) — XfmdDesktop.design, line 44.
- DebounceElapsed (message) — XfmdDesktop.design, line 45.
- DeliverGeneratedMain (message) — XfmdDesktop.design, line 46.
- DiagramInterpretation (channel) — XfmdDesktop.design, line 47.
- DiagramInterpretationContract (contract) — XfmdDesktop.design, line 48.
- DiagramInterpreterPort (interface) — XfmdDesktop.design, line 49.
- DiagramLayout (functionality) — XfmdDesktop.design, line 50.
- DiagramLayoutCalls (channel) — XfmdDesktop.design, line 51.
- DiagramLayoutCallsContract (contract) — XfmdDesktop.design, line 52.
- DiagramLayoutPort (interface) — XfmdDesktop.design, line 53.
- DiagramPreparation (functionality) — XfmdDesktop.design, line 54.
- DiagramScenePrepared (scenario) — XfmdDesktop.design, line 55.
- DirtyGeneratedDeliveryRejected (scenario) — XfmdDesktop.design, line 56.
- DirtyOpenCancelled (scenario) — XfmdDesktop.design, line 57.
- DiscardObsoleteCompletion (message) — XfmdDesktop.design, line 58.
- DiscardPdfCandidate (message) — XfmdDesktop.design, line 59.
- DismissContextMenu (message) — XfmdDesktop.design, line 60.
- DocumentBytes (field) — XfmdDesktop.design, line 61.
- DocumentCalls (channel) — XfmdDesktop.design, line 62.
- DocumentCallsContract (contract) — XfmdDesktop.design, line 63.

- DocumentChanged (message) — XfmdDesktop.design, line 64.
- DocumentIdentity (field) — XfmdDesktop.design, line 65.
- DocumentIndex (functionality) — XfmdDesktop.design, line 66.
- DocumentIndexService (unit) — XfmdDesktop.design, line 67.
- DocumentNavigation (feature) — XfmdDesktop.design, line 68.
- DocumentNotifications (channel) — XfmdDesktop.design, line 69.
- DocumentNotificationsContract (contract) — XfmdDesktop.design, line 70.
- DocumentOpened (message) — XfmdDesktop.design, line 71.
- DocumentPath (field) — XfmdDesktop.design, line 72.
- DocumentReferences (feature) — XfmdDesktop.design, line 73.
- DocumentRejected (message) — XfmdDesktop.design, line 74.
- DocumentRevision (field) — XfmdDesktop.design, line 75.
- DocumentSession (functionality) — XfmdDesktop.design, line 76.
- DocumentStateChanges (channel) — XfmdDesktop.design, line 77.
- DocumentStateChangesContract (contract) — XfmdDesktop.design, line 78.
- DocumentStateShape (contract) — XfmdDesktop.design, line 79.
- DocumentStorage (unit) — XfmdDesktop.design, line 80.
- Documents (unit) — XfmdDesktop.design, line 81.
- EditDocuments (usecase) — XfmdDesktop.design, line 82.
- EditIntents (channel) — XfmdDesktop.design, line 83.
- EditIntentsContract (contract) — XfmdDesktop.design, line 84.
- EditedPreviewPublished (scenario) — XfmdDesktop.design, line 85.
- EmbeddedVisuals (functionality) — XfmdDesktop.design, line 86.
- EventLoop (unit) — XfmdDesktop.design, line 87.
- EventScheduling (functionality) — XfmdDesktop.design, line 88.
- ExpandReference (message) — XfmdDesktop.design, line 89.
- ExportBytes (field) — XfmdDesktop.design, line 90.
- ExportDocument (field) — XfmdDesktop.design, line 91.

- ExportInterpretation (channel) — XfmdDesktop.design, line 92.
- ExportInterpretationContract (contract) — XfmdDesktop.design, line 93.
- ExportLayout (channel) — XfmdDesktop.design, line 94.
- ExportLayoutContract (contract) — XfmdDesktop.design, line 95.
- ExportPagesLaidOut (message) — XfmdDesktop.design, line 96.
- ExportPath (field) — XfmdDesktop.design, line 97.
- ExportRevision (field) — XfmdDesktop.design, line 98.
- ExportSnapshotParsed (message) — XfmdDesktop.design, line 99.
- ExportSnapshotShape (contract) — XfmdDesktop.design, line 100.
- ExternalLauncher (unit) — XfmdDesktop.design, line 101.
- ExternalOpenProtocol (interface) — XfmdDesktop.design, line 102.
- ExternalOpening (channel) — XfmdDesktop.design, line 103.
- ExternalOpeningContract (contract) — XfmdDesktop.design, line 104.
- ExternalTargetHandedOff (scenario) — XfmdDesktop.design, line 105.
- ExternalViewBroker (unit) — XfmdDesktop.design, line 106.
- ExternalViewGenerator (unit) — XfmdDesktop.design, line 107.
- FavoriteFileChosen (message) — XfmdDesktop.design, line 108.
- FavoriteFileOpens (scenario) — XfmdDesktop.design, line 109.
- FavoriteFolderChangesRoot (scenario) — XfmdDesktop.design, line 110.
- FavoriteFolderChosen (message) — XfmdDesktop.design, line 111.
- FileStorePort (interface) — XfmdDesktop.design, line 112.
- FilteredFileTree (functionality) — XfmdDesktop.design, line 113.
- FoxPresentation (functionality) — XfmdDesktop.design, line 114.
- FreezeExportSnapshot (message) — XfmdDesktop.design, line 115.
- FrozenExportSnapshot (dataset) — XfmdDesktop.design, line 116.
- FullscreenChangesPresentation (scenario) — XfmdDesktop.design, line 117.
- GeneratedAdmission (channel) — XfmdDesktop.design, line 118.
- GeneratedAdmissionContract (contract) — XfmdDesktop.design, line 119.

- GeneratedDelivery (channel) — XfmdDesktop.design, line 120.
- GeneratedDeliveryContract (contract) — XfmdDesktop.design, line 121.
- GeneratedDocumentCalls (channel) — XfmdDesktop.design, line 122.
- GeneratedDocumentCallsContract (contract) — XfmdDesktop.design, line 123.
- GeneratedDocumentChanged (message) — XfmdDesktop.design, line 124.
- GeneratedDocumentNavigation (functionality) — XfmdDesktop.design, line 125.
- GeneratedDocumentOpened (message) — XfmdDesktop.design, line 126.
- GeneratedIntents (channel) — XfmdDesktop.design, line 127.
- GeneratedIntentsContract (contract) — XfmdDesktop.design, line 128.
- GeneratedMainAccepted (message) — XfmdDesktop.design, line 129.
- GeneratedMainRejected (message) — XfmdDesktop.design, line 130.
- GeneratedReplacementReleasesOldLease (scenario) — XfmdDesktop.design, line 131.
- GeneratedSelectionState (dataset) — XfmdDesktop.design, line 132.
- GeneratedSelectionSupersedes (scenario) — XfmdDesktop.design, line 133.
- GeneratedViews (unit) — XfmdDesktop.design, line 134.
- GenerationLifecycle (channel) — XfmdDesktop.design, line 135.
- GenerationLifecycleContract (contract) — XfmdDesktop.design, line 136.
- GenerationSequence (field) — XfmdDesktop.design, line 137.
- GenerationStateShape (contract) — XfmdDesktop.design, line 138.
- Identity (unit) — XfmdDesktop.design, line 139.
- IndexChanges (channel) — XfmdDesktop.design, line 140.
- IndexChangesContract (contract) — XfmdDesktop.design, line 141.
- IndexIntents (channel) — XfmdDesktop.design, line 142.
- IndexIntentsContract (contract) — XfmdDesktop.design, line 143.
- InspectDirtyMain (message) — XfmdDesktop.design, line 144.
- InstallNewLease (message) — XfmdDesktop.design, line 145.
- InteractionObservationShape (contract) — XfmdDesktop.design, line 146.
- InterpretationCalls (channel) — XfmdDesktop.design, line 147.

- InterpretationCallsContract (contract) — XfmdDesktop.design, line 148.
- Interpreter (unit) — XfmdDesktop.design, line 149.
- InterpreterPort (interface) — XfmdDesktop.design, line 150.
- InvalidSelectionRetainsChild (scenario) — XfmdDesktop.design, line 151.
- KeepUnsentRelease (message) — XfmdDesktop.design, line 152.
- LaunchConfiguredProgram (message) — XfmdDesktop.design, line 153.
- LayoutCalls (channel) — XfmdDesktop.design, line 154.
- LayoutCallsContract (contract) — XfmdDesktop.design, line 155.
- LayoutExportPages (message) — XfmdDesktop.design, line 156.
- LayoutModel (message) — XfmdDesktop.design, line 157.
- LayoutTypedDiagram (message) — XfmdDesktop.design, line 158.
- LeaseLifecycle (channel) — XfmdDesktop.design, line 159.
- LeaseLifecycleContract (contract) — XfmdDesktop.design, line 160.
- LeaseNotifications (channel) — XfmdDesktop.design, line 161.
- LeaseNotificationsContract (contract) — XfmdDesktop.design, line 162.
- LeaseReleaseProtocol (interface) — XfmdDesktop.design, line 163.
- LivePreview (feature) — XfmdDesktop.design, line 164.
- LocalFileStorage (functionality) — XfmdDesktop.design, line 165.
- MainDocumentState (dataset) — XfmdDesktop.design, line 166.
- MapSourceAnchor (message) — XfmdDesktop.design, line 167.
- MarkCurrentSaved (message) — XfmdDesktop.design, line 168.
- MarkdownInterpretation (functionality) — XfmdDesktop.design, line 169.
- MarkdownPresentation (feature) — XfmdDesktop.design, line 170.
- MermaidDiagrams (feature) — XfmdDesktop.design, line 171.
- MermaidInterpretation (functionality) — XfmdDesktop.design, line 172.
- ModelLaidOut (message) — XfmdDesktop.design, line 173.
- NativeShell (unit) — XfmdDesktop.design, line 174.
- NavigateDocuments (usecase) — XfmdDesktop.design, line 175.

- Navigation (unit) — XfmdDesktop.design, line 176.
- NavigationCalls (channel) — XfmdDesktop.design, line 177.
- NavigationCallsContract (contract) — XfmdDesktop.design, line 178.
- NavigationHistory (functionality) — XfmdDesktop.design, line 179.
- NormalDesktop (mode) — XfmdDesktop.design, line 180.
- NotifyPreferenceChange (message) — XfmdDesktop.design, line 181.
- ObservationContext (field) — XfmdDesktop.design, line 182.
- OpenTarget (message) — XfmdDesktop.design, line 183.
- OpeningPolicy (channel) — XfmdDesktop.design, line 184.
- OpeningPolicyContract (contract) — XfmdDesktop.design, line 185.
- PageComposition (functionality) — XfmdDesktop.design, line 186.
- PagedPublication (feature) — XfmdDesktop.design, line 187.
- PaintPdfCandidate (message) — XfmdDesktop.design, line 188.
- ParseExportSnapshot (message) — XfmdDesktop.design, line 189.
- ParseMermaidBlock (message) — XfmdDesktop.design, line 190.
- ParseReference (message) — XfmdDesktop.design, line 191.
- ParseSnapshot (message) — XfmdDesktop.design, line 192.
- ParsedSnapshot (message) — XfmdDesktop.design, line 193.
- PdfCancelledBeforePublication (scenario) — XfmdDesktop.design, line 194.
- PdfExport (functionality) — XfmdDesktop.design, line 195.
- PdfSnapshotPublished (scenario) — XfmdDesktop.design, line 196.
- PersistPreferencesDraft (message) — XfmdDesktop.design, line 197.
- PollReleaseQueue (message) — XfmdDesktop.design, line 198.
- PreferenceChanges (channel) — XfmdDesktop.design, line 199.
- PreferenceChangesContract (contract) — XfmdDesktop.design, line 200.
- Preferences (unit) — XfmdDesktop.design, line 201.
- PreferencesPersistBeforeAdoption (scenario) — XfmdDesktop.design, line 202.
- PreferencesStorePort (interface) — XfmdDesktop.design, line 203.

- PrepareDiagramScenes (message) — XfmdDesktop.design, line 204.
- PrepareEmbeddedResources (message) — XfmdDesktop.design, line 205.
- PrepareExportResources (message) — XfmdDesktop.design, line 206.
- PrepareTypedDiagram (message) — XfmdDesktop.design, line 207.
- PresentFrame (message) — XfmdDesktop.design, line 208.
- PresentationEvents (channel) — XfmdDesktop.design, line 209.
- PresentationEventsContract (contract) — XfmdDesktop.design, line 210.
- Preview (unit) — XfmdDesktop.design, line 211.
- PreviewAdmission (channel) — XfmdDesktop.design, line 212.
- PreviewAdmissionContract (contract) — XfmdDesktop.design, line 213.
- PreviewPipeline (functionality) — XfmdDesktop.design, line 214.
- PreviewResourcesPrepared (scenario) — XfmdDesktop.design, line 215.
- PreviewScrollSynchronizesEditor (scenario) — XfmdDesktop.design, line 216.
- PreviewTextSelection (functionality) — XfmdDesktop.design, line 217.
- Publication (unit) — XfmdDesktop.design, line 218.
- PublicationDrawing (channel) — XfmdDesktop.design, line 219.
- PublicationDrawingContract (contract) — XfmdDesktop.design, line 220.
- PublicationInputs (channel) — XfmdDesktop.design, line 221.
- PublicationInputsContract (contract) — XfmdDesktop.design, line 222.
- PublicationIntents (channel) — XfmdDesktop.design, line 223.
- PublicationIntentsContract (contract) — XfmdDesktop.design, line 224.
- PublicationState (channel) — XfmdDesktop.design, line 225.
- PublicationStateContract (contract) — XfmdDesktop.design, line 226.
- PublishPages (usecase) — XfmdDesktop.design, line 227.
- PublishReferenceHeadings (message) — XfmdDesktop.design, line 228.
- QueuePreviousLease (message) — XfmdDesktop.design, line 229.
- ReadCandidate (message) — XfmdDesktop.design, line 230.
- ReadDiagrams (usecase) — XfmdDesktop.design, line 231.

- ReadDocuments (usecase) — XfmdDesktop.design, line 232.
- ReadReference (message) — XfmdDesktop.design, line 233.
- ReaderAuthor (actor) — XfmdDesktop.design, line 234.
- ReferenceHeadingsLoaded (scenario) — XfmdDesktop.design, line 235.
- ReferenceInterpretation (channel) — XfmdDesktop.design, line 236.
- ReferenceInterpretationContract (contract) — XfmdDesktop.design, line 237.
- ReferenceParsed (message) — XfmdDesktop.design, line 238.
- ReferenceRead (message) — XfmdDesktop.design, line 239.
- ReferenceStorage (channel) — XfmdDesktop.design, line 240.
- ReferenceStorageContract (contract) — XfmdDesktop.design, line 241.
- RegisteredProject (field) — XfmdDesktop.design, line 242.
- RejectInvalidSelection (message) — XfmdDesktop.design, line 243.
- ReleaseKeyboardGrab (message) — XfmdDesktop.design, line 244.
- ReleaseRetryAfterSendFailure (scenario) — XfmdDesktop.design, line 245.
- RemoveSentRelease (message) — XfmdDesktop.design, line 246.
- RenderHostPort (interface) — XfmdDesktop.design, line 247.
- RenderLayout (functionality) — XfmdDesktop.design, line 248.
- Renderer (unit) — XfmdDesktop.design, line 249.
- RendererPort (interface) — XfmdDesktop.design, line 250.
- ReplaceDocument (message) — XfmdDesktop.design, line 251.
- RequestPdfExport (message) — XfmdDesktop.design, line 252.
- RequestTreeRefresh (message) — XfmdDesktop.design, line 253.
- ResourcePreparation (channel) — XfmdDesktop.design, line 254.
- ResourcePreparationContract (contract) — XfmdDesktop.design, line 255.
- RestartDebounce (message) — XfmdDesktop.design, line 256.
- RetainDocumentAndAnchor (message) — XfmdDesktop.design, line 257.
- SaveThenReadFails (scenario) — XfmdDesktop.design, line 258.
- SavedBaselineBytes (field) — XfmdDesktop.design, line 259.

- ScheduledWork (channel) — XfmdDesktop.design, line 260.
- ScheduledWorkContract (contract) — XfmdDesktop.design, line 261.
- SchedulerPort (interface) — XfmdDesktop.design, line 262.
- ScrollDocuments (usecase) — XfmdDesktop.design, line 263.
- ScrollMotion (functionality) — XfmdDesktop.design, line 264.
- SdpProjectNavigation (functionality) — XfmdDesktop.design, line 265.
- SdpProjects (unit) — XfmdDesktop.design, line 266.
- SdpToolProtocol (interface) — XfmdDesktop.design, line 267.
- SelectGeneratedView (usecase) — XfmdDesktop.design, line 268.
- SelectInvalidView (message) — XfmdDesktop.design, line 269.
- SelectRegisteredView (message) — XfmdDesktop.design, line 270.
- SetChosenParentRoot (message) — XfmdDesktop.design, line 271.
- SetEditorAnchor (message) — XfmdDesktop.design, line 272.
- ShowDirtyRejection (message) — XfmdDesktop.design, line 273.
- SourceAnchorMapping (functionality) — XfmdDesktop.design, line 274.
- StalePreviewDiscarded (scenario) — XfmdDesktop.design, line 275.
- StartGeneration (message) — XfmdDesktop.design, line 276.
- StorageCalls (channel) — XfmdDesktop.design, line 277.
- StorageCallsContract (contract) — XfmdDesktop.design, line 278.
- SynchronizedScrolling (feature) — XfmdDesktop.design, line 279.
- TargetOpened (message) — XfmdDesktop.design, line 280.
- TargetPane (field) — XfmdDesktop.design, line 281.
- TargetWindow (field) — XfmdDesktop.design, line 282.
- TextEditing (functionality) — XfmdDesktop.design, line 283.
- TextMetricsPort (interface) — XfmdDesktop.design, line 284.
- ToggleFullscreen (message) — XfmdDesktop.design, line 285.
- TypedDiagramLaidOut (message) — XfmdDesktop.design, line 286.
- Typography (unit) — XfmdDesktop.design, line 287.

- TypographyAndDrawing (functionality) — XfmdDesktop.design, line 288.
- UnsavedAdmission (channel) — XfmdDesktop.design, line 289.
- UnsavedAdmissionContract (contract) — XfmdDesktop.design, line 290.
- UseFullscreen (usecase) — XfmdDesktop.design, line 291.
- UserPreviewScroll (message) — XfmdDesktop.design, line 292.
- ValidatePreferencesDraft (message) — XfmdDesktop.design, line 293.
- ValidateProposedRoot (message) — XfmdDesktop.design, line 294.
- ValidateSelection (message) — XfmdDesktop.design, line 295.
- ViewGenerationProtocol (interface) — XfmdDesktop.design, line 296.
- Viewport (unit) — XfmdDesktop.design, line 297.
- ViewportChanges (channel) — XfmdDesktop.design, line 298.
- ViewportChangesContract (contract) — XfmdDesktop.design, line 299.
- VisualResources (unit) — XfmdDesktop.design, line 300.
- WindowDeliveryProtocol (interface) — XfmdDesktop.design, line 301.
- WindowPresentation (channel) — XfmdDesktop.design, line 302.
- WindowPresentationContract (contract) — XfmdDesktop.design, line 303.
- WorkPathHistory (functionality) — XfmdDesktop.design, line 304.
- WorkPathNavigation (feature) — XfmdDesktop.design, line 305.
- Workspace (unit) — XfmdDesktop.design, line 306.
- WorkspaceChanges (channel) — XfmdDesktop.design, line 307.
- WorkspaceChangesContract (contract) — XfmdDesktop.design, line 308.
- WorkspaceControls (functionality) — XfmdDesktop.design, line 309.
- WorkspaceIntents (channel) — XfmdDesktop.design, line 310.
- WorkspaceIntentsContract (contract) — XfmdDesktop.design, line 311.
- WriteCurrent (message) — XfmdDesktop.design, line 312.
- XfmdDesktop (container) — XfmdDesktop.design, line 313.

Complete fact registry

All statements are preserved, including mode, ternary relation, sequence and placement arguments. Source traceability does not prove native code conformance.

- f0000 — AcceptCurrentFrame has message-kind = event. (XfmdDesktop.design, line 314).
- f0001 — AcceptCurrentFrame upholds InteractionObservationShape. (XfmdDesktop.design, line 315).
- f0002 — AcceptCurrentModel has message-kind = event. (XfmdDesktop.design, line 316).
- f0003 — AcceptCurrentModel upholds InteractionObservationShape. (XfmdDesktop.design, line 317).
- f0004 — AcceptWorkerTicket has message-kind = event. (XfmdDesktop.design, line 318).
- f0005 — AcceptWorkerTicket upholds InteractionObservationShape. (XfmdDesktop.design, line 319).
- f0006 — ActivateExternalTarget has message-kind = event. (XfmdDesktop.design, line 320).
- f0007 — ActivateExternalTarget upholds InteractionObservationShape. (XfmdDesktop.design, line 321).
- f0008 — ActivateRootAndHistory has message-kind = event. (XfmdDesktop.design, line 322).
- f0009 — ActivateRootAndHistory upholds InteractionObservationShape. (XfmdDesktop.design, line 323).
- f0010 — AdmitDocument has message-kind = request. (XfmdDesktop.design, line 324).
- f0011 — AdmitDocument upholds InteractionObservationShape. (XfmdDesktop.design, line 325).
- f0012 — AdmitGeneratedDocument has message-kind = request. (XfmdDesktop.design, line 326).

- f0013 — AdmitGeneratedDocument upholds InteractionObservationShape. (XfmdDesktop.design, line 327).
- f0014 — AdoptPreferencesDraft has message-kind = event. (XfmdDesktop.design, line 328).
- f0015 — AdoptPreferencesDraft upholds InteractionObservationShape. (XfmdDesktop.design, line 329).
- f0016 — AdvanceGenerationSequence has message-kind = event. (XfmdDesktop.design, line 330).
- f0017 — AdvanceGenerationSequence upholds InteractionObservationShape. (XfmdDesktop.design, line 331).
- f0018 — Application consumes ExternalOpenProtocol. (XfmdDesktop.design, line 332).
- f0019 — Application contains DocumentIndexService. (XfmdDesktop.design, line 333).
- f0020 — Application contains DocumentStorage. (XfmdDesktop.design, line 334).
- f0021 — Application contains Documents. (XfmdDesktop.design, line 335).
- f0022 — Application contains EventLoop. (XfmdDesktop.design, line 336).
- f0023 — Application contains GeneratedViews. (XfmdDesktop.design, line 337).
- f0024 — Application contains Identity. (XfmdDesktop.design, line 338).
- f0025 — Application contains NativeShell. (XfmdDesktop.design, line 339).
- f0026 — Application contains Navigation. (XfmdDesktop.design, line 340).
- f0027 — Application contains Preferences. (XfmdDesktop.design, line 341).
- f0028 — Application contains Preview. (XfmdDesktop.design, line 342).
- f0029 — Application contains Publication. (XfmdDesktop.design, line 343).
- f0030 — Application contains SdpProjects. (XfmdDesktop.design, line 344).
- f0031 — Application contains Typography. (XfmdDesktop.design, line 345).
- f0032 — Application contains Viewport. (XfmdDesktop.design, line 346).
- f0033 — Application contains VisualResources. (XfmdDesktop.design, line 347).
- f0034 — Application contains Workspace. (XfmdDesktop.design, line 348).

- f0035 — Application uses ExternalOpening as sender of LaunchConfiguredProgram in mode NormalDesktop. (XfmdDesktop.design, line 349).
- f0036 — Application uses NavigationCalls as receiver of TargetOpened in mode NormalDesktop. (XfmdDesktop.design, line 350).
- f0037 — Application uses NavigationCalls as sender of OpenTarget in mode NormalDesktop. (XfmdDesktop.design, line 351).
- f0038 — Application uses OpeningPolicy as receiver of ClassifyExternalTarget in mode NormalDesktop. (XfmdDesktop.design, line 352).
- f0039 — Application uses OpeningPolicy as sender of ClassifyExternalTarget in mode NormalDesktop. (XfmdDesktop.design, line 353).
- f0040 — Application uses WorkspaceChanges as sender of SetChosenParentRoot in mode NormalDesktop. (XfmdDesktop.design, line 354).
- f0041 — Application uses WorkspaceChanges as sender of ValidateProposedRoot in mode NormalDesktop. (XfmdDesktop.design, line 355).
- f0042 — Application uses WorkspaceIntents as receiver of ActivateExternalTarget in mode NormalDesktop. (XfmdDesktop.design, line 356).
- f0043 — Application uses WorkspaceIntents as receiver of ChooseInternalFile in mode NormalDesktop. (XfmdDesktop.design, line 357).
- f0044 — Application uses WorkspaceIntents as receiver of FavoriteFileChosen in mode NormalDesktop. (XfmdDesktop.design, line 358).
- f0045 — ApplicationIdentity allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 359).
- f0046 — ApplicationPreferences allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 360).
- f0047 — ApplicationPreferences contributes-to ConfigurableScrolling. (XfmdDesktop.design, line 361).
- f0048 — ApplicationPreferences contributes-to ConfigurePreferences. (XfmdDesktop.design, line 362).
- f0049 — ApplicationPreferences contributes-to DocumentNavigation. (XfmdDesktop.design, line 363).

- f0050 — ApplicationPreferences contributes-to DocumentReferences. (XfmdDesktop.design, line 364).
- f0051 — ApplicationPreferences contributes-to PagedPublication. (XfmdDesktop.design, line 365).
- f0052 — ApplyTextEdit has message-kind = event. (XfmdDesktop.design, line 366).
- f0053 — ApplyTextEdit upholds InteractionObservationShape. (XfmdDesktop.design, line 367).
- f0054 — AttemptRelease has message-kind = event. (XfmdDesktop.design, line 368).
- f0055 — AttemptRelease upholds InteractionObservationShape. (XfmdDesktop.design, line 369).
- f0056 — BeginPreferencesDraft has message-kind = event. (XfmdDesktop.design, line 370).
- f0057 — BeginPreferencesDraft upholds InteractionObservationShape. (XfmdDesktop.design, line 371).
- f0058 — BuildIdentity allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 372).
- f0059 — CacheCompatibleScene has message-kind = event. (XfmdDesktop.design, line 373).
- f0060 — CacheCompatibleScene upholds InteractionObservationShape. (XfmdDesktop.design, line 374).
- f0061 — CancelPdfRequest has message-kind = event. (XfmdDesktop.design, line 375).
- f0062 — CancelPdfRequest upholds InteractionObservationShape. (XfmdDesktop.design, line 376).
- f0063 — CancelPreviousChild has message-kind = event. (XfmdDesktop.design, line 377).
- f0064 — CancelPreviousChild upholds InteractionObservationShape. (XfmdDesktop.design, line 378).
- f0065 — CancelUnpublishedJob has message-kind = event. (XfmdDesktop.design, line 379).

- f0066 — CancelUnpublishedJob upholds InteractionObservationShape. (XfmdDesktop.design, line 380).
- f0067 — CandidateRead has message-kind = result. (XfmdDesktop.design, line 381).
- f0068 — CandidateRead replies-to ReadCandidate. (XfmdDesktop.design, line 382).
- f0069 — CandidateRead upholds InteractionObservationShape. (XfmdDesktop.design, line 383).
- f0070 — CandidateReadFailed has message-kind = result. (XfmdDesktop.design, line 384).
- f0071 — CandidateReadFailed replies-to ReadCandidate. (XfmdDesktop.design, line 385).
- f0072 — CandidateReadFailed upholds InteractionObservationShape. (XfmdDesktop.design, line 386).
- f0073 — CaptureContextTarget has message-kind = event. (XfmdDesktop.design, line 387).
- f0074 — CaptureContextTarget upholds InteractionObservationShape. (XfmdDesktop.design, line 388).
- f0075 — ChapterNavigation supports NavigateDocuments. (XfmdDesktop.design, line 389).
- f0076 — CheckCurrentMapping has message-kind = event. (XfmdDesktop.design, line 390).
- f0077 — CheckCurrentMapping upholds InteractionObservationShape. (XfmdDesktop.design, line 391).
- f0078 — CheckReferenceGeneration has message-kind = event. (XfmdDesktop.design, line 392).
- f0079 — CheckReferenceGeneration upholds InteractionObservationShape. (XfmdDesktop.design, line 393).
- f0080 — ChooseCancel has message-kind = result. (XfmdDesktop.design, line 394).
- f0081 — ChooseCancel replies-to ChooseUnsaved. (XfmdDesktop.design, line 395).

- f0082 — ChooseCancel upholds InteractionObservationShape. (XfmdDesktop.design, line 396).
- f0083 — ChooseInternalFile has message-kind = event. (XfmdDesktop.design, line 397).
- f0084 — ChooseInternalFile upholds InteractionObservationShape. (XfmdDesktop.design, line 398).
- f0085 — ChooseSave has message-kind = result. (XfmdDesktop.design, line 399).
- f0086 — ChooseSave replies-to ChooseUnsaved. (XfmdDesktop.design, line 400).
- f0087 — ChooseSave upholds InteractionObservationShape. (XfmdDesktop.design, line 401).
- f0088 — ChooseUnsaved has message-kind = request. (XfmdDesktop.design, line 402).
- f0089 — ChooseUnsaved upholds InteractionObservationShape. (XfmdDesktop.design, line 403).
- f0090 — ChooserOpensThenChangesRoot exercises BrowseWorkspace. (XfmdDesktop.design, line 404).
- f0091 — ChooserOpensThenChangesRoot has completeness = closed. (XfmdDesktop.design, line 405).
- f0092 — ChooserOpensThenChangesRoot runs-in NormalDesktop. (XfmdDesktop.design, line 406).
- f0093 — ChooserOpensThenChangesRoot step 1 sends ChooseInternalFile from NativeShell to Application via WorkspaceIntents. (XfmdDesktop.design, line 407).
- f0094 — ChooserOpensThenChangesRoot step 2 sends ValidateProposedRoot from Application to Workspace via WorkspaceChanges. (XfmdDesktop.design, line 408).
- f0095 — ChooserOpensThenChangesRoot step 3 sends OpenTarget from Application to Navigation via NavigationCalls. (XfmdDesktop.design, line 409).
- f0096 — ChooserOpensThenChangesRoot step 4 sends TargetOpened from Navigation to Application via NavigationCalls reply-to 3. (XfmdDesktop.design, line 410).
- f0097 — ChooserOpensThenChangesRoot step 5 sends SetChosenParentRoot

from Application to Workspace via WorkspaceChanges. (XfmdDesktop.design, line 411).

- f0098 — ClassifyExternalTarget has message-kind = event. (XfmdDesktop.design, line 412).
- f0099 — ClassifyExternalTarget upholds InteractionObservationShape. (XfmdDesktop.design, line 413).
- f0100 — CommitPdfCandidate has message-kind = event. (XfmdDesktop.design, line 414).
- f0101 — CommitPdfCandidate upholds InteractionObservationShape. (XfmdDesktop.design, line 415).
- f0102 — CommitVisit has message-kind = event. (XfmdDesktop.design, line 416).
- f0103 — CommitVisit upholds InteractionObservationShape. (XfmdDesktop.design, line 417).
- f0104 — CompleteObsoleteWorker has message-kind = event. (XfmdDesktop.design, line 418).
- f0105 — CompleteObsoleteWorker upholds InteractionObservationShape. (XfmdDesktop.design, line 419).
- f0106 — ConfigurableScrolling supports ConfigurePreferences. (XfmdDesktop.design, line 420).
- f0107 — ConfigurableScrolling supports ScrollDocuments. (XfmdDesktop.design, line 421).
- f0108 — ContextInteraction upholds ContextInteractionContract. (XfmdDesktop.design, line 422).
- f0109 — ContextInteractionContract has completeness = closed. (XfmdDesktop.design, line 423).
- f0110 — ContextInteractionContract permits CaptureContextTarget. (XfmdDesktop.design, line 424).
- f0111 — ContextInteractionContract permits DismissContextMenu. (XfmdDesktop.design, line 425).
- f0112 — ContextInteractionContract permits ReleaseKeyboardGrab. (XfmdDesktop.design, line 426).

- f0113 — ContextMenuDismissed exercises BrowseWorkspace. (XfmdDesktop.design, line 427).
- f0114 — ContextMenuDismissed has completeness = closed. (XfmdDesktop.design, line 428).
- f0115 — ContextMenuDismissed runs-in NormalDesktop. (XfmdDesktop.design, line 429).
- f0116 — ContextMenuDismissed step 1 sends CaptureContextTarget from NativeShell to NativeShell via ContextInteraction. (XfmdDesktop.design, line 430).
- f0117 — ContextMenuDismissed step 2 sends DismissContextMenu from NativeShell to NativeShell via ContextInteraction. (XfmdDesktop.design, line 431).
- f0118 — ContextMenuDismissed step 3 sends ReleaseKeyboardGrab from NativeShell to NativeShell via ContextInteraction. (XfmdDesktop.design, line 432).
- f0119 — CurrentWritten has message-kind = result. (XfmdDesktop.design, line 433).
- f0120 — CurrentWritten replies-to WriteCurrent. (XfmdDesktop.design, line 434).
- f0121 — CurrentWritten upholds InteractionObservationShape. (XfmdDesktop.design, line 435).
- f0122 — DebounceElapsed has message-kind = event. (XfmdDesktop.design, line 436).
- f0123 — DebounceElapsed upholds InteractionObservationShape. (XfmdDesktop.design, line 437).
- f0124 — DeliverGeneratedMain has message-kind = request. (XfmdDesktop.design, line 438).
- f0125 — DeliverGeneratedMain upholds InteractionObservationShape. (XfmdDesktop.design, line 439).
- f0126 — DiagramInterpretation upholds DiagramInterpretationContract. (XfmdDesktop.design, line 440).
- f0127 — DiagramInterpretationContract has completeness = closed. (XfmdDesktop.design, line 441).
- f0128 — DiagramInterpretationContract permits ParseMermaidBlock. (XfmdDesktop.design, line 442).

- f0129 — DiagramLayout allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 443).
- f0130 — DiagramLayout contributes-to MermaidDiagrams. (XfmdDesktop.design, line 444).
- f0131 — DiagramLayoutCalls upholds DiagramLayoutCallsContract. (XfmdDesktop.design, line 445).
- f0132 — DiagramLayoutCallsContract has completeness = closed. (XfmdDesktop.design, line 446).
- f0133 — DiagramLayoutCallsContract permits LayoutTypedDiagram. (XfmdDesktop.design, line 447).
- f0134 — DiagramLayoutCallsContract permits TypedDiagramLaidOut. (XfmdDesktop.design, line 448).
- f0135 — DiagramPreparation allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 449).
- f0136 — DiagramPreparation contributes-to MermaidDiagrams. (XfmdDesktop.design, line 450).
- f0137 — DiagramScenePrepared exercises ReadDiagrams. (XfmdDesktop.design, line 451).
- f0138 — DiagramScenePrepared has completeness = closed. (XfmdDesktop.design, line 452).
- f0139 — DiagramScenePrepared runs-in NormalDesktop. (XfmdDesktop.design, line 453).
- f0140 — DiagramScenePrepared step 1 sends ParseMermaidBlock from Interpreter to Interpreter via DiagramInterpretation. (XfmdDesktop.design, line 454).
- f0141 — DiagramScenePrepared step 2 sends PrepareTypedDiagram from Preview to VisualResources via ResourcePreparation. (XfmdDesktop.design, line 455).
- f0142 — DiagramScenePrepared step 3 sends LayoutTypedDiagram from VisualResources to Renderer via DiagramLayoutCalls. (XfmdDesktop.design, line 456).

- f0143 — DiagramScenePrepared step 4 sends TypedDiagramLaidOut from Renderer to VisualResources via DiagramLayoutCalls reply-to 3. (XfmdDesktop.design, line 457).
- f0144 — DiagramScenePrepared step 5 sends CacheCompatibleScene from VisualResources to VisualResources via ResourcePreparation. (XfmdDesktop.design, line 458).
- f0145 — DirtyGeneratedDeliveryRejected exercises SelectGeneratedView. (XfmdDesktop.design, line 459).
- f0146 — DirtyGeneratedDeliveryRejected has completeness = closed. (XfmdDesktop.design, line 460).
- f0147 — DirtyGeneratedDeliveryRejected runs-in NormalDesktop. (XfmdDesktop.design, line 461).
- f0148 — DirtyGeneratedDeliveryRejected step 1 sends DeliverGeneratedMain from ExternalViewGenerator to GeneratedViews via GeneratedDelivery. (XfmdDesktop.design, line 462).
- f0149 — DirtyGeneratedDeliveryRejected step 2 sends InspectDirtyMain from GeneratedViews to Documents via GeneratedAdmission. (XfmdDesktop.design, line 463).
- f0150 — DirtyGeneratedDeliveryRejected step 3 sends ShowDirtyRejection from GeneratedViews to NativeShell via PresentationEvents. (XfmdDesktop.design, line 464).
- f0151 — DirtyGeneratedDeliveryRejected step 4 sends GeneratedMainRejected from GeneratedViews to ExternalViewGenerator via GeneratedDelivery reply-to 1. (XfmdDesktop.design, line 465).
- f0152 — DirtyOpenCancelled exercises NavigateDocuments. (XfmdDesktop.design, line 466).
- f0153 — DirtyOpenCancelled has completeness = closed. (XfmdDesktop.design, line 467).
- f0154 — DirtyOpenCancelled runs-in NormalDesktop. (XfmdDesktop.design, line 468).
- f0155 — DirtyOpenCancelled step 1 sends AdmitDocument from Navigation to Documents via DocumentCalls. (XfmdDesktop.design, line 469).

- f0156 — DirtyOpenCancelled step 2 sends ChooseUnsaved from Documents to NativeShell via UnsavedAdmission. (XfmdDesktop.design, line 470).
- f0157 — DirtyOpenCancelled step 3 sends ChooseCancel from NativeShell to Documents via UnsavedAdmission reply-to 2. (XfmdDesktop.design, line 471).
- f0158 — DirtyOpenCancelled step 4 sends DocumentRejected from Documents to Navigation via DocumentCalls reply-to 1. (XfmdDesktop.design, line 472).
- f0159 — DiscardObsoleteCompletion has message-kind = event. (XfmdDesktop.design, line 473).
- f0160 — DiscardObsoleteCompletion upholds InteractionObservationShape. (XfmdDesktop.design, line 474).
- f0161 — DiscardPdfCandidate has message-kind = event. (XfmdDesktop.design, line 475).
- f0162 — DiscardPdfCandidate upholds InteractionObservationShape. (XfmdDesktop.design, line 476).
- f0163 — DismissContextMenu has message-kind = event. (XfmdDesktop.design, line 477).
- f0164 — DismissContextMenu upholds InteractionObservationShape. (XfmdDesktop.design, line 478).
- f0165 — DocumentBytes has presence = required. (XfmdDesktop.design, line 479).
- f0166 — DocumentBytes has value-type = bytes. (XfmdDesktop.design, line 480).
- f0167 — DocumentCalls upholds DocumentCallsContract. (XfmdDesktop.design, line 481).
- f0168 — DocumentCallsContract has completeness = closed. (XfmdDesktop.design, line 482).
- f0169 — DocumentCallsContract permits AdmitDocument. (XfmdDesktop.design, line 483).
- f0170 — DocumentCallsContract permits DocumentOpened. (XfmdDesktop.design, line 484).
- f0171 — DocumentCallsContract permits DocumentRejected. (XfmdDesktop.design, line 485).

- f0172 — DocumentChanged has message-kind = event. (XfmdDesktop.design, line 486).
- f0173 — DocumentChanged upholds InteractionObservationShape. (XfmdDesktop.design, line 487).
- f0174 — DocumentIdentity has presence = required. (XfmdDesktop.design, line 488).
- f0175 — DocumentIdentity has value-type = unsigned. (XfmdDesktop.design, line 489).
- f0176 — DocumentIndex allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 490).
- f0177 — DocumentIndex contributes-to ChapterNavigation. (XfmdDesktop.design, line 491).
- f0178 — DocumentIndex contributes-to DocumentReferences. (XfmdDesktop.design, line 492).
- f0179 — DocumentIndexService consumes FileStorePort. (XfmdDesktop.design, line 493).
- f0180 — DocumentIndexService consumes InterpreterPort. (XfmdDesktop.design, line 494).
- f0181 — DocumentIndexService owns DocumentIndex. (XfmdDesktop.design, line 495).
- f0182 — DocumentIndexService uses IndexChanges as receiver of CheckReferenceGeneration in mode NormalDesktop. (XfmdDesktop.design, line 496).
- f0183 — DocumentIndexService uses IndexChanges as sender of CheckReferenceGeneration in mode NormalDesktop. (XfmdDesktop.design, line 497).
- f0184 — DocumentIndexService uses IndexChanges as sender of PublishReferenceHeadings in mode NormalDesktop. (XfmdDesktop.design, line 498).
- f0185 — DocumentIndexService uses IndexIntents as receiver of ExpandReference in mode NormalDesktop. (XfmdDesktop.design, line 499).

- f0186 — DocumentIndexService uses ReferenceInterpretation as receiver of ReferenceParsed in mode NormalDesktop. (XfmdDesktop.design, line 500).
- f0187 — DocumentIndexService uses ReferenceInterpretation as sender of ParseReference in mode NormalDesktop. (XfmdDesktop.design, line 501).
- f0188 — DocumentIndexService uses ReferenceStorage as receiver of ReferenceRead in mode NormalDesktop. (XfmdDesktop.design, line 502).
- f0189 — DocumentIndexService uses ReferenceStorage as sender of ReadReference in mode NormalDesktop. (XfmdDesktop.design, line 503).
- f0190 — DocumentNavigation supports NavigateDocuments. (XfmdDesktop.design, line 504).
- f0191 — DocumentNotifications upholds DocumentNotificationsContract. (XfmdDesktop.design, line 505).
- f0192 — DocumentNotificationsContract has completeness = closed. (XfmdDesktop.design, line 506).
- f0193 — DocumentNotificationsContract permits CommitVisit. (XfmdDesktop.design, line 507).
- f0194 — DocumentNotificationsContract permits DocumentChanged. (XfmdDesktop.design, line 508).
- f0195 — DocumentNotificationsContract permits GeneratedDocumentChanged. (XfmdDesktop.design, line 509).
- f0196 — DocumentOpened has message-kind = result. (XfmdDesktop.design, line 510).
- f0197 — DocumentOpened replies-to AdmitDocument. (XfmdDesktop.design, line 511).
- f0198 — DocumentOpened upholds InteractionObservationShape. (XfmdDesktop.design, line 512).
- f0199 — DocumentPath has presence = required. (XfmdDesktop.design, line 513).
- f0200 — DocumentPath has value-type = text. (XfmdDesktop.design, line 514).
- f0201 — DocumentReferences supports NavigateDocuments. (XfmdDesktop.design, line 515).

- f0202 — DocumentRejected has message-kind = result. (XfmdDesktop.design, line 516).
- f0203 — DocumentRejected replies-to AdmitDocument. (XfmdDesktop.design, line 517).
- f0204 — DocumentRejected upholds InteractionObservationShape. (XfmdDesktop.design, line 518).
- f0205 — DocumentRevision has presence = required. (XfmdDesktop.design, line 519).
- f0206 — DocumentRevision has value-type = unsigned. (XfmdDesktop.design, line 520).
- f0207 — DocumentSession allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 521).
- f0208 — DocumentSession contributes-to DocumentNavigation. (XfmdDesktop.design, line 522).
- f0209 — DocumentSession contributes-to LivePreview. (XfmdDesktop.design, line 523).
- f0210 — DocumentSession contributes-to MarkdownPresentation. (XfmdDesktop.design, line 524).
- f0211 — DocumentSession contributes-to PagedPublication. (XfmdDesktop.design, line 525).
- f0212 — DocumentStateChanges upholds DocumentStateChangesContract. (XfmdDesktop.design, line 526).
- f0213 — DocumentStateChangesContract has completeness = closed. (XfmdDesktop.design, line 527).
- f0214 — DocumentStateChangesContract permits MarkCurrentSaved. (XfmdDesktop.design, line 528).
- f0215 — DocumentStateChangesContract permits ReplaceDocument. (XfmdDesktop.design, line 529).
- f0216 — DocumentStateShape has completeness = closed. (XfmdDesktop.design, line 530).
- f0217 — DocumentStateShape has-field DocumentBytes. (XfmdDesktop.design, line 531).

- f0218 — DocumentStateShape has-field DocumentIdentity. (XfmdDesktop.design, line 532).
- f0219 — DocumentStateShape has-field DocumentPath. (XfmdDesktop.design, line 533).
- f0220 — DocumentStateShape has-field DocumentRevision. (XfmdDesktop.design, line 534).
- f0221 — DocumentStateShape has-field SavedBaselineBytes. (XfmdDesktop.design, line 535).
- f0222 — DocumentStorage owns LocalFileStorage. (XfmdDesktop.design, line 536).
- f0223 — DocumentStorage uses ReferenceStorage as receiver of ReadReference in mode NormalDesktop. (XfmdDesktop.design, line 537).
- f0224 — DocumentStorage uses ReferenceStorage as sender of ReferenceRead in mode NormalDesktop. (XfmdDesktop.design, line 538).
- f0225 — DocumentStorage uses StorageCalls as receiver of ReadCandidate in mode NormalDesktop. (XfmdDesktop.design, line 539).
- f0226 — DocumentStorage uses StorageCalls as receiver of WriteCurrent in mode NormalDesktop. (XfmdDesktop.design, line 540).
- f0227 — DocumentStorage uses StorageCalls as sender of CandidateRead in mode NormalDesktop. (XfmdDesktop.design, line 541).
- f0228 — DocumentStorage uses StorageCalls as sender of CandidateReadFailed in mode NormalDesktop. (XfmdDesktop.design, line 542).
- f0229 — DocumentStorage uses StorageCalls as sender of CurrentWritten in mode NormalDesktop. (XfmdDesktop.design, line 543).
- f0230 — Documents consumes FileStorePort. (XfmdDesktop.design, line 544).
- f0231 — Documents holds MainDocumentState. (XfmdDesktop.design, line 545).
- f0232 — Documents owns DocumentSession. (XfmdDesktop.design, line 546).
- f0233 — Documents owns TextEditing. (XfmdDesktop.design, line 547).
- f0234 — Documents uses DocumentCalls as receiver of AdmitDocument in mode NormalDesktop. (XfmdDesktop.design, line 548).

- f0235 — Documents uses DocumentCalls as sender of DocumentOpened in mode NormalDesktop. (XfmdDesktop.design, line 549).
- f0236 — Documents uses DocumentCalls as sender of DocumentRejected in mode NormalDesktop. (XfmdDesktop.design, line 550).
- f0237 — Documents uses DocumentNotifications as sender of CommitVisit in mode NormalDesktop. (XfmdDesktop.design, line 551).
- f0238 — Documents uses DocumentNotifications as sender of DocumentChanged in mode NormalDesktop. (XfmdDesktop.design, line 552).
- f0239 — Documents uses DocumentNotifications as sender of GeneratedDocumentChanged in mode NormalDesktop. (XfmdDesktop.design, line 553).
- f0240 — Documents uses DocumentStateChanges as receiver of MarkCurrentSaved in mode NormalDesktop. (XfmdDesktop.design, line 554).
- f0241 — Documents uses DocumentStateChanges as receiver of ReplaceDocument in mode NormalDesktop. (XfmdDesktop.design, line 555).
- f0242 — Documents uses DocumentStateChanges as sender of MarkCurrentSaved in mode NormalDesktop. (XfmdDesktop.design, line 556).
- f0243 — Documents uses DocumentStateChanges as sender of ReplaceDocument in mode NormalDesktop. (XfmdDesktop.design, line 557).
- f0244 — Documents uses EditIntents as receiver of ApplyTextEdit in mode NormalDesktop. (XfmdDesktop.design, line 558).
- f0245 — Documents uses GeneratedAdmission as receiver of InspectDirtyMain in mode NormalDesktop. (XfmdDesktop.design, line 559).
- f0246 — Documents uses GeneratedDocumentCalls as receiver of AdmitGeneratedDocument in mode NormalDesktop. (XfmdDesktop.design, line 560).
- f0247 — Documents uses GeneratedDocumentCalls as sender of GeneratedDocumentOpened in mode NormalDesktop. (XfmdDesktop.design, line 561).
- f0248 — Documents uses PublicationInputs as sender of FreezeExportSnapshot in mode NormalDesktop. (XfmdDesktop.design, line 562).

- f0249 — Documents uses StorageCalls as receiver of CandidateRead in mode NormalDesktop. (XfmdDesktop.design, line 563).
- f0250 — Documents uses StorageCalls as receiver of CandidateReadFailed in mode NormalDesktop. (XfmdDesktop.design, line 564).
- f0251 — Documents uses StorageCalls as receiver of CurrentWritten in mode NormalDesktop. (XfmdDesktop.design, line 565).
- f0252 — Documents uses StorageCalls as sender of ReadCandidate in mode NormalDesktop. (XfmdDesktop.design, line 566).
- f0253 — Documents uses StorageCalls as sender of WriteCurrent in mode NormalDesktop. (XfmdDesktop.design, line 567).
- f0254 — Documents uses UnsavedAdmission as receiver of ChooseCancel in mode NormalDesktop. (XfmdDesktop.design, line 568).
- f0255 — Documents uses UnsavedAdmission as receiver of ChooseSave in mode NormalDesktop. (XfmdDesktop.design, line 569).
- f0256 — Documents uses UnsavedAdmission as sender of ChooseUnsaved in mode NormalDesktop. (XfmdDesktop.design, line 570).
- f0257 — EditIntents upholds EditIntentsContract. (XfmdDesktop.design, line 571).
- f0258 — EditIntentsContract has completeness = closed. (XfmdDesktop.design, line 572).
- f0259 — EditIntentsContract permits ApplyTextEdit. (XfmdDesktop.design, line 573).
- f0260 — EditedPreviewPublished exercises EditDocuments. (XfmdDesktop.design, line 574).
- f0261 — EditedPreviewPublished has completeness = closed. (XfmdDesktop.design, line 575).
- f0262 — EditedPreviewPublished runs-in NormalDesktop. (XfmdDesktop.design, line 576).
- f0263 — EditedPreviewPublished step 1 sends ApplyTextEdit from NativeShell to Documents via EditIntents. (XfmdDesktop.design, line 577).
- f0264 — EditedPreviewPublished step 10 sends AcceptCurrentFrame from Preview to Preview via PreviewAdmission. (XfmdDesktop.design, line 578).

- f0265 — EditedPreviewPublished step 11 sends PresentFrame from Preview to NativeShell via PresentationEvents. (XfmdDesktop.design, line 579).
- f0266 — EditedPreviewPublished step 2 sends DocumentChanged from Documents to Preview via DocumentNotifications. (XfmdDesktop.design, line 580).
- f0267 — EditedPreviewPublished step 3 sends RestartDebounce from Preview to EventLoop via ScheduledWork. (XfmdDesktop.design, line 581).
- f0268 — EditedPreviewPublished step 4 sends DebounceElapsed from EventLoop to Preview via ScheduledWork. (XfmdDesktop.design, line 582).
- f0269 — EditedPreviewPublished step 5 sends ParseSnapshot from Preview to Interpreter via InterpretationCalls. (XfmdDesktop.design, line 583).
- f0270 — EditedPreviewPublished step 6 sends ParsedSnapshot from Interpreter to Preview via InterpretationCalls reply-to 5. (XfmdDesktop.design, line 584).
- f0271 — EditedPreviewPublished step 7 sends AcceptCurrentModel from Preview to Preview via PreviewAdmission. (XfmdDesktop.design, line 585).
- f0272 — EditedPreviewPublished step 8 sends LayoutModel from Preview to Renderer via LayoutCalls. (XfmdDesktop.design, line 586).
- f0273 — EditedPreviewPublished step 9 sends ModelLaidOut from Renderer to Preview via LayoutCalls reply-to 8. (XfmdDesktop.design, line 587).
- f0274 — EmbeddedVisuals allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 588).
- f0275 — EmbeddedVisuals contributes-to MarkdownPresentation. (XfmdDesktop.design, line 589).
- f0276 — EventLoop owns EventScheduling. (XfmdDesktop.design, line 590).
- f0277 — EventLoop uses ScheduledWork as receiver of RestartDebounce in mode NormalDesktop. (XfmdDesktop.design, line 591).
- f0278 — EventLoop uses ScheduledWork as sender of DebounceElapsed in mode NormalDesktop. (XfmdDesktop.design, line 592).
- f0279 — EventLoop uses ScheduledWork as sender of PollReleaseQueue in mode NormalDesktop. (XfmdDesktop.design, line 593).
- f0280 — EventScheduling allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 594).

- f0281 — EventScheduling contributes-to LivePreview. (XfmdDesktop.design, line 595).
- f0282 — ExpandReference has message-kind = event. (XfmdDesktop.design, line 596).
- f0283 — ExpandReference upholds InteractionObservationShape. (XfmdDesktop.design, line 597).
- f0284 — ExportBytes has presence = required. (XfmdDesktop.design, line 598).
- f0285 — ExportBytes has value-type = bytes. (XfmdDesktop.design, line 599).
- f0286 — ExportDocument has presence = required. (XfmdDesktop.design, line 600).
- f0287 — ExportDocument has value-type = unsigned. (XfmdDesktop.design, line 601).
- f0288 — ExportInterpretation upholds ExportInterpretationContract. (XfmdDesktop.design, line 602).
- f0289 — ExportInterpretationContract has completeness = closed. (XfmdDesktop.design, line 603).
- f0290 — ExportInterpretationContract permits ExportSnapshotParsed. (XfmdDesktop.design, line 604).
- f0291 — ExportInterpretationContract permits ParseExportSnapshot. (XfmdDesktop.design, line 605).
- f0292 — ExportLayout upholds ExportLayoutContract. (XfmdDesktop.design, line 606).
- f0293 — ExportLayoutContract has completeness = closed. (XfmdDesktop.design, line 607).
- f0294 — ExportLayoutContract permits ExportPagesLaidOut. (XfmdDesktop.design, line 608).
- f0295 — ExportLayoutContract permits LayoutExportPages. (XfmdDesktop.design, line 609).
- f0296 — ExportPagesLaidOut has message-kind = result. (XfmdDesktop.design, line 610).

- f0297 — ExportPagesLaidOut replies-to LayoutExportPages. (XfmdDesktop.design, line 611).
- f0298 — ExportPagesLaidOut upholds InteractionObservationShape. (XfmdDesktop.design, line 612).
- f0299 — ExportPath has presence = required. (XfmdDesktop.design, line 613).
- f0300 — ExportPath has value-type = text. (XfmdDesktop.design, line 614).
- f0301 — ExportRevision has presence = required. (XfmdDesktop.design, line 615).
- f0302 — ExportRevision has value-type = unsigned. (XfmdDesktop.design, line 616).
- f0303 — ExportSnapshotParsed has message-kind = result. (XfmdDesktop.design, line 617).
- f0304 — ExportSnapshotParsed replies-to ParseExportSnapshot. (XfmdDesktop.design, line 618).
- f0305 — ExportSnapshotParsed upholds InteractionObservationShape. (XfmdDesktop.design, line 619).
- f0306 — ExportSnapshotShape has completeness = closed. (XfmdDesktop.design, line 620).
- f0307 — ExportSnapshotShape has-field ExportBytes. (XfmdDesktop.design, line 621).
- f0308 — ExportSnapshotShape has-field ExportDocument. (XfmdDesktop.design, line 622).
- f0309 — ExportSnapshotShape has-field ExportPath. (XfmdDesktop.design, line 623).
- f0310 — ExportSnapshotShape has-field ExportRevision. (XfmdDesktop.design, line 624).
- f0311 — ExternalLauncher uses ExternalOpening as receiver of LaunchConfiguredProgram in mode NormalDesktop. (XfmdDesktop.design, line 625).
- f0312 — ExternalOpening upholds ExternalOpeningContract. (XfmdDesktop.design, line 626).

- f0313 — ExternalOpeningContract has completeness = closed. (XfmdDesktop.design, line 627).
- f0314 — ExternalOpeningContract permits LaunchConfiguredProgram. (XfmdDesktop.design, line 628).
- f0315 — ExternalTargetHandedOff exercises NavigateDocuments. (XfmdDesktop.design, line 629).
- f0316 — ExternalTargetHandedOff has completeness = closed. (XfmdDesktop.design, line 630).
- f0317 — ExternalTargetHandedOff runs-in NormalDesktop. (XfmdDesktop.design, line 631).
- f0318 — ExternalTargetHandedOff step 1 sends ActivateExternalTarget from NativeShell to Application via WorkspaceIntents. (XfmdDesktop.design, line 632).
- f0319 — ExternalTargetHandedOff step 2 sends ClassifyExternalTarget from Application to Application via OpeningPolicy. (XfmdDesktop.design, line 633).
- f0320 — ExternalTargetHandedOff step 3 sends LaunchConfiguredProgram from Application to ExternalLauncher via ExternalOpening. (XfmdDesktop.design, line 634).
- f0321 — ExternalViewBroker uses LeaseNotifications as receiver of AttemptRelease in mode NormalDesktop. (XfmdDesktop.design, line 635).
- f0322 — ExternalViewGenerator uses GeneratedDelivery as receiver of GeneratedMainAccepted in mode NormalDesktop. (XfmdDesktop.design, line 636).
- f0323 — ExternalViewGenerator uses GeneratedDelivery as receiver of GeneratedMainRejected in mode NormalDesktop. (XfmdDesktop.design, line 637).
- f0324 — ExternalViewGenerator uses GeneratedDelivery as sender of DeliverGeneratedMain in mode NormalDesktop. (XfmdDesktop.design, line 638).
- f0325 — ExternalViewGenerator uses GenerationLifecycle as receiver of CancelPreviousChild in mode NormalDesktop. (XfmdDesktop.design, line 639).
- f0326 — ExternalViewGenerator uses GenerationLifecycle as receiver of StartGeneration in mode NormalDesktop. (XfmdDesktop.design, line 640).
- f0327 — FavoriteFileChosen has message-kind = event. (XfmdDesktop.design, line 641).

- f0328 — FavoriteFileChosen upholds InteractionObservationShape. (XfmdDesktop.design, line 642).
- f0329 — FavoriteFileOpens exercises NavigateDocuments. (XfmdDesktop.design, line 643).
- f0330 — FavoriteFileOpens has completeness = closed. (XfmdDesktop.design, line 644).
- f0331 — FavoriteFileOpens runs-in NormalDesktop. (XfmdDesktop.design, line 645).
- f0332 — FavoriteFileOpens step 1 sends FavoriteFileChosen from NativeShell to Application via WorkspaceIntents. (XfmdDesktop.design, line 646).
- f0333 — FavoriteFileOpens step 2 sends OpenTarget from Application to Navigation via NavigationCalls. (XfmdDesktop.design, line 647).
- f0334 — FavoriteFileOpens step 3 sends AdmitDocument from Navigation to Documents via DocumentCalls. (XfmdDesktop.design, line 648).
- f0335 — FavoriteFileOpens step 4 sends ReadCandidate from Documents to DocumentStorage via StorageCalls. (XfmdDesktop.design, line 649).
- f0336 — FavoriteFileOpens step 5 sends CandidateRead from DocumentStorage to Documents via StorageCalls reply-to 4. (XfmdDesktop.design, line 650).
- f0337 — FavoriteFileOpens step 6 sends ReplaceDocument from Documents to Documents via DocumentStateChanges. (XfmdDesktop.design, line 651).
- f0338 — FavoriteFileOpens step 7 sends CommitVisit from Documents to Navigation via DocumentNotifications. (XfmdDesktop.design, line 652).
- f0339 — FavoriteFileOpens step 8 sends DocumentOpened from Documents to Navigation via DocumentCalls reply-to 3. (XfmdDesktop.design, line 653).
- f0340 — FavoriteFileOpens step 9 sends TargetOpened from Navigation to Application via NavigationCalls reply-to 2. (XfmdDesktop.design, line 654).
- f0341 — FavoriteFolderChangesRoot exercises BrowseWorkspace. (XfmdDesktop.design, line 655).
- f0342 — FavoriteFolderChangesRoot has completeness = closed. (XfmdDesktop.design, line 656).
- f0343 — FavoriteFolderChangesRoot runs-in NormalDesktop. (XfmdDesktop.design, line 657).

- f0344 — FavoriteFolderChangesRoot step 1 sends FavoriteFolderChosen from NativeShell to Workspace via WorkspaceIntents. (XfmdDesktop.design, line 658).
- f0345 — FavoriteFolderChangesRoot step 2 sends ActivateRootAndHistory from Workspace to Workspace via WorkspaceChanges. (XfmdDesktop.design, line 659).
- f0346 — FavoriteFolderChangesRoot step 3 sends RequestTreeRefresh from Workspace to NativeShell via WorkspaceChanges. (XfmdDesktop.design, line 660).
- f0347 — FavoriteFolderChosen has message-kind = event. (XfmdDesktop.design, line 661).
- f0348 — FavoriteFolderChosen upholds InteractionObservationShape. (XfmdDesktop.design, line 662).
- f0349 — FilteredFileTree allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 663).
- f0350 — FilteredFileTree contributes-to WorkPathNavigation. (XfmdDesktop.design, line 664).
- f0351 — FoxPresentation allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 665).
- f0352 — FoxPresentation contributes-to ConfigurableScrolling. (XfmdDesktop.design, line 666).
- f0353 — FoxPresentation contributes-to DocumentNavigation. (XfmdDesktop.design, line 667).
- f0354 — FoxPresentation contributes-to LivePreview. (XfmdDesktop.design, line 668).
- f0355 — FoxPresentation contributes-to MarkdownPresentation. (XfmdDesktop.design, line 669).
- f0356 — FoxPresentation contributes-to MermaidDiagrams. (XfmdDesktop.design, line 670).
- f0357 — FoxPresentation contributes-to PagedPublication. (XfmdDesktop.design, line 671).
- f0358 — FoxPresentation contributes-to SynchronizedScrolling. (XfmdDesktop.design, line 672).
- f0359 — FreezeExportSnapshot has message-kind = event. (XfmdDesktop.design, line 673).

- f0360 — FreezeExportSnapshot upholds InteractionObservationShape. (XfmdDesktop.design, line 674).
- f0361 — FrozenExportSnapshot upholds ExportSnapshotShape. (XfmdDesktop.design, line 675).
- f0362 — FullscreenChangesPresentation exercises UseFullscreen. (XfmdDesktop.design, line 676).
- f0363 — FullscreenChangesPresentation has completeness = closed. (XfmdDesktop.design, line 677).
- f0364 — FullscreenChangesPresentation runs-in NormalDesktop. (XfmdDesktop.design, line 678).
- f0365 — FullscreenChangesPresentation step 1 sends ToggleFullscreen from NativeShell to NativeShell via WindowPresentation. (XfmdDesktop.design, line 679).
- f0366 — FullscreenChangesPresentation step 2 sends RetainDocumentAndAnchor from NativeShell to Viewport via ViewportChanges. (XfmdDesktop.design, line 680).
- f0367 — GeneratedAdmission upholds GeneratedAdmissionContract. (XfmdDesktop.design, line 681).
- f0368 — GeneratedAdmissionContract has completeness = closed. (XfmdDesktop.design, line 682).
- f0369 — GeneratedAdmissionContract permits AdvanceGenerationSequence. (XfmdDesktop.design, line 683).
- f0370 — GeneratedAdmissionContract permits InspectDirtyMain. (XfmdDesktop.design, line 684).
- f0371 — GeneratedAdmissionContract permits RejectInvalidSelection. (XfmdDesktop.design, line 685).
- f0372 — GeneratedAdmissionContract permits ValidateSelection. (XfmdDesktop.design, line 686).
- f0373 — GeneratedDelivery upholds GeneratedDeliveryContract. (XfmdDesktop.design, line 687).
- f0374 — GeneratedDeliveryContract has completeness = closed. (XfmdDesktop.design, line 688).

- f0375 — GeneratedDeliveryContract permits DeliverGeneratedMain. (XfmdDesktop.design, line 689).
- f0376 — GeneratedDeliveryContract permits GeneratedMainAccepted. (XfmdDesktop.design, line 690).
- f0377 — GeneratedDeliveryContract permits GeneratedMainRejected. (XfmdDesktop.design, line 691).
- f0378 — GeneratedDocumentCalls upholds GeneratedDocumentCallsContract. (XfmdDesktop.design, line 692).
- f0379 — GeneratedDocumentCallsContract has completeness = closed. (XfmdDesktop.design, line 693).
- f0380 — GeneratedDocumentCallsContract permits AdmitGeneratedDocument. (XfmdDesktop.design, line 694).
- f0381 — GeneratedDocumentCallsContract permits GeneratedDocumentOpened. (XfmdDesktop.design, line 695).
- f0382 — GeneratedDocumentChanged has message-kind = event. (XfmdDesktop.design, line 696).
- f0383 — GeneratedDocumentChanged upholds InteractionObservationShape. (XfmdDesktop.design, line 697).
- f0384 — GeneratedDocumentNavigation allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 698).
- f0385 — GeneratedDocumentNavigation contributes-to SelectGeneratedView. (XfmdDesktop.design, line 699).
- f0386 — GeneratedDocumentOpened has message-kind = result. (XfmdDesktop.design, line 700).
- f0387 — GeneratedDocumentOpened replies-to AdmitGeneratedDocument. (XfmdDesktop.design, line 701).
- f0388 — GeneratedDocumentOpened upholds InteractionObservationShape. (XfmdDesktop.design, line 702).
- f0389 — GeneratedIntents upholds GeneratedIntentsContract. (XfmdDesktop.design, line 703).
- f0390 — GeneratedIntentsContract has completeness = closed. (XfmdDesktop.design, line 704).

- f0391 — GeneratedIntentsContract permits SelectInvalidView. (XfmdDesktop.design, line 705).
- f0392 — GeneratedIntentsContract permits SelectRegisteredView. (XfmdDesktop.design, line 706).
- f0393 — GeneratedMainAccepted has message-kind = result. (XfmdDesktop.design, line 707).
- f0394 — GeneratedMainAccepted replies-to DeliverGeneratedMain. (XfmdDesktop.design, line 708).
- f0395 — GeneratedMainAccepted upholds InteractionObservationShape. (XfmdDesktop.design, line 709).
- f0396 — GeneratedMainRejected has message-kind = result. (XfmdDesktop.design, line 710).
- f0397 — GeneratedMainRejected replies-to DeliverGeneratedMain. (XfmdDesktop.design, line 711).
- f0398 — GeneratedMainRejected upholds InteractionObservationShape. (XfmdDesktop.design, line 712).
- f0399 — GeneratedReplacementReleasesOldLease exercises SelectGeneratedView. (XfmdDesktop.design, line 713).
- f0400 — GeneratedReplacementReleasesOldLease has completeness = closed. (XfmdDesktop.design, line 714).
- f0401 — GeneratedReplacementReleasesOldLease runs-in NormalDesktop. (XfmdDesktop.design, line 715).
- f0402 — GeneratedReplacementReleasesOldLease step 1 sends DeliverGeneratedMain from ExternalViewGenerator to GeneratedViews via GeneratedDelivery. (XfmdDesktop.design, line 716).
- f0403 — GeneratedReplacementReleasesOldLease step 2 sends AdmitGeneratedDocument from GeneratedViews to Documents via GeneratedDocumentCalls. (XfmdDesktop.design, line 717).
- f0404 — GeneratedReplacementReleasesOldLease step 3 sends GeneratedDocumentChanged from Documents to GeneratedViews via DocumentNotifications. (XfmdDesktop.design, line 718).

- f0405 — GeneratedReplacementReleasesOldLease step 4 sends QueuePreviousLease from GeneratedViews to GeneratedViews via LeaseLifecycle. (XfmdDesktop.design, line 719).
- f0406 — GeneratedReplacementReleasesOldLease step 5 sends AttemptRelease from GeneratedViews to ExternalViewBroker via LeaseNotifications. (XfmdDesktop.design, line 720).
- f0407 — GeneratedReplacementReleasesOldLease step 6 sends GeneratedDocumentOpened from Documents to GeneratedViews via GeneratedDocumentCalls reply-to 2. (XfmdDesktop.design, line 721).
- f0408 — GeneratedReplacementReleasesOldLease step 7 sends InstallNewLease from GeneratedViews to GeneratedViews via LeaseLifecycle. (XfmdDesktop.design, line 722).
- f0409 — GeneratedReplacementReleasesOldLease step 8 sends GeneratedMainAccepted from GeneratedViews to ExternalViewGenerator via GeneratedDelivery reply-to 1. (XfmdDesktop.design, line 723).
- f0410 — GeneratedSelectionState upholds GenerationStateShape. (XfmdDesktop.design, line 724).
- f0411 — GeneratedSelectionSupersedes exercises SelectGeneratedView. (XfmdDesktop.design, line 725).
- f0412 — GeneratedSelectionSupersedes has completeness = closed. (XfmdDesktop.design, line 726).
- f0413 — GeneratedSelectionSupersedes runs-in NormalDesktop. (XfmdDesktop.design, line 727).
- f0414 — GeneratedSelectionSupersedes step 1 sends SelectRegisteredView from NativeShell to GeneratedViews via GeneratedIntents. (XfmdDesktop.design, line 728).
- f0415 — GeneratedSelectionSupersedes step 2 sends ValidateSelection from GeneratedViews to GeneratedViews via GeneratedAdmission. (XfmdDesktop.design, line 729).
- f0416 — GeneratedSelectionSupersedes step 3 sends CancelPreviousChild from GeneratedViews to ExternalViewGenerator via GenerationLifecycle. (XfmdDesktop.design, line 730).

- f0417 — GeneratedSelectionSupersedes step 4 sends AdvanceGenerationSequence from GeneratedViews to GeneratedViews via GeneratedAdmission. (XfmdDesktop.design, line 731).
- f0418 — GeneratedSelectionSupersedes step 5 sends StartGeneration from GeneratedViews to ExternalViewGenerator via GenerationLifecycle. (XfmdDesktop.design, line 732).
- f0419 — GeneratedViews consumes LeaseReleaseProtocol. (XfmdDesktop.design, line 733).
- f0420 — GeneratedViews consumes SchedulerPort. (XfmdDesktop.design, line 734).
- f0421 — GeneratedViews consumes ViewGenerationProtocol. (XfmdDesktop.design, line 735).
- f0422 — GeneratedViews consumes WindowDeliveryProtocol. (XfmdDesktop.design, line 736).
- f0423 — GeneratedViews holds GeneratedSelectionState. (XfmdDesktop.design, line 737).
- f0424 — GeneratedViews owns GeneratedDocumentNavigation. (XfmdDesktop.design, line 738).
- f0425 — GeneratedViews uses DocumentNotifications as receiver of GeneratedDocumentChanged in mode NormalDesktop. (XfmdDesktop.design, line 739).
- f0426 — GeneratedViews uses GeneratedAdmission as receiver of AdvanceGenerationSequence in mode NormalDesktop. (XfmdDesktop.design, line 740).
- f0427 — GeneratedViews uses GeneratedAdmission as receiver of RejectInvalidSelection in mode NormalDesktop. (XfmdDesktop.design, line 741).
- f0428 — GeneratedViews uses GeneratedAdmission as receiver of ValidateSelection in mode NormalDesktop. (XfmdDesktop.design, line 742).
- f0429 — GeneratedViews uses GeneratedAdmission as sender of AdvanceGenerationSequence in mode NormalDesktop. (XfmdDesktop.design, line 743).

- f0430 — GeneratedViews uses GeneratedAdmission as sender of InspectDirtyMain in mode NormalDesktop. (XfmdDesktop.design, line 744).
- f0431 — GeneratedViews uses GeneratedAdmission as sender of RejectInvalidSelection in mode NormalDesktop. (XfmdDesktop.design, line 745).
- f0432 — GeneratedViews uses GeneratedAdmission as sender of ValidateSelection in mode NormalDesktop. (XfmdDesktop.design, line 746).
- f0433 — GeneratedViews uses GeneratedDelivery as receiver of DeliverGeneratedMain in mode NormalDesktop. (XfmdDesktop.design, line 747).
- f0434 — GeneratedViews uses GeneratedDelivery as sender of GeneratedMainAccepted in mode NormalDesktop. (XfmdDesktop.design, line 748).
- f0435 — GeneratedViews uses GeneratedDelivery as sender of GeneratedMainRejected in mode NormalDesktop. (XfmdDesktop.design, line 749).
- f0436 — GeneratedViews uses GeneratedDocumentCalls as receiver of GeneratedDocumentOpened in mode NormalDesktop. (XfmdDesktop.design, line 750).
- f0437 — GeneratedViews uses GeneratedDocumentCalls as sender of AdmitGeneratedDocument in mode NormalDesktop. (XfmdDesktop.design, line 751).
- f0438 — GeneratedViews uses GeneratedIntents as receiver of SelectInvalidView in mode NormalDesktop. (XfmdDesktop.design, line 752).
- f0439 — GeneratedViews uses GeneratedIntents as receiver of SelectRegisteredView in mode NormalDesktop. (XfmdDesktop.design, line 753).
- f0440 — GeneratedViews uses GenerationLifecycle as sender of CancelPreviousChild in mode NormalDesktop. (XfmdDesktop.design, line 754).
- f0441 — GeneratedViews uses GenerationLifecycle as sender of StartGeneration in mode NormalDesktop. (XfmdDesktop.design, line 755).
- f0442 — GeneratedViews uses LeaseLifecycle as receiver of InstallNewLease in mode NormalDesktop. (XfmdDesktop.design, line 756).
- f0443 — GeneratedViews uses LeaseLifecycle as receiver of KeepUnsentRelease in mode NormalDesktop. (XfmdDesktop.design, line 757).

- f0444 — GeneratedViews uses LeaseLifecycle as receiver of QueuePreviousLease in mode NormalDesktop. (XfmdDesktop.design, line 758).
- f0445 — GeneratedViews uses LeaseLifecycle as receiver of RemoveSentRelease in mode NormalDesktop. (XfmdDesktop.design, line 759).
- f0446 — GeneratedViews uses LeaseLifecycle as sender of InstallNewLease in mode NormalDesktop. (XfmdDesktop.design, line 760).
- f0447 — GeneratedViews uses LeaseLifecycle as sender of KeepUnsentRelease in mode NormalDesktop. (XfmdDesktop.design, line 761).
- f0448 — GeneratedViews uses LeaseLifecycle as sender of QueuePreviousLease in mode NormalDesktop. (XfmdDesktop.design, line 762).
- f0449 — GeneratedViews uses LeaseLifecycle as sender of RemoveSentRelease in mode NormalDesktop. (XfmdDesktop.design, line 763).
- f0450 — GeneratedViews uses LeaseNotifications as sender of AttemptRelease in mode NormalDesktop. (XfmdDesktop.design, line 764).
- f0451 — GeneratedViews uses PresentationEvents as sender of ShowDirtyRejection in mode NormalDesktop. (XfmdDesktop.design, line 765).
- f0452 — GeneratedViews uses ScheduledWork as receiver of PollReleaseQueue in mode NormalDesktop. (XfmdDesktop.design, line 766).
- f0453 — GenerationLifecycle upholds GenerationLifecycleContract. (XfmdDesktop.design, line 767).
- f0454 — GenerationLifecycleContract has completeness = closed. (XfmdDesktop.design, line 768).
- f0455 — GenerationLifecycleContract permits CancelPreviousChild. (XfmdDesktop.design, line 769).
- f0456 — GenerationLifecycleContract permits StartGeneration. (XfmdDesktop.design, line 770).
- f0457 — GenerationSequence has presence = required. (XfmdDesktop.design, line 771).
- f0458 — GenerationSequence has value-type = unsigned. (XfmdDesktop.design, line 772).
- f0459 — GenerationStateShape has completeness = closed. (XfmdDesktop.design, line 773).

- f0460 — GenerationStateShape has-field GenerationSequence. (XfmdDesktop.design, line 774).
- f0461 — GenerationStateShape has-field RegisteredProject. (XfmdDesktop.design, line 775).
- f0462 — GenerationStateShape has-field TargetPane. (XfmdDesktop.design, line 776).
- f0463 — GenerationStateShape has-field TargetWindow. (XfmdDesktop.design, line 777).
- f0464 — Identity owns ApplicationIdentity. (XfmdDesktop.design, line 778).
- f0465 — Identity owns BuildIdentity. (XfmdDesktop.design, line 779).
- f0466 — IndexChanges upholds IndexChangesContract. (XfmdDesktop.design, line 780).
- f0467 — IndexChangesContract has completeness = closed. (XfmdDesktop.design, line 781).
- f0468 — IndexChangesContract permits CheckReferenceGeneration. (XfmdDesktop.design, line 782).
- f0469 — IndexChangesContract permits PublishReferenceHeadings. (XfmdDesktop.design, line 783).
- f0470 — IndexIntents upholds IndexIntentsContract. (XfmdDesktop.design, line 784).
- f0471 — IndexIntentsContract has completeness = closed. (XfmdDesktop.design, line 785).
- f0472 — IndexIntentsContract permits ExpandReference. (XfmdDesktop.design, line 786).
- f0473 — InspectDirtyMain has message-kind = event. (XfmdDesktop.design, line 787).
- f0474 — InspectDirtyMain upholds InteractionObservationShape. (XfmdDesktop.design, line 788).
- f0475 — InstallNewLease has message-kind = event. (XfmdDesktop.design, line 789).

- f0476 — InstallNewLease upholds InteractionObservationShape. (XfmdDesktop.design, line 790).
- f0477 — InteractionObservationShape has completeness = closed. (XfmdDesktop.design, line 791).
- f0478 — InteractionObservationShape has-field ObservationContext. (XfmdDesktop.design, line 792).
- f0479 — InterpretationCalls upholds InterpretationCallsContract. (XfmdDesktop.design, line 793).
- f0480 — InterpretationCallsContract has completeness = closed. (XfmdDesktop.design, line 794).
- f0481 — InterpretationCallsContract permits ParseSnapshot. (XfmdDesktop.design, line 795).
- f0482 — InterpretationCallsContract permits ParsedSnapshot. (XfmdDesktop.design, line 796).
- f0483 — Interpreter consumes DiagramInterpreterPort. (XfmdDesktop.design, line 797).
- f0484 — Interpreter owns MarkdownInterpretation. (XfmdDesktop.design, line 798).
- f0485 — Interpreter owns MermaidInterpretation. (XfmdDesktop.design, line 799).
- f0486 — Interpreter uses DiagramInterpretation as receiver of ParseMermaidBlock in mode NormalDesktop. (XfmdDesktop.design, line 800).
- f0487 — Interpreter uses DiagramInterpretation as sender of ParseMermaidBlock in mode NormalDesktop. (XfmdDesktop.design, line 801).
- f0488 — Interpreter uses ExportInterpretation as receiver of ParseExportSnapshot in mode NormalDesktop. (XfmdDesktop.design, line 802).
- f0489 — Interpreter uses ExportInterpretation as sender of ExportSnapshotParsed in mode NormalDesktop. (XfmdDesktop.design, line 803).
- f0490 — Interpreter uses InterpretationCalls as receiver of ParseSnapshot in mode NormalDesktop. (XfmdDesktop.design, line 804).
- f0491 — Interpreter uses InterpretationCalls as sender of ParsedSnapshot in mode NormalDesktop. (XfmdDesktop.design, line 805).

- f0492 — Interpreter uses ReferenceInterpretation as receiver of ParseReference in mode NormalDesktop. (XfmdDesktop.design, line 806).
- f0493 — Interpreter uses ReferenceInterpretation as sender of ReferenceParsed in mode NormalDesktop. (XfmdDesktop.design, line 807).
- f0494 — InvalidSelectionRetainsChild exercises SelectGeneratedView. (XfmdDesktop.design, line 808).
- f0495 — InvalidSelectionRetainsChild has completeness = closed. (XfmdDesktop.design, line 809).
- f0496 — InvalidSelectionRetainsChild runs-in NormalDesktop. (XfmdDesktop.design, line 810).
- f0497 — InvalidSelectionRetainsChild step 1 sends SelectInvalidView from NativeShell to GeneratedViews via GeneratedIntents. (XfmdDesktop.design, line 811).
- f0498 — InvalidSelectionRetainsChild step 2 sends RejectInvalidSelection from GeneratedViews to GeneratedViews via GeneratedAdmission. (XfmdDesktop.design, line 812).
- f0499 — KeepUnsentRelease has message-kind = event. (XfmdDesktop.design, line 813).
- f0500 — KeepUnsentRelease upholds InteractionObservationShape. (XfmdDesktop.design, line 814).
- f0501 — LaunchConfiguredProgram has message-kind = event. (XfmdDesktop.design, line 815).
- f0502 — LaunchConfiguredProgram upholds InteractionObservationShape. (XfmdDesktop.design, line 816).
- f0503 — LayoutCalls upholds LayoutCallsContract. (XfmdDesktop.design, line 817).
- f0504 — LayoutCallsContract has completeness = closed. (XfmdDesktop.design, line 818).
- f0505 — LayoutCallsContract permits LayoutModel. (XfmdDesktop.design, line 819).
- f0506 — LayoutCallsContract permits ModelLaidOut. (XfmdDesktop.design, line 820).

- f0507 — LayoutExportPages has message-kind = request. (XfmdDesktop.design, line 821).
- f0508 — LayoutExportPages upholds InteractionObservationShape. (XfmdDesktop.design, line 822).
- f0509 — LayoutModel has message-kind = request. (XfmdDesktop.design, line 823).
- f0510 — LayoutModel upholds InteractionObservationShape. (XfmdDesktop.design, line 824).
- f0511 — LayoutTypedDiagram has message-kind = request. (XfmdDesktop.design, line 825).
- f0512 — LayoutTypedDiagram upholds InteractionObservationShape. (XfmdDesktop.design, line 826).
- f0513 — LeaseLifecycle upholds LeaseLifecycleContract. (XfmdDesktop.design, line 827).
- f0514 — LeaseLifecycleContract has completeness = closed. (XfmdDesktop.design, line 828).
- f0515 — LeaseLifecycleContract permits InstallNewLease. (XfmdDesktop.design, line 829).
- f0516 — LeaseLifecycleContract permits KeepUnsentRelease. (XfmdDesktop.design, line 830).
- f0517 — LeaseLifecycleContract permits QueuePreviousLease. (XfmdDesktop.design, line 831).
- f0518 — LeaseLifecycleContract permits RemoveSentRelease. (XfmdDesktop.design, line 832).
- f0519 — LeaseNotifications upholds LeaseNotificationsContract. (XfmdDesktop.design, line 833).
- f0520 — LeaseNotificationsContract has completeness = closed. (XfmdDesktop.design, line 834).
- f0521 — LeaseNotificationsContract permits AttemptRelease. (XfmdDesktop.design, line 835).
- f0522 — LivePreview supports EditDocuments. (XfmdDesktop.design, line 836).

- f0523 — LocalFileStorage allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 837).
- f0524 — LocalFileStorage contributes-to DocumentNavigation. (XfmdDesktop.design, line 838).
- f0525 — LocalFileStorage contributes-to MarkdownPresentation. (XfmdDesktop.design, line 839).
- f0526 — MainDocumentState upholds DocumentStateShape. (XfmdDesktop.design, line 840).
- f0527 — MapSourceAnchor has message-kind = event. (XfmdDesktop.design, line 841).
- f0528 — MapSourceAnchor upholds InteractionObservationShape. (XfmdDesktop.design, line 842).
- f0529 — MarkCurrentSaved has message-kind = event. (XfmdDesktop.design, line 843).
- f0530 — MarkCurrentSaved upholds InteractionObservationShape. (XfmdDesktop.design, line 844).
- f0531 — MarkdownInterpretation allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 845).
- f0532 — MarkdownInterpretation contributes-to LivePreview. (XfmdDesktop.design, line 846).
- f0533 — MarkdownInterpretation contributes-to MarkdownPresentation. (XfmdDesktop.design, line 847).
- f0534 — MarkdownInterpretation contributes-to MermaidDiagrams. (XfmdDesktop.design, line 848).
- f0535 — MarkdownInterpretation contributes-to PagedPublication. (XfmdDesktop.design, line 849).
- f0536 — MarkdownPresentation supports ReadDocuments. (XfmdDesktop.design, line 850).
- f0537 — MermaidDiagrams supports ReadDiagrams. (XfmdDesktop.design, line 851).
- f0538 — MermaidDiagrams supports ReadDocuments. (XfmdDesktop.design, line 852).

- f0539 — MermaidInterpretation allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 853).
- f0540 — MermaidInterpretation contributes-to MermaidDiagrams. (XfmdDesktop.design, line 854).
- f0541 — ModelLaidOut has message-kind = result. (XfmdDesktop.design, line 855).
- f0542 — ModelLaidOut replies-to LayoutModel. (XfmdDesktop.design, line 856).
- f0543 — ModelLaidOut upholds InteractionObservationShape. (XfmdDesktop.design, line 857).
- f0544 — NativeShell owns FoxPresentation. (XfmdDesktop.design, line 858).
- f0545 — NativeShell owns WorkspaceControls. (XfmdDesktop.design, line 859).
- f0546 — NativeShell uses ContextInteraction as receiver of CaptureContextTarget in mode NormalDesktop. (XfmdDesktop.design, line 860).
- f0547 — NativeShell uses ContextInteraction as receiver of DismissContextMenu in mode NormalDesktop. (XfmdDesktop.design, line 861).
- f0548 — NativeShell uses ContextInteraction as receiver of ReleaseKeyboardGrab in mode NormalDesktop. (XfmdDesktop.design, line 862).
- f0549 — NativeShell uses ContextInteraction as sender of CaptureContextTarget in mode NormalDesktop. (XfmdDesktop.design, line 863).
- f0550 — NativeShell uses ContextInteraction as sender of DismissContextMenu in mode NormalDesktop. (XfmdDesktop.design, line 864).
- f0551 — NativeShell uses ContextInteraction as sender of ReleaseKeyboardGrab in mode NormalDesktop. (XfmdDesktop.design, line 865).
- f0552 — NativeShell uses EditIntents as sender of ApplyTextEdit in mode NormalDesktop. (XfmdDesktop.design, line 866).
- f0553 — NativeShell uses GeneratedIntents as sender of SelectInvalidView in mode NormalDesktop. (XfmdDesktop.design, line 867).
- f0554 — NativeShell uses GeneratedIntents as sender of SelectRegisteredView in mode NormalDesktop. (XfmdDesktop.design, line 868).
- f0555 — NativeShell uses IndexChanges as receiver of PublishReferenceHeadings in mode NormalDesktop. (XfmdDesktop.design, line 869).

- f0556 — NativeShell uses IndexIntents as sender of ExpandReference in mode NormalDesktop. (XfmdDesktop.design, line 870).
- f0557 — NativeShell uses PreferenceChanges as receiver of NotifyPreferenceChange in mode NormalDesktop. (XfmdDesktop.design, line 871).
- f0558 — NativeShell uses PreferenceChanges as sender of BeginPreferencesDraft in mode NormalDesktop. (XfmdDesktop.design, line 872).
- f0559 — NativeShell uses PresentationEvents as receiver of PresentFrame in mode NormalDesktop. (XfmdDesktop.design, line 873).
- f0560 — NativeShell uses PresentationEvents as receiver of ShowDirtyRejection in mode NormalDesktop. (XfmdDesktop.design, line 874).
- f0561 — NativeShell uses PublicationIntents as sender of CancelPdfRequest in mode NormalDesktop. (XfmdDesktop.design, line 875).
- f0562 — NativeShell uses PublicationIntents as sender of RequestPdfExport in mode NormalDesktop. (XfmdDesktop.design, line 876).
- f0563 — NativeShell uses UnsavedAdmission as receiver of ChooseUnsaved in mode NormalDesktop. (XfmdDesktop.design, line 877).
- f0564 — NativeShell uses UnsavedAdmission as sender of ChooseCancel in mode NormalDesktop. (XfmdDesktop.design, line 878).
- f0565 — NativeShell uses UnsavedAdmission as sender of ChooseSave in mode NormalDesktop. (XfmdDesktop.design, line 879).
- f0566 — NativeShell uses ViewportChanges as receiver of SetEditorAnchor in mode NormalDesktop. (XfmdDesktop.design, line 880).
- f0567 — NativeShell uses ViewportChanges as sender of RetainDocumentAndAnchor in mode NormalDesktop. (XfmdDesktop.design, line 881).
- f0568 — NativeShell uses ViewportChanges as sender of UserPreviewScroll in mode NormalDesktop. (XfmdDesktop.design, line 882).
- f0569 — NativeShell uses WindowPresentation as receiver of ToggleFullscreen in mode NormalDesktop. (XfmdDesktop.design, line 883).
- f0570 — NativeShell uses WindowPresentation as sender of ToggleFullscreen in mode NormalDesktop. (XfmdDesktop.design, line 884).

- f0571 — NativeShell uses WorkspaceChanges as receiver of RequestTreeRefresh in mode NormalDesktop. (XfmdDesktop.design, line 885).
- f0572 — NativeShell uses WorkspaceIntents as sender of ActivateExternalTarget in mode NormalDesktop. (XfmdDesktop.design, line 886).
- f0573 — NativeShell uses WorkspaceIntents as sender of ChooseInternalFile in mode NormalDesktop. (XfmdDesktop.design, line 887).
- f0574 — NativeShell uses WorkspaceIntents as sender of FavoriteFileChosen in mode NormalDesktop. (XfmdDesktop.design, line 888).
- f0575 — NativeShell uses WorkspaceIntents as sender of FavoriteFolderChosen in mode NormalDesktop. (XfmdDesktop.design, line 889).
- f0576 — Navigation owns NavigationHistory. (XfmdDesktop.design, line 890).
- f0577 — Navigation uses DocumentCalls as receiver of DocumentOpened in mode NormalDesktop. (XfmdDesktop.design, line 891).
- f0578 — Navigation uses DocumentCalls as receiver of DocumentRejected in mode NormalDesktop. (XfmdDesktop.design, line 892).
- f0579 — Navigation uses DocumentCalls as sender of AdmitDocument in mode NormalDesktop. (XfmdDesktop.design, line 893).
- f0580 — Navigation uses DocumentNotifications as receiver of CommitVisit in mode NormalDesktop. (XfmdDesktop.design, line 894).
- f0581 — Navigation uses NavigationCalls as receiver of OpenTarget in mode NormalDesktop. (XfmdDesktop.design, line 895).
- f0582 — Navigation uses NavigationCalls as sender of TargetOpened in mode NormalDesktop. (XfmdDesktop.design, line 896).
- f0583 — NavigationCalls upholds NavigationCallsContract. (XfmdDesktop.design, line 897).
- f0584 — NavigationCallsContract has completeness = closed. (XfmdDesktop.design, line 898).
- f0585 — NavigationCallsContract permits OpenTarget. (XfmdDesktop.design, line 899).
- f0586 — NavigationCallsContract permits TargetOpened. (XfmdDesktop.design, line 900).

- f0587 — NavigationHistory allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 901).
- f0588 — NavigationHistory contributes-to ChapterNavigation. (XfmdDesktop.design, line 902).
- f0589 — NavigationHistory contributes-to DocumentNavigation. (XfmdDesktop.design, line 903).
- f0590 — NavigationHistory contributes-to DocumentReferences. (XfmdDesktop.design, line 904).
- f0591 — NotifyPreferenceChange has message-kind = event. (XfmdDesktop.design, line 905).
- f0592 — NotifyPreferenceChange upholds InteractionObservationShape. (XfmdDesktop.design, line 906).
- f0593 — ObservationContext has presence = required. (XfmdDesktop.design, line 907).
- f0594 — ObservationContext has value-type = text. (XfmdDesktop.design, line 908).
- f0595 — OpenTarget has message-kind = request. (XfmdDesktop.design, line 909).
- f0596 — OpenTarget upholds InteractionObservationShape. (XfmdDesktop.design, line 910).
- f0597 — OpeningPolicy upholds OpeningPolicyContract. (XfmdDesktop.design, line 911).
- f0598 — OpeningPolicyContract has completeness = closed. (XfmdDesktop.design, line 912).
- f0599 — OpeningPolicyContract permits ClassifyExternalTarget. (XfmdDesktop.design, line 913).
- f0600 — PageComposition allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 914).
- f0601 — PageComposition contributes-to MarkdownPresentation. (XfmdDesktop.design, line 915).
- f0602 — PageComposition contributes-to MermaidDiagrams. (XfmdDesktop.design, line 916).

- f0603 — PageComposition contributes-to PagedPublication. (XfmdDesktop.design, line 917).
- f0604 — PagedPublication supports PublishPages. (XfmdDesktop.design, line 918).
- f0605 — PagedPublication supports ReadDocuments. (XfmdDesktop.design, line 919).
- f0606 — PaintPdfCandidate has message-kind = event. (XfmdDesktop.design, line 920).
- f0607 — PaintPdfCandidate upholds InteractionObservationShape. (XfmdDesktop.design, line 921).
- f0608 — ParseExportSnapshot has message-kind = request. (XfmdDesktop.design, line 922).
- f0609 — ParseExportSnapshot upholds InteractionObservationShape. (XfmdDesktop.design, line 923).
- f0610 — ParseMermaidBlock has message-kind = event. (XfmdDesktop.design, line 924).
- f0611 — ParseMermaidBlock upholds InteractionObservationShape. (XfmdDesktop.design, line 925).
- f0612 — ParseReference has message-kind = request. (XfmdDesktop.design, line 926).
- f0613 — ParseReference upholds InteractionObservationShape. (XfmdDesktop.design, line 927).
- f0614 — ParseSnapshot has message-kind = request. (XfmdDesktop.design, line 928).
- f0615 — ParseSnapshot upholds InteractionObservationShape. (XfmdDesktop.design, line 929).
- f0616 — ParsedSnapshot has message-kind = result. (XfmdDesktop.design, line 930).
- f0617 — ParsedSnapshot replies-to ParseSnapshot. (XfmdDesktop.design, line 931).
- f0618 — ParsedSnapshot upholds InteractionObservationShape. (XfmdDesktop.design, line 932).

- f0619 — PdfCancelledBeforePublication exercises PublishPages. (XfmdDesktop.design, line 933).
- f0620 — PdfCancelledBeforePublication has completeness = closed. (XfmdDesktop.design, line 934).
- f0621 — PdfCancelledBeforePublication runs-in NormalDesktop. (XfmdDesktop.design, line 935).
- f0622 — PdfCancelledBeforePublication step 1 sends CancelPdfRequest from NativeShell to Publication via PublicationIntents. (XfmdDesktop.design, line 936).
- f0623 — PdfCancelledBeforePublication step 2 sends CancelUnpublishedJob from Publication to Publication via PublicationState. (XfmdDesktop.design, line 937).
- f0624 — PdfCancelledBeforePublication step 3 sends DiscardPdfCandidate from Publication to Publication via PublicationState. (XfmdDesktop.design, line 938).
- f0625 — PdfExport allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 939).
- f0626 — PdfExport contributes-to MermaidDiagrams. (XfmdDesktop.design, line 940).
- f0627 — PdfExport contributes-to PagedPublication. (XfmdDesktop.design, line 941).
- f0628 — PdfSnapshotPublished exercises PublishPages. (XfmdDesktop.design, line 942).
- f0629 — PdfSnapshotPublished has completeness = closed. (XfmdDesktop.design, line 943).
- f0630 — PdfSnapshotPublished runs-in NormalDesktop. (XfmdDesktop.design, line 944).
- f0631 — PdfSnapshotPublished step 1 sends RequestPdfExport from NativeShell to Publication via PublicationIntents. (XfmdDesktop.design, line 945).
- f0632 — PdfSnapshotPublished step 2 sends FreezeExportSnapshot from Documents to Publication via PublicationInputs. (XfmdDesktop.design, line 946).
- f0633 — PdfSnapshotPublished step 3 sends ParseExportSnapshot from Publication to Interpreter via ExportInterpretation. (XfmdDesktop.design, line 947).

- f0634 — PdfSnapshotPublished step 4 sends ExportSnapshotParsed from Interpreter to Publication via ExportInterpretation reply-to 3. (XfmdDesktop.design, line 948).
- f0635 — PdfSnapshotPublished step 5 sends PrepareExportResources from Publication to VisualResources via ResourcePreparation. (XfmdDesktop.design, line 949).
- f0636 — PdfSnapshotPublished step 6 sends LayoutExportPages from Publication to Renderer via ExportLayout. (XfmdDesktop.design, line 950).
- f0637 — PdfSnapshotPublished step 7 sends ExportPagesLaidOut from Renderer to Publication via ExportLayout reply-to 6. (XfmdDesktop.design, line 951).
- f0638 — PdfSnapshotPublished step 8 sends PaintPdfCandidate from Publication to Typography via PublicationDrawing. (XfmdDesktop.design, line 952).
- f0639 — PdfSnapshotPublished step 9 sends CommitPdfCandidate from Publication to Publication via PublicationState. (XfmdDesktop.design, line 953).
- f0640 — PersistPreferencesDraft has message-kind = event. (XfmdDesktop.design, line 954).
- f0641 — PersistPreferencesDraft upholds InteractionObservationShape. (XfmdDesktop.design, line 955).
- f0642 — PollReleaseQueue has message-kind = event. (XfmdDesktop.design, line 956).
- f0643 — PollReleaseQueue upholds InteractionObservationShape. (XfmdDesktop.design, line 957).
- f0644 — PreferenceChanges upholds PreferenceChangesContract. (XfmdDesktop.design, line 958).
- f0645 — PreferenceChangesContract has completeness = closed. (XfmdDesktop.design, line 959).
- f0646 — PreferenceChangesContract permits AdoptPreferencesDraft. (XfmdDesktop.design, line 960).
- f0647 — PreferenceChangesContract permits BeginPreferencesDraft. (XfmdDesktop.design, line 961).
- f0648 — PreferenceChangesContract permits NotifyPreferenceChange. (XfmdDesktop.design, line 962).

- f0649 — PreferenceChangesContract permits PersistPreferencesDraft. (XfmdDesktop.design, line 963).
- f0650 — PreferenceChangesContract permits ValidatePreferencesDraft. (XfmdDesktop.design, line 964).
- f0651 — Preferences consumes PreferencesStorePort. (XfmdDesktop.design, line 965).
- f0652 — Preferences owns ApplicationPreferences. (XfmdDesktop.design, line 966).
- f0653 — Preferences uses PreferenceChanges as receiver of AdoptPreferencesDraft in mode NormalDesktop. (XfmdDesktop.design, line 967).
- f0654 — Preferences uses PreferenceChanges as receiver of BeginPreferencesDraft in mode NormalDesktop. (XfmdDesktop.design, line 968).
- f0655 — Preferences uses PreferenceChanges as receiver of PersistPreferencesDraft in mode NormalDesktop. (XfmdDesktop.design, line 969).
- f0656 — Preferences uses PreferenceChanges as receiver of ValidatePreferencesDraft in mode NormalDesktop. (XfmdDesktop.design, line 970).
- f0657 — Preferences uses PreferenceChanges as sender of AdoptPreferencesDraft in mode NormalDesktop. (XfmdDesktop.design, line 971).
- f0658 — Preferences uses PreferenceChanges as sender of NotifyPreferenceChange in mode NormalDesktop. (XfmdDesktop.design, line 972).
- f0659 — Preferences uses PreferenceChanges as sender of PersistPreferencesDraft in mode NormalDesktop. (XfmdDesktop.design, line 973).
- f0660 — Preferences uses PreferenceChanges as sender of ValidatePreferencesDraft in mode NormalDesktop. (XfmdDesktop.design, line 974).
- f0661 — PreferencesPersistBeforeAdoption exercises ConfigurePreferences. (XfmdDesktop.design, line 975).
- f0662 — PreferencesPersistBeforeAdoption has completeness = closed. (XfmdDesktop.design, line 976).

- f0663 — PreferencesPersistBeforeAdoption runs-in NormalDesktop. (XfmdDesktop.design, line 977).
- f0664 — PreferencesPersistBeforeAdoption step 1 sends BeginPreferencesDraft from NativeShell to Preferences via PreferenceChanges. (XfmdDesktop.design, line 978).
- f0665 — PreferencesPersistBeforeAdoption step 2 sends ValidatePreferencesDraft from Preferences to Preferences via PreferenceChanges. (XfmdDesktop.design, line 979).
- f0666 — PreferencesPersistBeforeAdoption step 3 sends PersistPreferencesDraft from Preferences to Preferences via PreferenceChanges. (XfmdDesktop.design, line 980).
- f0667 — PreferencesPersistBeforeAdoption step 4 sends AdoptPreferencesDraft from Preferences to Preferences via PreferenceChanges. (XfmdDesktop.design, line 981).
- f0668 — PreferencesPersistBeforeAdoption step 5 sends NotifyPreferenceChange from Preferences to NativeShell via PreferenceChanges. (XfmdDesktop.design, line 982).
- f0669 — PrepareDiagramScenes has message-kind = event. (XfmdDesktop.design, line 983).
- f0670 — PrepareDiagramScenes upholds InteractionObservationShape. (XfmdDesktop.design, line 984).
- f0671 — PrepareEmbeddedResources has message-kind = event. (XfmdDesktop.design, line 985).
- f0672 — PrepareEmbeddedResources upholds InteractionObservationShape. (XfmdDesktop.design, line 986).
- f0673 — PrepareExportResources has message-kind = event. (XfmdDesktop.design, line 987).
- f0674 — PrepareExportResources upholds InteractionObservationShape. (XfmdDesktop.design, line 988).
- f0675 — PrepareTypedDiagram has message-kind = event. (XfmdDesktop.design, line 989).

- f0676 — PrepareTypedDiagram upholds InteractionObservationShape. (XfmdDesktop.design, line 990).
- f0677 — PresentFrame has message-kind = event. (XfmdDesktop.design, line 991).
- f0678 — PresentFrame upholds InteractionObservationShape. (XfmdDesktop.design, line 992).
- f0679 — PresentationEvents upholds PresentationEventsContract. (XfmdDesktop.design, line 993).
- f0680 — PresentationEventsContract has completeness = closed. (XfmdDesktop.design, line 994).
- f0681 — PresentationEventsContract permits PresentFrame. (XfmdDesktop.design, line 995).
- f0682 — PresentationEventsContract permits ShowDirtyRejection. (XfmdDesktop.design, line 996).
- f0683 — Preview consumes InterpreterPort. (XfmdDesktop.design, line 997).
- f0684 — Preview consumes RenderHostPort. (XfmdDesktop.design, line 998).
- f0685 — Preview consumes RendererPort. (XfmdDesktop.design, line 999).
- f0686 — Preview consumes SchedulerPort. (XfmdDesktop.design, line 1000).
- f0687 — Preview owns PreviewPipeline. (XfmdDesktop.design, line 1001).
- f0688 — Preview owns PreviewTextSelection. (XfmdDesktop.design, line 1002).
- f0689 — Preview uses DocumentNotifications as receiver of DocumentChanged in mode NormalDesktop. (XfmdDesktop.design, line 1003).
- f0690 — Preview uses InterpretationCalls as receiver of ParsedSnapshot in mode NormalDesktop. (XfmdDesktop.design, line 1004).
- f0691 — Preview uses InterpretationCalls as sender of ParseSnapshot in mode NormalDesktop. (XfmdDesktop.design, line 1005).
- f0692 — Preview uses LayoutCalls as receiver of ModelLaidOut in mode NormalDesktop. (XfmdDesktop.design, line 1006).
- f0693 — Preview uses LayoutCalls as sender of LayoutModel in mode NormalDesktop. (XfmdDesktop.design, line 1007).

- f0694 — Preview uses PresentationEvents as sender of PresentFrame in mode NormalDesktop. (XfmdDesktop.design, line 1008).
- f0695 — Preview uses PreviewAdmission as receiver of AcceptCurrentFrame in mode NormalDesktop. (XfmdDesktop.design, line 1009).
- f0696 — Preview uses PreviewAdmission as receiver of AcceptCurrentModel in mode NormalDesktop. (XfmdDesktop.design, line 1010).
- f0697 — Preview uses PreviewAdmission as receiver of AcceptWorkerTicket in mode NormalDesktop. (XfmdDesktop.design, line 1011).
- f0698 — Preview uses PreviewAdmission as receiver of CompleteObsoleteWorker in mode NormalDesktop. (XfmdDesktop.design, line 1012).
- f0699 — Preview uses PreviewAdmission as receiver of DiscardObsoleteCompletion in mode NormalDesktop. (XfmdDesktop.design, line 1013).
- f0700 — Preview uses PreviewAdmission as sender of AcceptCurrentFrame in mode NormalDesktop. (XfmdDesktop.design, line 1014).
- f0701 — Preview uses PreviewAdmission as sender of AcceptCurrentModel in mode NormalDesktop. (XfmdDesktop.design, line 1015).
- f0702 — Preview uses PreviewAdmission as sender of AcceptWorkerTicket in mode NormalDesktop. (XfmdDesktop.design, line 1016).
- f0703 — Preview uses PreviewAdmission as sender of CompleteObsoleteWorker in mode NormalDesktop. (XfmdDesktop.design, line 1017).
- f0704 — Preview uses PreviewAdmission as sender of DiscardObsoleteCompletion in mode NormalDesktop. (XfmdDesktop.design, line 1018).
- f0705 — Preview uses ResourcePreparation as sender of PrepareDiagramScenes in mode NormalDesktop. (XfmdDesktop.design, line 1019).
- f0706 — Preview uses ResourcePreparation as sender of PrepareEmbeddedResources in mode NormalDesktop. (XfmdDesktop.design, line 1020).
- f0707 — Preview uses ResourcePreparation as sender of PrepareTypedDiagram in mode NormalDesktop. (XfmdDesktop.design, line 1021).

- f0708 — Preview uses ScheduledWork as receiver of DebounceElapsed in mode NormalDesktop. (XfmdDesktop.design, line 1022).
- f0709 — Preview uses ScheduledWork as sender of RestartDebounce in mode NormalDesktop. (XfmdDesktop.design, line 1023).
- f0710 — PreviewAdmission upholds PreviewAdmissionContract. (XfmdDesktop.design, line 1024).
- f0711 — PreviewAdmissionContract has completeness = closed. (XfmdDesktop.design, line 1025).
- f0712 — PreviewAdmissionContract permits AcceptCurrentFrame. (XfmdDesktop.design, line 1026).
- f0713 — PreviewAdmissionContract permits AcceptCurrentModel. (XfmdDesktop.design, line 1027).
- f0714 — PreviewAdmissionContract permits AcceptWorkerTicket. (XfmdDesktop.design, line 1028).
- f0715 — PreviewAdmissionContract permits CompleteObsoleteWorker. (XfmdDesktop.design, line 1029).
- f0716 — PreviewAdmissionContract permits DiscardObsoleteCompletion. (XfmdDesktop.design, line 1030).
- f0717 — PreviewPipeline allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 1031).
- f0718 — PreviewPipeline contributes-to LivePreview. (XfmdDesktop.design, line 1032).
- f0719 — PreviewPipeline contributes-to MarkdownPresentation. (XfmdDesktop.design, line 1033).
- f0720 — PreviewPipeline contributes-to MermaidDiagrams. (XfmdDesktop.design, line 1034).
- f0721 — PreviewPipeline contributes-to PagedPublication. (XfmdDesktop.design, line 1035).
- f0722 — PreviewResourcesPrepared exercises ReadDocuments. (XfmdDesktop.design, line 1036).
- f0723 — PreviewResourcesPrepared has completeness = closed. (XfmdDesktop.design, line 1037).

- f0724 — PreviewResourcesPrepared runs-in NormalDesktop. (XfmdDesktop.design, line 1038).
- f0725 — PreviewResourcesPrepared step 1 sends ParseSnapshot from Preview to Interpreter via InterpretationCalls. (XfmdDesktop.design, line 1039).
- f0726 — PreviewResourcesPrepared step 2 sends ParsedSnapshot from Interpreter to Preview via InterpretationCalls reply-to 1. (XfmdDesktop.design, line 1040).
- f0727 — PreviewResourcesPrepared step 3 sends PrepareEmbeddedResources from Preview to VisualResources via ResourcePreparation. (XfmdDesktop.design, line 1041).
- f0728 — PreviewResourcesPrepared step 4 sends PrepareDiagramScenes from Preview to VisualResources via ResourcePreparation. (XfmdDesktop.design, line 1042).
- f0729 — PreviewResourcesPrepared step 5 sends AcceptWorkerTicket from Preview to Preview via PreviewAdmission. (XfmdDesktop.design, line 1043).
- f0730 — PreviewResourcesPrepared step 6 sends LayoutModel from Preview to Renderer via LayoutCalls. (XfmdDesktop.design, line 1044).
- f0731 — PreviewResourcesPrepared step 7 sends ModelLaidOut from Renderer to Preview via LayoutCalls reply-to 6. (XfmdDesktop.design, line 1045).
- f0732 — PreviewResourcesPrepared step 8 sends PresentFrame from Preview to NativeShell via PresentationEvents. (XfmdDesktop.design, line 1046).
- f0733 — PreviewScrollSynchronizesEditor exercises ScrollDocuments. (XfmdDesktop.design, line 1047).
- f0734 — PreviewScrollSynchronizesEditor has completeness = closed. (XfmdDesktop.design, line 1048).
- f0735 — PreviewScrollSynchronizesEditor runs-in NormalDesktop. (XfmdDesktop.design, line 1049).
- f0736 — PreviewScrollSynchronizesEditor step 1 sends UserPreviewScroll from NativeShell to Viewport via ViewportChanges. (XfmdDesktop.design, line 1050).
- f0737 — PreviewScrollSynchronizesEditor step 2 sends CheckCurrentMapping from Viewport to Viewport via ViewportChanges. (XfmdDesktop.design, line 1051).

- f0738 — PreviewScrollSynchronizesEditor step 3 sends MapSourceAnchor from Viewport to Viewport via ViewportChanges. (XfmdDesktop.design, line 1052).
- f0739 — PreviewScrollSynchronizesEditor step 4 sends SetEditorAnchor from Viewport to NativeShell via ViewportChanges. (XfmdDesktop.design, line 1053).
- f0740 — PreviewTextSelection allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 1054).
- f0741 — PreviewTextSelection contributes-to MarkdownPresentation. (XfmdDesktop.design, line 1055).
- f0742 — PreviewTextSelection contributes-to MermaidDiagrams. (XfmdDesktop.design, line 1056).
- f0743 — Publication consumes InterpreterPort. (XfmdDesktop.design, line 1057).
- f0744 — Publication consumes RendererPort. (XfmdDesktop.design, line 1058).
- f0745 — Publication consumes TextMetricsPort. (XfmdDesktop.design, line 1059).
- f0746 — Publication holds FrozenExportSnapshot. (XfmdDesktop.design, line 1060).
- f0747 — Publication owns PdfExport. (XfmdDesktop.design, line 1061).
- f0748 — Publication uses ExportInterpretation as receiver of ExportSnapshotParsed in mode NormalDesktop. (XfmdDesktop.design, line 1062).
- f0749 — Publication uses ExportInterpretation as sender of ParseExportSnapshot in mode NormalDesktop. (XfmdDesktop.design, line 1063).
- f0750 — Publication uses ExportLayout as receiver of ExportPagesLaidOut in mode NormalDesktop. (XfmdDesktop.design, line 1064).
- f0751 — Publication uses ExportLayout as sender of LayoutExportPages in mode NormalDesktop. (XfmdDesktop.design, line 1065).
- f0752 — Publication uses PublicationDrawing as sender of PaintPdfCandidate in mode NormalDesktop. (XfmdDesktop.design, line 1066).
- f0753 — Publication uses PublicationInputs as receiver of FreezeExportSnapshot in mode NormalDesktop. (XfmdDesktop.design, line 1067).
- f0754 — Publication uses PublicationIntents as receiver of CancelPdfRequest in mode NormalDesktop. (XfmdDesktop.design, line 1068).

- f0755 — Publication uses PublicationIntents as receiver of RequestPdfExport in mode NormalDesktop. (XfmdDesktop.design, line 1069).
- f0756 — Publication uses PublicationState as receiver of CancelUnpublishedJob in mode NormalDesktop. (XfmdDesktop.design, line 1070).
- f0757 — Publication uses PublicationState as receiver of CommitPdfCandidate in mode NormalDesktop. (XfmdDesktop.design, line 1071).
- f0758 — Publication uses PublicationState as receiver of DiscardPdfCandidate in mode NormalDesktop. (XfmdDesktop.design, line 1072).
- f0759 — Publication uses PublicationState as sender of CancelUnpublishedJob in mode NormalDesktop. (XfmdDesktop.design, line 1073).
- f0760 — Publication uses PublicationState as sender of CommitPdfCandidate in mode NormalDesktop. (XfmdDesktop.design, line 1074).
- f0761 — Publication uses PublicationState as sender of DiscardPdfCandidate in mode NormalDesktop. (XfmdDesktop.design, line 1075).
- f0762 — Publication uses ResourcePreparation as sender of PrepareExportResources in mode NormalDesktop. (XfmdDesktop.design, line 1076).
- f0763 — PublicationDrawing upholds PublicationDrawingContract. (XfmdDesktop.design, line 1077).
- f0764 — PublicationDrawingContract has completeness = closed. (XfmdDesktop.design, line 1078).
- f0765 — PublicationDrawingContract permits PaintPdfCandidate. (XfmdDesktop.design, line 1079).
- f0766 — PublicationInputs upholds PublicationInputsContract. (XfmdDesktop.design, line 1080).
- f0767 — PublicationInputsContract has completeness = closed. (XfmdDesktop.design, line 1081).
- f0768 — PublicationInputsContract permits FreezeExportSnapshot. (XfmdDesktop.design, line 1082).
- f0769 — PublicationIntents upholds PublicationIntentsContract. (XfmdDesktop.design, line 1083).

- f0770 — PublicationIntentsContract has completeness = closed. (XfmdDesktop.design, line 1084).
- f0771 — PublicationIntentsContract permits CancelPdfRequest. (XfmdDesktop.design, line 1085).
- f0772 — PublicationIntentsContract permits RequestPdfExport. (XfmdDesktop.design, line 1086).
- f0773 — PublicationState upholds PublicationStateContract. (XfmdDesktop.design, line 1087).
- f0774 — PublicationStateContract has completeness = closed. (XfmdDesktop.design, line 1088).
- f0775 — PublicationStateContract permits CancelUnpublishedJob. (XfmdDesktop.design, line 1089).
- f0776 — PublicationStateContract permits CommitPdfCandidate. (XfmdDesktop.design, line 1090).
- f0777 — PublicationStateContract permits DiscardPdfCandidate. (XfmdDesktop.design, line 1091).
- f0778 — PublishReferenceHeadings has message-kind = event. (XfmdDesktop.design, line 1092).
- f0779 — PublishReferenceHeadings upholds InteractionObservationShape. (XfmdDesktop.design, line 1093).
- f0780 — QueuePreviousLease has message-kind = event. (XfmdDesktop.design, line 1094).
- f0781 — QueuePreviousLease upholds InteractionObservationShape. (XfmdDesktop.design, line 1095).
- f0782 — ReadCandidate has message-kind = request. (XfmdDesktop.design, line 1096).
- f0783 — ReadCandidate upholds InteractionObservationShape. (XfmdDesktop.design, line 1097).
- f0784 — ReadReference has message-kind = request. (XfmdDesktop.design, line 1098).
- f0785 — ReadReference upholds InteractionObservationShape. (XfmdDesktop.design, line 1099).

- f0786 — ReaderAuthor pursues BrowseSdpProject. (XfmdDesktop.design, line 1100).
- f0787 — ReaderAuthor pursues BrowseWorkspace. (XfmdDesktop.design, line 1101).
- f0788 — ReaderAuthor pursues ConfigurePreferences. (XfmdDesktop.design, line 1102).
- f0789 — ReaderAuthor pursues EditDocuments. (XfmdDesktop.design, line 1103).
- f0790 — ReaderAuthor pursues NavigateDocuments. (XfmdDesktop.design, line 1104).
- f0791 — ReaderAuthor pursues PublishPages. (XfmdDesktop.design, line 1105).
- f0792 — ReaderAuthor pursues ReadDiagrams. (XfmdDesktop.design, line 1106).
- f0793 — ReaderAuthor pursues ReadDocuments. (XfmdDesktop.design, line 1107).
- f0794 — ReaderAuthor pursues ScrollDocuments. (XfmdDesktop.design, line 1108).
- f0795 — ReaderAuthor pursues SelectGeneratedView. (XfmdDesktop.design, line 1109).
- f0796 — ReaderAuthor pursues UseFullscreen. (XfmdDesktop.design, line 1110).
- f0797 — ReferenceHeadingsLoaded exercises NavigateDocuments. (XfmdDesktop.design, line 1111).
- f0798 — ReferenceHeadingsLoaded has completeness = closed. (XfmdDesktop.design, line 1112).
- f0799 — ReferenceHeadingsLoaded runs-in NormalDesktop. (XfmdDesktop.design, line 1113).
- f0800 — ReferenceHeadingsLoaded step 1 sends ExpandReference from NativeShell to DocumentIndexService via IndexIntents. (XfmdDesktop.design, line 1114).
- f0801 — ReferenceHeadingsLoaded step 2 sends ReadReference from DocumentIndexService to DocumentStorage via ReferenceStorage. (XfmdDesktop.design, line 1115).

- f0802 — ReferenceHeadingsLoaded step 3 sends ReferenceRead from DocumentStorage to DocumentIndexService via ReferenceStorage reply-to 2. (XfmdDesktop.design, line 1116).
- f0803 — ReferenceHeadingsLoaded step 4 sends ParseReference from DocumentIndexService to Interpreter via ReferenceInterpretation. (XfmdDesktop.design, line 1117).
- f0804 — ReferenceHeadingsLoaded step 5 sends ReferenceParsed from Interpreter to DocumentIndexService via ReferenceInterpretation reply-to 4. (XfmdDesktop.design, line 1118).
- f0805 — ReferenceHeadingsLoaded step 6 sends CheckReferenceGeneration from DocumentIndexService to DocumentIndexService via IndexChanges. (XfmdDesktop.design, line 1119).
- f0806 — ReferenceHeadingsLoaded step 7 sends PublishReferenceHeadings from DocumentIndexService to NativeShell via IndexChanges. (XfmdDesktop.design, line 1120).
- f0807 — ReferenceInterpretation upholds ReferenceInterpretationContract. (XfmdDesktop.design, line 1121).
- f0808 — ReferenceInterpretationContract has completeness = closed. (XfmdDesktop.design, line 1122).
- f0809 — ReferenceInterpretationContract permits ParseReference. (XfmdDesktop.design, line 1123).
- f0810 — ReferenceInterpretationContract permits ReferenceParsed. (XfmdDesktop.design, line 1124).
- f0811 — ReferenceParsed has message-kind = result. (XfmdDesktop.design, line 1125).
- f0812 — ReferenceParsed replies-to ParseReference. (XfmdDesktop.design, line 1126).
- f0813 — ReferenceParsed upholds InteractionObservationShape. (XfmdDesktop.design, line 1127).
- f0814 — ReferenceRead has message-kind = result. (XfmdDesktop.design, line 1128).

- f0815 — ReferenceRead replies-to ReadReference. (XfmdDesktop.design, line 1129).
- f0816 — ReferenceRead upholds InteractionObservationShape. (XfmdDesktop.design, line 1130).
- f0817 — ReferenceStorage upholds ReferenceStorageContract. (XfmdDesktop.design, line 1131).
- f0818 — ReferenceStorageContract has completeness = closed. (XfmdDesktop.design, line 1132).
- f0819 — ReferenceStorageContract permits ReadReference. (XfmdDesktop.design, line 1133).
- f0820 — ReferenceStorageContract permits ReferenceRead. (XfmdDesktop.design, line 1134).
- f0821 — RegisteredProject has presence = required. (XfmdDesktop.design, line 1135).
- f0822 — RegisteredProject has value-type = text. (XfmdDesktop.design, line 1136).
- f0823 — RejectInvalidSelection has message-kind = event. (XfmdDesktop.design, line 1137).
- f0824 — RejectInvalidSelection upholds InteractionObservationShape. (XfmdDesktop.design, line 1138).
- f0825 — ReleaseKeyboardGrab has message-kind = event. (XfmdDesktop.design, line 1139).
- f0826 — ReleaseKeyboardGrab upholds InteractionObservationShape. (XfmdDesktop.design, line 1140).
- f0827 — ReleaseRetryAfterSendFailure exercises SelectGeneratedView. (XfmdDesktop.design, line 1141).
- f0828 — ReleaseRetryAfterSendFailure has completeness = closed. (XfmdDesktop.design, line 1142).
- f0829 — ReleaseRetryAfterSendFailure runs-in NormalDesktop. (XfmdDesktop.design, line 1143).
- f0830 — ReleaseRetryAfterSendFailure step 1 sends AttemptRelease from GeneratedViews to ExternalViewBroker via LeaseNotifications. (XfmdDesktop.design, line 1144).

- f0831 — ReleaseRetryAfterSendFailure step 2 sends KeepUnsentRelease from GeneratedViews to GeneratedViews via LeaseLifecycle. (XfmdDesktop.design, line 1145).
- f0832 — ReleaseRetryAfterSendFailure step 3 sends PollReleaseQueue from EventLoop to GeneratedViews via ScheduledWork. (XfmdDesktop.design, line 1146).
- f0833 — ReleaseRetryAfterSendFailure step 4 sends AttemptRelease from GeneratedViews to ExternalViewBroker via LeaseNotifications. (XfmdDesktop.design, line 1147).
- f0834 — ReleaseRetryAfterSendFailure step 5 sends RemoveSentRelease from GeneratedViews to GeneratedViews via LeaseLifecycle. (XfmdDesktop.design, line 1148).
- f0835 — RemoveSentRelease has message-kind = event. (XfmdDesktop.design, line 1149).
- f0836 — RemoveSentRelease upholds InteractionObservationShape. (XfmdDesktop.design, line 1150).
- f0837 — RenderLayout allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 1151).
- f0838 — RenderLayout contributes-to LivePreview. (XfmdDesktop.design, line 1152).
- f0839 — RenderLayout contributes-to MarkdownPresentation. (XfmdDesktop.design, line 1153).
- f0840 — RenderLayout contributes-to MermaidDiagrams. (XfmdDesktop.design, line 1154).
- f0841 — RenderLayout contributes-to PagedPublication. (XfmdDesktop.design, line 1155).
- f0842 — RenderLayout contributes-to SynchronizedScrolling. (XfmdDesktop.design, line 1156).
- f0843 — Renderer consumes TextMetricsPort. (XfmdDesktop.design, line 1157).
- f0844 — Renderer owns DiagramLayout. (XfmdDesktop.design, line 1158).
- f0845 — Renderer owns PageComposition. (XfmdDesktop.design, line 1159).
- f0846 — Renderer owns RenderLayout. (XfmdDesktop.design, line 1160).

- f0847 — Renderer uses DiagramLayoutCalls as receiver of LayoutTypedDiagram in mode NormalDesktop. (XfmdDesktop.design, line 1161).
- f0848 — Renderer uses DiagramLayoutCalls as sender of TypedDiagramLaidOut in mode NormalDesktop. (XfmdDesktop.design, line 1162).
- f0849 — Renderer uses ExportLayout as receiver of LayoutExportPages in mode NormalDesktop. (XfmdDesktop.design, line 1163).
- f0850 — Renderer uses ExportLayout as sender of ExportPagesLaidOut in mode NormalDesktop. (XfmdDesktop.design, line 1164).
- f0851 — Renderer uses LayoutCalls as receiver of LayoutModel in mode NormalDesktop. (XfmdDesktop.design, line 1165).
- f0852 — Renderer uses LayoutCalls as sender of ModelLaidOut in mode NormalDesktop. (XfmdDesktop.design, line 1166).
- f0853 — ReplaceDocument has message-kind = event. (XfmdDesktop.design, line 1167).
- f0854 — ReplaceDocument upholds InteractionObservationShape. (XfmdDesktop.design, line 1168).
- f0855 — RequestPdfExport has message-kind = event. (XfmdDesktop.design, line 1169).
- f0856 — RequestPdfExport upholds InteractionObservationShape. (XfmdDesktop.design, line 1170).
- f0857 — RequestTreeRefresh has message-kind = event. (XfmdDesktop.design, line 1171).
- f0858 — RequestTreeRefresh upholds InteractionObservationShape. (XfmdDesktop.design, line 1172).
- f0859 — ResourcePreparation upholds ResourcePreparationContract. (XfmdDesktop.design, line 1173).
- f0860 — ResourcePreparationContract has completeness = closed. (XfmdDesktop.design, line 1174).
- f0861 — ResourcePreparationContract permits CacheCompatibleScene. (XfmdDesktop.design, line 1175).
- f0862 — ResourcePreparationContract permits PrepareDiagramScenes. (XfmdDesktop.design, line 1176).

- f0863 — ResourcePreparationContract permits PrepareEmbeddedResources. (XfmdDesktop.design, line 1177).
- f0864 — ResourcePreparationContract permits PrepareExportResources. (XfmdDesktop.design, line 1178).
- f0865 — ResourcePreparationContract permits PrepareTypedDiagram. (XfmdDesktop.design, line 1179).
- f0866 — RestartDebounce has message-kind = event. (XfmdDesktop.design, line 1180).
- f0867 — RestartDebounce upholds InteractionObservationShape. (XfmdDesktop.design, line 1181).
- f0868 — RetainDocumentAndAnchor has message-kind = event. (XfmdDesktop.design, line 1182).
- f0869 — RetainDocumentAndAnchor upholds InteractionObservationShape. (XfmdDesktop.design, line 1183).
- f0870 — SaveThenReadFails exercises NavigateDocuments. (XfmdDesktop.design, line 1184).
- f0871 — SaveThenReadFails has completeness = closed. (XfmdDesktop.design, line 1185).
- f0872 — SaveThenReadFails runs-in NormalDesktop. (XfmdDesktop.design, line 1186).
- f0873 — SaveThenReadFails step 1 sends AdmitDocument from Navigation to Documents via DocumentCalls. (XfmdDesktop.design, line 1187).
- f0874 — SaveThenReadFails step 2 sends ChooseUnsaved from Documents to NativeShell via UnsavedAdmission. (XfmdDesktop.design, line 1188).
- f0875 — SaveThenReadFails step 3 sends ChooseSave from NativeShell to Documents via UnsavedAdmission reply-to 2. (XfmdDesktop.design, line 1189).
- f0876 — SaveThenReadFails step 4 sends WriteCurrent from Documents to DocumentStorage via StorageCalls. (XfmdDesktop.design, line 1190).
- f0877 — SaveThenReadFails step 5 sends CurrentWritten from DocumentStorage to Documents via StorageCalls reply-to 4. (XfmdDesktop.design, line 1191).
- f0878 — SaveThenReadFails step 6 sends MarkCurrentSaved from Documents to Documents via DocumentStateChanges. (XfmdDesktop.design, line 1192).

- f0879 — SaveThenReadFails step 7 sends ReadCandidate from Documents to DocumentStorage via StorageCalls. (XfmdDesktop.design, line 1193).
- f0880 — SaveThenReadFails step 8 sends CandidateReadFailed from DocumentStorage to Documents via StorageCalls reply-to 7. (XfmdDesktop.design, line 1194).
- f0881 — SaveThenReadFails step 9 sends DocumentRejected from Documents to Navigation via DocumentCalls reply-to 1. (XfmdDesktop.design, line 1195).
- f0882 — SavedBaselineBytes has presence = required. (XfmdDesktop.design, line 1196).
- f0883 — SavedBaselineBytes has value-type = bytes. (XfmdDesktop.design, line 1197).
- f0884 — ScheduledWork upholds ScheduledWorkContract. (XfmdDesktop.design, line 1198).
- f0885 — ScheduledWorkContract has completeness = closed. (XfmdDesktop.design, line 1199).
- f0886 — ScheduledWorkContract permits DebounceElapsed. (XfmdDesktop.design, line 1200).
- f0887 — ScheduledWorkContract permits PollReleaseQueue. (XfmdDesktop.design, line 1201).
- f0888 — ScheduledWorkContract permits RestartDebounce. (XfmdDesktop.design, line 1202).
- f0889 — ScrollMotion allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 1203).
- f0890 — ScrollMotion contributes-to ConfigurableScrolling. (XfmdDesktop.design, line 1204).
- f0891 — ScrollMotion contributes-to SynchronizedScrolling. (XfmdDesktop.design, line 1205).
- f0892 — SdpProjectNavigation allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 1206).
- f0893 — SdpProjectNavigation contributes-to BrowseSdpProject. (XfmdDesktop.design, line 1207).
- f0894 — SdpProjects consumes SchedulerPort. (XfmdDesktop.design, line 1208).

- f0895 — SdpProjects consumes SdpToolProtocol. (XfmdDesktop.design, line 1209).
- f0896 — SdpProjects owns SdpProjectNavigation. (XfmdDesktop.design, line 1210).
- f0897 — SelectInvalidView has message-kind = event. (XfmdDesktop.design, line 1211).
- f0898 — SelectInvalidView upholds InteractionObservationShape. (XfmdDesktop.design, line 1212).
- f0899 — SelectRegisteredView has message-kind = event. (XfmdDesktop.design, line 1213).
- f0900 — SelectRegisteredView upholds InteractionObservationShape. (XfmdDesktop.design, line 1214).
- f0901 — SetChosenParentRoot has message-kind = event. (XfmdDesktop.design, line 1215).
- f0902 — SetChosenParentRoot upholds InteractionObservationShape. (XfmdDesktop.design, line 1216).
- f0903 — SetEditorAnchor has message-kind = event. (XfmdDesktop.design, line 1217).
- f0904 — SetEditorAnchor upholds InteractionObservationShape. (XfmdDesktop.design, line 1218).
- f0905 — ShowDirtyRejection has message-kind = event. (XfmdDesktop.design, line 1219).
- f0906 — ShowDirtyRejection upholds InteractionObservationShape. (XfmdDesktop.design, line 1220).
- f0907 — SourceAnchorMapping allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 1221).
- f0908 — SourceAnchorMapping contributes-to ChapterNavigation. (XfmdDesktop.design, line 1222).
- f0909 — SourceAnchorMapping contributes-to ConfigurableScrolling. (XfmdDesktop.design, line 1223).
- f0910 — SourceAnchorMapping contributes-to DocumentNavigation. (XfmdDesktop.design, line 1224).

- f0911 — SourceAnchorMapping contributes-to DocumentReferences. (XfmdDesktop.design, line 1225).
- f0912 — SourceAnchorMapping contributes-to PagedPublication. (XfmdDesktop.design, line 1226).
- f0913 — SourceAnchorMapping contributes-to SynchronizedScrolling. (XfmdDesktop.design, line 1227).
- f0914 — StalePreviewDiscarded exercises EditDocuments. (XfmdDesktop.design, line 1228).
- f0915 — StalePreviewDiscarded has completeness = closed. (XfmdDesktop.design, line 1229).
- f0916 — StalePreviewDiscarded runs-in NormalDesktop. (XfmdDesktop.design, line 1230).
- f0917 — StalePreviewDiscarded step 1 sends CompleteObsoleteWorker from Preview to Preview via PreviewAdmission. (XfmdDesktop.design, line 1231).
- f0918 — StalePreviewDiscarded step 2 sends DiscardObsoleteCompletion from Preview to Preview via PreviewAdmission. (XfmdDesktop.design, line 1232).
- f0919 — StartGeneration has message-kind = event. (XfmdDesktop.design, line 1233).
- f0920 — StartGeneration upholds InteractionObservationShape. (XfmdDesktop.design, line 1234).
- f0921 — StorageCalls upholds StorageCallsContract. (XfmdDesktop.design, line 1235).
- f0922 — StorageCallsContract has completeness = closed. (XfmdDesktop.design, line 1236).
- f0923 — StorageCallsContract permits CandidateRead. (XfmdDesktop.design, line 1237).
- f0924 — StorageCallsContract permits CandidateReadFailed. (XfmdDesktop.design, line 1238).
- f0925 — StorageCallsContract permits CurrentWritten. (XfmdDesktop.design, line 1239).
- f0926 — StorageCallsContract permits ReadCandidate. (XfmdDesktop.design, line 1240).

- f0927 — StorageCallsContract permits WriteCurrent. (XfmdDesktop.design, line 1241).
- f0928 — SynchronizedScrolling supports ScrollDocuments. (XfmdDesktop.design, line 1242).
- f0929 — TargetOpened has message-kind = result. (XfmdDesktop.design, line 1243).
- f0930 — TargetOpened replies-to OpenTarget. (XfmdDesktop.design, line 1244).
- f0931 — TargetOpened upholds InteractionObservationShape. (XfmdDesktop.design, line 1245).
- f0932 — TargetPane has presence = required. (XfmdDesktop.design, line 1246).
- f0933 — TargetPane has value-type = text. (XfmdDesktop.design, line 1247).
- f0934 — TargetWindow has presence = required. (XfmdDesktop.design, line 1248).
- f0935 — TargetWindow has value-type = text. (XfmdDesktop.design, line 1249).
- f0936 — TextEditing allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 1250).
- f0937 — TextEditing contributes-to ConfigurableScrolling. (XfmdDesktop.design, line 1251).
- f0938 — TextEditing contributes-to LivePreview. (XfmdDesktop.design, line 1252).
- f0939 — ToggleFullscreen has message-kind = event. (XfmdDesktop.design, line 1253).
- f0940 — ToggleFullscreen upholds InteractionObservationShape. (XfmdDesktop.design, line 1254).
- f0941 — TypedDiagramLaidOut has message-kind = result. (XfmdDesktop.design, line 1255).
- f0942 — TypedDiagramLaidOut replies-to LayoutTypedDiagram. (XfmdDesktop.design, line 1256).
- f0943 — TypedDiagramLaidOut upholds InteractionObservationShape. (XfmdDesktop.design, line 1257).
- f0944 — Typography owns TypographyAndDrawing. (XfmdDesktop.design, line 1258).

- f0945 — Typography uses PublicationDrawing as receiver of PaintPdfCandidate in mode NormalDesktop. (XfmdDesktop.design, line 1259).
- f0946 — TypographyAndDrawing allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 1260).
- f0947 — TypographyAndDrawing contributes-to MarkdownPresentation. (XfmdDesktop.design, line 1261).
- f0948 — TypographyAndDrawing contributes-to MermaidDiagrams. (XfmdDesktop.design, line 1262).
- f0949 — TypographyAndDrawing contributes-to PagedPublication. (XfmdDesktop.design, line 1263).
- f0950 — UnsavedAdmission upholds UnsavedAdmissionContract. (XfmdDesktop.design, line 1264).
- f0951 — UnsavedAdmissionContract has completeness = closed. (XfmdDesktop.design, line 1265).
- f0952 — UnsavedAdmissionContract permits ChooseCancel. (XfmdDesktop.design, line 1266).
- f0953 — UnsavedAdmissionContract permits ChooseSave. (XfmdDesktop.design, line 1267).
- f0954 — UnsavedAdmissionContract permits ChooseUnsaved. (XfmdDesktop.design, line 1268).
- f0955 — UserPreviewScroll has message-kind = event. (XfmdDesktop.design, line 1269).
- f0956 — UserPreviewScroll upholds InteractionObservationShape. (XfmdDesktop.design, line 1270).
- f0957 — ValidatePreferencesDraft has message-kind = event. (XfmdDesktop.design, line 1271).
- f0958 — ValidatePreferencesDraft upholds InteractionObservationShape. (XfmdDesktop.design, line 1272).
- f0959 — ValidateProposedRoot has message-kind = event. (XfmdDesktop.design, line 1273).
- f0960 — ValidateProposedRoot upholds InteractionObservationShape. (XfmdDesktop.design, line 1274).

- f0961 — ValidateSelection has message-kind = event. (XfmdDesktop.design, line 1275).
- f0962 — ValidateSelection upholds InteractionObservationShape. (XfmdDesktop.design, line 1276).
- f0963 — Viewport consumes RenderHostPort. (XfmdDesktop.design, line 1277).
- f0964 — Viewport consumes SchedulerPort. (XfmdDesktop.design, line 1278).
- f0965 — Viewport owns ScrollMotion. (XfmdDesktop.design, line 1279).
- f0966 — Viewport owns SourceAnchorMapping. (XfmdDesktop.design, line 1280).
- f0967 — Viewport uses ViewportChanges as receiver of CheckCurrentMapping in mode NormalDesktop. (XfmdDesktop.design, line 1281).
- f0968 — Viewport uses ViewportChanges as receiver of MapSourceAnchor in mode NormalDesktop. (XfmdDesktop.design, line 1282).
- f0969 — Viewport uses ViewportChanges as receiver of RetainDocumentAndAnchor in mode NormalDesktop. (XfmdDesktop.design, line 1283).
- f0970 — Viewport uses ViewportChanges as receiver of UserPreviewScroll in mode NormalDesktop. (XfmdDesktop.design, line 1284).
- f0971 — Viewport uses ViewportChanges as sender of CheckCurrentMapping in mode NormalDesktop. (XfmdDesktop.design, line 1285).
- f0972 — Viewport uses ViewportChanges as sender of MapSourceAnchor in mode NormalDesktop. (XfmdDesktop.design, line 1286).
- f0973 — Viewport uses ViewportChanges as sender of SetEditorAnchor in mode NormalDesktop. (XfmdDesktop.design, line 1287).
- f0974 — ViewportChanges upholds ViewportChangesContract. (XfmdDesktop.design, line 1288).
- f0975 — ViewportChangesContract has completeness = closed. (XfmdDesktop.design, line 1289).
- f0976 — ViewportChangesContract permits CheckCurrentMapping. (XfmdDesktop.design, line 1290).
- f0977 — ViewportChangesContract permits MapSourceAnchor. (XfmdDesktop.design, line 1291).

- f0978 — ViewportChangesContract permits RetainDocumentAndAnchor. (XfmdDesktop.design, line 1292).
- f0979 — ViewportChangesContract permits SetEditorAnchor. (XfmdDesktop.design, line 1293).
- f0980 — ViewportChangesContract permits UserPreviewScroll. (XfmdDesktop.design, line 1294).
- f0981 — VisualResources consumes DiagramLayoutPort. (XfmdDesktop.design, line 1295).
- f0982 — VisualResources consumes TextMetricsPort. (XfmdDesktop.design, line 1296).
- f0983 — VisualResources owns DiagramPreparation. (XfmdDesktop.design, line 1297).
- f0984 — VisualResources owns EmbeddedVisuals. (XfmdDesktop.design, line 1298).
- f0985 — VisualResources uses DiagramLayoutCalls as receiver of TypedDiagramLaidOut in mode NormalDesktop. (XfmdDesktop.design, line 1299).
- f0986 — VisualResources uses DiagramLayoutCalls as sender of LayoutTypedDiagram in mode NormalDesktop. (XfmdDesktop.design, line 1300).
- f0987 — VisualResources uses ResourcePreparation as receiver of CacheCompatibleScene in mode NormalDesktop. (XfmdDesktop.design, line 1301).
- f0988 — VisualResources uses ResourcePreparation as receiver of PrepareDiagramScenes in mode NormalDesktop. (XfmdDesktop.design, line 1302).
- f0989 — VisualResources uses ResourcePreparation as receiver of PrepareEmbeddedResources in mode NormalDesktop. (XfmdDesktop.design, line 1303).
- f0990 — VisualResources uses ResourcePreparation as receiver of PrepareExportResources in mode NormalDesktop. (XfmdDesktop.design, line 1304).
- f0991 — VisualResources uses ResourcePreparation as receiver of PrepareTypedDiagram in mode NormalDesktop. (XfmdDesktop.design, line 1305).

- f0992 — VisualResources uses ResourcePreparation as sender of CacheCompatibleScene in mode NormalDesktop. (XfmdDesktop.design, line 1306).
- f0993 — WindowPresentation upholds WindowPresentationContract. (XfmdDesktop.design, line 1307).
- f0994 — WindowPresentationContract has completeness = closed. (XfmdDesktop.design, line 1308).
- f0995 — WindowPresentationContract permits ToggleFullscreen. (XfmdDesktop.design, line 1309).
- f0996 — WorkPathHistory allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 1310).
- f0997 — WorkPathHistory contributes-to WorkPathNavigation. (XfmdDesktop.design, line 1311).
- f0998 — WorkPathNavigation supports BrowseWorkspace. (XfmdDesktop.design, line 1312).
- f0999 — Workspace owns FilteredFileTree. (XfmdDesktop.design, line 1313).
- f1000 — Workspace owns WorkPathHistory. (XfmdDesktop.design, line 1314).
- f1001 — Workspace uses WorkspaceChanges as receiver of ActivateRootAndHistory in mode NormalDesktop. (XfmdDesktop.design, line 1315).
- f1002 — Workspace uses WorkspaceChanges as receiver of SetChosenParentRoot in mode NormalDesktop. (XfmdDesktop.design, line 1316).
- f1003 — Workspace uses WorkspaceChanges as receiver of ValidateProposedRoot in mode NormalDesktop. (XfmdDesktop.design, line 1317).
- f1004 — Workspace uses WorkspaceChanges as sender of ActivateRootAndHistory in mode NormalDesktop. (XfmdDesktop.design, line 1318).
- f1005 — Workspace uses WorkspaceChanges as sender of RequestTreeRefresh in mode NormalDesktop. (XfmdDesktop.design, line 1319).
- f1006 — Workspace uses WorkspaceIntents as receiver of FavoriteFolderChosen in mode NormalDesktop. (XfmdDesktop.design, line 1320).

- f1007 — WorkspaceChanges upholds WorkspaceChangesContract. (XfmdDesktop.design, line 1321).
- f1008 — WorkspaceChangesContract has completeness = closed. (XfmdDesktop.design, line 1322).
- f1009 — WorkspaceChangesContract permits ActivateRootAndHistory. (XfmdDesktop.design, line 1323).
- f1010 — WorkspaceChangesContract permits RequestTreeRefresh. (XfmdDesktop.design, line 1324).
- f1011 — WorkspaceChangesContract permits SetChosenParentRoot. (XfmdDesktop.design, line 1325).
- f1012 — WorkspaceChangesContract permits ValidateProposedRoot. (XfmdDesktop.design, line 1326).
- f1013 — WorkspaceControls allocated-to XfmdDesktop in mode NormalDesktop. (XfmdDesktop.design, line 1327).
- f1014 — WorkspaceControls contributes-to ChapterNavigation. (XfmdDesktop.design, line 1328).
- f1015 — WorkspaceControls contributes-to ConfigurableScrolling. (XfmdDesktop.design, line 1329).
- f1016 — WorkspaceControls contributes-to DocumentNavigation. (XfmdDesktop.design, line 1330).
- f1017 — WorkspaceControls contributes-to DocumentReferences. (XfmdDesktop.design, line 1331).
- f1018 — WorkspaceControls contributes-to MarkdownPresentation. (XfmdDesktop.design, line 1332).
- f1019 — WorkspaceControls contributes-to PagedPublication. (XfmdDesktop.design, line 1333).
- f1020 — WorkspaceControls contributes-to SynchronizedScrolling. (XfmdDesktop.design, line 1334).
- f1021 — WorkspaceControls contributes-to UseFullscreen. (XfmdDesktop.design, line 1335).
- f1022 — WorkspaceControls contributes-to WorkPathNavigation. (XfmdDesktop.design, line 1336).

- f1023 — WorkspaceIntents upholds WorkspaceIntentsContract. (XfmdDesktop.design, line 1337).
- f1024 — WorkspaceIntentsContract has completeness = closed. (XfmdDesktop.design, line 1338).
- f1025 — WorkspaceIntentsContract permits ActivateExternalTarget. (XfmdDesktop.design, line 1339).
- f1026 — WorkspaceIntentsContract permits ChooseInternalFile. (XfmdDesktop.design, line 1340).
- f1027 — WorkspaceIntentsContract permits FavoriteFileChosen. (XfmdDesktop.design, line 1341).
- f1028 — WorkspaceIntentsContract permits FavoriteFolderChosen. (XfmdDesktop.design, line 1342).
- f1029 — WriteCurrent has message-kind = request. (XfmdDesktop.design, line 1343).
- f1030 — WriteCurrent upholds InteractionObservationShape. (XfmdDesktop.design, line 1344).
- f1031 — XfmdDesktop contains Application. (XfmdDesktop.design, line 1345).
- f1032 — XfmdDesktop contains Interpreter. (XfmdDesktop.design, line 1346).
- f1033 — XfmdDesktop contains Renderer. (XfmdDesktop.design, line 1347).