

version: '3.8'

services:

--- 1. 관리자 포털 (PHP로 변경) ---

admin_entry:

image: php:7.4-apache

container_name: admin_entry

ports:

- "8003:80"

volumes:

- ./admin_src:/var/www/html # PHP 기본 경로로 변경

networks:

sme_internal_network:

ipv4_address: 192.168.20.40

--- 2. A 고객사 (OWASP Juice Shop) ---

client_a_owasp:

build:

context: ./client_a_juice_src

container_name: client_a_OWASP

ports:

- "8000:3000"

networks:

sme_internal_network:

ipv4_address: 192.168.20.10

--- 3. B 고객사 (DVWA) --

client_b_dvwa:

image: sagikazarmark/dvwa

container_name: client_b_dvwa

ports:

- "8001:80"

volumes:

- ./dvwa_src:/var/www/html

networks:

sme_internal_network:

ipv4_address: 192.168.20.20

--- 4. C 고객사 (bWAPP) ---

client_c_bwapp:

```
image: raesene/bwapp
container_name: client_c_bwapp
ports:
  - "8002:80"
volumes:
  - ./bwapp_src:/app
networks:
  sme_internal_network:
    ipv4_address: 192.168.20.30
```

--- 5. 암호키 서버 (최종 목표) ---

```
key_vault_server:
  image: hashicorp/vault:latest
  container_name: key_vault_server
  ports:
    - "8200:8200"
  environment:
```

- 'VAULT_DEV_ROOT_TOKEN_ID=my_root_token' # [보안취약점] KISA 가이드의 취약한 기본 인증 (Source: 8470)

```
  - 'VAULT_ADDR=http://127.0.0.1:8200'
  cap_add:
    - IPC_LOCK
  networks:
    sme_internal_network:
      ipv4_address: 192.168.20.50
```

```
networks:
  sme_internal_network:
    driver: bridge
    ipam:
      config:
        - subnet: 192.168.20.0/24
```