

Inmp 搭建 Nginx1.12.1; mysql5.6; php7.2

1、安装依赖

```
1 yum install gcc bison bison-devel zlib-devel libmcrypt-devel mcrypt mhash-  
devel openssl-devel libxml2-devel libcurl-devel bzip2-devel readline-devel  
libedit-devel sqlite-devel libpng-devel libjpeg-devel freetype freetype-devel
```

2、nginx

```
1 [nginx]  
2 name=nginx repo  
3 baseurl=http://nginx.org/packages/centos/6/$basearch/  
4 gpgcheck=0  
5 enabled=1  
6  
7 yum install nginx -y
```

2、php

```
1 rpm -Uvh http://ftp.iij.ad.jp/pub/linux/fedora/epel/6/x86_64/epel-release-6-  
8.noarch.rpm  
2 rpm -Uvh http://rpms.famillecollet.com/enterprise/remi-release-6.rpm  
3  
4 yum -y install --enablerepo=remi --enablerepo=remi-php56 php php-bcmath php-  
opcache php-devel php-mbstring php-mcrypt php-mysqlnd php-gd php-xml php-  
memcache php-redis php-fpm php-mysql php-common php-mssql  
5  
6 vim /etc/php.ini  
7 expose_php = Off #关闭phpxini  
8  
9 service php-fpm restart #启动php  
10 chkconfig php-fpm --level 2345 on #设置开机启动
```

3、mysql

```
1 [mysql56-community]  
2 name=MySQL 5.6 Community Server
```

```
3 baseurl=http://repo.mysql.com/yum/mysql-5.6-community/el/6/$basearch/
4 gpgcheck=0
5 enabled=0
6
7 yum -y install mysql-community-client mysql-community-devel mysql-community-
server
8
9 GRANT ALL PRIVILEGES ON *.* TO 'root'@'%' IDENTIFIED BY '123456' WITH GRANT
OPTION;
10 flush privileges;
```

4、download zabbix

```
1 wget -O zabbix-3.4.2.tar.gz
http://sourceforge.net/projects/zabbix/files/ZABBIX%20Latest%20Stable/3.4.2/zab
bbix-3.4.2.tar.gz/download
2
3 wget http://repo.zabbix.com/zabbix/3.4/rhel/6/x86_64/zabbix-get-3.4.4-
2.el6.x86_64.rpm
4 yum install -y zabbix-get-3.4.4-2.el6.x86_64.rpm
```

5、create database

```
1 CREATE DATABASE zabbix DEFAULT CHARACTER SET utf8mb4 COLLATE
utf8mb4_general_ci;
2 CREATE USER 'zabbix'@'%' IDENTIFIED BY '123456';
3 grant all privileges on zabbix.* to zabbix@localhost identified by '123456';
4
5 mysql> use zabbix;
6 mysql> source /home/bfxy/soft/zabbix-3.4.2/database/mysql/schema.sql;
7 mysql> source /home/bfxy/soft/zabbix-3.4.2/database/mysql/data.sql;
8 mysql> source /home/bfxy/soft/zabbix-3.4.2/database/mysql/images.sql;
9 mysql> quit
```

6、编译zabbix

```
1 yum install -y net-snmp net-snmp-devel curl curl-devel mysql-devel libevent-
devel pcre-devel
2
3 ./configure --prefix=/home/bfxy/servers/zabbix --with-mysql --with-net-snmp --
```

```
4 with-libcurl --enable-server --enable-agent --enable-proxy
5 make && make install
```

7、zabbix_agent.conf

```
1 LogFile=/home/bfxy/logs/zabbix_agentd.log
2 Server=127.0.0.1
3 ServerActive=127.0.0.1
4 Hostname=Zabbix server
```

8、zabbix_server.conf

```
1 LogFile=/home/bfxy/logs/zabbix_server.log
2 DBName=zabbix
3 DBUser=zabbix
4 DBHost=localhost
5 DBPassword=123456
6 AlertScriptsPath=/home/bfxy/servers/zabbix/alertscript
```

9、php.ini

```
1 sudo sed -i 's/post_max_size = 8M/post_max_size = 32M/g' /etc/php.ini
2 sudo sed -i 's/upload_max_filesize = 2M/upload_max_filesize = 50M/g'
   /etc/php.ini
3 sudo sed -i 's;/date.timezone =/date.timezone =PRC/' /etc/php.ini
4 sudo sed -i 's/max_execution_time = 30/max_execution_time = 600/g'
   /etc/php.ini
5 sudo sed -i 's/max_input_time = 60/max_input_time = 600/g' /etc/php.ini
6 sudo sed -i 's/memory_limit = 128M/memory_limit = 256M/g' /etc/php.ini
7
8 #vim /usr/local/php/etc/php.ini
9 cgi.fix_pathinfo=1
10
11 /etc/init.d/php-fpm restart
12
13 vim /etc/ld.so.conf
14 /usr/lib64/mysql
15 ldconfig
```

10、复制php页面,并设置权限

```
1 cp -rf /home/bfxy/soft/zabbix-3.4.2/frontends/php/ /www/php
2 #chown www.www -R /www/php/
```

11、nginx

```
1 server {
2     listen      80;
3     server_name localhost;
4
5     #charset koi8-r;
6     #access_log /var/log/nginx/host.access.log  main;
7     root /home/bfxy/servers/zabbix/php
8     index index.php index.html index.htm
9     location / {
10         if (!-e $request_filename) {
11             rewrite ^(.*)$ /index.php/$1 last;
12             break;
13         }
14     }
15
16     location ~ /\.php {
17         fastcgi_pass 127.0.0.1:9000;
18         fastcgi_index index.php;
19         include fastcgi_params;
20         set $real_script_name $fastcgi_script_name;
21         if ($fastcgi_script_name ~ "^(.+?\\.php)(/.+)$") {
22             set $real_script_name $1;
23             set $path_info $2;
24         }
25         fastcgi_param SCRIPT_FILENAME $document_root$real_script_name;
26         fastcgi_param SCRIPT_NAME $real_script_name;
27         fastcgi_param PATH_INFO $path_info;
28     }
29 }
```

12、开启中文

```
1 #vim /usr/local/zabbix/php/include/locales.inc.php
2 'zh_CN' => ['name' => _('Chinese (zh_CN)'), 'display' => true],
3 #/etc/init.d/php-fpm restart
```

```
sudo setfacl -R -m u:nginx:rwx /var/lib/php
```

```
zabbix-agent
```