


DSA Data Structures Algorithms Interview Preparation Data Science Topic-wise Practice C C++

# **Handling Categorical Data in Python**

Save Article





Categorical data is a set of predefined categories or groups an observation can fall into. Categorical data can be found everywhere. For instance, survey responses like marital status, profession, educational qualifications, etc. However, certain problems can arise with categorical data that must be dealt with before proceeding with any other task. This article discusses various methods to handle categorical data. So, let us take a look at some problems posed by categorical data and how to handle them.

As mentioned earlier, categorical data can only take up a finite set of values. However, due to human error, while filling out a survey form, or any other reason, some bogus values could be found in the dataset.

## **Importing Libraries**

<u>Python</u> libraries make it very easy for us to handle the data and perform typical and complex tasks with a single line of code.

- <u>Pandas</u> This library helps to load the data frame in a 2D array format and has multiple functions to perform analysis tasks in one go.
- <u>Numpy</u> Numpy arrays are very fast and can perform large computations in a very short time.
- Matplotlib/Seaborn This library is used to draw visualizations.
- Sklearn This module contains multiple libraries having pre-implemented functions to perform tasks from data preprocessing to model development and evaluation.

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sb

from sklearn.preprocessing import LabelEncoder
```

Now let's load the dataset into the pandas dataframe.

# Python3

```
main_data = pd.read_csv('demographics.csv')
main_data.head()
```

#### **Output:**

	first_name	last_name	blood_type	marriage_status	income	device
0	Abdul	Colon	A+	married	145000	AndroidOS
1	Abdul	Pierce	B+	married	85000	MacOS
2	Desirae	Pierce	B+	MARRIED	130000	iOS
3	Shannon	Gibson	A+	married	175000	MacOS
4	Desirae	Little	B+	unmarried	130000	MacOS

First five rows of the dataset

To understand membership constraints, consider the feature, and blood type. We need to verify whether the blood type feature consists of bogus values or not. First, we need to create a data frame with all possible values of blood type that are valid.

```
# create a new dataframe with possible values for blood type
blood_type_categories = pd.DataFrame({
    'blood_type': ['A+', 'A-', 'B+', 'B-', 'AB+', 'AB-', 'O+', 'O-']
})
blood_type_categories
```



Now, the bogus values can be found using the difference method.

## Python3

```
# finding bogus categories
unique_blood_types_main = set(main_data['blood_type'])
bogus_blood_types = unique_blood_types_main.difference(
    blood_type_categories['blood_type']
)
bogus_blood_types
```

Once the bogus values are found, the corresponding rows can be dropped from the dataset. In some scenarios, the values could be replaced with other values if there is information available. However, since there is no information available regarding the true blood type, they will be dropped.

## Python3

```
# extracting records with bogus blood types
bogus_records_index = main_data['blood_type'].isin(bogus_blood_types)
# drop the records with bogus blood types
without_bogus_records = main_data[~bogus_records_index]
without_bogus_records['blood_type'].unique()
```

### **Output:**

```
array(['A+', 'B+', 'A-', 'AB-', 'AB+', 'B-', 'O-', 'O+'], dtype=object)
```

#### **Inconsistent Categories**

Inconsistencies could arise in categorical data quite often. Consider the feature, marriage status. Let us take a look at all the unique values of marital status.

## Python3

```
# exploring inconsistencies in marriage status category
main_data['marriage_status'].unique()
```

#### **Output:**

It is quite evident that there are redundant categories due to leading and trailing spaces as well as capital letters. First, let us deal with capital letters.

```
# removing values with capital letters
inconsistent_data = main_data.copy()
inconsistent_data['marriage_status'] = inconsistent_data['marriage_status']\
    .str.lower()
inconsistent_data['marriage_status'].unique()
```

Next, we will deal with leading and trailing spaces.

## Python3

```
inconsistent_data['marriage_status'] = inconsistent_data['marriage_status']\
    .str.strip()
inconsistent_data['marriage_status'].unique()
```

#### **Output:**

```
array(['married', 'unmarried', 'divorced', 'separated'], dtype=object)
```

### **Remapping Categories**

Numerical data like age or income can be mapped to different groups. This helps in getting more insights about the dataset. Let us explore the income feature.

## Python3

#### **Output:**

```
Max income - 190000, Min income - 40000
```

Now, let us create the range and labels for the income feature. Pandas' <u>cut</u> method is used to achieve this.

	first_name	last_name	blood_type	marriage_status	income	device	income_groups
0	Abdul	Colon	A+	married	145000	AndroidOS	125k-150k
1	Abdul	Pierce	B+	married	85000	MacOS	75k-100k
2	Desirae	Pierce	B+	MARRIED	130000	iOS	125k-150k
3	Shannon	Gibson	A+	married	175000	MacOS	150k+
4	Desirae	Little	B+	unmarried	130000	MacOS	125k-150k


First five rows of the dataset.

Now, it is easier to visualize the distribution.

# Python3

```
remapping_data['income_groups'].value_counts().plot.bar()
```

### **Output:**



Barplot for the count of each income category

## **Cleaning Categorical Data**

To understand this problem, a new data frame with just one feature, phone numbers are created.


```
phone_numbers = []
```

```
for i in range(100):
    # phone numbers could be of length 9 or 10
    number = random.randint(100000000, 9999999999)

# +91 code is inserted in some cases
    if(i % 2 == 0):
        phone_numbers.append('+91 ' + str(number))
    else:
        phone_numbers.append(str(number))

phone_numbers_data = pd.DataFrame({
        'phone_numbers': phone_numbers
})

phone_numbers_data.head()
```



Based on the use case, the code before numbers could be dropped or added for missing ones. Similarly, phone numbers with less than 10 numbers should be discarded.

## Python3

```
phone_numbers_data['phone_numbers'] = phone_numbers_data['phone_numbers']\
    .str.replace('\+91 ', '')

num_digits = phone_numbers_data['phone_numbers'].str.len()
invalid_numbers_index = phone_numbers_data[num_digits < 10].index
phone_numbers_data['phone_numbers'] = phone_numbers_data.drop(
    invalid_numbers_index)
phone_numbers_data = phone_numbers_data.dropna()</pre>
```

ı	phone_numbers
0	5377617628
2	7152234401
3	2839400071
4	7651215019
5	4451571165

Finally, we can verify whether the data is clean or not.


## Python3

```
assert phone_numbers_data['phone_numbers'].str.contains('\+91 ').all() == False
assert (phone_numbers_data['phone_numbers'].str.len() != 10).all() == False
```

# **Visualizing Categorical Data**

Various plots could be used to visualize categorical data to get more insights about the data. So, let us visualize the number of people belonging to each blood type. We will make use of the seaborn library to achieve this.


# Python3



Countplot for blood\_type category

Furthermore, we can see the relationship between income and the marital status of a person using a <u>boxplot</u>.

# Python3



### **Encoding Categorical Data**

Certain learning algorithms like regression and neural networks require their input to be numbers. Hence, categorical data must be converted to numbers to use these algorithms. Let us take a look at some encoding methods.

#### **Label Encoding**

With <u>label encoding</u>, we can number the categories from 0 to num\_categories – 1. Let us apply label encoding on the blood type feature.

## Python3

```
le = LabelEncoder()
without_bogus_records['blood_type'] = le.fit_transform(
    without_bogus_records['blood_type'])
without_bogus_records['blood_type'].unique()
```

#### **Output:**

```
array([0, 4, 1, 3, 2, 5, 7, 6])
```

### **One-hot Encoding**

There are certain limitations of label encoding that are taken care of by one-hot encoding.

## Python3



### **Ordinal Encoding**

Categorical data can be ordinal, where the order is of importance. For such features, we want to preserve the order after encoding as well. We will perform ordinal encoding on income groups. We want to preserve the order as 40K-75K < 75K-100K < 100K-125K < 125K-150K < 150K+

## Python3

#### **Output:**

	first_name	last_name	blood_type	marriage_status	income	device	income_groups
0	Abdul	Colon	A+	married	145000	AndroidOS	4
1	Abdul	Pierce	B+	married	85000	MacOS	2
2	Desirae	Pierce	B+	MARRIED	130000	iOS	4
3	Shannon	Gibson	A+	married	175000	MacOS	5
4	Desirae	Little	B+	unmarried	130000	MacOS	4

Similarly, different encodings can be applied according to the use case.

### **Related Articles**

- 1. Handling Categorical Data with Bokeh Python
- 2. How to convert categorical data to binary data in Python?
- 3. How to convert categorical string data into numeric in Python?
- 4. Exploring Categorical Data
- 5. Pandas Filling NaN in Categorical data

- 6. ML | One Hot Encoding to treat Categorical data parameters
- 7. Python | Pandas.Categorical()
- 8. Python | Pandas Categorical DataFrame creation
- 9. Python Categorical Encoding using Sunbird
- 10. How to handle missing values of categorical variables in Python?

Previous

#### **Article Contributed By:**



#### Vote for difficulty



Article Tags: Picked, Technical Scripter 2022, Python, Technical Scripter

Practice Tags: python

Improve Article

Report Issue



A-143, 9th Floor, Sovereign Corporate Tower, Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

**Company** Languages

About Us Python

Careers Java

In Media C++

Contact Us GoLang

Privacy Policy SQL

Copyright Policy R Language

Third-Party Copyright Notices Android Tutorial

Advertise with us

#### **Data Structures**

Array Sorting

**Algorithms** 

Recursion

Write & Earn

**Data Science & ML** 

**Python** 

String Searching

Linked List Greedy

Stack Dynamic Programming

Queue Pattern Searching

Graph Backtracking

### **Web Development**

Tree

HTML Write an Article

CSS Improve an Article

JavaScript Pick Topics to Write

Bootstrap Write Interview Experience

ReactJS Internships

AngularJS Video Internship

NodeJS

#### **Computer Science**

GATE CS Notes Data Science With Python

Operating Systems Data Science For Beginner

Computer Network Machine Learning Tutorial

Database Management System Maths For Machine Learning

Software Engineering Pandas Tutorial

Digital Logic Design NumPy Tutorial

Engineering Maths NLP Tutorial

#### **Interview Corner**

Company Preparation Python Tutorial

Preparation for SDE	Python Programming Examples		
Company Interview Corner	Django Tutorial		
Experienced Interview	Python Projects		
Internship Interview	Python Tkinter		
Competitive Programming	OpenCV Python Tutorial		
Aptitude			

GfG School	UPSC/SSC/BANKING
CBSE Notes for Class 8	SSC CGL Syllabus
CBSE Notes for Class 9	SBI PO Syllabus
CBSE Notes for Class 10	IBPS PO Syllabus
CBSE Notes for Class 11	UPSC Ethics Notes
CBSE Notes for Class 12	UPSC Economics Notes
English Grammar	UPSC History Notes

 $@ geeks for geeks \, , \, Some \, rights \, reserved \,$