



(<https://www.ques10.com/>)



Search (<https://www.ques10.com/local/search/page/>)

Ask Question (<https://www.ques10.com/p/new/post/>)

Login (<https://www.ques10.com/site/login/?next=/p/42324/explain-flajolet-martin-algorithm-with-example/>)

## Explain Flajolet Martin Algorithm with example.

written 3.9 years ago by

modified 16 months ago by



swatisharma (<https://www.ques10.com/u/swatisharma/>) • 1.1k



besharateif739 (<https://www.ques10.com/u/besharateif739/>) • 10

2

49k  
views

big data analytics (<https://www.ques10.com/t/big%20data%20analytics/>)

[ADD COMMENT](#)

[FOLLOW](#)

[SHARE](#)

[EDIT \(https://www.ques10.com/p/edit/42324/\)](https://www.ques10.com/p/edit/42324/)



Thanks for excellent explanation. But I have one question. When  $x=4$ , Hash function's output is 5 and there are 5 zeros in tail. Therefore our max R is 5 and distinct elements will be 32. But in input stream we have 4 distinct elements. I think, we should not count all-zero element. May you explain more, please?

16 months ago by besharateif739 (<https://www.ques10.com/u/355589/>) • 10

## 2 Answers

---

written 3.9 years ago by



yashbeer (<https://www.ques10.com/u/>) ★ 10k

8

8

5.5k  
views

**Flajolet-Martin algorithm** approximates the number of unique objects in a stream or a database in one pass. If the stream contains  $n$  elements with  $m$  of them unique, this algorithm runs in  $O(n)$  time and needs  $O(\log(m))$  memory.

### Algorithm:

1. Create a bit vector (bit array) of sufficient length  $L$ , such that  $2^L > n$ , the number of elements in the stream. Usually a 64-bit vector is sufficient since  $2^64$  is quite large for most purposes.
2. The  $i$ -th bit in this vector/array represents whether we have seen a hash function value whose binary representation ends in  $0^i$ . So initialize each bit to 0.

3. The  $i$ -th bit in this vector/array represents whether we have seen a hash function value whose binary representation ends in  $0i$ . So initialize each bit to 0.
4. The  $i$ -th bit in this vector/array represents whether we have seen a hash function value whose binary representation ends in  $0i$ . So initialize each bit to 0.
5. Once input is exhausted, get the index of the first 0 in the bit array (call this  $R$ ). By the way, this is just the number of consecutive 1s (i.e. we have seen  $0, 00, \dots, 0^{R-1}$  as the output of the hash function) plus one.
6. Calculate the number of unique words as  $2^R / \phi$ , where  $\phi$  is 0.77351. A proof for this can be found in the original paper listed in the reference section.
7. The standard deviation of  $R$  is a constant:  $\sigma(R) = 1.12$ . (In other words,  $R$  can be off by about 1 for  $1 - 0.68 = 32\%$  of the observations, off by 2 for about  $1 - 0.95 = 5\%$  of the observations, off by 3 for  $1 - 0.997 = 0.3\%$  of the observations using the Empirical rule of statistics). This implies that our count can be off by a factor of 2 for 32% of the observations, off by a factory of 4 for 5% of the observations, off by a factor of 8 for 0.3% of the observations and so on.

**Example:**

$$S = 1, 3, 2, 1, 2, 3, 4, 3, 1, 2, 3, 1$$

$$h(x) = (6x + 1) \bmod 5$$

Assume  $|b| = 5$

x	h(x)	Rem	Binary	r(a)
1	7	2	00010	1

x	h(x)	Rem	Binary	r(a)
3	19	4	00100	2
2	13	3	00011	0
1	7	2	00010	1
2	13	3	00011	0
3	19	4	00100	2
4	25	0	00000	5
3	19	4	00100	2
1	7	2	00010	1
2	13	3	00011	0
3	19	4	00100	2
1	7	2	00010	1

$$R = \max(r(a)) = 5$$

$$\text{So no. of distinct elements} = N = 2^R = 2^5 = 32$$

**ADD COMMENT**   **SHARE**   **EDIT** (<https://www.ques10.com/p/edit/43223/>)

---

written 3.9 years ago by



teamques10 (<https://www.ques10.com/u/1/t>) **48k**

PG  
BT

2

2.4k  
views

- We may want to know how many different elements have appeared in the stream.
- For example, we wish to know how many distinct users visited the website till now or in last 2 hours.
- If no of distinct elements required to process many streams then keeping data in main memory is challenge.
- FM algorithm gives an efficient way to count the distinct elements in a stream.
- It is possible to estimate the no. of distinct elements by hashing the elements of the universal set to a bit string that is sufficiently long.
- The length of the bit string must be sufficient that there are more possible results of the hash function than there are elements in the universal set.

- Whenever we apply a hash function  $h$  to a stream element  $a$ , the bit string  $h(a)$  will end in some number of 0s, possibly none.
- Call this as tail length for a hash.
- Let  $R$  be the maximum tail length of any  $a$  seen so far in the stream.
- Then we shall use estimate  $2^R$  for the number of distinct elements seen in the stream.
- Consider a stream as:

$S = \{1, 2, 1, 3\}$

Let hash function be  $2x + 2 \bmod 4$

- When we apply the hash function we get remainder represented in binary as follows:

000, 101, 000 considering bit string length as 3.

- Maximum tail length  $R$  will be 3.
- No of distinct elements will be  $2^R = 2^3 = 8$
- Here the estimates may be too large or too low depending on hash function.
- We may apply multiple hash functions and combine the estimate to get near accurate values.

**ADD COMMENT**   **SHARE**   **EDIT** (<https://www.ques10.com/p/edit/43533/>)

Please log in (<https://www.ques10.com/site/login/?next=/p/42324/explain-flajolet-martin-algorithm-with-example/>) to add an answer.

COMMUNITY	CONTENT	COMPANY
Users ( <a href="https://www.ques10.com/user/list/">https://www.ques10.com/user/list/</a> )	All posts ( <a href="https://www.ques10.com/t/latest">https://www.ques10.com/t/latest</a> )	About ( <a href="https://www.ques10.com/info/about/">https://www.ques10.com/info/about/</a> )
Levels ( <a href="https://www.ques10.com/info/levels/">https://www.ques10.com/info/levels/</a> )	Tags ( <a href="https://www.ques10.com/t/">https://www.ques10.com/t/</a> )	Team ( <a href="https://www.ques10.com/info/team/">https://www.ques10.com/info/team/</a> )
Badges ( <a href="https://www.ques10.com/b/list/">https://www.ques10.com/b/list/</a> )	Dashboard ( <a href="https://www.ques10.com/dashboard/">https://www.ques10.com/dashboard/</a> )	Privacy ( <a href="https://www.ques10.com/info/privacy/">https://www.ques10.com/info/privacy/</a> )

**Submit question paper solutions and earn money**  (<https://www.ques10.com/info/solutions/>)