

Program 1

AIM : Design and implement a neural based network for generating word embedding for words in a document corpus :

```
import torch
import torch.nn as nn
import torch.optim as optim
from collections import Counter
import re
import random
```

```
# -----
```

```
# 1. Preprocess Corpus
```

```
# -----
```

```
def tokenize(text):
```

```
    # very simple tokenizer: lowercase + split on non-letters
```

```
    return re.findall(r"\b\w+\b", text.lower())
```

```
corpus = """Natural language processing enables computers to understand
human language.
```

```
Word embeddings map words into continuous vector space.
```

```
Neural networks can be used to learn these embeddings from context words in a
document corpus."""
```

```
tokens = tokenize(corpus)
```

```
# -----
```

```
# 2. Build Vocabulary
```

```
# -----
```

```
word_counts = Counter(tokens)
```

```
vocab = {w: i for i, (w, _) in enumerate(word_counts.items())}
```

```
id2word = {i: w for w, i in vocab.items()}
```

```
vocab_size = len(vocab)
```

```
# -----
```

```
# 3. Generate Training Data (Skip-gram)
```

```
# -----
```

```
def generate_pairs(tokens, window_size=2):
```

```
    pairs = []
```

```
    for i, center in enumerate(tokens):
```

```

        for j in range(max(0, i - window_size), min(len(tokens), i + window_size + 1)):
            if i != j:
                pairs.append((center, tokens[j]))
    return pairs

```

```

pairs = generate_pairs(tokens, window_size=2)
print("Sample training pairs:", pairs[:10])

```

Convert to indices

```

training_data = [(vocab[c], vocab[o]) for c, o in pairs]

```

-----

4. Define Neural Network

-----

```

class Word2Vec(nn.Module):

```

```

    def __init__(self, vocab_size, embed_dim):
        super(Word2Vec, self).__init__()
        self.embeddings = nn.Embedding(vocab_size, embed_dim) # input layer
        self.output = nn.Linear(embed_dim, vocab_size)         # output layer

```

```

    def forward(self, center_word):
        embed = self.embeddings(center_word)
        out = self.output(embed)
        return out

```

-----

5. Training

-----

```

embed_dim = 50
model = Word2Vec(vocab_size, embed_dim)
criterion = nn.CrossEntropyLoss()
optimizer = optim.Adam(model.parameters(), lr=0.01)

```

```

for epoch in range(50):

```

```

    total_loss = 0

```

```

    for center, context in training_data:

```

```

        center_tensor = torch.tensor([center], dtype=torch.long)

```

```

        context_tensor = torch.tensor([context], dtype=torch.long)

```

```

        optimizer.zero_grad()

```

```

        output = model(center_tensor)
        loss = criterion(output, context_tensor)
        loss.backward()
        optimizer.step()
        total_loss += loss.item()
    if (epoch+1) % 10 == 0:
        print(f"Epoch {epoch+1}, Loss: {total_loss:.4f}")

# -----
# 6. Extract Word Embeddings
# -----
embeddings = model.embeddings.weight.data
print("\nWord Embedding for 'language':\n", embeddings[vocab["language"]])
print("\nWord Embedding for 'neural':\n", embeddings[vocab["neural"]])

```

Output

Sample training pairs: [('natural', 'language'), ('natural', 'processing'), ('language', 'natural'), ('language', 'processing'), ('language', 'enables'), ('processing', 'natural'), ('processing', 'language'), ('processing', 'enables'), ('processing', 'computers'), ('enables', 'language')]

Epoch 10, Loss: 264.6419

Epoch 20, Loss: 248.5941

Epoch 30, Loss: 238.4213

Epoch 40, Loss: 235.1496

Epoch 50, Loss: 230.1036

Word Embedding for 'language':

```

tensor([-0.5211, -0.0398, -0.1866, -0.0288, -0.4527, -0.0603, -0.0144, -0.0196,
        0.1168, -0.3704, -0.0470,  0.7273, -0.1065, -0.0066,  0.0832,  0.3182,
        0.0571, -0.1028, -0.1645, -0.4021,  0.0821,  0.0520,  0.2955, -0.1912,
        -0.0548, -1.0331,  0.2676, -0.4810, -0.5650, -0.0550, -0.5612, -1.7615,
        -0.5346, -0.0154, -0.2718,  0.0328, -0.6433, -0.3753, -0.0761, -0.7315,
        -0.1847, -0.0831, -0.2612,  0.0465, -0.1019, -0.0099,  0.0117, -0.0886,
        0.0460, -0.2623])

```

Word Embedding for 'neural':

```

tensor([ 3.1592e-01,  3.4966e-01,  7.2536e-01, -1.6453e-01,  6.2357e-01,
        -6.7021e-04,  9.6454e-01,  9.2496e-01, -5.9064e-01, -1.9390e-02,
        -1.2982e-01, -4.0040e-01,  2.2320e-01,  2.1080e-01,  7.8963e-02,

```

```
3.8069e-01, 6.1177e-01, 5.3831e-02, 6.1975e-01, -4.6652e-01,
9.4187e-01, -3.6157e-02, -8.6640e-01, 1.0516e+00, 1.1266e-01,
-2.0185e-02, 4.1761e-01, 1.5600e-01, 4.9597e-01, 5.4737e-01,
-2.0418e+00, 4.1971e-01, -9.3843e-02, -6.3190e-01, 4.0373e-01,
8.7371e-01, -4.5783e-01, -1.0898e+00, 7.4455e-02, -8.4540e-01,
1.5338e+00, -5.6010e-01, -6.4116e-02, -1.7250e-01, 3.5546e-01,
1.2032e-01, -3.7513e-01, 6.1328e-01, -1.3033e+00, 1.2831e+00])
```

Program 2

AIM : Write a program to demonstrate the working of a deep neural network for classification task.

```
pip install torch
```

```
pip install scikit-learn
```

```
import torch
```

```
import torch.nn as nn
```

```
import torch.optim as optim
```

```
from sklearn.datasets import load_iris
```

```
from sklearn.model_selection import train_test_split
```

```
from sklearn.preprocessing import StandardScaler
```

```
# -----
```

```
# 1. Load Dataset (Iris)
```

```
# -----
```

```
iris = load_iris()
```

```
X = iris.data # features
```

```
y = iris.target # labels (0, 1, 2)
```

```
# Normalize features
```

```
scaler = StandardScaler()
```

```
X = scaler.fit_transform(X)
```

```
# Convert to torch tensors
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
random_state=42)
```

```
X_train = torch.tensor(X_train, dtype=torch.float32)
```

```
y_train = torch.tensor(y_train, dtype=torch.long)
```

```
X_test = torch.tensor(X_test, dtype=torch.float32)
```

```

y_test = torch.tensor(y_test, dtype=torch.long)

# -----
# 2. Define Deep Neural Network
# -----
class DeepNN(nn.Module):
    def __init__(self, input_size, hidden1, hidden2, num_classes):
        super(DeepNN, self).__init__()
        self.fc1 = nn.Linear(input_size, hidden1) # input → hidden1
        self.relu1 = nn.ReLU()
        self.fc2 = nn.Linear(hidden1, hidden2)    # hidden1 → hidden2
        self.relu2 = nn.ReLU()
        self.fc3 = nn.Linear(hidden2, num_classes) # hidden2 → output

    def forward(self, x):
        out = self.fc1(x)
        out = self.relu1(out)
        out = self.fc2(out)
        out = self.relu2(out)
        out = self.fc3(out)
        return out

# -----
# 3. Initialize Model
# -----
input_size = X.shape[1] # 4 features
hidden1, hidden2 = 16, 8
num_classes = 3        # iris has 3 classes
model = DeepNN(input_size, hidden1, hidden2, num_classes)

# Loss and optimizer
criterion = nn.CrossEntropyLoss()
optimizer = optim.Adam(model.parameters(), lr=0.01)

# -----
# 4. Training
# -----
epochs = 100
for epoch in range(epochs):
    # Forward pass

```

```

outputs = model(X_train)
loss = criterion(outputs, y_train)

# Backward pass
optimizer.zero_grad()
loss.backward()
optimizer.step()

if (epoch+1) % 10 == 0:
    print(f"Epoch [{epoch+1}/{epochs}], Loss: {loss.item():.4f}")

# -----
# 5. Evaluation
# -----
with torch.no_grad():
    test_outputs = model(X_test)
    _, predicted = torch.max(test_outputs, 1)
    accuracy = (predicted == y_test).sum().item() / y_test.size(0)

print("\nClassification Accuracy on Test Data: {:.2f}%".format(accuracy * 100))

```

Output

```

Epoch [10/100], Loss: 1.0312
Epoch [20/100], Loss: 0.8220
Epoch [30/100], Loss: 0.6012
Epoch [40/100], Loss: 0.4739
Epoch [50/100], Loss: 0.3485
Epoch [60/100], Loss: 0.2633
Epoch [70/100], Loss: 0.2148
Epoch [80/100], Loss: 0.1813
Epoch [90/100], Loss: 0.1578
Epoch [100/100], Loss: 0.1397

```

Classification Accuracy on Test Data: 100.00%

Program 3

AIM : Design and implement a Convolutional Neural Network(CNN) for classification of image dataset

pip install torch torchvision

```
import torch
import torch.nn as nn
import torch.optim as optim
import torch.nn.functional as F
import torchvision
import torchvision.transforms as transforms

# -----
# 1. Load Dataset (MNIST)
# -----
transform = transforms.Compose([transforms.ToTensor()])

train_dataset = torchvision.datasets.MNIST(root='./data', train=True,
                                           download=True, transform=transform)
test_dataset = torchvision.datasets.MNIST(root='./data', train=False,
                                           download=True, transform=transform)

train_loader = torch.utils.data.DataLoader(dataset=train_dataset,
                                           batch_size=64, shuffle=True)
test_loader = torch.utils.data.DataLoader(dataset=test_dataset,
                                           batch_size=64, shuffle=False)

# -----
# 2. Define CNN Model
# -----
class CNN(nn.Module):
    def __init__(self):
        super(CNN, self).__init__()
        self.conv1 = nn.Conv2d(1, 16, kernel_size=3, padding=1) # 1→16
        self.pool = nn.MaxPool2d(2, 2)
        self.conv2 = nn.Conv2d(16, 32, kernel_size=3, padding=1) # 16→32
        self.fc1 = nn.Linear(32 * 7 * 7, 128)
        self.fc2 = nn.Linear(128, 10) # 10 classes (digits 0-9)
```

```

def forward(self, x):
    x = self.pool(F.relu(self.conv1(x))) # [1,28,28] → [16,14,14]
    x = self.pool(F.relu(self.conv2(x))) # [16,14,14] → [32,7,7]
    x = x.view(-1, 32 * 7 * 7)         # flatten
    x = F.relu(self.fc1(x))
    x = self.fc2(x)
    return x

```

```
# -----
```

```
# 3. Initialize Model
```

```
# -----
```

```
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
```

```
model = CNN().to(device)
```

```
criterion = nn.CrossEntropyLoss()
```

```
optimizer = optim.Adam(model.parameters(), lr=0.001)
```

```
# -----
```

```
# 4. Training
```

```
# -----
```

```
epochs = 5
```

```
for epoch in range(epochs):
```

```
    running_loss = 0.0
```

```
    for images, labels in train_loader:
```

```
        images, labels = images.to(device), labels.to(device)
```

```
        optimizer.zero_grad()
```

```
        outputs = model(images)
```

```
        loss = criterion(outputs, labels)
```

```
        loss.backward()
```

```
        optimizer.step()
```

```
    running_loss += loss.item()
```

```
    print(f"Epoch {epoch+1}/{epochs}, Loss: {running_loss/len(train_loader):.4f}")
```

```
# -----
```

```
# 5. Evaluation
```

```
# -----
```

```
correct, total = 0, 0
```

```
with torch.no_grad():
```



```

train_loader = torch.utils.data.DataLoader(dataset=train_dataset,
                                             batch_size=128, shuffle=True)

# -----
# 2. Define Autoencoder
# -----
class Autoencoder(nn.Module):
    def __init__(self):
        super(Autoencoder, self).__init__()
        # Encoder (compression)
        self.encoder = nn.Sequential(
            nn.Linear(28 * 28, 128),
            nn.ReLU(True),
            nn.Linear(128, 64),
            nn.ReLU(True),
            nn.Linear(64, 32) # Compressed representation
        )
        # Decoder (reconstruction)
        self.decoder = nn.Sequential(
            nn.Linear(32, 64),
            nn.ReLU(True),
            nn.Linear(64, 128),
            nn.ReLU(True),
            nn.Linear(128, 28 * 28),
            nn.Sigmoid() # output values between 0-1
        )

    def forward(self, x):
        x = self.encoder(x)
        x = self.decoder(x)
        return x

# -----
# 3. Initialize Model
# -----
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
model = Autoencoder().to(device)
criterion = nn.MSELoss()
optimizer = optim.Adam(model.parameters(), lr=0.001)

```

```

# -----
# 4. Training
# -----
epochs = 10
for epoch in range(epochs):
    running_loss = 0.0
    for images, _ in train_loader:
        images = images.view(-1, 28*28).to(device) # Flatten
        optimizer.zero_grad()
        outputs = model(images)
        loss = criterion(outputs, images) # Compare with original
        loss.backward()
        optimizer.step()
        running_loss += loss.item()
    print(f'Epoch {epoch+1}/{epochs}, Loss: {running_loss/len(train_loader):.4f}')

# -----
# 5. Demonstrate Compression & Reconstruction
# -----
# Get some test images
test_dataset = torchvision.datasets.MNIST(root='./data', train=False,
                                         download=True, transform=transform)
test_loader = torch.utils.data.DataLoader(dataset=test_dataset,
                                         batch_size=10, shuffle=True)

# Show original and reconstructed
model.eval()
with torch.no_grad():
    images, _ = next(iter(test_loader))
    images = images.view(-1, 28*28).to(device)
    outputs = model(images)

# Move to CPU and reshape
images = images.view(-1, 1, 28, 28).cpu()
outputs = outputs.view(-1, 1, 28, 28).cpu()

# Plot
fig, axes = plt.subplots(2, 10, figsize=(10, 2))
for i in range(10):
    # Original

```

```
axes[0][i].imshow(images[i].squeeze(), cmap='gray')
axes[0][i].axis("off")
# Reconstructed
axes[1][i].imshow(outputs[i].squeeze(), cmap='gray')
axes[1][i].axis("off")
plt.show()
```

Output

```
Epoch 1/10, Loss: 0.0604
Epoch 2/10, Loss: 0.0303
Epoch 3/10, Loss: 0.0239
Epoch 4/10, Loss: 0.0206
Epoch 5/10, Loss: 0.0185
Epoch 6/10, Loss: 0.0171
Epoch 7/10, Loss: 0.0160
Epoch 8/10, Loss: 0.0149
Epoch 9/10, Loss: 0.0141
Epoch 10/10, Loss: 0.0134
```

Program 5

AIM : Design and implement a deep learning network for classification of textual documents.

```
pip install tensorflow scikit-learn numpy
```

```
import numpy as np
from sklearn.datasets import fetch_20newsgroups
from sklearn.model_selection import train_test_split
from tensorflow.keras.preprocessing.text import Tokenizer
from tensorflow.keras.preprocessing.sequence import pad_sequences
from tensorflow.keras.utils import to_categorical
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Embedding, LSTM, Dense

print("Step 1: Loading dataset ...")
data = fetch_20newsgroups(subset='all')
texts, labels = data.data, data.target
```

```

num_classes = len(set(labels))
print(f"Loaded {len(texts)} documents across {num_classes} classes.")

print("\nStep 2: Preprocessing text ...")
MAX_WORDS = 10000 # vocabulary size
MAX_LEN = 300     # max tokens per document

tokenizer = Tokenizer(num_words=MAX_WORDS, oov_token="<OOV>")
tokenizer.fit_on_texts(texts)

X = tokenizer.texts_to_sequences(texts)
X = pad_sequences(X, maxlen=MAX_LEN)
y = to_categorical(labels, num_classes=num_classes)
print("Text converted to padded sequences.")

print("\nStep 3: Splitting into train and test ...")
X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.2, random_state=42
)
print(f"Training samples: {len(X_train)}, Testing samples: {len(X_test)}")

print("\nStep 4: Building deep learning model ...")
model = Sequential([
    Embedding(input_dim=MAX_WORDS, output_dim=128,
input_length=MAX_LEN),
    LSTM(128),
    Dense(num_classes, activation="softmax")
])
model.compile(loss="categorical_crossentropy",
              optimizer="adam",
              metrics=["accuracy"])
print(model.summary())

print("\nStep 5: Training model ...")
history = model.fit(X_train, y_train,
                    epochs=5,
                    batch_size=64,
                    validation_split=0.1,
                    verbose=2)

```

```
print("\nStep 6: Evaluating model on test set ...")
loss, acc = model.evaluate(X_test, y_test, verbose=0)
print(f"Test Accuracy: {acc:.4f}")
```

Output

Step 1: Loading dataset ...

Loaded 18846 documents across 20 classes.

Step 2: Preprocessing text ...

Text converted to padded sequences.

Step 3: Splitting into train and test ...

Training samples: 15076, Testing samples: 3770

Step 4: Building deep learning model ...

Model: "sequential"

Layer (type)	Output Shape	Param #
embedding (Embedding)	(None, 300, 128)	1280000
lstm (LSTM)	(None, 128)	131584
dense (Dense)	(None, 20)	2580
Total params: 1414164 (5.39 MB)		
Trainable params: 1414164 (5.39 MB)		
Non-trainable params: 0 (0.00 Byte)		

None

Step 5: Training model ...

Epoch 1/5

212/212 - 76s - loss: 2.6723 - accuracy: 0.1621 - val_loss: 2.2644 - val_accuracy: 0.3150 - 76s/epoch - 357ms/step

Epoch 2/5

212/212 - 86s - loss: 1.9426 - accuracy: 0.3839 - val_loss: 1.8901 - val_accuracy: 0.4198 - 86s/epoch - 407ms/step

Epoch 3/5

212/212 - 92s - loss: 1.5213 - accuracy: 0.5242 - val_loss: 1.9722 - val_accuracy: 0.4244 - 92s/epoch - 433ms/step

Epoch 4/5

212/212 - 92s - loss: 1.3967 - accuracy: 0.5716 - val_loss: 1.6435 - val_accuracy: 0.4894 - 92s/epoch - 433ms/step

Epoch 5/5

212/212 - 90s - loss: 1.0232 - accuracy: 0.6859 - val_loss: 1.4114 - val_accuracy: 0.5590 - 90s/epoch - 423ms/step

Step 6: Evaluating model on test set ...

Test Accuracy: 0.5804

Program 6

AIM : Design and implement a deep learning network for forecasting time series data.

pip install numpy scikit-learn tensorflow

```
import numpy as np
from sklearn.preprocessing import StandardScaler
from sklearn.metrics import mean_squared_error, mean_absolute_error
import tensorflow as tf
from tensorflow.keras.models import Model
from tensorflow.keras.layers import Input, LSTM, Dense, TimeDistributed
```

1) Generate synthetic time series

```
def generate_series(n=1000):
    t = np.arange(n)
    trend = 0.01 * t
    seasonal = np.sin(2 * np.pi * t / 50)
    noise = 0.1 * np.random.randn(n)
    series = 10 + trend + seasonal + noise
    return series
```

```
series = generate_series(1000)
```

```

# -----
# 2) Scale data
scaler = StandardScaler()
series_scaled = scaler.fit_transform(series.reshape(-1,1)).flatten()

# -----
# 3) Windowing
INPUT_WINDOW = 30
OUTPUT_WINDOW = 10

def make_windows(data, input_w, output_w):
    X, Y = [], []
    for i in range(len(data) - input_w - output_w):
        X.append(data[i:i+input_w])
        Y.append(data[i+input_w:i+input_w+output_w])
    return np.array(X), np.array(Y)

X, Y = make_windows(series_scaled, INPUT_WINDOW, OUTPUT_WINDOW)
X = X[... , np.newaxis]
Y = Y[... , np.newaxis]

# Train/test split (80/20)
split = int(0.8 * len(X))
X_train, X_test = X[:split], X[split:]
Y_train, Y_test = Y[:split], Y[split:]

# -----
# 4) Build Seq2Seq LSTM model
# Encoder
encoder_inputs = Input(shape=(INPUT_WINDOW,1))
encoder_lstm = LSTM(64, return_state=True)
encoder_outputs, state_h, state_c = encoder_lstm(encoder_inputs)
encoder_states = [state_h, state_c]

# Decoder
decoder_inputs = Input(shape=(OUTPUT_WINDOW,1))
decoder_lstm = LSTM(64, return_sequences=True, return_state=True)
decoder_outputs, _, _ = decoder_lstm(decoder_inputs,
initial_state=encoder_states)
decoder_dense = TimeDistributed(Dense(1))

```

```

decoder_outputs = decoder_dense(decoder_outputs)

model = Model([encoder_inputs, decoder_inputs], decoder_outputs)
model.compile(optimizer='adam', loss='mse', metrics=['mae'])

# Prepare decoder input (teacher forcing)
decoder_input_train = np.zeros_like(Y_train)
decoder_input_test = np.zeros_like(Y_test)

# -----
# 5) Train
history = model.fit([X_train, decoder_input_train], Y_train,
                    validation_data=([X_test, decoder_input_test], Y_test),
                    epochs=20, batch_size=32, verbose=1)

# -----
# 6) Evaluate
preds = model.predict([X_test, decoder_input_test])
preds_unscaled =
scaler.inverse_transform(preds.reshape(-1,1)).reshape(preds.shape)
Y_test_unscaled =
scaler.inverse_transform(Y_test.reshape(-1,1)).reshape(Y_test.shape)

mae = mean_absolute_error(Y_test_unscaled.flatten(), preds_unscaled.flatten())
rmse = np.sqrt(mean_squared_error(Y_test_unscaled.flatten(),
preds_unscaled.flatten()))
print(f"Test MAE: {mae:.4f}, Test RMSE: {rmse:.4f}")

```

Output

```

Epoch 1/20
24/24 [=====] - 4s 49ms/step - loss: 0.2551 - mae:
0.3946 - val_loss: 0.3036 - val_mae: 0.4672
Epoch 2/20
24/24 [=====] - 0s 13ms/step - loss: 0.0757 - mae:
0.2349 - val_loss: 0.1495 - val_mae: 0.3149
Epoch 3/20
24/24 [=====] - 0s 13ms/step - loss: 0.0617 - mae:
0.2132 - val_loss: 0.1106 - val_mae: 0.2658
Epoch 4/20

```

24/24 [=====] - 0s 17ms/step - loss: 0.0520 - mae: 0.1943 - val_loss: 0.1049 - val_mae: 0.2621

Epoch 5/20

24/24 [=====] - 0s 17ms/step - loss: 0.0333 - mae: 0.1499 - val_loss: 0.0716 - val_mae: 0.2159

Epoch 6/20

24/24 [=====] - 0s 15ms/step - loss: 0.0109 - mae: 0.0790 - val_loss: 0.0705 - val_mae: 0.2389

Epoch 7/20

24/24 [=====] - 0s 16ms/step - loss: 0.0046 - mae: 0.0535 - val_loss: 0.0344 - val_mae: 0.1554

Epoch 8/20

24/24 [=====] - 0s 16ms/step - loss: 0.0038 - mae: 0.0493 - val_loss: 0.0350 - val_mae: 0.1611

Epoch 9/20

24/24 [=====] - 0s 14ms/step - loss: 0.0035 - mae: 0.0469 - val_loss: 0.0469 - val_mae: 0.1950

Epoch 10/20

24/24 [=====] - 0s 16ms/step - loss: 0.0031 - mae: 0.0444 - val_loss: 0.0212 - val_mae: 0.1240

Epoch 11/20

24/24 [=====] - 0s 17ms/step - loss: 0.0028 - mae: 0.0428 - val_loss: 0.0180 - val_mae: 0.1133

Epoch 12/20

24/24 [=====] - 0s 17ms/step - loss: 0.0029 - mae: 0.0430 - val_loss: 0.0187 - val_mae: 0.1168

Epoch 13/20

24/24 [=====] - 0s 17ms/step - loss: 0.0026 - mae: 0.0412 - val_loss: 0.0118 - val_mae: 0.0895

Epoch 14/20

24/24 [=====] - 0s 12ms/step - loss: 0.0026 - mae: 0.0410 - val_loss: 0.0165 - val_mae: 0.1104

Epoch 15/20

24/24 [=====] - 0s 16ms/step - loss: 0.0026 - mae: 0.0407 - val_loss: 0.0084 - val_mae: 0.0747

Epoch 16/20

24/24 [=====] - 0s 16ms/step - loss: 0.0027 - mae: 0.0413 - val_loss: 0.0169 - val_mae: 0.1130

Epoch 17/20

24/24 [=====] - 0s 16ms/step - loss: 0.0025 - mae: 0.0399 - val_loss: 0.0089 - val_mae: 0.0776

Epoch 18/20

24/24 [=====] - 0s 17ms/step - loss: 0.0024 - mae: 0.0392 - val_loss: 0.0122 - val_mae: 0.0926

Epoch 19/20

24/24 [=====] - 0s 17ms/step - loss: 0.0024 - mae: 0.0392 - val_loss: 0.0077 - val_mae: 0.0713

Epoch 20/20

24/24 [=====] - 0s 15ms/step - loss: 0.0026 - mae: 0.0408 - val_loss: 0.0076 - val_mae: 0.0707

6/6 [=====] - 1s 8ms/step

Test MAE: 0.2083, Test RMSE: 0.2570

Program 7

AIM : Write a program to enable pre-train models to classify a given image dataset

```
project_folder/      ← Your main project folder
├── main.py           ← Python script
├── data/              ← Dataset folder
│   ├── train/         ← Training images
│   │   ├── cat/       ← Class 1 training images
│   │   │   ├── cat1.jpg
│   │   │   ├── cat2.jpg
│   │   │   └── ...
│   │   ├── dog/       ← Class 2 training images
│   │   │   ├── dog1.jpg
│   │   │   ├── dog2.jpg
│   │   │   └── ...
│   └── val/           ← Validation images
│       ├── cat/       ← Class 1 validation images
│       │   ├── cat3.jpg
│       │   └── ...
│       └── dog/       ← Class 2 validation images
│           ├── dog3.jpg
│           └── ...
```

pip install tensorflow

```
from tensorflow.keras.preprocessing.image import ImageDataGenerator
```

```
from tensorflow.keras.models import Model
from tensorflow.keras.layers import Dense, GlobalAveragePooling2D
from tensorflow.keras.applications import ResNet50
from tensorflow.keras.applications.resnet50 import preprocess_input
```

1) Dataset paths adjust as per requirement

```
train_dir = "data/train"
val_dir = "data/val"
img_size = (224, 224)
batch_size = 32
```

2) Data generators

```
train_gen =
ImageDataGenerator(preprocessing_function=preprocess_input).flow_from_directory(
    train_dir, target_size=img_size, batch_size=batch_size,
    class_mode='categorical'
)
val_gen =
ImageDataGenerator(preprocessing_function=preprocess_input).flow_from_directory(
    val_dir, target_size=img_size, batch_size=batch_size, class_mode='categorical'
)
```

```
num_classes = train_gen.num_classes
```

3) Pre-trained model (ResNet50) without top layer

```
base_model = ResNet50(weights='imagenet', include_top=False,
input_shape=(224,224,3))
base_model.trainable = False # Freeze base model
```

4) Add classification head

```
x = base_model.output
x = GlobalAveragePooling2D()(x)
x = Dense(128, activation='relu')(x)
predictions = Dense(num_classes, activation='softmax')(x)
```

```
model = Model(inputs=base_model.input, outputs=predictions)
```

5) Compile model

```
model.compile(optimizer='adam', loss='categorical_crossentropy',  
metrics=['accuracy'])
```

6) Train model

```
model.fit(train_gen, validation_data=val_gen, epochs=5)
```

7) Evaluate model

```
loss, acc = model.evaluate(val_gen)
```

```
print(f"Validation Loss: {loss:.4f}, Validation Accuracy: {acc:.4f}")
```

Output

Found 18 images belonging to 2 classes.

Found 2 images belonging to 2 classes.

Epoch 1/5

```
1/1 [=====] - 5s 5s/step - loss: 0.5678 - accuracy:  
0.7222 - val_loss: 0.0982 - val_accuracy: 1.0000
```

Epoch 2/5

```
1/1 [=====] - 1s 935ms/step - loss: 0.0476 -  
accuracy: 1.0000 - val_loss: 0.0172 - val_accuracy: 1.0000
```

Epoch 3/5

```
1/1 [=====] - 1s 918ms/step - loss: 0.0094 -  
accuracy: 1.0000 - val_loss: 0.0040 - val_accuracy: 1.0000
```

Epoch 4/5

```
1/1 [=====] - 1s 927ms/step - loss: 0.0031 -  
accuracy: 1.0000 - val_loss: 0.0011 - val_accuracy: 1.0000
```

Epoch 5/5

```
1/1 [=====] - 1s 1s/step - loss: 0.0012 - accuracy:  
1.0000 - val_loss: 3.5405e-04 - val_accuracy: 1.0000
```

```
1/1 [=====] - 0s 126ms/step - loss: 3.5405e-04 -  
accuracy: 1.0000
```

Validation Loss: 0.0004, Validation Accuracy: 1.0000

Program 8

AIM : Simple Grid World Problem: Design a custom 2D grid world where the agent navigates from a start position to a goal, avoiding obstacles. Environment: Custom grid (easily implemented in Python)

```
import random
```

```
class GridWorld:
```

```
    def __init__(self, width, height, start, goal, obstacles=[]):
        # Initialize grid dimensions, start & goal positions, and obstacles
        self.width = width
        self.height = height
        self.start = start
        self.goal = goal
        self.obstacles = obstacles
        self.reset()
```

```
    def reset(self):
        # Reset the agent to the start position
        self.agent_pos = self.start
        return self.agent_pos
```

```
    def render(self):
        # Print the current grid with agent, start, goal, and obstacles
        for i in range(self.height):
            row = ""
            for j in range(self.width):
                if (i, j) == self.agent_pos:
                    row += 'A ' # Agent's current position
                elif (i, j) == self.start:
                    row += 'S ' # Start position
                elif (i, j) == self.goal:
                    row += 'G ' # Goal position
                elif (i, j) in self.obstacles:
                    row += 'O ' # Obstacle
                else:
                    row += '. ' # Empty cell
            print(row)
```

```
print()
```

```
def step(self, action):
```

```
    # Move the agent in the given direction: 'up', 'down', 'left', 'right'
```

```
    x, y = self.agent_pos
```

```
    if action == 'up':
```

```
        x -= 1
```

```
    elif action == 'down':
```

```
        x += 1
```

```
    elif action == 'left':
```

```
        y -= 1
```

```
    elif action == 'right':
```

```
        y += 1
```

```
    else:
```

```
        print("Invalid action! Use: up, down, left, right")
```

```
    # Check if new position is within grid boundaries
```

```
    if 0 <= x < self.height and 0 <= y < self.width:
```

```
        new_pos = (x, y)
```

```
    else:
```

```
        new_pos = self.agent_pos # Stay in place if moving out of bounds
```

```
    self.agent_pos = new_pos
```

```
    # Determine reward and whether the episode is done
```

```
    if new_pos == self.goal:
```

```
        reward = 1 # Reached goal
```

```
        done = True
```

```
    elif new_pos in self.obstacles:
```

```
        reward = -1 # Hit an obstacle
```

```
        done = True
```

```
    else:
```

```
        reward = -0.01 # Small penalty for each step
```

```
        done = False
```

```
    return new_pos, reward, done
```

```
# -----
```

```
# User-controlled agent with RANDOM obstacles
```

```

# -----
width, height = 5, 5
start = (0, 0)
goal = (4, 4)

# Generate random obstacles (3 positions each run)
all_positions = [(i, j) for i in range(height) for j in range(width)]
all_positions.remove(start)
all_positions.remove(goal)
obstacles = random.sample(all_positions, 3)

env = GridWorld(width, height, start, goal, obstacles)
state = env.reset()
done = False

print("Welcome to Grid World!\n")
print("Game Rules:")
print(" - Reach the Goal (G) to win ")
print(" - Avoid Obstacles (O), or you lose")
print(" - You are the Agent (A), starting from Start (S)")
print(" - Use commands: up, down, left, right to move\n")

env.render()

while not done:
    action = input("Enter your move (up, down, left, right): ")
    state, reward, done = env.step(action)
    print(f"New State: {state}, Reward: {reward}")
    env.render()

if state == goal:
    print("Congratulations! You reached the goal!")
else:
    print(" Game Over! You hit an obstacle.")

```

Output

Welcome to Grid World!

Game Rules:

- Reach the Goal (G) to win
- Avoid Obstacles (O), or you lose
- You are the Agent (A), starting from Start (S)
- Use commands: up, down, left, right to move

```
A . . . .
. . . O .
. . O . .
. . . O .
. . . . G
```

Enter your move (up, down, left, right): down

New State: (1, 0), Reward: -0.01

```
S . . . .
A . . O .
. . O . .
. . . O .
. . . . G
```

Enter your move (up, down, left, right): down

New State: (2, 0), Reward: -0.01

```
S . . . .
. . . O .
A . O . .
. . . O .
. . . . G
```

Enter your move (up, down, left, right): right

New State: (2, 1), Reward: -0.01

```
S . . . .
. . . O .
. A O . .
. . . O .
. . . . G
```

Enter your move (up, down, left, right): right

New State: (2, 2), Reward: -1

```
S . . . .
. . . O .
. . A . .
```

... O .
... G

Game Over! You hit an obstacle.

Thank You