TETRISRL

AI1704 - REL301m Assignment

SE171792 / Nguyen Anh Hao

CONTENTS

01.
TETRIS ENVIROMENT

- Define Piece, Grid, Generators, Rotations, ...
- Define game characteristics

02.
ES ALGORITHM

- The 4 heuristics
- Evolution strategies
- Training strategies

03.
RESULTS & DEMO

- Test results
- Demo agent

Tetris environment



A basic Tetris environment include:

- Piece
- Grid
- Piece generator
- Rotation method
- Drop method
- Check valid position
- Clear line method

Piece is defined with 7 available shapes:



Piece generator is defined with 2 game mode:

Mode	‘classics’	‘random’
Describe	7-bag random generator: 7 pieces are shuffled and put into a bag, then generator will pop a piece each time. Until no more pieces in bag, the bag will be refilled.	The new piece is randomly selected by random.choice()
Difficulty	Normal	Hard

IDENTIFY TETRIS CHARACTERISTICS

01.

Large action space

Each piece has 1-4 possible rotations, each rotation has 7-10 possible drop place.
-> action space upto >30 .

02.

Delay + sparse reward

Target of Tetris is to clear the rows, which cannot happen immediately after placing a piece.

03.

Randomness

The piece is generated randomly, which mean the agent must be able to adapt unpredictable future state.

04.

Balance challenge

The model must effectively balance between moves that yield quick, small rewards and those that set the stage for larger, future rewards.

EVOLUTION STRATEGIES

FIND A HEURISTIC FUNCTION FOR POLICY

Through research process, we have found a reliable work, thanks to Lee Yiyuan from Rice University, Singapore. Source: CodeMyRoad

HARDWARE COMPATIBLE

ES does not require a powerful GPU as its parallel processing capabilities seem to be better suited to CPUs.

f1:
Aggregate height





f2:
Clear lines

f3:
Holes





f4:
Bumpiness

THE HEURISTIC FUNCTION

$$\text{reward} = w_1 f_1 + w_2 f_2 + w_3 f_3 + w_4 f_4$$

$$\text{bumpiness} = \sum_{i=1}^{\text{cols}-1} |H[i] - H[i+1]|$$



$$bumpiness = 6 = |3-5| + |5-5| + ... + |4-4| + |4-5|$$

THE HEURISTIC FUNCTION

$$\text{reward} = w_1 f_1 + w_2 f_2 + w_3 f_3 + w_4 f_4$$

THE HEURISTIC FUNCTION

$$\text{reward} = w_1 f_1 + w_2 f_2 + w_3 f_3 + w_4 f_4$$

Evolution Strategies:

1. Agent scan through all possible action in current state and ***choose the action that gain maximum reward(1)*** calculated by the heuristic function.

2. Agent performs action continuously until game_over = True, then ***return the total clear lines*** as reward(2) to update the weights of heuristic function.

Note: reward(1) and reward(2) are different variables.

Agent has 2 options to decide the next move:

Mode	'normal'	'promax'
Describe	Scan through all possible moves of current piece, calculate reward for each move and choose the move that gain maximum reward to be the next move	Scan all possible moves of the current piece, calculate the reward. For each move, scan all possible moves of the next piece, calculate the reward. Sum the rewards of each pair of current and next pieces. Choose the pair that gain maximum reward.
Complexity	O(n)	O(n^2)

ES EXPLORATION FLOW

Heuristic weights initialization

Load pre-trained weights to baseline or baseline = [-0.5 0.5 -0.5 -0.5]

Parallel processing

Allow candidates to play <num_games> and record the rewards received

LOAD WEIGHTS → CREATE CANDIDATES → EVALUATE CANDIDATES → UPDATE BASELINE → LOOP FOR N GENERATIONS

Population initialization

Create Gaussian noises and apply to baseline

$$\text{candidates} = \text{baseline} + \sigma \cdot \text{noises}$$

$$\text{standardized_rewards} = \frac{\text{rewards} - \text{mean_reward}}{\text{std}(\text{rewards}) + 10^{-8}}$$

$$\text{update} = \left(\frac{\alpha}{\sigma \cdot \text{population_size}}\right) \cdot (\text{noise}^T \cdot \text{standardized_rewards})$$

$$\text{baseline} \leftarrow \text{baseline} + \text{update}$$

ES EXPLOITATION FLOW

Evaluate training config

Review model performance carefully and config model hyperparameters (sigma, lr, max_moves)

Parallel processing

Allow candidates to play <num_games> and record the rewards received

CONFIGURATION → CREATE CANDIDATES → EVALUATE CANDIDATES → UPDATE BASELINE → LOOP FOR N GENERATIONS

Population initialization

Create a Gaussian noise and apply to baseline

$$\text{candidates} = \text{baseline} + \sigma \cdot \text{noises}$$

Choose elite candidate

Elite candidate is the candidate that perform the best (gain highest rewards)

$$\text{baseline} = \text{elite_candidate}$$


Classic/Normal 100 games statistics
Base
First exploration
First exploitation
Best model
Lee YiYuan
60000
40000
20000
0
20968
423
41
94
65113
81170
3796
468
9532
1099
52464
Max Score
Min Score
Avg Score
Average Moves
Max Moves



AGENT DEMO

THANKS !