



Initialize Stage

Here's the whole loop, start to finish.

Two ways the stage gets set

1. **Real gameplay (between maps):** in the *previous* map — a door/trigger/menu — right before you load the bar:

```
Get Game Instance → Cast VTGGameInstanceBase → Set Current Stage =
"Stage_Bar_Intro"
→ Open Level (L2Bar)
```

Because the GameInstance survives the load, the bar opens already knowing its stage. **Set it before** `Open Level` — after is too late (`BeginPlay` already ran).

2. **Testing (no previous map):** on the **placed** `BPLM_BarBack` **actor** in the level (not the class) → Details → Stage|Testing:

- tick `Override Stage For Testing`
- type `Test Stage` = **"Stage_Bar_After"**

Hit Play — the level behaves as that stage. Untick before shipping.

How BPLM reads it and puts things in place

In `BPLM_BarBack`, add the `OnStageBegin` event (fires on `BeginPlay` with the resolved Name):

```
Event OnStageBegin (Stage) → Switch on Name (Stage)
├─ "Stage_Bar_Intro" → [Chain A: enable/move/play things for intro]
├─ "Stage_Bar_After" → [Chain B: the after-FC setup]
└─ Default           → [fallback]
```

(Right-click → **Switch on Name** → add a pin per stage Name.)

Division of labor — why everything lands right

- **Destroy-self actors** (SmartTrigger / ISX / CameraLock...): each removes itself on BeginPlay via `Is Active Stage(its own Name)` → false → Destroy. → wrong-stage stuff disappears.
- `BPLM.OnStageBegin`: does the **positive** setup — move/enable/spawn/play for the active stage. → right-stage stuff turns on.

Both read the **same** `Get Active Stage`, which is a pure lookup → order doesn't matter, so it's all consistent the instant the map loads.

Full bar example

[Prev map] Set Current Stage = "Stage_Bar_Intro" → Open Level L2Bar



[L2Bar loads]

- SmartTrigger/ISX/etc → `IsActiveStage("Stage_Bar_After")` = false → destroy
- `BPLM_BarBack.OnStageBegin("Stage_Bar_Intro")` → Chain A runs



Scene is exactly the Intro layout.

One tip

Keep your stage Names consistent and listed somewhere (a comment or a Name-returning function), since they're typed text — "Stage_Bar_Intro", "Stage_Bar_After", etc. A typo = no match = Default.

Want me to add a tiny C++ `GetAllKnownStages()` or named constants so you're not retyping Name strings and risking typos?