

Runs a Grails application as a JAR file with an embedded Tomcat or Jetty server

Grails Standalone Plugin - Reference Documentation

Authors: Burt Beckwith

Version: 1.2.2

Table of Contents

- 1** Introduction to the Standalone Plugin
- 2** Running the application

1 Introduction to the Standalone Plugin

The Standalone plugin builds a runnable JAR file with an embedded war built from your application and an embedded Tomcat 7 or Jetty 7 instance. This allows you to build a single archive that can be run on any computer with Java 5 or higher by running `java -jar standalone.jar`. This can be convenient for demos or even very lightweight installs of low-traffic Grails applications.

Release History

- October 29, 2013
 - 1.2.2 release
- May 10, 2013
 - 1.2.1 release
- May 10, 2013
 - 1.2 release
- August 16, 2012
 - 1.1.1 release
- August 6, 2012
 - 1.1 release
- August 4, 2012
 - 1.0.1 release
- July 8, 2011
 - initial 1.0 release

2 Running the application

Building the jar

The first step is to run the [build-standalone](#) script, e.g.

```
grails prod build-standalone
```

or

```
grails -Dgrails.env=demo build-standalone our_cool_demo.jar
```

If you pass the `--jetty` flag the embedded server will be Jetty instead of the default Tomcat, for example

```
grails prod build-standalone --jetty
```

or

```
grails -Dgrails.env=demo build-standalone our_cool_demo.jar --jetty
```

You can change the default embedded server to Jetty by adding this to BuildConfig.groovy:

```
grails.plugin.standalone.useJetty = true
```

If you've set Jetty to the default, you can force a Tomcat build later with the `--tomcat` flag:

```
grails build-standalone --tomcat
```

Build Configuration

There are several configuration settings that you can use to change how the jar is built; add any of these to BuildConfig.groovy to override the defaults:

Property	Default Value	Meaning
grails.plugin.standalone.ecjDependency	'org.eclipse.jdt.core.compiler:ecj:3.7.1'	the dependency config for the ECJ jar
grails.plugin.standalone.extraDependencies	none	extra dependency jars to include in the standalone jar
grails.plugin.standalone.ivyLogLevel	'warn'	the Ivy log level
grails.plugin.standalone.jettyServletApiDependency	'javax.servlet:servlet-api:2.5' 'javax.servlet:javax.servlet-api:3.0.1'	or the Jetty servlet API jar dependency
grails.plugin.standalone.jettyVersion	'7.6.0.v20120127'	the version of Jetty to use
grails.plugin.standalone.tomcatVersion	'7.0.47'	the version of Tomcat to use
grails.plugin.standalone.tomcatDependencies	'tomcat-annotations-api', 'tomcat-api', 'tomcat-catalina-ant', 'tomcat-catalina', 'tomcat-coyote', 'tomcat-juli', 'tomcat-servlet-api', 'tomcat-util'	the Tomcat jars to use
grails.plugin.standalone.tomcatEmbedDependencies	'tomcat-embed-core', 'tomcat-embed-jasper', 'tomcat-embed-logging-juli', 'tomcat-embed-logging-log4j'	the Tomcat embed jars to use
grails.plugin.standalone.mainClass	'grails.plugin.standalone.JettyLauncher' 'grails.plugin.standalone.Launcher'	or Optionally specify a custom main class to include in the MANIFEST.MF. Note that you will then be required to call either grails.plugin.standalone.JettyLauncher or grails.plugin.standalone.Launcher yourself

Running the server

As long as the target machine has Java 5 or higher available, all you need to do next is run

```
java -jar /path/to/jar_name.jar
```

There are several arguments you can pass to customize how the application runs, using name=value syntax:

1. `context`, the context name; if not specified it defaults to "" (the "root" context)
2. `host`, the host name; if not specified it defaults to "localhost"
3. `port`, the HTTP port; if not specified it defaults to 8080
4. `httpsPort`, the HTTPS port; there is no default for this, but if specified you can also specify the keystore path and password
5. `keystorePath` or `javax.net.ssl.keyStore`, the SSL keystore path; if not specified a temporary keystore will be generated
6. `keystorePassword` or `javax.net.ssl.keyStorePassword`, the SSL keystore password; required if an existing keystore path is specified
7. `truststorePath` or `javax.net.ssl.trustStore`, the SSL truststore path
8. `trustStorePassword` or `javax.net.ssl.trustStorePassword`, the SSL truststore password; required if an existing truststore path is specified
9. `enableClientAuth`, whether to enable client auth, defaults to false
10. `workDir`, the working directory where the war file is extracted, defaults to the system temp directory
11. `enableCompression`, whether to enable compression (Tomcat only)
12. `compressableMimeTypes`, a comma separated list of MIME types for which HTTP compression may be used; defaults to the Tomcat defaults, "text/html,text/xml,text/plain"
13. `sessionTimeout`, the session timeout in minutes; defaults to 30
14. `nio` or `tomcat.nio`, whether to use NIO; defaults to true

In addition, if you specify a value that is the name of a system property (e.g. 'home.dir'), the system property value will be used.

For example running

```
java -jar /path/to/jar_name.jar
```

will start a server at `http://localhost:8080/` and

```
java -jar /path/to/jar_name.jar context=cool_demo port=9000
```

will start a server at `http://localhost:9000/cool_demo`

```
java -jar /path/to/jar_name.jar context=cool_demo port=8080 httpsPort=8443
```

will start a server at `http://localhost:8080/cool_demo` and will also support SSL at `https://localhost:8443/cool_demo`

