

Dual-boot Bitlocker Drives

Rohit Goswami · 2024-07-28 · config · archlinux · encryption · dualboot · win

`cryptsetup` has partial support for `bitlocker` encrypted drives, but `dislocker` works better with dual booted machines.

Crucially `cryptsetup` doesn't work with partially encrypted drives.

```
cryptsetup --version
# cryptsetup 2.7.3 flags: UDEV BLKID KEYRING KERNEL_CAPI HW_OPAL
sudo cryptsetup --type bitlk open /dev/nvme0n1p3 windows
# Activation of partially decrypted BITLK device is not supported.
```

Usage of `dislocker` is rather straightforward^[1].

```
sudo mkdir -p /media/{bitlocker,Windows}
# Get the Bitlocker drive, assumes there's only one
export BTLDRIVE=$(blkid | grep "BitLocker" | awk '{print $1}' | sed 's:///')
sudo dislocker -v -V $BTLDRIVE -- /media/bitlocker
# Type might also be exfat depending on the configuration
sudo mount -t ntfs-3g -o loop,rw /media/bitlocker/dislocker-file /media/Windows/
```

Cleanup is equally straightforward, where the inner drive needs to be unmounted before the outer one.

```
sudo umount /media/{Windows,bitlocker}
```