

Local precommit dependencies

Rohit Goswami · 2023-11-01 · build · packaging · precommit

Recently a bunch of my pre-commit CI jobs started failing due to dependency resolution issues. The easiest way to ensure reliable usage is to have locally installed tools used. Consider:

```
- repo: https://github.com/poccc/pre-commit-hooks
  rev: v1.3.5
  hooks:
    - id: cppcheck
      args: ["--error-exitcode=1"]
```

Which leaves one dependent on an external repo. This can be rewritten as:

```
- repo: local
  hooks:
    - id: cppcheck
      name: cppcheck
      entry: cppcheck
      language: system
      types_or: [c++, c]
      args: ["--error-exitcode=1"]
```

With this local setup, it is necessary to adjust the CI configuration:

```
name: pre-commit
on:
  pull_request:
  push:
    branches: [main]
jobs:
  pre-commit:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v4
      - name: Install Conda environment
        # Using a lock file is optional but heavily recommended
        uses: mamba-org/setup-micromamba@v1
        with:
          environment-file: conda-lock.yml
          environment-name: ci
      - name: Run precommit
        shell: bash -l {0}
        run: |
          pipx run pre-commit run -a
```

This ensures the `pre-commit` action is executed within the `conda` environment, which is assumed to have `pipx` and the dependencies present.