



Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Improved Random Feature Method

-PDEs and Machine Learning

Haojun Qin¹

¹School of Mathematical Sciences
University of Sciences and Technology of China

May 18th, 2023



Table of Contents

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM
Numerical result
Analysis

- 1 Project Team Members
- 2 Brief Introduction of RFM
- 3 Improved RFM
- 4 Numerical result
- 5 Analysis



Table of Contents

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM
Numerical result
Analysis

- 1 Project Team Members
- 2 Brief Introduction of RFM
- 3 Improved RFM
- 4 Numerical result
- 5 Analysis



Project Team Members

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

- Haojun Qin, USTC
- Xianglong Hou, USTC.
- Bingsong Gao, USTC.
- Lei Zhao, USTC.
- Advisor: Jingrun Chen, Suzhou Institute for Advanced Research, USTC.



Table of Contents

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM
Numerical result
Analysis

- 1 Project Team Members
- 2 Brief Introduction of RFM**
- 3 Improved RFM
- 4 Numerical result
- 5 Analysis



RFM

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Consider the following problem:

$$\begin{cases} \mathcal{L}u(x) = f(x), & x \in \Omega \\ \mathcal{B}u(x) = g(x), & x \in \partial\Omega \end{cases}$$

The solution is approximated by a linear combination of some trial function:

$$u(x) \approx u_M(x) = \sum_{i=1}^M u_i \phi_i(x).$$

$\phi_i(x)$ is called the trial function (generated by neural network).



Trial Function

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Define $\phi_i(x)$ as the ones that occur naturally in neural network:

$$\phi_i(x) = \sigma(k_i \cdot x + b_i).$$

where σ is some scalar nonlinear function called activation function, $k_i \in \mathbb{R}^d$, $b_i \in \mathbb{R}$ are some random but fixed parameters.

Activation function such as \sin , \cos , \tanh can all be used.



Partition of unity

We start with a set of points $\{x_j\}_{j=1}^{M_p}$, each of which serves as the center for a component in the partition. And $\{d_j\}_{j=0}^{M_p}$ are the diameter of each component in the partition.

Define ψ^a and ψ^b in 1-dimension case:




Figure: ψ^a (red) and ψ^b (blue)



Construction of Trial Function

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Now we have a partition of unity consisting M_p components:

$$\{x_j\}_{j=1}^{M_p} + \{d_j\}_{j=1}^{M_p} \implies \{\psi_j\}_{j=1}^{M_p}.$$

For each component, we define M original trial functions:

$$\phi_{ij}(x) = \sigma(k_{ij} \cdot x + b_{ij}), \quad i = 1, 2, \dots, M.$$

Apply ψ_j to ϕ_{ij} :

$$u_M(x) = \sum_{j=1}^{M_p} \sum_{i=1}^M u_{ij} \phi_{ij}(x) \psi_j(x)$$



Loss Function

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

The trial function is:

$$u_M(x) = \sum_{j=1}^{M_p} \sum_{i=1}^M u_{ij} \phi_{ij}(x) \psi_j(x)$$

Collect $|C_I|$ points in Ω and $|C_B|$ points on $\partial\Omega$. And define the Loss Function:

$$L = \sum_{x_k \in C_I} \lambda_k \|\mathcal{L}u_M(x_k) - f(x_k)\|_{l^2}^2 + \sum_{x_j \in C_B} \lambda_j \|\mathcal{B}u_M(x_j) - g(x_j)\|_{l^2}^2.$$

where λ_k are the penalty parameters.

By using least-squares method, we obtain u_{ij} minimizing L .



RFM

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis




Figure: Random Feature Method



Table of Contents

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

- 1 Project Team Members
- 2 Brief Introduction of RFM
- 3 Improved RFM**
- 4 Numerical result
- 5 Analysis



Reinforced-RFM

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Consider a constrained problem and then transform it into quadratic programming:
Original:

$$\begin{aligned} \min \quad & \sum_{x_k \in C_I} \lambda_k \|\mathcal{L}u_M(x_k) - f(x_k)\|_{l^2}^2 \\ \text{s.t.} \quad & \mathcal{B}u_M(x_j) = g(x_j), \quad \forall x_j \in C_B \end{aligned}$$

QP:

$$\begin{aligned} \min \quad & \|Ax - b\|_{l^2}^2 \\ \text{s.t.} \quad & Cx = d \end{aligned}$$

Solve by augmented lagrangian method.



Strict-RFM

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Aim: Enforce the exact boundary conditions.

Key Method: Apply distance function to the construction of trial function.

Example

Consider the ODE problem:

$$\begin{cases} y'' = f(x, y, y') \\ y(a) = 0, y(b) = 0 \end{cases}$$

Define the distance function $L(x) = (x - a)(b - x)$ satisfying $L(a) = 0, L(b) = 0, L(x) \neq 0$ when $x \neq a, b$.

For any trial function $\phi(x)$, $\phi(x)L(x)$ always satisfies boundary conditions strictly.



Table of Contents

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

- 1 Project Team Members
- 2 Brief Introduction of RFM
- 3 Improved RFM
- 4 Numerical result**
- 5 Analysis



1-dimension problem

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Example (Helmholtz equation)

$$\begin{cases} \frac{d^2 u(x)}{dx^2} - \lambda u(x) = f(x) & x \in \Omega, \\ u(0) = c_1, \quad u(8) = c_2. \end{cases}$$

Choose

$$u(x) = 4 \cos(4(x + \frac{3}{20})) + 5 \sin(\sqrt{5}(x + \frac{7}{20})) + 2 \sin(\sqrt{3}(x + \frac{1}{20})) + 3 \sin(x + \frac{17}{20}) + 2.$$



1-dimension problem

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

M_P	M	Q	RFM		Reinforced-RFM		Strict-RFM	
			L_∞	L^2	L_∞	L^2	L_∞	L^2
4	50	50	1.01E-02	1.18E-02	1.13E-02	1.33E-02	1.63E-02	1.27E-02
8	50	50	2.61E-07	2.92E-07	2.11E-07	2.37E-07	2.99E-07	4.27E-07
16	50	50	1.65E-09	1.74E-09	5.16E-10	4.76E-10	1.18E-09	8.98E-10
32	50	50	3.46E-11	2.55E-11	4.66E-12	5.64E-12	1.72E-11	1.49E-11

Table: Helmholtz equation error



2-dimension problem

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Example (Poisson equation)

$$\begin{cases} \Delta u(x, y) = f(x, y) & x \in [0, 1] \times [0, 1], \\ u(x, 0) = g_1(x), \quad u(x, 1) = g_2(x), \\ u(0, y) = h_1(y), \quad u(1, y) = h_2(y). \end{cases}$$

Choose $u(x, y) =$
 $-[1.5 \cos(\pi x + 0.4\pi) + 2 \cos(2\pi x - 0.2\pi)][1.5 \cos(\pi y + 0.4\pi) + 2 \cos(2\pi y - 0.2\pi)].$



2-dimension problem

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis




Figure: Poisson equation error



2-dimension problem

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

M	Q_x	Q_y	RFM		Reinforced-RFM		Strict-RFM	
			L_∞	L^2	L_∞	L^2	L_∞	L^2
200	30	30	6.91E-08	1.60E-08	1.36E-05	4.16E-06	2.24E-09	4.54E-10
200	35	35	1.14E-07	2.57E-08	1.25E-06	2.62E-07	4.56E-09	7.17E-10
200	40	40	1.35E-07	1.76E-08	2.30E-06	6.25E-07	1.20E-08	2.36E-09
300	30	30	9.88E-10	1.45E-10	1.54E-06	4.85E-08	1.90E-10	5.01E-11
300	35	35	6.37E-10	8.31E-11	4.86E-07	1.41E-07	6.10E-11	1.15E-11
300	40	40	2.09E-09	4.00E-10	9.87E-06	2.72E-06	5.80E-11	1.52E-11

Table: Poisson equation error



2-dimension problem

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

M	Q_x	Q_y	RFM	Reinforced-RFM	Strict-RFM
			Boundary	Boundary	Boundary
200	30	30	6.91E-08	3.75E-09	0
200	35	35	7.69E-08	2.53E-10	0
200	40	40	1.23E-07	3.49E-10	0
300	30	30	7.42E-10	1.70E-10	0
300	35	35	6.37E-10	1.20E-10	0
300	40	40	6.56E-10	4.67E-10	0

Table: Poisson boundary error



2-dimension problem

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Example (Elasticity equation)

$$\begin{cases} \frac{E}{1-\mu^2} (u_{xx} + \frac{1-\mu}{2} u_{yy} + \frac{1+\mu}{2} v_{xy}) + X = 0 & \text{in } \Omega, \\ \frac{E}{1-\mu^2} (v_{yy} + \frac{1-\mu}{2} v_{xx} + \frac{1+\mu}{2} u_{xy}) + Y = 0 & \text{in } \Omega, \\ \frac{E}{1-\mu^2} (n_x (u_x + \mu v_y) + n_y \frac{1-\mu}{2} (u_y + v_x)) = \hat{X} & \text{on } \Gamma_1, \\ \frac{E}{1-\mu^2} (n_y (v_y + \mu u_x) + n_x \frac{1-\mu}{2} (v_x + u_y)) = \hat{Y} & \text{on } \Gamma_1, \\ u = U & \text{on } \Gamma_2, \\ v = V & \text{on } \Gamma_2. \end{cases}$$

Choose

$$\begin{cases} u = -\frac{px_2}{6EI} [(6L - 3x_1)x_1 + (2 + \mu)(x_2^2 - \frac{D^2}{4})], \\ v = \frac{p}{6EI} [3\mu(L - x_1)x_2^2 + (4 + 5\mu)\frac{D^2x_1}{4} + (3L - x_1)x_1^2]. \end{cases}$$



2-dimension problem

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

N	Q_x	Q_y	RFM		Reinforced-RFM	
			L_∞	L^2	L_∞	L^2
1	20	20	3.57E-14	7.25E-15	5.69E-10	1.93E-10
1	40	40	7.86E-16	2.35E-16	3.17E-11	1.32E-11
1	60	60	2.47E-16	3.50E-17	5.57E-09	1.53E-09
2	20	20	2.53E-14	1.08E-14	4.28E-10	1.41E-10
2	40	40	3.63E-16	8.87E-17	9.50E-11	3.48E-11
2	60	60	9.27E-17	1.48E-17	6.23E-10	2.57E-10

Table: Elasticity equation u error



2-dimension problem

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

N	Q_x	Q_y	RFM		Reinforced-RFM	
			L_∞	L^2	L_∞	L^2
1	20	20	2.22E-07	5.68E-08	7.44E-04	1.61E-04
1	40	40	3.18E-08	1.77E-09	3.88E-03	9.79E-04
1	60	60	1.53E-08	1.06E-09	2.45E-05	6.40E-06
2	20	20	2.47E-07	5.32E-08	2.20E-03	5.83E-04
2	40	40	1.90E-08	8.26E-10	5.64E-04	8.47E-05
2	60	60	1.64E-08	3.89E-10	7.42E-05	1.29E-05

Table: Elasticity equation boundary error



Table of Contents

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM
Numerical result

Analysis

- 1 Project Team Members
- 2 Brief Introduction of RFM
- 3 Improved RFM
- 4 Numerical result
- 5 Analysis



Low Rank

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Recall the quadratic programming:

$$\begin{aligned} \min \quad & \|Ax - b\|_{l^2}^2 \\ \text{s.t.} \quad & Cx = d \end{aligned}$$

Observation: C is a low-rank matrix.



Low Rank

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Row	Column	Rank	Row	Column	Rank
2400	800	150	2400	1200	152
2800	800	149	2800	1200	151
3200	800	149	3200	1200	150

Table: rank(C)

Row	Column	Rank	Row	Column	Rank
160	800	126	640	800	136
320	800	135	800	3200	364
480	800	136	1600	3200	378

Table: rank(C)



Low Rank

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

QP:

$$\begin{aligned} \min \quad & \|Ax - b\|_2^2 \\ \text{s.t.} \quad & Cx = d \end{aligned}$$

- Feasible domain $\{x : Cx = d\}$ is an empty set. Without carefully choosing parameters, the augmented lagrangian method could easily get stuck in a loop.
- When $\|Cx - d\|$ decreases, $\|Ax - b\|$ would increase. We have to make a compromise between \mathcal{L} and \mathcal{B} .
- When dealing with very large matrix, the unimproved iterative algorithm will increase the error and reduce the efficiency.



Future Plan

Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Plan:

- (1). Prior estimation.
- (2). Collocation strategy.
- (3). Efficient least-squares algorithm.



Improved
Random Feature
Method

Haojun Qin

Project Team
Members

Brief
Introduction of
RFM

Improved RFM

Numerical result

Analysis

Thanks for listening!