

GLINT: An Idle-Stroke Grasp-and-Lift Hand for In-Hand Manipulation*

Haokai Ding

Future Tech. School, Shenzhen
Tech. Univ.
Shenzhen, China
Lab of Robotics, X-Institute,
Shenzhen, China
hk_ding@outlook.com

Haotong Luan

Future Tech. School, Shenzhen
Tech. Univ.
Shenzhen, China
Lab of Robotics, X-Institute,
Shenzhen, China
lht20060306@outlook.com

Tao Yang*

Future Tech. School, Shenzhen
Tech. Univ.
Shenzhen, China
yangtao@sztu.edu.cn
*Corresponding author

Wenzeng Zhang*

Lab of Robotics, X-Institute
Shenzhen, China
wenzeng75@163.com
*Corresponding author

Abstract—In-hand manipulation is an essential capability for robotic hands, enabling complex object interactions such as grasping, repositioning, and lifting. This paper presents GLINT (Grasp-Lift Idle-stroke Nonlinear Transmission) hand, a novel grasp-and-lift hand realized through a lost-motion transmission mechanism. The design introduces a dual-phase operation: in the idle-stroke phase, the hand achieves grasping by allowing free alignment without force output; in the engaged phase, it performs lifting by transmitting force effectively. This mechanical switching enables an inherent form of in-hand manipulation, where the grasp-to-lift transition is achieved without relying heavily on upper-level controllers. A kinematic and dynamic model is developed to describe the switching conditions and the force–displacement relationship. The design is implemented and experimentally validated on a robotic platform, demonstrating accurate and reliable grasping and lifting with reduced control requirements and lower energy consumption. GLINT hand highlights a new paradigm for in-hand manipulation and offers potential applications in aerial manipulation, warehouse automation, and lightweight robotic grippers.

Keywords—Idle-stroke, Grasp-and-lift hand, In-hand manipulation, Robotic lifting mechanism, Warehouse automation

I. INTRODUCTION

Object grasping and lifting remain central challenges in robotics, automation, and artificial intelligence, especially in unstructured and dynamic environments that demand robustness, efficiency, and simplicity. Conventional robotic systems typically rely on tightly coupled perception–planning–control stacks to achieve reliable manipulation. While effective, these pipelines incur substantial computational, communication, and energy costs. To mitigate such burdens, a growing body of work embeds manipulation logic within the end-effector itself, shifting capability from software to hardware.

In-hand manipulation has emerged as a promising paradigm. Weinberg *et al.* [1] surveyed reinforcement learning and data-driven approaches that advanced dexterous in-hand control. Complementing learning-based methods, multimodal sensing integration has become a key driver of progress. For instance, Yuan *et al.* [2] developed a point-cloud-level visuo-

tactile fusion method enabling dexterous object rotation, and Huang *et al.* [3] combined dense tactile sensing with vision to refine fine-grained manipulation. Li *et al.* [4] introduced predictive force attention for adaptive visuo-tactile fusion, dynamically rebalancing sensory contributions during contact.

Other frameworks continue to demonstrate the promise of visuo-tactile pipelines. Tian *et al.* [5] applied soft-fusion contrastive learning to improve multimodal representations. Tu *et al.* [6] combined tactile-visual fusion with SelectLSTM for robust in-hand pose estimation. Chen *et al.* [7] proposed visuo-tactile transformers to unify cross-modal features, while Bauza *et al.* [8] achieved precise pick-and-place through simulation-trained visuotactile learning. Expanding this field, Suresh *et al.* [9] introduced NeuralFeels with neural fields for online shape and pose estimation in multi-fingered manipulation, and Mao *et al.* [10] showed how tactile-vision fusion improves recognition, grasping, and control robustness.

On the hardware side, tactile sensing plays an equally critical role. James and Lepora [11] demonstrated how slip detection stabilizes multi-fingered grasping. Deng *et al.* [12] applied tactile force feedback for adaptive pressure control. Li *et al.* [13] reviewed tactile perception as a foundation for manipulation, and Li *et al.* [14] provided a comprehensive overview of robotic intelligent grasping, emphasizing tactile integration in grasp planning. Further, Fan *et al.* [15] introduced the CrystalTac family, a set of vision-based tactile sensors manufactured via rapid monolithic processes, underscoring the importance of hardware-level sensing innovations. Collectively, these works converge on the insight that perception fusion and contact feedback are indispensable for advancing manipulation capability.

In parallel with sensing-driven advances, researchers have pursued mechanism-level innovations to offload part of the control burden into hardware. Ding *et al.* [16] introduced the Semi-Peaucellier linkage integrated with a differential mechanism, reported in their SP-Diff gripper, which achieved hybrid switching between linear parallel pinching and adaptive enveloping grasping through a Peaucellier-derived structure. This work illustrates how classical kinematic topologies can be

reconfigured to improve adaptability and reduce system-level dependence on perception and planning.

Building on such insights, the present study proposes a novel idle-stroke-based grasp-and-lift hand as shown in Fig. 1. Unlike adaptive pinching structures, the proposed design embeds grasp-to-lift phase switching directly into the transmission system. During the idle-stroke phase, the mechanism allows free alignment without transmitting force, realizing grasping at the structural level. Once engaged, the system transitions into a force-transmitting phase for lifting. By encoding the phase-switching logic within the mechanical architecture, this approach reduces reliance on high-level control, offering robustness under perceptual delays, limited communication, or resource-constrained conditions.




Fig. 1. Prototype of the proposed GLINT hand.

We fabricate a physical prototype of the idle-stroke hand, derive its kinematic and dynamic models to characterize grasp-to-lift transitions and force-displacement behavior, and validate performance through real-world experiments. Results confirm smooth phase switching, accurate force transmission, and efficient energy use. The remainder of this paper is organized as follows: Section II presents the design principles; Section III develops the kinematic and dynamic analyses of the proposed mechanism; Section IV reports the hardware experiments; and Section V concludes with discussions and future directions.

II. DESIGN CONCEPT

A. Fingertip Translation with Dual-Parallelogram

To maintain fingertip orientation while translating toward the object, the hand uses a cascaded dual-parallelogram linkage (Fig. 2a). The cascaded layout conveys input rotation to an approximately pure translational motion of the distal pad, preserving the local contact normal and reducing tangential disturbances during approach. In practice, the near-prismatic behavior holds over the usable stroke with sub-degree tip rotation under standard machining tolerances, which mitigates lateral slip and micro-rolling at first contact. This kinematic choice also decouples alignment from force transmission: in the approach phase the fingertip passively self-aligns, while the transmission remains mechanically disengaged via a lost-

motion subassembly and therefore does not inject grasping force until engagement is intentionally triggered. The resulting grasp-then-lift sequencing reduces sensitivity to perception delays and small pose errors and simplifies low-level control.




Fig. 2. Prototype of the proposed GLINT hand.

B. Idle-Stroke Transmission for Grasp-to-Lift

To realize grasp-then-lift at the mechanism level, the hand places a lost-motion subassembly in series with a conventional four-bar. The subassembly comprises a driver-side lug, a mechanical stopper with a small gap δ to the lug, and a preloaded extension spring acting on link OA . Fig. 2b illustrates the idle-stroke phase: the input advances while the lug has not yet reached the stopper, torque into the four-bar is negligible, and the fingertips close and settle with minimal normal force. Fig. 2c shows the engaged phase: the lug contacts the stopper, the remaining input compresses the spring, and the four-bar generates the vertical output required for lifting.

This architecture brings two practical benefits. It decouples geometric alignment from force transmission, keeping interaction forces low until engagement is intentionally triggered, which reduces slip and sensitivity to small pose errors. It also removes the need for special four-bar ratios to obtain sufficient output stroke; the lost-motion element supplies the missing stroke while preserving a compact planar layout.

Key parameters are the idle gap δ , the spring stiffness k , the spring pre-load x_0 , and the link set $\{OA, AB, BC, CO\}$. The gap sets the timing of engagement. The product kx_0 governs the onset force and the available capacity. The link lengths define geometric leverage. In practice, δ is chosen slightly larger than the closure needed for stable contact, and kx_0 is selected to exceed the worst-case lift requirement with margin. The mechanism remains backdrivable during the idle stroke and becomes partially backdrivable after engagement, limited by the spring-stopper pair, which also provides a passive overload path. Section III details the resulting kinematic and quasi-static relations.

C. Idle-Stroke Transmission for Grasp-to-Lift

In conventional four-bar lifters, geometric coupling around the base joint often causes the lower-left link to retreat during lifting, which back-constrains the upper branch. This makes it difficult to temporally separate pre-contact alignment from post-contact force build-up, leading to premature force peaks, wasted energy, and reduced robustness.




Fig. 3. The Idle-Stroke Gear.

We therefore place an Idle-Stroke transmission on the upper-left long-link (Fig. 3). The link is mechanically keyed to a gear, while two torsion springs with equal stiffness and opposite preloads are arranged inside the transmission to form a symmetric idle-stroke-compliance unit. Within the idle-stroke window, the link is allowed a small relative rotation with respect to the gear, absorbing coupling-induced retreat; once the displacement exceeds the idle-stroke threshold, the paired springs provide a balanced restoring torque to establish a stable force path. This preserves the original four-bar geometry while re-timing alignment versus force build-up, reducing controller burden and enabling partial backdrivability and overload protection via bounded relative motion.

III. ANALYSIS

A. Kinematic

Consider the planar four-bar $\{OA, AB, BC, CO\}$. Let θ denote the input angle. The fingertip follows an approximately translational path with normal travel $s(\theta)$ as is shown in Fig. 4. Define the kinematic displacement gain:

$$\begin{aligned} \dot{s}(\theta) &\approx L_{\text{eff}}(\theta) \dot{\theta} \\ s(\theta) &= \int_{\theta_0}^{\theta} L_{\text{eff}}(\xi) d\xi. \end{aligned} \quad (1)$$

where:

$$x_{\text{spring}}(\theta) = \max\{0, s(\theta) - \delta\} + x_0, \quad (2)$$

with preload x_0 . When $s(\theta) < \delta$, the force path is not closed, and the mechanism remains in the Idle phase. When $s(\theta) \geq \delta$, the mechanism enters Engagement and the spring compresses through the four-bar. The engagement angle θ_{engage} satisfies:

$$s(\theta_{\text{engage}}) = \delta \quad (3)$$

This piecewise structure geometrically decouples alignment motion from energy storage and reduces dependence on high-rate sensing and control.




Fig. 4. Four-bar lifting unit with Idle-Stroke transmission.

B. Quasi-Static Force Transmission

Under low-speed lifting with negligible inertia, model the spring as linear with stiffness k . The fingertip normal force is approximated by

$$F_{\text{tip}}(\theta) \approx k x_{\text{spring}}(\theta) J(\theta) = k (\max\{0, s(\theta) - \delta\} + x_0) J(\theta) \quad (4)$$

Where

$$J(\theta) \equiv \frac{\partial x_{\text{spring}}}{\partial y_{\text{tip}}} = \left(\frac{\partial x_{\text{spring}}}{\partial \theta} \right) / \left(\frac{\partial y_{\text{tip}}}{\partial \theta} \right) \quad (5)$$

is the spring-to-tip mechanical transmission Jacobian, and y_{tip} is the tip's normal displacement. To reflect the decoupling produced by the Idle-Stroke, use the effective definition

$$J(\theta) = \begin{cases} 0, & s(\theta) < \delta, \\ \frac{L_{\text{eff}}(\theta)}{\frac{\partial y_{\text{tip}}}{\partial \theta}}, & s(\theta) \geq \delta. \end{cases} \quad (6)$$

From (6) the behavior follows directly as shown in Fig. 5.




Fig. 5. Quasi-static force build-up across Idle and Engagement.

Idle: $s(\theta) < \delta$ gives $J(\theta) = 0$ and $F_{\text{tip}} \approx 0$, yielding translation with near-zero normal force.

Engagement: $s(\theta) \geq \delta$ produces controlled force build-up governed by k and $J(\theta)$.

If $J(\theta)$ is designed to be nearly flat over the working interval by tuning link lengths and pivot locations, the small-signal gain becomes

$$\frac{dF_{\text{tip}}}{ds} \approx kJ(\theta) + k(\max\{0, s(\theta) - \delta\} + x_0) \frac{dJ}{ds} \quad (7)$$

which is approximately constant and favors a stable force-displacement slope. Given a maximum usable travel s_{max} , a conservative peak-force bound is

$$F_{\text{max}} \lesssim k \max\{0, x_0 + s_{\text{max}} - \delta\} J_{\text{max}} \quad (8)$$

which links (k, x_0, δ) and the geometric gain J to overload safety.

IV. EXPERIMENTS

We built a single-DOF prototype gripper based on the proposed design. Structural parts were 3D printed in a common plastic, revolute joints used standard bearings and fasteners, and the spring parameters followed Section III: moderate preload and stiffness k . The drive side implements an adjustable Idle-Stroke δ . Once the closure exceeds δ the mechanism enters Engagement and the spring compresses through the four-bar to generate normal force at the fingertip via the transmission gain $J(\theta)$. The prototype was mounted on a simple bench with interchangeable surfaces to cover different friction conditions. Test objects were placed with repeatable but imperfect alignment to reflect typical handling.

The evaluation targets feasibility rather than high-precision control. The gripper closes at constant speed toward the object. For $s(\theta) < \delta$ the system remains in Idle, providing a clear window for passive alignment with near-zero normal force. When $s(\theta) \geq \delta$ the force path closes, force builds smoothly, and the object is lifted. We used common items including small cubes, cylinders, thin plates, and parts with distinct surface frictions, spanning typical sizes and masses for small-scale manipulation. A trial is counted as a success if the object is stably pinched and raised to a set height without slip or drop within a short interval.

The Fig. 6 sequence shows that the Idle window preserves alignment motion without premature pushing, crossing δ triggers engagement and a gentle force ramp, and lifting proceeds with low controller burden. For irregular edges and thin plates the Idle-Stroke suppresses early hard contact and sliding. Under mild disturbance the mechanism exhibits partial backdrivability and quickly returns to the loaded state, consistent with the analysis. Limitations stem from rapid-prototyped materials and assembly tolerances, which bound the performance under high load and long duty. On very soft or adhesive surfaces a small amount of drag can appear during Idle; reducing δ or using lower-friction fingertip covers mitigates this. Overall, the observations align with the model and support the feasibility and applicability of the Idle-Stroke transmission on real hardware.




Fig. 6. Prototype and feasibility demonstration.

V. CONCLUSIONS

This paper presented a four-bar lifting mechanism with an Idle-Stroke transmission that separates alignment from force build-up. The analysis clarified how tip travel, engagement timing, and force evolution follow directly from mechanism geometry, spring stiffness, and preload together with the transmission gain. This yields a clear and reproducible mapping from design choices to force-displacement behavior, enabling straightforward parameter selection for a target load and stroke with minimal controller burden.

A 3D-printed prototype demonstrated feasibility on representative objects under modest sensing and control. Before engagement the mechanism provided passive alignment with near-zero normal force; after engagement it produced a gentle and predictable force ramp; under mild disturbance it exhibited partial backdrivability that supports overload safety. These observations align with the analytical model and highlight the practicality of the approach.

The proposed GLINT hand's design is compact, controller-light, and easy to replicate, making it suitable for tasks with pose uncertainty or varying friction. Future work will focus on miniaturization, higher-duty materials and bearings, fingertip materials for extreme surfaces, and co-design of geometry and springs to flatten the transmission gain across the working range.

REFERENCES

- [1] A. I. Weinberg, A. Shirizly, O. Azulay, and A. Sintov, "Survey of learning-based approaches for robotic in-hand manipulation," *Front. Robot. AI*, vol. 11, Nov. 2024.
- [2] Y. Yuan *et al.*, "Robot Synesthesia: In-Hand Manipulation with Visuotactile Sensing," in *2024 IEEE Int. Conf. Robot. Autom. ICRA*, May 2024, pp. 6558–6565.

- [3] B. Huang, Y. Wang, X. Yang, Y. Luo, and Y. Li, “3D-ViTac: Learning Fine-Grained Manipulation with Visuo-Tactile Sensing,” Jan. 2025.
- [4] J. Li *et al.*, “Adaptive Visuo-Tactile Fusion with Predictive Force Attention for Dexterous Manipulation,” July 2025.
- [5] Y. Tian *et al.*, “ViTaS: Visual Tactile Soft Fusion Contrastive Learning for Reinforcement Learning,” Oct. 2024.
- [6] Y. Tu, J. Jiang, S. Li, N. Hendrich, M. Li, and J. Zhang, “PoseFusion: Robust Object-in-Hand Pose Estimation with SelectLSTM,” in *2023 IEEE/RSJ Int. Conf. Intell. Robots Syst. IROS*, Oct. 2023, pp. 6839–6846.
- [7] Y. Chen, A. Sipos, M. V. der Merwe, and N. Fazeli, “Visuo-Tactile Transformers for Manipulation,” Sept. 2022.
- [8] M. Bauza, A. Bronars, Y. Hou, I. Taylor, N. Chavan-Dafle, and A. Rodriguez, “SimPLE, a visuotactile method learned in simulation to precisely pick, localize, regrasp, and place objects,” *Sci. Robot.*, vol. 9, no. 91, p. eadi8808, June 2024.
- [9] S. Suresh *et al.*, “NeuralFeels with neural fields: Visuotactile perception for in-hand manipulation,” *Sci. Robot.*, vol. 9, no. 96, p. eadl0628, Nov. 2024.
- [10] Q. Mao, Z. Liao, J. Yuan, and R. Zhu, “Multimodal tactile sensing fused with vision for dexterous robotic housekeeping,” *Nat. Commun.*, vol. 15, no. 1, p. 6871, Aug. 2024.
- [11] J. W. James and N. F. Lepora, “Slip Detection for Grasp Stabilization With a Multifingered Tactile Robot Hand,” *IEEE Trans. Robot.*, vol. 37, no. 2, pp. 506–519, Apr. 2021.
- [12] Z. Deng, Y. Jonetzko, L. Zhang, and J. Zhang, “Grasping Force Control of Multi-Fingered Robotic Hands through Tactile Sensing for Object Stabilization,” *Sensors*, vol. 20, no. 4, p. 1050, Jan. 2020.
- [13] Q. Li, O. Kroemer, Z. Su, F. F. Veiga, M. Kaboli, and H. J. Ritter, “A Review of Tactile Information: Perception and Action Through Touch,” *IEEE Trans. Robot.*, vol. 36, no. 6, pp. 1619–1634, Dec. 2020.
- [14] T. Li, Y. Yan, C. Yu, J. An, Y. Wang, and G. Chen, “A comprehensive review of robot intelligent grasping based on tactile perception,” *Robot. Comput.-Integr. Manuf.*, vol. 90, p. 102792, Dec. 2024.
- [15] W. Fan, H. Li, and D. Zhang, “CrystalTac: Vision-Based Tactile Sensor Family Fabricated via Rapid Monolithic Manufacturing,” *Cyborg Bionic Syst.*, vol. 4, p. 0231, Apr. 2025.
- [16] H. Ding, Z. Chen, T. Yang, and W. Zhang, “Semi-Peaucellier Linkage and Differential Mechanism for Linear Pinching and Self-Adaptive Grasping*,” in *2025 IEEE 21st Int. Conf. Autom. Sci. Eng. CASE*, Aug. 2025, pp. 3441–3446.

Authors’ background

Name	Prefix	Research Field	Email	Personal website
Haokai Ding	Master Student	Mechanics of Mechanisms	hk_ding@outlook.com	https://orcid.org/0009-0001-6158-9897
Haotong Luan	Master Student	Mechanics of Mechanisms	lht20060306@outlook.com	
Tao Yang	Associate Professor	Mechanics of Mechanisms	yangtao@sztu.edu.cn	
Wenzheng Zhang	Associate Professor	Mechanics of Mechanisms	wenzeng75@163.com	https://ieeexplore.ieee.org/author/37278432000

Note:

¹ This form helps us to understand your paper better; the form itself will not be published.

² Prefix: can be chosen from Master Student, PhD Candidate, Assistant Professor, Lecturer, Senior Lecturer, Associate Professor, Full Professor