

Add Books

ISBN

Name

Submit

Clear

update Books

ISBN

Name

Submit

Clear

Delete Books

ISBN

Submit

Clear

books with ISBN > 1000

- 12345 - ISBN: 12345
- u - ISBN: 1234567
- harland - ISBN: 123456789

```

1 <script setup>
2 import { ref } from 'vue'
3 import {
4   collection,
5   addDoc,
6   onSnapshot,
7   query,
8   serverTimestamp,
9   where,
0   getDocs,
1   deleteDoc,
2   doc,
3   updateDoc,
4 } from 'firebase/firestore';
5 import { auth, db } from '@firebase'
6 import BookList from '@components/BookList.vue';
7
8 const formData = ref({
9   isbn: null,
0   name: null
1 })
2
3 const updateform = ref({
4   isbn: null,
5   name: null
6 })
7
8 const deleteisbn = ref(null);
9

```

```

const submitForm = async () => {
  console.log(formData.value.isbn)
  console.log(formData.value.name)

  try {
    const isbnNumber = Number(formData.value.isbn)
    if (isNaN(isbnNumber)) {
      alert("ISBN is invalid")
      return
    }

    await addDoc(collection(db, 'books'), {
      isbn: isbnNumber,
      name: formData.value.name
    })
    formData.value.isbn = null
    formData.value.name = null

  } catch (err) {
    console.log(err)
  }

  window.location.reload()
}

```

```

<template>
  <div class="container mt-5">
    <div class="row">
      <div class="col-sm-10 col-md-8 offset-md-1 col-lg-10">
        <h1 class="text-center">Add Books</h1>
        <form @submit.prevent="submitForm">
          <div class="row mb-3">
            <div class="col-md-6 col-sm-6">
              <label for="isbn" class="form-label">ISBN</label>
              <input type="text" class="form-control" id="username" v-model="formData.isbn">
              <!-- <div v-if="errors.username" class="text-danger">{{ errors.username }}</div -->
            </div>
            <div class="col-md-6">
              <label for="name" class="form-label">Name</label>
              <input type="text" class="form-control" id="username" v-model="formData.name">
              <!-- <div v-if="errors.username" class="text-danger">{{ errors.username }}</div -->
              <!-- <div v-if="errors.gender" class="text-danger">{{ errors.gender }}</div -->
            </div>
          </div>
          <div class="text-center">
            <button type="submit" class="btn btn-primary me-2">Submit</button>
            <button type="button" class="btn btn-secondary me-2" @click="clearForm">Clear</button>
            <!-- <button type="button" class="btn btn-danger" @click="clearAll">Clear All</button -->
          </div>
        </form>
      </div>
    </div>
  </div>

```

Set 2

books

a1skXzGCPqyq...

books

a1skXzGCPqyqDISFHV8d

+ Start collection

books

+ Add document

Ue05J5y7FAcmEOZIGL3Q

a1skXzGCPqyqDISFHV8d

pZD3TQHVV0zIqg1D98aU

+ Start collection

+ Add field

isbn: 123456789

name: "harland"

Cloud Firestore / Database

books

a1skXzGCPqyqDISFHV8d

books

a1skXzGCPqyqDISFHV8d

Cloud Firestore / Database

books

pZD3TQHVV0zI...

books

pZD3TQHVV0zIqg1D98aU

+ Start collection

books

+ Add document

Ue05J5y7FAcmEOZIGL3Q

a1skXzGCPqyqDISFHV8d

pZD3TQHVV0zIqg1D98aU

+ Start collection

+ Add field

isbn: 1234567

name: "u"

Cloud Firestore / Database

books

Ue05J5y7FAcm...

books

Ue05J5y7FAcmEOZIGL3Q

+ Start collection

books

+ Add document

Ue05J5y7FAcmEOZIGL3Q

a1skXzGCPqyqDISFHV8d

pZD3TQHVV0zIqg1D98aU

+ Start collection

+ Add field

isbn: 12345

name: 12345

Task 8.2

Set 1

```
const updateForm = async () => {
  console.log(updateform.value.isbn)
  console.log(updateform.value.name)
  try {
    const isbnNumber = Number(updateform.value.isbn)
    if (isNaN(isbnNumber)) {
      alert("ISBN is invalid")
      return
    }

    const q = query(collection(db, 'books'), where('isbn', '==', isbnNumber));
    const querySnapshot = await getDocs(q);
    console.log(querySnapshot)
    if (querySnapshot.empty){
      alert("No book have the ISBN with"+ isbnNumber)
      return
    }
    querySnapshot.forEach(async (element) => {
      const bookref = element.ref;
      await updateDoc(bookref, {
        name: isbnNumber
      })
    });
    updateform.value.isbn = null
    updateform.value.name = null

  } catch (err) {
    console.log(err)
  }
  window.location.reload()
}
```

```

const deleteForm = async () => {
  // const isbnNumber = Number(deleteForm.value)
  try {
    const isbnNumber = Number(deleteForm.value)
    if (isNaN(isbnNumber)) {
      alert("ISBN is invalid")
      return
    }

    const q = query(collection(db, 'books'), where('isbn', '==', isbnNumber));
    const querySnapshot = await getDocs(q);
    if (querySnapshot.empty){
      alert("No book have the ISBN with"+ isbnNumber)
      return
    }

    await Promise.all(querySnapshot.docs.map(d => deleteDoc(d.ref)));
    deleteForm.value= null
  } catch (err) {
    console.log(err)
  }
  window.location.reload()
}

```

```

<div class="row">
  <div class="col-sm-10 col-md-8 offset-md-1 col-lg-10">
    <h1 class="text-center">update Books</h1>
    <form @submit.prevent="updateForm">
      <div class="row mb-3">
        <div class="col-md-6 col-sm-6">
          <label for="isbn" class="form-label">ISBN</label>
          <input type="text" class="form-control" id="username" v-model="updateForm.isbn">
        </div>
        <div class="col-md-6">
          <label for="name" class="form-label">Name</label>
          <input type="text" class="form-control" id="username" v-model="updateForm.name">
        </div>
      </div>
      <div class="text-center">
        <button type="submit" class="btn btn-primary me-2">Submit</button>
        <button type="button" class="btn btn-secondary me-2" @click="clearForm">Clear</button>
      </div>
    </form>
  </div>
</div>

```

```

<div class="row">
  <div class="col-sm-10 col-md-8 offset-md-1 col-lg-10">
    <h1 class="text-center">Delete Books</h1>
    <form @submit.prevent="deleteForm">
      <div class="row mb-3">
        <div class="col-md-6 col-sm-6">
          <label for="isbn" class="form-label">ISBN</label>
          <input type="text" class="form-control" id="username" v-model="deleteisbn">
          <!-- <div v-if="errors.username" class="text-danger">{{ errors.username }}</div> -->
        </div>
      </div>
      <div class="text-center">
        <button type="submit" class="btn btn-primary me-2">Submit</button>
        <button type="button" class="btn btn-secondary me-2" @click="clearForm">Clear</button>
        <!-- <button type="button" class="btn btn-danger" @click="clearAll">Clear All</button> -->
      </div>
    </form>
  </div>
</div>

```

Set 2

books with ISBN > 1000

- ISBN: 2456-high order
- ISBN: 12345-12345
- ISBN: 123456-null
- ISBN: 333333-higher
- ISBN: 1234567-u
- ISBN: 123456789-harland

books with ISBN > 1000 (ordered)

- ISBN: 123456789-harland
- ISBN: 1234567-u
- ISBN: 333333-higher
- ISBN: 123456-null
- ISBN: 12345-12345
- ISBN: 2456-high order

books with ISBN > 1000 (only shown 3)

- ISBN: 2456-high order
- ISBN: 12345-12345
- ISBN: 123456-null

```
const fetchOrderedBooks = async () => {
  try {
    const q = query(collection(db, 'books'), where('isbn', '>', 100), orderBy(['isbn', 'desc']));
    const querySnapshot = await getDocs(q);

    const booksArray = [];
    querySnapshot.forEach(element => {
      booksArray.push({ id: element.id, ...element.data() })
    });
    console.log(booksArray)
    orderedBooks.value = booksArray;
  } catch (err) {
    console.log(err)
  }
}

const fetchLimitedBooks = async () => {
  try {
    const q = query(collection(db, 'books'), where('isbn', '>', 100), limit(3));
    const querySnapshot = await getDocs(q);

    const booksArray = [];
    querySnapshot.forEach(element => {
      booksArray.push({ id: element.id, ...element.data() })
    });
    console.log(booksArray)
    limitedBooks.value = booksArray;
  } catch (err) {
    console.log(err)
  }
}
```

```

<template>
  <div>
    <h1>books with ISBN > 1000</h1>
    <ul>
      <li v-for="book in books" :key="book.id">
        ISBN: {{ book.isbn }}-{{ book.name }}
      </li>
    </ul>
  </div>

  <div>
    <h1>books with ISBN > 1000 (ordered)</h1>
    <ul>
      <li v-for="book in orderedBooks" :key="book.id">
        ISBN: {{ book.isbn }}-{{ book.name }}
      </li>
    </ul>
  </div>

  <div>
    <h1>books with ISBN > 1000 (only shown 3)</h1>
    <ul>
      <li v-for="book in limitedBooks" :key="book.id">
        ISBN: {{ book.isbn }}-{{ book.name }} </li>
    </ul>
  </div>
</template>

```

GITHUB submission:

The efolio submission for lab 7 and lab 8 are mixed on GitHub.