Lecture 7: Neural Networks



https://journals.plos.org/plosone/article/figure/image?download&size=large&id=info:doi/10.1371/journal.pone.0141357.g001

Haiping Lu

YouTube Playlist: https://www.youtube.com/c/HaipingLu/

COM4059/6059: MLAI20@The University of Sheffield

Week 7 Contents / Objectives

- Learning with Neurons
- Neural Networks (NNs)
- NN Decision Boundary & Features
- Convolutional NN Basics
- Convolutional NN Unboxing

Week 7 Contents / Objectives

- **Learning with Neurons**
- Neural Networks (NNs)
- NN Decision Boundary & Features
- Convolutional NN Basics
- Convolutional NN Unboxing

Did you know ?

Pigeons identify Breast Cancer



Just as well as radiologists

https://pbs.twimg.com/media/DqczsWhX4AErP0h.jpg:large

https://www.youtube.com/watch?v=flzGjnJLyS0

The Neuron Metaphor

- Neurons
  - Accept information from multiple inputs
  - Transmit information to other neurons
- Multiply inputs by weights along edges
- Apply some function to the inputs at each node





A Neuron Analogous to the Brain



Neural Network

- Network of neurons
- Linear neuron $w_0 + w_1x_1 + w_2x_2 + w_3x_3$



Activation Functions

- Commonly used activation functions

- Sigmoid: $\sigma(z) = \frac{1}{1+\exp(-z)}$
- Tanh: $\tanh(z) = \frac{\exp(z)-\exp(-z)}{\exp(z)+\exp(-z)}$
- ReLU (Rectified Linear Unit): $\mathrm{ReLU}(z) = \max(0, z)$







Computation in Neural Networks

- Forward pass
  - Making **prediction**s (**decision**s)
  - Plug in the input x, get the output y



output units

hidden units

input units

$$\mathbf{o} = g\left(\left(W^{(2)}\right)^T \boldsymbol{h} + b^{(2)}\right)$$

$$\mathbf{h} = g\left(\left(W^{(1)}\right)^T \boldsymbol{x} + b^{(1)}\right)$$

- Backward pass (backpropagation for optimisation)
  - Compute the gradient of the **cost** (**loss**/**error**) function with respect to the weights to find good values for weights

Autograd: Chain Rule

- Univariate chain rule

$$\frac{d}{dt}g\big(f(t)\big) = \frac{dg}{df}\cdot\frac{df}{dt}$$

- Multivariate chain rule

$$\frac{\partial g}{\partial x} = \sum \frac{\partial g}{\partial f_i}\frac{\partial f_i}{\partial x}$$



Week 7 Contents / Objectives

- Learning with Neurons
- **Neural Networks (NNs)**
- NN Decision Boundary & Features
- Convolutional NN Basics
- Convolutional NN Unboxing

AlexNet for ImageNet LSVRC-2010

Input image (pixels)

- Five convolutional layers (w/max-pooling)
- Three fully connected layers

1000-way softmax



Data, Model, Metric for Learning

1. Given training data:

$$\{\boldsymbol{x}_i, \boldsymbol{y}_i\}_{i=1}^{N}$$

Face *Face* *Not a face*



2. Choose each of these:

– Decision function/model

$$\hat{\boldsymbol{y}} = f_{\boldsymbol{\theta}}(\boldsymbol{x}_i)$$

Examples: Linear regression, Logistic regression, Neural Network

– Loss function/metric

$$\ell(\hat{\boldsymbol{y}}, \boldsymbol{y}_i) \in \mathbb{R}$$

Examples: Mean-squared error, Cross Entropy

Data, Model, Metric, Optimisation

1. Given training data:

$$\{\boldsymbol{x}_i, \boldsymbol{y}_i\}_{i=1}^{N}$$

2. Choose each of these:

- Decision function/model

$$\hat{\boldsymbol{y}} = f_{\boldsymbol{\theta}}(\boldsymbol{x}_i)$$

- Loss function/metric

$$\ell(\hat{\boldsymbol{y}}, \boldsymbol{y}_i) \in \mathbb{R}$$

3. Define goal:

- Objective function

$$\boldsymbol{\theta}^* = \arg\min_{\boldsymbol{\theta}} \sum_{i=1}^{N} \ell(f_{\boldsymbol{\theta}}(\boldsymbol{x}_i), \boldsymbol{y}_i)$$

4. Train/optimize with SGD: (take small steps opposite the gradient)

$$\boldsymbol{\theta}^{(t+1)} = \boldsymbol{\theta}^{(t)} - \eta_t \nabla \ell(f_{\boldsymbol{\theta}}(\boldsymbol{x}_i), \boldsymbol{y}_i)$$

Data, Model, Metric, Optimisation

1. Given training data:

$$\{\boldsymbol{x}_i, \boldsymbol{y}_i\}_{i=1}^{N}$$

2. Choose each of these:

– Decision function/mod

$$\hat{\boldsymbol{y}} = f_{\boldsymbol{\theta}}(\boldsymbol{x}_i)$$

– Loss function/metric

$$\ell(\hat{\boldsymbol{y}}, \boldsymbol{y}_i) \in \mathbb{R}$$

3. Define goal:

– Objective function

$$(f_{\boldsymbol{\theta}}(\boldsymbol{x}_i), \boldsymbol{y}_i)$$

*Compute **gradients** via backpropagation Using automatic differentiation*

opposite the gradient)

$$\boldsymbol{\theta}^{(t} \quad {}^{(t)} - \eta_t \nabla \ell(f_{\boldsymbol{\theta}}(\boldsymbol{x}_i), \boldsymbol{y}_i)$$

Linear Regression Model (x → y)

$$y = h_{\boldsymbol{\theta}}(\boldsymbol{x}) = \sigma(\boldsymbol{\theta}^T \boldsymbol{x})$$

where $\sigma(a) = a$



Linear Regression Neural Networks

- **Question**: What happens when we arrange **linear neurons** in a multilayer network?



Linear Regression Neural Networks

- Nothing special happens.
  - The product of two linear transformations is itself a linear transformation.



$$f(x,\vec{\theta}) = \sum_{i=0}^{D} \theta_{1,i} \sum_{n=0}^{N-1} \theta_{0,i,n} x_n$$

$$f(x,\vec{\theta}) = \sum_{i=0}^{D} \theta_{1,i} [\theta_{0,i}^T \vec{x}]$$

$$\boxed{f(x,\vec{\theta}) = \sum_{i=0}^{D} [\hat{\theta}_i^T \vec{x}]}$$

Logistic Regression Model (x → y)

$$y = h_{\boldsymbol{\theta}}(\boldsymbol{x}) = \sigma(\boldsymbol{\theta}^T \boldsymbol{x})$$

where $\sigma(a) = \dfrac{1}{1 + \exp(-a)}$



Output

y

θ_1 θ_2 θ_3 θ_M

Input

x_1 x_2 x_3 ... x_M

Logistic Regression Neural Networks



Independent (input) variables

Weights (Coefficients)

Hidden layer

Weights (Coefficients)

Dependent (output) variable (Prediction /estimate/ target)

Week 7 Contents / Objectives

- Learning with Neurons
- Neural Networks (NNs)
- **NN Decision Boundary & Features**
- Convolutional NN Basics
- Convolutional NN Unboxing

Hidden Layers → Decisions





Decision Boundary

- 0 hidden layers: linear classifier
  - Hyperplanes



Example from to Eric Postma via Jason Eisner

Decision Boundary

- 1 hidden layer
  - Boundary of **convex** region (open or closed)





Example from to Eric Postma via Jason Eisner

Decision Boundary



- 2 hidden layers
  - Combinations of convex regions



Example from to Eric Postma via Jason Eisner

Deeper Networks



Different Levels of Abstraction

- We don’t know the “right” levels of abstraction
- So let the model figure it out!



Example from Honglak Lee (NeurIPS 2010)

Different Levels of Abstraction

Face Recognition:

- Deep Network can build up increasingly higher levels of abstraction
- Lines, parts, regions



Example from Honglak Lee (NeurIPS 2010)

Different Levels of Abstraction





Example from Honglak Lee (NeurIPS 2010)

Machine Learning Ingredients

- **Data**: + pre-processing (& visualisation), e.g., $\mathcal{N}(0,1)$
- **Model**
  - Structure ~ Architecture ← expert knowledge
    - Must **specify** before ML, can optimise via cross validation (CV)
  - **Hyper-parameter**, e.g., prior, #degree, layer ← knowledge
    - Must **specify** (choices) and can optimise via CV (***tuning***)
  - Parameters (theta)
    - Compute/learn parameter, e.g., **weights**, bias ← optimisation alg.
- Evaluation **metric** (what's best): loss/error function
- **Optimisation**: (how to find the best) learnable parameters

Neural Network Training



Data → Model → Metric →Optimisation



https://slazebni.cs.illinois.edu/fall18/assignment2/nn.gif

Neural Network Ingredients

- **Data**: + pre-processing, e.g., $\mathcal{N}(0,1)$
- **Model**
  - Structure/Architecture: layered network
  - **Hyper-parameter**: layer specs, e.g. #layers, #neurons/units, activation function
  - Parameters (theta): layer weights & biases
- Evaluation metric (loss): max likelihood (min NLL), cross-entropy, etc.
- Optimisation: backpropagation (gradient-based)

Week 7 Contents / Objectives

- Learning with Neurons
- Neural Networks (NNs)
- NN Decision Boundary & Features
- **Convolutional NN Basics**
- Convolutional NN Unboxing

Fully Connected (FC) Layer

- Linear layers such as linear/logistic regression
- What if our network is bigger?
  - Input image: 200 × 200 pixels, first hidden layer: 500 units
  - **Question**: How many weights for input→1st hidden?

    20 million
  - **Q**: Why is using an FC layer problematic for images?
    - Computing predictions (forward pass) will take a long time
    - A large number of weights requires a lot of training data to avoid overfitting
    - Small shift in image can result in large change in prediction
    - Not making use of the image geometry

Convolutional Neural Network

- Key ideas:
  - Locally-connected layers: look for local features in small regions of the image
  - Weight-sharing: detect the same local features across the entire image





Weight Sharing

- Each neuron on the higher layer detects the same feature, but in different locations on the lower layer

The red connections all have the same weight.



"Detecting" = the output (activation) is high if the feature is present

"Feature" = something in the image, like an edge, blob or shape

Forward Pass Example (Single Channel)



https://developer.nvidia.com/sites/default/files/pictures/2018/convolution-2.gif

- The kernel/filter (yellow) contains the trainable weights. In the above, the kernel *size* is 3 ×3.
- The "*convolved features*" is another term for "convolution output"

Example of convolution

Greyscale input image: 7 ×7

Convolution **kernel**: 3 × 3

Questions:

- How many units are in the output?
- How many trainable weights are there?



Convolution in RGB for colour images



The kernel: a 3-D tensor! In this example, the kernel has size **3** ×3 × 3.

The first number 3: the number of **input channels** or **input feature maps**

Detecting Multiple Features

- **Q**: What if we want to detect many features of the input? (e.g. **both** horizontal edges and vertical edges, and maybe even other features?)
- **A**: Have many convolutional filters!



Input image size: 3 × 32 × 32

Convolution kernel (4D): **3** × 3 × 3× **5**

- The number **3** is the number of **input channels** or **input feature maps**
- The number **5** is the number of **output channels** or **output feature maps**

Zero Padding



Add zeros around the border of the image (can add more than one pixel of zeros)

Question: Why might we want to add zero padding?

- Keep the next layer's width and height consistent with the previous
- Keep the information around the border of the image

Strided Convolution



Shift the kernel by **2** (stride=2) when computing the next output feature.

Objective: to consolidate (summarise) information

输入本来是3×3，但是通过转置卷积，
使得该层变成7×7
用3×3的kernal做卷积，得到5×5的输出

Transpose Convolution Layer



(a) Convolutional layer: the input size is $W_1 = H_1 = 5$; the receptive field $F = 3$; the convolution is performed with stride $S = 1$ and no padding ($P = 0$). The output Yis of size $W_2 = H_2 = 3$.



(b) Transposed convolutional layer: input size $W_1 = H_1 = 3$; transposed convolution with stride $S = 2$; padding with $P = 1$; and a receptive field of $F = 3$. The output Yis of size $W_2 = H_2 = 5$.

https://www.mdpi.com/2072-4292/9/6/522/htm

More at https://github.com/vdumoulin/conv_arithmetic

Week 7 Contents / Objectives

- Learning with Neurons
- Neural Networks (NNs)
- NN Decision Boundary & Features
- Convolutional NN Basics
- **Convolutional NN Unboxing**

Convolutional Neural Networks







Fully Connected Layer

32x32x3 image → stretch to 3072 x 1



Convolution Layer

Tensor: Preserve spatial structure

Filters always extend the full depth of the input volume

- 32x32x3 image



- 5x5x3 filter

- **Convolve** the filter with the image
- i.e. "slide over the image spatially, computing dot products"

Convolution Layer



32x32x3 image

5x5x3 filter w

1 number:
the result of taking a dot product between the filter and a small 5x5x3 chunk of the image
(i.e. 5*5*3 = 75-dimensional dot product + bias)

$$w^T x + b$$

Convolution Layer



Convolution Layer

consider a second, green filter



Convolution Layer

For example, if we had 6 5x5 filters, we'll get 6 separate activation maps:



We stack these up to get a "new image" of size 28x28x6!

Convolution Operation



7x7 input (spatially)
assume 3x3 filter

Convolution Operation



7x7 input (spatially)
assume 3x3 filter

Convolution Operation



7x7 input (spatially)
assume 3x3 filter

→ **5x5 output**

After three more sliding and dot products

Convolution with **Stride**



7x7 input (spatially)
assume 3x3 filter
applied **with stride 2**

Convolution with **Stride**



7x7 input (spatially)
assume 3x3 filter
applied **with stride 2**

Convolution with **Stride**



7x7 input (spatially)
assume 3x3 filter
applied **with stride 2**
→ **3x3 output!**

Convolution with **Stride**



Question: 7x7 input (spatially) assume 3x3 filter applied **with stride 3?**

doesn't fit!

cannot apply 3x3 filter on 7x7 input with stride 3 (unless ignoring parts).

Convolution – Size of output



Output size:

(N - F) / stride + 1

e.g. N = 7, F = 3:

stride 1 => (7 - 3)/1 + 1 = 5

stride 2 => (7 - 3)/2 + 1 = 3

stride 3 => (7 - 3)/3 + 1 = 2.33

Zero Padding



e.g. input 7x7
3x3 filter, applied with **stride 1**
pad with 1 pixel border => what is the output?

7x7 output!
in general, common to see CONV layers with stride 1, filters of size FxF, and zero-padding with (F-1)/2. (will preserve size spatially)
e.g. F = 3 => zero pad with 1
F = 5 => zero pad with 2
F = 7 => zero pad with 3

Convolution Shrinks

Example: 32x32 input convolved repeatedly with 5x5 filters shrinks volumes spatially! (32 → 28 → 24 ...).



Exercises

- Input volume: **32x32x3;** 10 5x5 filters with stride 1, pad 2
  - Output volume size?
  - 
  - Number of parameters for this layer?
  - 

Pooling Layer: Downsampling

- Make the representations smaller and more manageable → dimensionality reduction
- Operate over each activation map independently:



Max Pooling

Single depth slice



max pool with 2x2 filters
and stride 2



Lab 7 CNN (See notebook for details)

```
__init__(self):
super(CNN, self).__init__()
self.conv1 = nn.Conv2d(3, 6, 5) #3: #
self.pool = nn.MaxPool2d(2, 2)
self.conv2 = nn.Conv2d(6, 16, 5)
self.fc1 = nn.Linear(16 * 5 * 5, 120)
self.fc2 = nn.Linear(120, 84)
self.fc3 = nn.Linear(84, 10)

forward(self, x):
x = self.pool(F.relu(self.conv1(x)))
x = self.pool(F.relu(self.conv2(x)))
x = x.view(-1, 16 * 5 * 5)
x = F.relu(self.fc1(x))
x = F.relu(self.fc2(x))
x = self.fc3(x)
return x
```

- Initial Image Size: $3 \times 32 \times 32$
- After `conv1`: $6 \times 28 \times 28$ (32
- After Pooling: $6 \times 14 \times 14$ (ima
- After `conv2`: $16 \times 10 \times 10$ (14
- After Pooling: $16 \times 5 \times 5$ (halve
- After `fc1`: 120
- After `fc2`: 84
- After `fc3`: 10 (**= number of cla**

Acknowledgement

- The slides used materials from: *Matt Gormley, Eric Xing, Nina Balcan, Fei-Fei Li & Justin Johnson & Serena Yeung, Lisa Zhang, Michael Guerzhoy, Svetlana Lazebnik, Ismini Lourentzou, Dekai Wu*

Recommended Reading

- CS231n: Convolutional Neural Networks for Visual Recognition from Stanford (Fei-Fei Li et al.)
- The Deep Learning Book with a free official **html** version provided by the authors (Ian Goodfellow et al.)
- Convolution arithmetic

- PyTorch documentations

- The lab notebook and references

Next

Lab notebooks

Feedback (if any)

@end of the week