Aug.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	−40 °C TO +105°C(90%RH MAX)	STORAGE TEMPERATURE RANGE	−30°C TO +70°C(90%RH MAX)
	POWER	—— W	CHARACTERISTIC IMPEDANCE	50 Ω (0 TO 8 GHz)
	PECULIARITY	———	APPLICABLE CABLE	———

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		—	—
ELECTRIC CHARACTERISTICS				
CONTACT RESISTANCE	10 mA MAX (DC OR 1000 Hz).	CENTER CONTACT 20 mΩ MAX.	X	—
		OUTER CONTACT 10 mΩ MAX.	X	—
INSULATION RESISTANCE	100 V DC.	500 MΩ MIN.	X	—
VOLTAGE PROOF	200 V AC FOR 1 min.CURRENT LEAKAGE 2mA MAX.	NO FLASHOVER OR BREAKDOWN.	X	X
VOLTAGE STANDING WAVE RATIO ⚠2	FREQUENCY 0.045 TO 6 GHz.	VSWR 1.3 MAX.	X	—
	FREQUENCY 6 TO 8 GHz.	VSWR 1.4 MAX.		
INSERTION LOSS	FREQUENCY — TO — GHz	— dB MAX	—	—
MECHANICAL CHARACTERISTICS				
CONTACT INSERTION AND EXTRACTION FORCES	BY STEEL GAUGE.	INSERTION FORCE ——— N MAX.	—	—
		EXTRACTION FORCE ——— N MIN	—	—
INSERTION AND EXTRACTION FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE ——— N MAX.	—	—
		EXTRACTION FORCE ——— N MAX.	—	—
MECHANICAL OPERATION	30 TIMES INSERTIONS AND EXTRACTIONS.	1) CONTACT RESISTANCE: CENTER CONTACT 25 mΩMAX. OUTER CONTACT 15 mΩMAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
VIBRATION	FREQUENCY 10 TO 100 Hz SINGLE AMPLITUDE 1.5 mm, 59 m/s^2 AT 5 CYCLES FOR 3 DIRECTIONS.	1) NO ELECTRICAL DISCONTINUITY OF 1μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
SHOCK	735 m/s^2 DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 6 DIRECTIONS.		X	—
CABLE CLAMP ROBUSTNESS (AGAINST CABLE PULL)	APPLYING A PULL FORCE THE CABLE AXIALLY AT ——— N MAX.	1) NO WITHDRAWAL AND BREAKAGE OF CABLE. 2) NO BREAKAGE OF CLAMP.	—	—
ENVIRONMENTAL CHARACTERISTICS				
DAMP HEAT	EXPOSED AT 40 °C, 95 % TOTAL 96 h	1) INSULATION RESISTANCE: 10 MΩ MIN. (AT HIGH HUMIDITY) 2) INSULATION RESISTANCE: 500 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -40 → 5−35→ +105→ 5−35°C TIME 30 → 3 → 30 → 3 min. UNDER 5 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.	VSWR 1.3 MAX.	X	—

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
⚠2	1	DIS-D-00005074	NK.NINOMIYA	TS.NOBE	20200619

REMARK
2500PCS ／REEL

Unless otherwise specified, refer to JIS C 5402.

APPROVED	IJ.MITANI	20050105
CHECKED	MH.YAMANE	20050105
DESIGNED	NK.NINOMIYA	20050105
DRAWN	MA.SAEKI	20050105

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-302540-10

HRS	SPECIFICATION SHEET	PART NO.	U.FL-R-SMT-1(10)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL331-0472-2-10 ⚠2	1/1

FORM HD0011-2-1