

Add, Delete, Modify VLANs	
Create VLAN	<pre>config t vlan <id></pre>
	Example (to create VLAN2) <pre>config t vlan 2</pre>
Name VLAN	<pre>config t vlan <id> name <vlan's name></pre>
	Example (to create VLAN2) <pre>config t vlan 2 name AvoCafe</pre>
Assign VLAN memberships	<pre>int <port label> switchport access vlan <id> exit</pre>
	Example (to assign fa0/1 to VLAN2) <pre>int fa0/1 switchport access vlan 2 exit</pre>
Assign VLAN memberships (range)	<pre>int <port label range> switchport mode access switchport access vlan <id></pre>
	Example (to assign fa0/1, fa0/2, fa0/3 to VLAN2) <pre>int range fa0/1-3 switchport mode access switchport access vlan 2</pre>
Delete VLAN memberships	<pre>int <port label> no switchport access vlan <vlan_id></pre>
	Example (to remove fa0/1 from VLAN2) <pre>int fa0/1 no switchport access vlan 2</pre>
Delete VLAN	<pre>no vlan <vlan_id></pre>
	Example (to remove VLAN2) <pre>no vlan 2</pre>

Check VLAN Info	
Show all VLAN (brief)	show vlan br
Show specific VLAN (ID#)	show vlan id (eg. <i>show vlan 2</i>)
Show specific VLAN (name)	show vlan name (eg. <i>show vlan avocafe</i>)
Show specific VLAN (interface)	show int interface_id (eg. <i>show int fa0/1</i>)
Check all VLAN status	show int switchport

VLAN Spanning	
Set Trunk mode	<pre>config t int fa <port label> switchport mode trunk</pre> Example (to set fa0/1 as trunk) <pre>int fa0/1 switchport mode trunk</pre>
Set specific VLAN through Trunk	<pre>int fa <port label for trunk> switchport trunk allowed vlan <id></pre> Example (to allow vlan2,3,4 passthrough) <pre>int fa0/1 switchport trunk allowed vlan 2,3,4</pre>
Check Trunk status	show int trunk

Inter-VLAN Routing	
Set Trunk mode (on the switch)	<pre>config t int fa <port label> switchport mode trunk</pre>
Set dot1q (on the router)	<pre>config t int fa <port label> no shut int fa <port label for subinterfaces> encap dot1q <vlan ID> ip address <router IP> <net mask> exit</pre> Example: <pre>int fa0/1 no shut int fa0/1.2 encap dot1q 2 ip address 192.168.2.254 255.255.255.0</pre>
Step3: Check dot1q status	show run