

Advanced JavaScript

Section 3: Synchronous and Asynchronous Execution, Callbacks and Higher Order Functions & Strict Mode

1.1 Synchronous and Asynchronous Execution

JavaScript at its core is a synchronous language which means that it executes code in sequence i.e. line by line. This therefore means the JavaScript code will not execute the next line of code (i.e. statement) until the first line of code has completed execution. For example if we had two functions of functionOne and functionTwo, the functionTwo cannot execute until functionOne has completely finished its execution.

The downside of synchronous code is that it can block execution of the next code until the current function is completely finished. Asynchronous code on the other hand allows multiple code to run at the same time asynchronously without having any issues of code blocking. This therefore allows different code to execute and complete at different times regardless the order the function was called.

```
function funcOne() {  
  console.log("I am function One");  
};  
  
function funcTwo() {  
  console.log("I am function Two");  
};  
  
function loopFunc() {  
  setTimeout(function() {  
    let i = 0;  
    for(i; i < 10000; i++) {  
      // Do something on loop  
    };  
    console.log("Looping Complete");  
  }, 5000);  
};  
  
funcOne();  
loopFunc();  
funcTwo();
```

JavaScript can have asynchronous execution but it is still a single threaded language and this is due to the JavaScript Event Loop. The Event Loop does not block execution and will allow the next line of code to execute and will only call the callback function once it has completed its execution and has returned something back. The `setTimeout()` API allows us to demonstrate asynchronous code in JavaScript.

```
I am function One  
I am function Two  
Looping Complete
```

In real world websites/webapps the code will make a request to the server to either fetch or write to a database. This server request generally takes some time to complete its execution and/or return something back. While this server request is occurring you would want to move onto the next line of code and do something else (i.e. you do not want users to sit around and wait for something to happen which would make for a very poor user experience). This is how a loader spinner is added when fetching data using the asynchronous code pattern.

1.2 Callbacks and Higher Order Functions

A callback is a function that is passed to another function. This is a design pattern when we want to write code asynchronously. Functions in JavaScript are “first class objects” which means that we can pass a function as an argument in another function and later execute it inside that function.

```
setTimeout(function() {  
  console.log("I am a callback function");  
}, 1000);
```

The `setTimeout` is an example of this whereby it takes in a function which it executes after a set amount of time in milliseconds. The anonymous function is what we would call a callback function.

```
setTimeout(myCallback, 1000);  
  
function myCallback() {  
  console.log("I am a callback function");  
};
```

The `setTimeout` can also call-back a function we have declared and does not have to be an anonymous function. The first argument would be a reference to the function as an object.

The `setTimeout` function takes in two arguments the first is the function to callback whether that is an anonymous function or a reference to a function object and the second is the time the `setTimeout` should wait before it executes the function.

The `.addEventListener` is another example of a method that uses a callback function. The callback function is the second argument that gets called whenever the first argument event is triggered e.g. on a click event. Again, the `.addEventListener` can take either an anonymous function or a function object reference as the second parameter.

```
document.getElementById("button").addEventListener("click", function() {  
  console.log("Button clicked");  
});  
  
function buttonClicked() {  
  console.log("Button clicked");  
};  
  
document.getElementById("button").addEventListener("click", buttonClicked);
```

We are basically passing around a function and it looks like just a variable even though we know it is a function which is the uniqueness about JavaScript i.e. the functions are specialised objects which allows us to pass them around like a variable.

It is important to note that we do not invoke the function using the open and closed round brackets after the function name because we do not want to immediately invoke the function because we would only want to callback the function at a later time i.e. on an event or after a set timer.

A Higher Order Function is a function that takes another function as an argument or returns a function. The array object has a special method called `forEach`. This method takes in a callback function as its argument.

```
const animals = ["Cat", "Dog", "Fish", "Zebra"];

animals.forEach(function(animal) {
  console.log(animal);
});
```

The `.forEach()` method loops through each array items which we can get access to and do something with it. In the example on the left we console log each animal in the list.

The `.forEach()` is a Higher Order function because it requires to take in another function as its argument. The `forEach` method will throw a `TypeError` if a function is not passed in as an argument.

```
const animals = ["Cat", "Dog", "Fish", "Zebra"];

animals.forEach(printAnimal);

function printAnimal(animal) {
  console.log(animal);
};
```

We can also pass in a declared function into the `.forEach()` method and this will continue to work. This is demonstrated in the example on the left which achieves the same output as the anonymous function example above.

Again we do not invoke the function but pass it as a reference function object. The function will get called for each item in the array.

There are other array methods which are Higher Order Functions i.e. take in a function as its argument. For example: the `.filter()` method takes in a function as its argument. This allows us to return a subset from the array. The `.map()` method also takes in a function as its argument and this allows us to return a new array from the original array.

```
const animals = ["Cat", "Dog", "Fish", "Zebra"];

console.log(animals.filter(function(someAnimal) {
  return someAnimal.startsWith("F");
}));
```

The `.startsWith()` method is case sensitive and will return any items that matches whatever is passed in as the argument. In the example on the left this will return Fish only.

```
const animalsStartWithF = animals.filter(function(someAnimal) {
  return someAnimal.startsWith("F");
});

console.log(animalsStartWithF);
```

Note because the `.filter()` method returns a value we can assign/store this return value in a variable.

```
const people = [
  { name: "John Doe", age: 40 },
  { name: "Sue Finch", age: 55 },
  { name: "Chloe Dalton", age: 30 }
];

const peopleNames = people.map(mapPersonName);

function mapPersonName (person) {
  return person.name;
};

console.log(peopleNames);

[ 'John Doe', 'Sue Finch', 'Chloe Dalton' ]
```

In the example on the left the `.map()` function takes in a function as its argument. This can either be an anonymous function or a reference function object. This is also true for the `.filter()` example.

When using a reference function object as the argument we must not invoke the function right away for these Higher Order Functions.

The `.map()` method example returns back a new array object with only the first names extracted.

The `.map()` method is useful if we want to alter/transform the data as we extract it from the array to create a new array object (we do not have transform the data but we have the option available) while the `.filter()` method is useful for returning whatever we are looking for within the array without any alteration/transformation to the data extracted.

A Higher Order Function can also return a function inside of a function.

```
function numberStringify(num) ·{  
  ··· return num.toString();  
};  
  
const numToString = numberStringify(33);  
console.log(numToString);
```

In the example on the left we can transform a number passed into the function into a string. The `.toString()` is a built-in method that we can call in JavaScript which reruns a string representation of the data type e.g. a number type into a string type.

```
function removeFirstLetter(str) ·{  
  ··· return str.substring(1);  
};  
  
const greet = "HEllo"  
const fixedString = removeFirstLetter(greet);  
console.log(fixedString);
```

Another example of a Higher Order Function which returns a function. The `.substring()` method allows us to return a substring starting from an index. In the example on the left this will return the string starting at index 1 which is the letter E and returns all characters after this index.

The concept of Callbacks and Higher Order Functions are simple; however, they can be become used for more complex executions. We can use both Callbacks and Higher Order Functions together.

In the example on the right we have a `logMyNumber` which takes in a function as its argument. At the end of the function we can invoke the callback function. Note: we could have named this argument anything like `cb`, `something`, etc.

We have another function called `logger` which console logs. We can therefore invoke the `logMyNumber` function and pass the `logger` function as its argument. The `logger` function will be called back once the loop completes execution.

Callbacks makes our code more dynamic/flexible i.e. we can create another function that logs something different. So long as we pass to the `logMyFunction` a callback function as a reference function object correctly, it does not matter which function we pass as the callback function. This therefore makes our function more flexible as seen in the example code to the right.

```
function logMyNumber(callback) ·{  
  ··· for (let i = 0; i < 1000; i++) ·{  
    ····· // Loop  
    ·····  
    ···};  
  ··· callback();  
};  
  
function logger() ·{  
  ··· console.log("Loop Complete!");  
};  
  
function somethingDifferent() ·{  
  ··· console.log("I'm Done Looping!");  
};  
  
logMyNumber(logger);  
logMyNumber(somethingDifferent);
```