

사용 예제

index.js

```
import React from "react";
import ReactDOM from "react-dom/client";
import App from "./App";
import { BrowserRouter } from "react-router-dom";

const root = ReactDOM.createRoot(document.getElementById("root"));
root.render(
  <React.StrictMode>
    <BrowserRouter>
      <App />
    </BrowserRouter>
  </React.StrictMode>
);
```

App.js

```
import "antd/dist/antd.css";

import { Divider, Steps } from "antd";
import { useState } from "react";
const { Step } = Steps;

const App = () => {
  const [current, setCurrent] = useState(0);

  const onChange = (value) => {
    console.log("onChange:", current);
    setCurrent(value);
  };

  return (
    <>
      <Steps current={current} onChange={onChange}>
        <Step title="Step 1" description="This is a description." />
        <Step title="Step 2" description="This is a description." />
        <Step title="Step 3" description="This is a description." />
      </Steps>

      <Divider />

      <Steps current={current} onChange={onChange} direction="vertical">
        <Step title="Step 1" description="This is a description." />
        <Step title="Step 2" description="This is a description." />
      </Steps>
    </>
  );
};
```

```
      <Step title="Step 3" description="This is a description." />
    </Steps>
  </>
);
};

export default App;
```

참고 링크

- <https://ant.design/>
- <https://programming119.tistory.com/168>

실행결과

