Login (https://www.solid-run.com/my-account/)

Products ▼ Solutions (https://www.solid-run.com/iot-gateway-solutions/)

Downloads (https://www.solid-run.com/downloads/) Support ▼ Company ▼

Shop (https://www.solid-run.com/shop/)

Q

\$0.00(0)

HummingBoard

 $m/free scale-imx6-family/) > Humming Board \ Family \ (https://www.solid-run.com/free scale-imx6-family/humming board/) > Humming Board \ Specifications$

Overview (https://www.solid-run.com/freescale-imx6-family/hummingboard/)

Specifications

Documentation (https://www.solid-run.com/freescale-imx6-family/hummingboard/hummingboard-documentation-block-diagram/)

	From \$98.00	From \$83.00	From \$83.00	From \$73.00
	HummingBoard-	HummingBoard-	HummingBoard	HummingBoard
SoM Model*	Edge	Gate	Рго	Base
	NXP-	NXP-	NXP-	NXP-
Memory and Storage	Freescale i.MX6 based Solo to Quad Core SoM (https://www.solid-	Freescale i.MX6 based Solo to Quad Core SoM (https://www.solid-	Freescale i.MX6 based Solo to Quad Core SoM (https://www.solid-	Freescale i.MX6 based Solo to Dual Core SoM (https://www.solid-
Connectivity	run.com/freescale- imx6- family/imx6- som/)	run.com/freescale- imx6- family/imx6- som/)	run.com/freescale- imx6- family/imx6- som/)	run.com/freescale- imx6- family/imx6- som/)
Media	Up to 2GB DDR3 uSD, eMMC	Up to 2GB DDR3 uSD	Up to 2GB DDR3 uSD, mSATA*	Up to 2GB DDR3 uSD

	(4GB), M.2 (2242)*	1xRJ-45**,	1xRJ-45**,	1xRJ-45**
I/O	1xRJ-45**, 4xUSB2.0, mPCIE with SIM card holder	4*USB2.0, mPCIE with SIM card holder	2xHost USB2.0, 2xHeader USB 2.0, mPCIE- half size	2xHost USB 2.0 HDMI-Out, SPDIF
Power	HDMI-Out, LVDS, Analog Audio	HDMI-Out MIPI-CSI-2 and MIPI-DSI, Parallel Camera	HDMI-Out, LVDS,SPDIF, Analog Audio MIPI- CSI-2	MIPI- CSI-2 Camera
Dimensions	MIPI-CSI-2 and MIPI-DSI, Parallel	Carriera	Camera	
Software	Camera (on GPIO header)	Reset Button, 36		Reset Button, 26 pins GPIO Header
Environment	Reset Button, 36 pins GPIO	pins GPIO Header, RTC with Battery	Reset Button, 26 pins GPIO Header, RTC, IR	5V, uUSB
	Header, RTC with Battery, IR	mikroBUS click interface	riedder, ivre, iiv	34, 4035
	7V-36V, 5.5mm in	7V-36V, 5.5mm in	5V, uUSB	85mmx56mm
	(Twist and Lock mechanism)	(Twist and Lock mechanism)	85mmx56mm	Linux
	·	102mmx69mm	Linux	No Enclosure
	102mmx69mm Linux	Linux	No Enclosure	Buy now (https://www.solid- run.com/?p=2737)
	Metal Enclosure (https://www.solid- run.com/wp-	Metal Enclosure (https://www.solid- run.com/wp-	Buy now (https://www.solid- run.com/?p=2786)	
	content/uploads/20 enclosure-04.jpg)	159949AL/HPLANGS/20 enclosure-04.jpg)	<u>4</u> 5/11/hummingboar	d-
	Buy now (https://www.solid- run.com/?p=4129)	Buy now (https://www.solid- run.com/?p=4953)		

^{*} Supported with SoM i2eX and above

^{** 1000} Mbps link is limited to 470Mbps actual bandwidth due to internal chip buses

NXP-Freescale iMX6 Family (https://www.solid-run.com/freescale-imx6-family/) Marvell ARMADA Family (https://www.solid-run.com/marvell-armada-family/)	:
	;
Marvell ARMADA Family (https://www.solid-run.com/marvell-armada-family/)	
	:
Intel Braswell Family (https://www.solid-run.com/intel-braswell-family/)	:
Mix & Match (https://www.solid-run.com/freescale-imx6-family/mix-match/)	:
Support	
Learning Center (https://www.solid-run.com/learning-center/)	:
SolidRun Wiki (http://wiki.solid-run.com/index.php?title=Main_Page)	:
Forums & Community (http://forum.solid-run.com/)	:
FAQ (https://www.solid-run.com/faq/)	;
Quality & Reliability (https://www.solid-run.com/longevity/)	;
Terms & Conditions (https://www.solid-run.com/terms-conditions/)	:
Warranty and Return Terms (https://www.solid-run.com/warranty-and-return-terms/)	:
Company	
About SolidRun (https://www.solid-run.com/about-solidrun/)	:
Partners (https://www.solid-run.com/partners/)	:
Resellers (https://www.solid-run.com/resellers/)	:
Careers (https://www.solid-run.com/careers/)	:
Press Room (https://www.solid-run.com/press-room/)	:
Blog (https://www.solid-run.com/blog/)	:
Brand Guidelines (https://www.solid-run.com/brand-guidelines/)	:
Fallowille	
Follow Us	