Distributed Deepfake Detection using Parallel AI Systems

Haram Arshad, Department of Computer Science, IISAT, Gujranwala

***Abstract*— The rapid advancement of generative AI has led to highly realistic deepfake videos and synthetic audio, posing significant threats to digital security and trust. Traditional detection methods struggle with generalization and robustness, especially against adversarial attacks. Recent research explores innovative approaches, including FPGA-accelerated quantized models for efficient deepfake classification, spatial-temporal inconsistency learning to identify forged videos, and hybrid CNN-Transformer architectures for improved generalization. Additionally, novel audio deepfake detection techniques leverage physical models like the Doppler effect and drumhead vibrations to enhance accuracy. Another promising method, Disjoint Diffusion Deepfake Detection (D4), employs frequency-based partitioning to improve adversarial robustness. These distributed and parallel AI-driven solutions demonstrate significant improvements in detection accuracy, speed, and resilience against evolving deepfake threats..**

Keywords*— *Distributed Systems, Parallel Processing, Deepfake Detection, FPGA Acceleration, Vision Transformer (ViT), Adversarial Robustness, Spatial-Temporal Analysis.

I. INTRODUCTION

In recent years, rapid advancements in generative artificial intelligence (AI) models—especially deep learning techniques like Generative Adversarial Networks (GANs), Variational Autoencoders (VAEs), and Diffusion Models—have led to the creation of extremely realistic fake digital content known as *deepfakes*. Deepfakes involve the artificial manipulation or generation of audio, video, and images to mislead viewers by imitating real individuals' likenesses or voices. These manipulations are often indistinguishable to the human eye or ear, making them particularly dangerous in today's media-driven society. While such technology holds promise for creative industries, advertising, education, and entertainment, its misuse poses severe threats to personal privacy, public trust, social security, and even political stability.

What makes this threat more critical is the speed and accessibility with which these deepfakes can now be created. With easy-to-use tools and free online models, even individuals with limited technical expertise can generate convincing fake content. The rapid democratization of generative AI tools means the line between truth and fiction in digital media is becoming increasingly blurred. The need for robust, scalable, and intelligent detection systems has never been more urgent, particularly as these technologies continue to evolve at a pace faster than our defenses.

Field and Background

This research falls under a multidisciplinary domain that intersects *Parallel and Distributed Systems*, *Cybersecurity*, and *AI-based Signal Processing*. It combines concepts from machine learning, computer architecture, and real-time analytics to create scalable solutions for one of the most pressing challenges in digital security. Traditional deepfake detectors generally operate on standalone systems using deep learning models trained on pre-collected datasets. However, these detectors struggle to handle the increasing volume, diversity, and complexity of multimedia content generated daily across social media platforms, surveillance systems, and communication channels.

Moreover, the existing models are resource-intensive and often constrained by the hardware capabilities of a single machine. As the demand for real-time detection across massive datasets grows, the limitations of single-node systems become increasingly apparent. Distributed systems offer a compelling solution by enabling multiple computing nodes to work collaboratively, distributing the computational load and memory requirements across machines. Parallel AI systems, which make use of multi-threaded CPU cores, GPUs, FPGAs, or TPUs, can significantly reduce training and inference time by processing multiple tasks simultaneously.

The combination of these two technologies—distributed computing and parallel AI—forms the backbone of our proposed detection infrastructure.

Not only do they address the speed and scalability issues, but they also improve reliability by incorporating fault-tolerant mechanisms and supporting heterogeneous processing environments.

Historical Context and Evolving Threats

The concept of media manipulation is not new, but the emergence of deepfakes marks a significant escalation in both realism and accessibility. Initially, deepfakes appeared as novelty tools for swapping faces in short videos, often shared for comedic effect. However, the capabilities of generative AI quickly outgrew these benign applications. Today, deepfakes are used to impersonate celebrities, defame public figures, commit fraud, and manipulate public opinion.

Audio deepfakes have proven to be particularly insidious due to their subtlety and ease of integration into existing communication systems. For example, attackers have successfully used AI-generated voices to impersonate executives and instruct employees to carry out unauthorized financial transactions. This highlights the potential of deepfakes not only as tools of deception but also as instruments of financial and geopolitical disruption.

Early detection approaches focused on visual artifacts such as mismatched shadows, lip-sync errors, and abnormal eye movements. However, these techniques are no longer effective against high-resolution deepfakes produced by cutting-edge GANs and diffusion models. The next generation of detection systems must therefore go beyond surface-level inconsistencies and analyze deeper signals embedded in audio and visual content—signals that are often imperceptible to the human eye but can be detected by AI models trained on complex patterns and temporal dynamics.

Problem Statement

Despite considerable progress in recent years, deepfake detection systems still face several unresolved challenges:

- **Generalization Issues**: Most detection models are trained on specific datasets and often fail to perform well when faced with deepfakes generated using different methods or under different lighting, angles, or voices.
- **Scalability Constraints**: With billions of images and videos uploaded to the internet daily, it is not feasible to rely on centralized detection systems alone. A scalable architecture capable of parallel and distributed detection is essential.
- **Adversarial Vulnerability**: Deep learning-based detectors are susceptible to adversarial attacks. Slight, carefully crafted perturbations—often invisible to humans—can completely fool these models, rendering them unreliable in high-risk environments.
- **Computational Costs**: Models with high accuracy often require large computational resources, making them unsuitable for real-time or edge deployment.
- **Lack of Multi-Modal Integration**: Many detectors are modality-specific, meaning they can analyze either video or audio but not both together. This weakens their effectiveness in analyzing real-world deepfakes that typically involve multiple sensory modalities.

These challenges necessitate a holistic approach that combines innovation in algorithm design, system architecture, and hardware optimization.

Research Direction and Motivation

This research proposes a comprehensive framework for *Distributed Deepfake Detection using Parallel AI Systems*. The key objective is to build a modular and scalable system in which various specialized deepfake detection algorithms—addressing both audio and video content—can operate in parallel across distributed hardware environments. Each node in the distributed network can process a segment of incoming data, analyze it using optimized AI models, and feed the results back to a central decision engine. This setup reduces bottlenecks, increases throughput, and supports real-time decision-making.

Recent techniques provide valuable inspiration. For instance, **VoiceRadar**, which integrates principles from wave physics like the Doppler effect and drumhead vibrations, can detect micro-frequency anomalies in AI-generated audio.

Similarly, architectures like **U-YNet**, which combines segmentation and classification on FPGA-accelerated platforms, demonstrate how hardware-aware designs can significantly boost real-time detection of video deepfakes.

In addressing adversarial robustness, ensemble models such as **D4** partition the frequency domain to prevent single-point failures and significantly lower the success rate of attacks. By incorporating such specialized methods into a larger distributed system, it becomes possible to monitor high-traffic digital environments efficiently and with high confidence.

This direction not only enables better detection accuracy and speed but also contributes to broader goals in AI safety, digital trust, and media integrity. The resulting system would be well-suited for deployment in government cybersecurity operations, social media moderation pipelines, media forensics labs, and other mission-critical environments where deepfake threats are most damaging.

.

II. METHODS

This section reviews the approaches and methodologies used across the five selected research papers on deepfake detection. Each paper introduces a unique technique or architecture to detect manipulated audio or visual content using either handcrafted features, deep learning, signal processing, or hybrid methods. Below is a summary of the methodologies, presented as a review of each individual paper.

1) Deepfake CLI – FPGA-Accelerated Detection with U-YNet

The first research paper proposes **Deepfake CLI**, a novel framework that combines software and hardware optimization to accelerate deepfake detection using FPGAs. The methodology is divided into two primary components: software implementation and hardware deployment. On the software side, the authors implemented a multitask deep learning model named **U-YNet**, capable of simultaneously performing classification and segmentation. The backbone architecture is based on UNet, where features extracted by the encoder are fed into both the segmentation decoder and a parallel classification branch. The model was trained using the **DFDC dataset**, the largest benchmark for deepfakes, though it lacked segmentation masks. To address this, the researchers generated masks by computing the pixel-wise difference between real and fake frames. A data leakage issue emerged due to face repetition across training and testing sets, which was resolved by clustering similar faces and restructuring the dataset to prevent overlap. The model was trained using a combined cross-entropy loss (for segmentation) and binary cross-entropy loss (for classification), optimized using Adam over 40 epochs on NVIDIA DGX-1.

On the hardware front, the focus was to enable real-time inference by deploying the model on a **Xilinx VCK5000 FPGA board**. This involved a three-step hardware pipeline: **quantization**, **compilation**, and **inference**. First, the trained FP32 model was quantized to **INT8** using Vitis AI's post-training quantization, reducing computational load while maintaining accuracy. Then, the quantized model was compiled for the DPU variant specific to the VCK5000 using the Vitis-AI compiler, which optimized instruction sets and reduced memory footprint. In the final inference step, real-time testing was performed using Vitis AI Runtime (VART), processing image batches for classification and segmentation. The system achieved **316.80 FPS** for classification with **93% accuracy**, and a significantly higher **775 FPS** for the segmentation-only variant. Benchmarking showed superior performance compared to GPU nodes like Nvidia Tesla T4 and V100, emphasizing the advantage of a hardware-aware deepfake detection model optimized for FPGAs.

2) Temporal and Spectral Feature Fusion for Audio Deepfakes

The authors of VoiceRadar present a physics-inspired framework for deepfake audio detection by modeling how sound waves behave in real physical systems. They use two key concepts: the **Doppler Effect** and **drumhead vibrations**, to analyze differences in micro-frequency patterns between human and AI-generated voices. First, the system converts input audio into embeddings using the HuBERT model and then analyzes the frequency distribution through three types of motion—**translational**, **rotational**, and

vibrational—using the mathematical properties of Bessel functions. These micro-frequencies are then combined to compute the observed frequency using the Doppler equation, capturing subtle variations in audio signals. A physics-augmented deep neural network is trained using this frequency information as a regularizing factor in the loss function, helping it distinguish between natural and synthetic audio. Finally, the trained model is used to infer whether a given audio sample is genuine or AI-generated.

3) CNN-Based Visual Artifact Detection with Attention

This study introduces a novel approach to DeepFake video detection by focusing on spatial and temporal inconsistencies that arise from frame-by-frame face manipulation. The authors treat the problem as a binary classification task and propose a modular framework called the **Spatiotemporal Inconsistency Learning (STIL) block**, which is embedded into a ResNet backbone. The STIL block consists of three specialized modules: the **Spatial Inconsistency Module (SIM)** to detect artifacts and blending irregularities within single frames, the **Temporal Inconsistency Module (TIM)** to identify frame-to-frame anomalies such as facial jittering using orthogonal temporal differences, and the **Information Supplement Module (ISM)** to bridge spatial and temporal features for enhanced detection performance. To ensure efficiency, the input is split along channels and processed in two separate pathways. SIM uses multi-scale convolutions and pooling to extract spatial anomalies, while TIM leverages directional temporal difference maps (horizontal and vertical) without introducing extra parameters. ISM supplements TIM using features from SIM through attention-weighted fusion. The model is trained using 8-frame video sequences and evaluated on multiple public datasets (FF++, Celeb-DF, DFDC, WildDeepfake). Through comprehensive experiments and ablation studies, the authors demonstrate that STIL significantly improves detection accuracy and generalization, especially under low-quality or cross-dataset conditions.s.

4) Hybrid CNN-ViT Model (HCiT)

The fourth paper introduces a hybrid deepfake detection framework called **HCiT (Hybrid CNN–Vision Transformer)**, which integrates Convolutional Neural Networks (CNNs) and Vision Transformers (ViTs) to exploit both local and global feature representations. The process begins with **face detection and cropping** using the Dlib library to extract aligned face regions from video frames, ensuring the focus remains on manipulated facial areas while discarding irrelevant background content. These cropped images are passed through a **CNN backbone**, specifically the Xception network, pre-trained on ImageNet and fine-tuned on deepfake datasets, to extract low-level spatial features. Rather than feeding raw image patches into the ViT, the model utilizes **CNN-extracted feature maps** as inputs to the transformer module, allowing it to capture long-range dependencies via self-attention mechanisms. The transformer encoder, equipped with positional embeddings and a classification token, processes these features through stacked layers of multi-head self-attention and MLP blocks. Finally, a softmax classifier predicts whether a given video segment is real or fake. This **hybrid design combines the spatial efficiency of CNNs with the contextual modeling power of ViTs**, resulting in improved detection performance with reduced computational cost. The method is evaluated on benchmark datasets including FaceForensics++, DFDC-preview, and Celeb-DF, demonstrating high accuracy, robustness, and generalization..

5) Frequency-Partitioned Ensemble Learning (D4)

The authors propose **D4**, a robust deepfake detection framework that leverages **frequency-space redundancy** and ensemble learning to detect diffusion-generated fake images, even under adversarial conditions. Unlike prior approaches that use entire feature sets or diverse architectures, D4 focuses on **disjoint frequency partitions** within the Discrete Cosine Transform (DCT) spectrum of images. The insight is that deepfakes contain discriminative artifacts widely distributed across frequency bands — and this **redundancy** can be exploited to build independent, non-overlapping models.

In the D4 pipeline, the DCT spectrum of each input image is divided into frequency bands using a **saliency-based partitioning scheme**. Each partition is then fed into a dedicated CNN model trained only on that subset, resulting in multiple **independently adversarially-trained detectors**. A **voting-based ensemble mechanism** aggregates their predictions to make the final classification. This partitioning ensures that an adversarial attack must simultaneously perturb several distinct feature spaces — significantly increasing the robustness of the system.

Theoretical analysis further supports the claim that such a design reduces the **shared adversarial subspace**, making it harder for adversaries to fool the ensemble. Experiments show that D4 outperforms prior methods on deepfakes generated by both GANs and diffusion models, while remaining resilient to black-box adversarial attacks and requiring **no additional inference-time overhead**.

III. Results

Each paper brings a unique strategy to the complex challenge of deepfake detection, targeting different modalities, adversarial threats, and deployment environments. These diverse approaches reflect the growing demand for reliable and efficient detection systems, especially as generative models continue to evolve in sophistication.

Deepfake CLI delivers outstanding performance through a combination of multitask deep learning and hardware-level acceleration. Its U-YNet architecture performs both classification and segmentation, and the deployment of this model on a Xilinx VCK5000 FPGA significantly enhances speed without compromising accuracy. The model reaches a real-time throughput of **775 frames per second for segmentation** and **316.8 FPS for classification**, alongside a **classification accuracy of 93%**. These results far exceed those of common GPU platforms like Nvidia Tesla T4 and V100. The efficiency comes from careful quantization (FP32 to INT8) and instruction-level optimization using the Vitis AI compiler. This makes Deepfake CLI a strong candidate for use in **real-time surveillance systems, edge computing environments, and embedded security hardware** where both speed and precision are non-negotiable.

Paper	Modality	Key Result	Strength
Deepfake CLI	Video (Frames)	93% accuracy, 775 FPS	Real-time FPGA acceleration
VoiceRadar	Audio	Frequency-level anomaly detection	Physics-based, robust voice spoof detection
STIL	Video (Sequences)	High accuracy on FF++, DFDC, Celeb-DF	Handles spatial & temporal inconsistencies
HCiT	Video (Faces)	High detection with low cost	Combines local CNN + global ViT features
D4	Images	Adversarially robust ensemble	Defends against black-box attacks

VoiceRadar, on the other hand, addresses a less-charted territory: **audio-based deepfake detection**. Unlike traditional classifiers that analyze raw audio waveforms or spectrograms, this method introduces a **physics-inspired approach** grounded in real-world audio propagation phenomena. Using HuBERT embeddings and simulating Doppler shifts and vibrational behaviors (such as those of a drumhead), the system captures **micro-frequency fluctuations** that are typically ignored by AI voice generators. While the authors do not present exact accuracy percentages, the proposed model is shown to detect frequency-level inconsistencies that **humans and basic classifiers overlook**. The application of Bessel functions and frequency distribution modeling in a deep learning context gives VoiceRadar a **distinct edge in scenarios like voice biometric systems, fraud detection in voice assistants, or synthetic speech in video manipulation**.

The **STIL framework** (Spatiotemporal Inconsistency Learning) tackles **video-based deepfakes**, particularly those involving facial manipulation across multiple frames. The model is built around three modules: the Spatial Inconsistency Module (SIM), the Temporal

Inconsistency Module (TIM), and the Information Supplement Module (ISM), each contributing to identifying different types of tampering. The system processes 8-frame sequences and cleverly splits data along channels for dual-path analysis — one handling pixel-level artifacts and the other capturing temporal disruptions such as jitter and motion discontinuities. Evaluation was performed on leading public datasets like **FaceForensics++, DFDC, WildDeepfake, and Celeb-DF**, where STIL consistently outperformed baseline models. Its ability to generalize well across multiple datasets and perform under low-resolution or noisy video conditions makes it a **robust and scalable solution** for deployment in online video platforms, fake news detection tools, and media integrity monitoring systems.

The fourth paper proposes **HCiT**, a hybrid architecture that merges the **local spatial feature strength of CNNs (specifically the Xception network)** with the **global modeling capability of Vision Transformers (ViTs)**. By using CNNs to extract low-level features before passing them to a ViT encoder, HCiT maintains computational efficiency while gaining the benefits of self-attention for long-range dependency modeling. Evaluated on challenging datasets including **FaceForensics++, DFDC-preview, and Celeb-DF**, HCiT demonstrated **strong performance and generalization**, particularly in detecting **subtle manipulations** such as lighting inconsistencies, boundary blending, or semantic mismatches in facial expressions. Moreover, by replacing raw image tokenization with pre-extracted CNN features, the model reduces overall complexity and becomes suitable for **real-world systems where processing power and memory are limited** — such as smartphone applications or browser-based detection tools.

Finally, **D4** introduces a novel ensemble-based detection framework that is specifically optimized for **robustness against adversarial attacks**. Instead of combining different model architectures, D4 partitions the **frequency-space (using the Discrete Cosine Transform)** into disjoint subsets, each fed into its own CNN model. This approach leverages the observation that deepfake artifacts are **redundantly distributed across frequency bands**, allowing each model to learn distinct yet valuable signals. To ensure balance and resilience, **saliency-based partitioning** assigns important frequencies to different models fairly. During inference, a **voting mechanism** is used to determine whether an image is real or fake. Theoretical analysis shows that this design substantially reduces the **shared adversarial subspace**, making it difficult for attackers to fool the entire ensemble. Despite being adversarially trained, the D4 framework adds **no extra inference-time cost**, which is a major advantage for practical deployment. D4 significantly outperforms traditional ensemble and single-model detectors on both **GAN-generated and diffusion-generated images**, especially under black-box conditions, making it an excellent fit for **secure content moderation systems, high-risk digital forensics, and platform-scale image verification**.

IV. CONCLUSION

This review analyzed five innovative research papers addressing the multifaceted challenge of deepfake detection across both audio and visual domains. Each approach offers a unique perspective and solution, combining deep learning, signal processing, hybrid modeling, and hardware optimization to improve detection accuracy, robustness, and efficiency.

The Deepfake CLI framework stands out for its real-time performance through FPGA-based acceleration. By deploying a multitask deep learning model (U-YNet) on the Xilinx VCK5000, it achieved high throughput (775 FPS for segmentation) and 93% classification accuracy, proving ideal for real-time detection in high-volume environments.

VoiceRadar took a novel route by using physics-inspired modeling of audio signals, detecting micro-frequency anomalies derived from Doppler and vibrational effects. Though lacking standard performance metrics, it shows potential for detecting subtle audio deepfakes in security-focused applications like voice authentication.

The STIL approach handled video-based deepfakes by targeting inconsistencies both within and across frames using spatial and temporal modules. Its success across various datasets and

challenging quality conditions highlights its robustness and adaptability for practical use on internet content and social media.

The HCiT framework integrated CNNs and Vision Transformers to combine spatial detail with global context. By focusing solely on facial regions and leveraging ViTs for long-range attention, it maintained strong detection accuracy with improved efficiency—well-suited for mobile and resource-constrained systems.

D4 provided the most adversarially robust visual detection model, using frequency-partitioned ensembles based on the Discrete Cosine Transform. Its disjoint training and voting-based ensemble make it particularly resistant to black-box attacks, outperforming previous ensemble methods while maintaining low computational overhead.

Collectively, these methods show that the future of deepfake detection lies in hybrid, resilient, and efficient systems. Cross-domain feature fusion (like audio physics or frequency analysis), hardware-awareness, and ensemble robustness emerge as key strategies. While progress is evident, continued research is essential to keep pace with increasingly sophisticated deepfake generation techniques, especially in adversarial contexts.

ACKNOWLEDGMENT

This research paper is the result of continuous learning, critical analysis, and dedicated effort during my academic journey. I undertook this task with the aim of deepening my understanding of the current challenges in deepfake detection and exploring the range of innovative solutions proposed by the research community. Throughout the process, I was able to enhance my ability to interpret complex methodologies, evaluate technical performance metrics, and extract meaningful insights from diverse academic papers. This not only expanded my grasp of deep learning, ensemble models, and adversarial robustness but also sharpened my skills in scientific writing, organization, and technical comparison.

I would like to express my sincere gratitude to my instructors and peers who provided encouragement, guidance, and motivation during the development of this paper. Their insights and feedback helped me stay focused and continuously improve the quality of my work. I also acknowledge the authors of the original research papers whose groundbreaking contributions inspired the core of this review.

This paper is dedicated to all learners and researchers committed to developing ethical AI systems and defending digital integrity in a time when media manipulation poses serious societal risks. Finally, I would like to dedicate my efforts to my family, whose support and belief in my capabilities have always been my greatest strength. Their patience, prayers, and encouragement have made this academic milestone possible, and I share this achievement with them wholeheartedly.

REFERENCES

[1] DEEPFAKE CLI: Accelerated Deepfake Detection using FPGAs Omkar Bhilare ? 1 , 2 , Rahul Singh ? 1 , 2 , Vedant Paranjape ? 1 , 2 , Sravan Chittupalli ? 1 , 2 , Shraddha Suratkar 1 , 2 , and Faruk Kazi 1 , 2*)*

[2] VoiceRadar: Voice Deepfake Detection using Micro-Frequency and Compositional Analysis Kavita Kumari† , Maryam Abbasihafshejani‡ , Alessandro Pegoraro† , Phillip Rieger† , Kamyar Arshi† , Murtuza Jadliwala‡ and Ahmad-Reza Sadeghi†. †Technical University of Darmstadt, ‡The University of Texas at San Antonio.

[3] Spatiotemporal Inconsistency Learning for DeepFake Video Detection Zhihao Gu∗ Shanghai Jiao Tong University ellery-holmes@sjtu.edu.cn Yang Chen∗ Tencent Youtu Lab wizyangchen@tencent.com Taiping Yao∗ Tencent Youtu Lab taipingyao@tencent.com Shouhong Ding† Tencent Youtu Lab ericshding@tencent.com Jilin Li Tencent Youtu Lab jerolinli@tencent.com Feiyue Huang Tencent Youtu Lab garyhuang@tencent.com Lizhuang Ma† Shanghai Jiao Tong University ma-lz@cs.sjtu.edu.cn.

[4] Deepfake Detection Using Spatiotemporal Transformer BACHIR KADDAR∗ , University of Ibn Khaldoun-Tiaret, Algeria SID AHMED FEZZA∗ , National Higher School of Telecommunications and ICT, Algeria ZAHID AKHTAR, State University of New York Polytechnic Institute, USA WASSIM HAMIDOUCHE, Univ. Rennes, INSA Rennes, CNRS, France ABDENOUR HADID, Sorbonne Center for Artiicial Intelligence, Sorbonne University Abu Dhabi, UAE JOAN SERRA-SAGRISTA, Universitat Autònoma de Barcelona, Spain].

[5] D4: Detection of Adversarial Diffusion Deepfakes Using Disjoint Ensembles Ashish Hooda†*, Neal Mangaokar‡*, Ryan Feng‡ , Kassem Fawaz† , Somesh Jha† , and Atul Prakash‡ † University of Wisconsin–Madison {ahooda,kfawaz,sjha}@wisc.edu ‡ University of Michigan {nealmgkr,rtfeng,aprakash}@umich.edu].