

GTOC12: Sustainable Asteroid Mining

TheAntipodes

GTOC12 Workshop
Beijing, China
15 January 2024

Roberto Armellin, Andrea Bellome,
Xiaoyu Fu, Harry Holt, Cristina Parigini,
Minduli Wijayatunga, Jack Yarndley



TE PŪNAHA ĀTEA
AUCKLAND SPACE INSTITUTE



Team & Roles



Roberto

- Preliminary analysis
- Team coordination



Jack

- Asteroid groups
- Beam search
- Trajectory optimization
- Post-competition developments



Harry

- Mixing chains
- Interface



Minduli

- Trajectory optimization
- Mission processing



Andrea

- Beam search




Cristina

- Mixing chains
- Solution selection
- Asteroids groups



Xiaoyu



Overview

Strategy

**Trajectory
Optimization**

**Post-Competition
Developments**

**Asteroid
Subsets & Chains**

**Solution
Selection**

Strategy


Preliminary Analysis

Simplifications

- All missions are the same
- Self-cleaning mission with collection in reverse order
- Departure and arrival legs have same $\Delta t_{d/a}$ and $\Delta v_{d/a}$
- All asteroid hops have the same Δt_{a2a} and Δv_{a2a}

Outcome

- Solutions with ~40 ships seemed achievable
- No more than 10 miners per ship
- Self-cleaning missions have some potentials (considering the small size of the groups)



Strategy: The Plan

Asteroid Pruning

- Reduce the asteroid population by **pruning** on
 - Orbital elements
 - Departure and arrival phasing

Beam Search

- Independent **forward/backward** chains construction
- Use of **low-thrust surrogate**

Mixing

- GA optimizer to build **mixed missions**
- Score maximization **including bonus**

Refinement

- Low-thrust optimization with **indirect method**
- Final manual removal/addition of asteroids

Strategy: The Reality

Asteroid Grouping

- Create **groups of asteroids** based on average minimum Lambert cost

Beam Search

- Forward and backward beam search to build **self-cleaning missions**
- Lambert cost with **heuristic penalty** (feasibility issues)

Trajectory Optimization

- Fixed-time **low-thrust** trajectory optimization using **successive convex optimization**
- Manual optimization of **rendezvous times** to increase returned mass

Solution Selection

- GA or integer programming to **select the subset of missions** to maximize the score (including bonus)

Asteroid Subsets & Chains

Subset Generation

1. Apply loose pruning cuts to asteroid dataset to reduce size



20% of asteroids cut

2. Calculate the *average lowest* Lambert Δv between each asteroid and its close neighbours throughout the competition timeframe with transfer time-of-flight from 150 to 400 days

3. Create subsets of 'near' asteroid based on a threshold

Subsets are generally **not** independent

- Combination strategies for independent subsets were explored but not extensively used in the submitted solution



Beam Search for Chain Generation


Construction is performed on each subset **one asteroid at a time** until the ship returns to Earth

- Branching new trajectory legs
- Selecting promising options for further branching
- Search also performed with reversed collection

Lambert Δv is used to cost each arc with time-of-flights between

- 500-700 days for initial and terminal transfers (adjusted Δv based on the 6 km s^{-1} provided)
- 170-250 days for intermediate transfers

Heuristic is introduced to try **improve feasibility** in low-thrust refinement



Asteroids	Beam Search	Direct Solution	
		Mined Mass (kg)	Fuel Remaining (kg)
7	lambert	609.6	-195.4
	heuristic	571.9	126.2
8	lambert	632.6	-258.6
	heuristic	620.5	-50.1
9	lambert	671.6	-391.2
	heuristic	653.6	-163.2

$$\text{tof} \geq \begin{cases} c_1 \sqrt[3]{\Delta v} & \text{(initial transfer)} \\ c_2 \sqrt[3]{\Delta v} & \text{(terminal transfer)} \\ c_3 \Delta v (1 + m_{\text{current}}/m_{\text{max}}) + hc_4 & \text{(deploying)} \\ c_5 \Delta v + hc_6 & \text{(collecting)} \end{cases}$$

Trajectory Optimization

Sequential Convex Programming

Sequential Convex Programming (SCP) can be used to solve the low-thrust trajectory optimization problems in GTOC12 **efficiently**

- Linearization around a reference trajectory using the State Transition Matrix (STM)
 - Using Lambert-based reference
 - Drawback: limited accuracy of this approximation
- Allows for a convex formulation of the trajectory optimization problem
- The key step is to **repeatedly linearize and resolve** until the dynamics are accurately expressed

$$\mathbf{x}_{n+1} = A_n \mathbf{x}_n + B_n \mathbf{u}_n + C_n$$

$$A_n = \left. \frac{\partial}{\partial \mathbf{x}} \int_{t_n}^{t_{n+1}} \dot{\mathbf{x}} dt \right|_{(\bar{\mathbf{x}}_n, \bar{\mathbf{u}}_n)}$$


$$B_n = \left. \frac{\partial}{\partial \mathbf{u}} \int_{t_n}^{t_{n+1}} \dot{\mathbf{x}} dt \right|_{(\bar{\mathbf{x}}_n, \bar{\mathbf{u}}_n)}$$

$$C_n = \bar{\mathbf{x}}_n - A_n \bar{\mathbf{x}}_n - B_n \bar{\mathbf{u}}_n$$

DifferentialEquations.jl
+ ForwardDiff.jl
= **Fast and flexible STM**
calculation



Convex Program



- All legs are linked via initial and terminal constraints with a fixed time sequence so that the **entire trajectory can be solved at once**
- Dynamics expressed in a **logged-mass form** helps to improve convergence
- The Δv provided in the initial and terminal Earth legs can be included in the state constraints. GA are included in a similar manner but were not used

Refer to paper (in review) for implementation specifics


Performance in GTOC12

ID Sequence	[0, 25279, 27464, 24025, 37117, 3750, 3196, 51591, 47047, 14516, 14516, 3750, 47047, 37117, 3196, 51591, 27464, 25279, 24025, -3]
Time Sequence (MJD)	[64458.0, 64983.0, 65148.0, 65388.0, 65643.0, 65848.0, 66043.0, 66258.0, 66588.0, 66773.0, 68023.0, 68188.0, 68448.0, 68648.0, 68808.0, 68908.0, 69083.0, 69193.0, 69353.0, 69807.0]

Example

- Best (self-cleaning) ship included in our solution
- 711.29kg returned mass 9-asteroid chain
- 5-day discretization used with zero-order-hold control interpolation


**~0.5 seconds for the
entire low-thrust solve
process per ship**




Manual Refinement

Trajectories from the beam search tended to have excess/missing fuel at termination, so we **manually edited the rendezvous times** to increase mined mass whilst remaining feasible.

- Large increase in average mined mass per ship (613.95kg to 652.38kg)
- NOT optimal in **two ways**: our time, and the solution



649.99kg refined to 711.29kg



**Post-Competition
refinement later**

Solution Selection


Selection Approach

Methodology


- GA optimizer to select the mining ships from the pool of solutions
- Half of the ships are randomly selected initially
- Repeated cycles of adding and swapping ships based on the average mass as a ranking function
- Objective function is the total mined mass




- Algorithm initially developed for combining deployment and collector sequences
- Mixed-integer programming provides superior performance and guarantees of optimality



Selection Result



Solution Timeframe




Submitted Solution

- **5th in competition**
- 27 self-cleaning ships
- 222 asteroids mined
- 8.22 ratio (222/27)
- Average mass returned per ship was **652.38kg**
- Very limited HPC use; majority of calculations using our home machines

Time of submission:
July 16, 2023 01:23 NZT

J = 15488.896



Post-Competition Developments

Problems in Approach Taken

Ship Selection

- algorithm slow and not necessarily optimal
- tends naturally to a mixed-integer programming approach

*improved **first***

Beam Search

- only a local optimization routine
- no support for mixed solutions
- reliant on custom heuristics

*improved **last***

Manual Refinement

- extremely time consuming and not at all optimal
- some ideas with convex

*improved **next***

Strategy: Post-Competition

Asteroid Grouping

- Create **large groups of asteroids** based on a **range** of statistics

MIP-based Chain Optimization

- Custom MIP formulation similar to the **optimal flow problems**
- Provides the best n chains **based on Lambert Δv**
- Able to generate mixed chains

Trajectory & Rendezvous Optimization

- Variable-time **low-thrust** trajectory optimization using **successive convex optimization**
- Finds optimal rendezvous times that **maximize returned mass**

Solution Selection

- MIP-based solution selection to handle **large amounts** of self-cleaning and mixed ships

Ship Selection with MIP

Mixed Integer Formulation

- Binary variable for each possible ship
- Constraints based on asteroids
- Benchmark: obtain all optimal ship combinations of size **1-50** from **580** mixed and self-cleaning ships
 - Gurobi (Commercial) = 0.95s
 - HiGHS (Open-Source) = 1.40s

Either case: optimal ship selection is fast

maximize $\sum ms$

$$\sum_{s \in g} s = \text{len}(g) \quad \forall g$$

$$\sum c_{a,s} s \leq 2 \quad \forall a$$

$$\sum s \leq N$$

s = ships (binary variable)

m = returned mass per ship

a = asteroids (1:60000)

g = ship groups

N = number ships

$c_{a,s}$ = visited count of a by s


Combined Top 10 Solutions

All solutions

- 35 ships (NC)
- 719.79kg average
- Optimal combination:
 - 35x JPL

Only self-cleaning


- 30 ships (+2)
- 679.03kg average
- Optimal combination:
 - 10x OptimiCS
 - 8x ESA
 - 7x TheAntipodes
 - 2x NUDT-LIPSAM
 - 3x Σ TEAM



Adaptive-Mesh Convex Optimization


- The SCP algorithm is modified to add the time discretization as a decision variable in the optimization, allowing the SCP to **operate with an adaptive mesh and non-fixed rendezvous times**
- Achieved by adding a 'time delation' parameter into the STM and linearizing the rendezvous position constraints
- Convergence is more problematic (needing more iterations) due to increased nonlinearity but can be achieved using trust regions

SCP can optimize multi-target rendezvous timing




Application to Our Solution

- Nelder-mead simplex local optimizer for comparison, with decision variables of rendezvous times
- **~1h run time** for Nelder-mead per ship
- **<20sec run time** per ship for 20-day convex dynamic discretization



Application to Top 10 Solutions

- All optimization performed with **20-day** dynamic discretization
- Most teams have significant available improvements
- Mixed solutions tended to have greater improvements
- Further improvement (~0.8kg/ship) available with change to 5-day adaptive discretization




MIP Process for Chain Creation

MIP for chain creation is based on the design of **binary optimal flow problems**

1. Select subset to operate within
2. Choose number of deployments and collections, and how many chains to create
3. Choose a fixed time schedule for rendezvous
4. Calculate the transfer Δv for all possible transfers at each stage of the trajectory (used Lambert Δv but can be low-thrust)
5. Initialise a binary variable for the transfers that are 'cheap' (below some limit)
6. Setup constraints on binary variables (e.g. self-cleaning, deploy + collect) and solve MIP
7. Optimize time schedule of solution with time-refinement, and repeat process from step 4

Repeated across many subsets to develop new solution sets




Best Self-Cleaning Solution Found

- 37 ships, 338 asteroids (9.14 ratio)
- 730.95kg average (729.44kg needed for 37 ships)
 - Mixture of 8, 9 and 10 asteroid chains
 - Highest self-cleaning chain 780.84kg (10 asteroid)
 - All ships return >700kg

```
Check successfully!  
The number of mining ships is 37 ;  
The number of mined asteroids is 338 ;  
The total resource mass is 27045.3 kg.  
Press any key to continue . . . |
```

J = 22847.922




Best Solution Found

- 39 ships, 356 asteroids (9.13 ratio)
- 742.95kg average (742.60kg needed for 39 ships)
 - JPL group 1 (14 mixed) modified (average 752.52kg)
 - JPL group 2 (6 mixed) modified (average 735.54kg)
 - Custom 2 mixed (average 752.90kg)
 - 17 custom self-cleaning (average 736.52kg)

```
Check successfully!  
The number of mining ships is 39 ;  
The number of mined asteroids is 356 ;  
The total resource mass is 28975.1 kg.  
Press any key to continue . . . |
```

J = 24474.156



GTOC12: Sustainable Asteroid Mining

TheAntipodes

Roberto Armellin

Harry Holt

Cristina Parigini

Minduli Wijayatunga

Jack Yarndley



Andrea Bellome



Xiaoyu Fu

Independent Subset Generation

Methodology

- Using graph theory to create independent subsets
- Adjacency matrix is sparse but can be reordered so that connected asteroids are near to each other
- Asteroid set can then be pruned based on this criterion
- Post-competition we found that the MATLAB function `symrcm` provided a superior result

