

MBR Intelligent Site Assistant

User Guide · Version 0.3.2

A self-hosted conversational site search for WordPress.

No external APIs. No monthly fees. Nothing leaves your server.

Published by Little Web Shack · littlewebshack.com
Author: Robert Palmer

Contents

1. Introduction	4
1.1 What it does	4
1.2 What it is not	4
2. How it works	4
2.1 The query pipeline	4
2.2 Confidence levels	5
2.3 The four database tables	5
3. Installation	6
3.1 Requirements	6
3.2 Installing the plugin	6
4. First-time setup	6
4.1 Run a full reindex	6
4.2 Test with the chat tester	6
4.3 Configure and enable the widget	7
5. The admin dashboard	7
5.1 Plugin Status	7
5.2 Database Tables	7
5.3 Index Status	7
5.4 Widget Settings	7
5.5 Feedback & Queries	8
5.6 Tokeniser Tester	8
5.7 Search Tester (raw BM25)	8
5.8 Chat Tester (full pipeline)	8
6. The widget: placement and customisation	8
6.1 Floating bubble mode	8
6.2 Inline mode via shortcode	8
6.3 Running both at once	9
6.4 Assets and conditional loading	9
7. Intents	9
7.1 Built-in intents	9
7.2 Editing intents	9
7.3 How matching works	10

8. Synonyms	10
8.1 Built-in groups	10
8.2 Editing synonym groups	10
8.3 When to add a synonym vs an intent	11
9. Indexing behaviour	11
9.1 What gets indexed	11
9.2 Automatic re-indexing on save	11
9.3 Field weighting	11
10. REST API	11
10.1 POST /wp-json/mbr-isa/v1/ask	12
10.2 POST /wp-json/mbr-isa/v1/feedback	12
10.3 Error responses	13
11. Privacy, data, and rate limiting	13
11.1 What the plugin stores	13
11.2 IP hashing	13
11.3 No outbound traffic	13
11.4 Rate limiting	13
12. Troubleshooting	14
13. Uninstalling and keeping data	14
13.1 Keeping data across a reinstall	15
14. Technical reference	15
14.1 Plugin settings option	15
14.2 Other options	15
14.3 File layout	16
14.4 JavaScript integration	16
15. Support and version information	16

1. Introduction

The MBR Intelligent Site Assistant is a WordPress plugin that adds a conversational chat widget to your site. Visitors type questions in plain English, and the assistant responds with short messages and links to the most relevant pages on your site.

The plugin runs entirely on your own server. There is no external API call for each query, no monthly subscription, and no visitor data sent to a third party. The ranking is done in pure PHP and MySQL using a well-understood information retrieval algorithm (BM25), layered with intent matching for common questions and synonym expansion for natural phrasing.

1.1 What it does

- Adds a floating chat bubble, or an inline widget via shortcode.
- Indexes your published posts and pages automatically when they are saved.
- Matches common questions ("contact", "pricing") to pre-written answers.
- Expands queries with synonyms so "WP" finds content tagged "WordPress".
- Logs queries and thumbs-up / thumbs-down feedback so you can tune responses.
- Provides an admin diagnostic page with search, tokeniser, and chat testers.

1.2 What it is not

Despite the word *assistant*, this plugin is not a large language model and does not generate text. It retrieves and surfaces content you have already written, and answers a short list of canned questions. If a visitor asks something you have not written about, the assistant will politely say it could not find anything, and invite them to rephrase.

This is a deliberate design choice. The plugin produces predictable, auditable responses with no hallucination risk — and it does it without sending your visitors' questions to an outside service.

2. How it works

When a visitor submits a question, the plugin runs it through a five-stage pipeline. Understanding this pipeline will help you tune the plugin effectively.

2.1 The query pipeline

Each query is processed in the following order:

- **Intent match.** The raw query is checked against configured intent triggers. If any trigger matches as a substring (or regex, if prefixed with `re :`), the matching intent's canned response is returned immediately. Search is skipped.
- **Tokenisation.** If no intent matched, the query is lowercased, stripped of punctuation, split on whitespace, filtered against an English stopword list, and each surviving word is reduced to its stem using a Porter stemmer.
- **Synonym expansion.** Each stemmed token is looked up in the synonym map. Matching terms add their siblings to the token list.

- **Ranking.** The expanded tokens are scored against the inverted index using BM25, with title matches weighted higher than body matches.
- **Formatting.** Results are classified by confidence (high, medium, low, or none), a matching message is chosen, and short highlighted snippets are built around the query terms.

2.2 Confidence levels

The responder picks one of four confidence levels based on the top result's BM25 score and how much it dominates the second result. Each level changes both the framing message and how many results are returned.

Level	Rule	Results shown	Typical framing
High	Top score ≥ 1.5 and $\geq 1.5 \times$ the runner-up	Up to 1	"Here is what I found."
Medium	Top score ≥ 1.0	Up to 3	"These look relevant."
Low	Top score > 0 but below 1.0	Up to 3	"I'm not sure, but these might help."
None	No results	0	"I couldn't find anything."

2.3 The four database tables

The plugin creates four custom tables, all prefixed with your WordPress table prefix followed by `mbrisa_`:

Table	Purpose
<code>mbrisa_terms</code>	Dictionary of every unique token, with document frequency for BM25 IDF.
<code>mbrisa_documents</code>	One row per indexed post or page: title, URL, token count, content hash, and a short excerpt for display.
<code>mbrisa_postings</code>	Inverted index — which terms appear in which documents, with frequency per field (title / content / excerpt).
<code>mbrisa_queries</code>	Log of every query asked through the widget, with intent match, result count, top score, and feedback.

3. Installation

3.1 Requirements

- WordPress 5.8 or later
- PHP 7.4 or later
- Standard MySQL / MariaDB — no special extensions required
- No external services, API keys, or network access

3.2 Installing the plugin

Because this plugin is distributed through Little Web Shack rather than the WordPress.org repository, installation is a manual upload:

- Download `mbr-intelligent-site-assistant.zip` from littlewebshack.com.
- In your WordPress admin, go to **Plugins** → **Add New**, then click **Upload Plugin**.
- Choose the ZIP file and click **Install Now**, then **Activate Plugin**.
- On activation, the four database tables are created and the default settings are seeded. Any existing published posts and pages will *not* be indexed automatically at this point — you need to run a full reindex once (see § 4).

Note. The floating chat widget is *off* by default on a fresh install. This is intentional — the plugin wants you to run a reindex and check the tokeniser before the widget starts talking to real visitors.

4. First-time setup

After activation, open **Tools** → **MBR ISA Diagnostic** in your WordPress admin. The whole plugin is configured from this one screen. The typical first-run sequence is: reindex, test, configure the widget, enable the widget.

4.1 Run a full reindex

Scroll to the **Index Status** section and click **Run Full Reindex**. This wipes the index tables and rebuilds them from every published post and page (or whichever post types you have enabled in the settings). Indexing 100 posts typically takes a few seconds on a modest host.

When it finishes you should see non-zero values for *Documents indexed*, *Unique terms in dictionary*, and *Total postings*.

4.2 Test with the chat tester

At the bottom of the diagnostic page, the **Chat Tester** runs the full query pipeline exactly as the public widget would. Type a question you expect the plugin to handle — for example, "how do I contact you" (which should match the built-in Contact intent), or a word you know appears on several pages of your site.

Expand the *Raw response payload* details to see the exact JSON the widget will receive. This is invaluable when diagnosing why a query is not producing the result you expected.

4.3 Configure and enable the widget

Scroll up to **Widget Settings**. The important fields are:

Setting	Purpose
Floating widget	Tick to show the chat bubble on every page. Leave off if you only want to embed the widget inline via
Position	Bottom-right (default) or bottom-left.
Widget title	Header text in the chat panel. Default: "Site Assistant".
Greeting message	First message the assistant shows when the panel opens.
Input placeholder	Ghost text in the input box.

Save your changes. If you ticked **Floating widget**, the bubble will now appear on the front end of your site.

5. The admin dashboard

The Diagnostic page at **Tools** → **MBR ISA Diagnostic** is divided into eight sections. This chapter explains what each one shows and when you will use it.

5.1 Plugin Status

Quick sanity check: plugin version, database schema version, server PHP version, and the REST endpoint URL the widget will post to. If you are troubleshooting a broken widget, confirm this URL returns a valid response when you POST to it.

5.2 Database Tables

A four-row table showing whether each of the plugin's custom tables exists. Under normal operation all four should show a green tick. If any table is missing, deactivate and reactivate the plugin to trigger the activation routine again.

5.3 Index Status

Shows document, term, and posting counts, plus the timestamp of the last full reindex. Also hosts the **Run Full Reindex** button. A reindex is safe to run at any time — it wipes and rebuilds the index tables from scratch. You should run one after:

- Bulk-importing or bulk-editing posts
- Changing the list of enabled post types
- Modifying the stopword list or tokeniser (unlikely in normal use)
- Restoring from a backup

5.4 Widget Settings

All of the visible configuration lives here. See § 4.3 for a field-by-field breakdown and § 6 for more on widget placement.

5.5 Feedback & Queries

Seven-day statistics — total queries, thumbs up, thumbs down, how many returned zero results, and how many hit an intent. Below that is a table of the 30 most recent queries. Rows tinted red are zero-result queries or queries that received a thumbs-down. These are the ones worth looking at first, because each one represents either a missing intent, a missing synonym, or a gap in your site's content.

5.6 Tokeniser Tester

Paste any text and see exactly what the tokeniser does to it: original, cleaned, split, after stopwords, after stemming. Mostly useful when debugging — for instance, if you are surprised that a particular word is not matching, tokenise the query and tokenise the page title and compare.

5.7 Search Tester (raw BM25)

Runs the search pipeline *without* intent matching or synonym expansion, and shows a full trace of which terms were looked up and their scores. Useful when you want to confirm the ranking itself is behaving correctly, independent of the higher-level pipeline stages.

5.8 Chat Tester (full pipeline)

Runs exactly what the public widget runs, and shows the conversational output with the confidence badge and the raw JSON payload. This is the primary tool for tuning intents and synonyms.

6. The widget: placement and customisation

6.1 Floating bubble mode

With **Floating widget** ticked in settings, a small chat bubble appears on every page of the front end, pinned to the bottom-right or bottom-left. Clicking the bubble opens the chat panel. The widget is automatically skipped on feeds, embeds, the favicon endpoint, and the robots.txt endpoint.

6.2 Inline mode via shortcode

To embed the widget within the flow of a specific page — for example, a dedicated "Ask" page — use the shortcode:

```
[mbr_isa_chat]
```

The shortcode supports four optional attributes that override the global settings for that one embed:

Attribute	Effect
title	Overrides the widget title shown in the panel header.
greeting	Overrides the first assistant message.
placeholder	Overrides the input placeholder text.
height	Sets the panel height — any valid CSS unit, e.g. 500px, 80vh.

Example:

```
[mbr_isa_chat title="Ask us anything" greeting="What are you looking for?" height="600px"]
```

6.3 Running both at once

It is safe to leave the floating widget on and also place a shortcode on a specific page. Each instance gets its own unique ID and operates independently. Session storage is shared, so a conversation started in one instance persists if the visitor switches to the other.

6.4 Assets and conditional loading

The widget's CSS and JavaScript are only enqueued on pages where they are actually needed: either because the floating widget is enabled site-wide, or because the current page contains the shortcode. Pages that use neither do not load the assets.

7. Intents

An intent pairs a list of trigger phrases with a canned response. When a query matches any trigger, the intent's response is returned immediately — no search, no ranking. Intents are the single biggest usability win in a site assistant, because they let you give a perfect answer to every common question.

7.1 Built-in intents

The plugin ships with five default intents, active unless you override the `mbr_isa_intents` option with your own list:

ID	Example triggers
contact	contact, email address, get in touch, how do I reach
pricing	how much, what do you charge, pricing, your rates, cost of
services	what services, what do you do, what do you offer, can you build
hours	opening hours, what hours, when are you open, business hours
help	need help, can you help, I am stuck, not working

7.2 Editing intents

At version 0.3.2 there is no admin UI for editing intents yet — they live in the `mbr_isa_intents` option and can be set programmatically or via any options inspector plugin. The structure is a list of associative arrays:

```
update_option( 'mbr_isa_intents', [
    [
        'id'          => 'contact',
        'label'       => 'Contact',
        'triggers'    => [ 'contact', 'email', 'get in touch' ],
        'response'    => 'You can reach me at hello@example.com or via the contact form.',
        'confidence' => 1.0,
    ],
],
```

```
// ...more intents...
] );
```

7.3 How matching works

- Triggers are matched case-insensitively as substrings of the raw query.
- A trigger prefixed with `re :` is treated as a regex (useful for word-boundary matches, e.g. `re :\bhours?\b`).
- If more than one intent matches, the one with the highest *confidence* value wins.
- Empty queries are never matched: neither are intents missing an ID, triggers, or a response.

Tip. Use the *Recent queries* list on the diagnostic page to find questions that returned zero results, then add triggers or intents to cover them.

8. Synonyms

A synonym group is a list of terms that should be considered equivalent for searching. If any term in a group appears in a query, the others are added to the search before ranking. Matching happens on *stems*, not raw words, so "shops" and "shop" are already equivalent before synonyms kick in.

8.1 Built-in groups

The defaults cover the common web-industry vocabulary:

Group
wp, wordpress
site, website, webpage
ecommerce, e-commerce, shop, store, online shop
price, pricing, cost, fee, rate, quote
contact, email, reach, get in touch
help, support, assistance
plugin, extension, add-on, addon
theme, template, skin
build, develop, create, make
seo, search engine optimisation, search engine optimization

8.2 Editing synonym groups

Like intents, synonyms are stored as a single option. Each group is a simple array of strings; the plugin stems every term internally, so you write them as a human would type them:

```
update_option( 'mbr_isa_synonyms', [
    [ 'wp', 'wordpress' ],
    [ 'delivery', 'shipping', 'dispatch' ],
```

```
[ 'vegan', 'plant-based', 'plant based' ],  
  // ...  
] );
```

8.3 When to add a synonym vs an intent

Add a **synonym** when the missing phrasing is something visitors say but your content uses a different word. Add an **intent** when the question has a canned answer that does not correspond to any single page on your site.

9. Indexing behaviour

9.1 What gets indexed

By default, published posts and pages are indexed. The indexer pulls the title, post content, and excerpt fields, tokenises them, and stores per-field term frequencies so that title matches can be weighted higher than body matches at query time.

To enable additional post types, update the `enabled_post_types` entry in the plugin settings option:

```
$s = get_option( 'mbr_isa_settings', [] );  
$s['enabled_post_types'] = [ 'post', 'page', 'product' ];  
update_option( 'mbr_isa_settings', $s );  
  
// Then run a full reindex from the diagnostic page.
```

9.2 Automatic re-indexing on save

The indexer hooks `save_post`, `deleted_post`, and `trashed_post`. Every time you save or publish a post of an enabled type, the indexer recomputes the content hash; if it has changed, the document's entry in the index is updated. If the post is unpublished, trashed, or deleted, it is removed from the index. Revisions and autosaves are ignored.

9.3 Field weighting

BM25 is applied per field with the following default weights:

Field	Default weight
Title	3.0
Excerpt	1.5
Content	1.0

Weights are stored in the plugin settings option as `field_weight_title`, `field_weight_excerpt`, and `field_weight_body`. The BM25 parameters `bm25_k1` (default 1.2) and `bm25_b` (default 0.75) are also stored there.

10. REST API

The chat widget talks to the plugin via two REST endpoints, both under the `mbr-isa/v1` namespace. Both are public (no authentication) but nonce-protected when called from the widget, and rate-limited per IP.

10.1 POST `/wp-json/mbr-isa/v1/ask`

Accepts a user question and returns the full structured chat response.

Request body:

```
{
  "query": "how do I contact you",
  "session_id": "optional-32-char-session-id"
}
```

Successful response (intent hit):

```
{
  "type": "intent",
  "intent_id": "contact",
  "intent_label": "Contact",
  "message": "You can get in touch via the contact form...",
  "results": [],
  "suggestions": ["Ask me something else about this site"],
  "session_id": "...",
  "query_id": 1234
}
```

Successful response (search hit, medium confidence):

```
{
  "type": "search_results",
  "confidence": "medium",
  "message": "These look relevant:",
  "results": [
    { "title": "...", "url": "...", "snippet": "... <mark>match</mark> ...", "score": 2.14 }
  ],
  "suggestions": [],
  "session_id": "...",
  "query_id": 1235
}
```

10.2 POST `/wp-json/mbr-isa/v1/feedback`

Records a thumbs-up (1), thumbs-down (-1), or neutral (0) against a previously-logged query.

```
{
  "query_id": 1234,
  "feedback": 1
}
```

Feedback is only accepted within one hour of the original query. Older queries return a 410 Gone response to discourage scripted bulk-feedback.

10.3 Error responses

Code	Error	Meaning
400	mbr_isa_invalid_query_id	query_id missing or not a positive integer
400	mbr_isa_invalid_feedback	feedback value not in {-1, 0, 1}
404	mbr_isa_not_found	query_id does not exist in the log
410	mbr_isa_feedback_expired	More than an hour has passed since the query
429	mbr_isa_rate_limited	Per-IP rate limit exceeded
500	mbr_isa_db_error	Database write failed when storing feedback

11. Privacy, data, and rate limiting

11.1 What the plugin stores

The plugin stores only what it needs to answer queries and help you tune the assistant:

- **Post content, as an inverted index.** Stored across the `mbrisa_terms`, `mbrisa_documents`, and `mbrisa_postings` tables. This is derived from content you have already published.
- **Query log.** Each query submitted through the widget is logged in `mbrisa_queries` with the query text, matched intent (if any), top score, result count, optional feedback value, session ID, created-at timestamp, and a hashed version of the requester's IP address.
- **No personal identifiers.** The plugin does not record user accounts, cookies, emails, or raw IPs.

11.2 IP hashing

Where an IP address is needed — for rate limiting and for a loose approximation of unique askers in the query log — it is immediately hashed with SHA-256 and your site's WordPress salt. The raw IP is never stored. The hashed value is not reversible without access to your site's salt.

11.3 No outbound traffic

The plugin makes no outbound HTTP requests during normal operation. Every query is answered from data on your own server. This is a core design constraint, not an optional setting.

11.4 Rate limiting

Both REST endpoints are protected by a per-IP-hash sliding window stored in WordPress transients. Defaults:

Endpoint	Default limit	Configurable via
/mbr-isa/v1/ask	30 requests / minute	rate_limit_per_min in settings
/mbr-isa/v1/feedback	20 requests / minute	Hardcoded for this release

When the limit is hit the endpoint returns 429 Too Many Requests and the widget shows a "you are asking too quickly" message.

12. Troubleshooting

The widget does not appear on the site

- Check that **Floating widget** is enabled under Widget Settings.
- Confirm your active theme calls `wp_footer()`. If it does not, the floating widget cannot render — use the shortcode instead.
- Open your browser's developer console and look for JavaScript errors from `chat-widget.js`.
- Confirm `window.mbrAisa` is defined with a `restUrl`. If not, something has stripped the localized script tag.

Queries return no results even though the content exists

- Run a full reindex. This is the most common cause on a fresh install.
- Check Index Status shows a non-zero document count.
- Use the Tokeniser Tester on both your query and the page title — see which tokens actually come out.
- If the query uses different vocabulary to your content, add a synonym group.
- Confirm the post type is listed in `enabled_post_types`.

An intent is firing when it should not

- Triggers are substrings, so a trigger like *help* will match *I need help finding the shop*. Either remove the trigger or tighten it with a regex prefix (`re:\bhelp\b`).
- Use the Chat Tester to see which intent ID is firing.

The widget says "too many requests"

- You are hitting the per-IP rate limit. Wait a minute and try again.
- If you are testing programmatically, raise `rate_limit_per_min` in the plugin settings option.

Reindex takes a long time or times out

- The reindex is synchronous and batches 50 posts at a time. For very large sites (thousands of posts) it may exceed PHP's `max_execution_time`.
- Temporarily raise `max_execution_time` in `php.ini`, or run the reindex from a CLI environment where time limits do not apply.

A database table is missing after activation

- Deactivate and reactivate the plugin to re-run the activator.
- Check that the WordPress database user has `CREATE TABLE` permission on your database.

13. Uninstalling and keeping data

Deactivating the plugin leaves all data intact — the tables, options, and widget settings are preserved so you can reactivate later without losing anything. Deleting the plugin (via **Plugins** → **Delete**) by default drops all four custom tables, all plugin options, and all transients.

13.1 Keeping data across a reinstall

If you plan to delete the plugin and reinstall later, set the `mbr_isa_keep_data_on_uninstall` option to a truthy value *before* deletion. With that option set, the uninstall routine skips all cleanup and leaves your index and query log untouched.

```
update_option( 'mbr_isa_keep_data_on_uninstall', 1 );
```

14. Technical reference

14.1 Plugin settings option

All widget and engine configuration lives in one option: `mbr_isa_settings`. The structure and defaults:

Key	Default	Purpose
<code>enabled_post_types</code>	<code>['post', 'page']</code>	Which post types are indexed.
<code>bm25_k1</code>	1.2	BM25 term-frequency saturation constant.
<code>bm25_b</code>	0.75	BM25 length-normalisation constant.
<code>field_weight_title</code>	3.0	Score multiplier for title-field matches.
<code>field_weight_excerpt</code>	1.5	Score multiplier for excerpt matches.
<code>field_weight_body</code>	1.0	Score multiplier for content matches.
<code>widget_enabled</code>	false	Show floating bubble site-wide.
<code>widget_position</code>	'bottom-right'	'bottom-right' or 'bottom-left'.
<code>widget_title</code>	(empty)	Overrides panel title if set.
<code>widget_greeting</code>	(empty)	Overrides greeting message if set.
<code>widget_placeholder</code>	(empty)	Overrides input placeholder if set.
<code>log_queries</code>	true	Whether to log queries.
<code>rate_limit_per_min</code>	30	Max /ask requests per minute, per IP.

14.2 Other options

Option	Purpose
<code>mbr_isa_version</code>	Installed plugin version string.
<code>mbr_isa_db_version</code>	Schema version for future migrations.
<code>mbr_isa_intents</code>	Array of intent definitions (defaults used if empty).
<code>mbr_isa_synonyms</code>	Array of synonym groups (defaults used if empty).
<code>mbr_isa_index_status</code>	Cached counts shown on the diagnostic page.
<code>mbr_isa_keep_data_on_uninstall</code>	If truthy, skip all cleanup on delete.

14.3 File layout

mbr-intelligent-site-assistant/	
■■■ mbr-intelligent-site-assistant.php	Main plugin bootstrap
■■■ readme.txt	
■■■ uninstall.php	Full-cleanup routine
■■■ assets/	
■ ■■■ css/chat-widget.css	Widget styling
■ ■■■ js/chat-widget.js	Widget controller
■■■ data/	
■ ■■■ stopwords-en.php	English stopwords list
■■■ includes/	
■■■ class-mbr-isa-activator.php	Creates tables, seeds options
■■■ class-mbr-isa-deactivator.php	Deactivation hooks
■■■ class-mbr-isa-tokeniser.php	Clean / split / stem
■■■ class-mbr-isa-bm25.php	BM25 scoring
■■■ class-mbr-isa-indexer.php	Index build, search, field weights
■■■ class-mbr-isa-synonyms.php	Synonym expansion
■■■ class-mbr-isa-intents.php	Intent matching
■■■ class-mbr-isa-responder.php	Confidence, messages, snippets
■■■ class-mbr-isa-query-handler.php	Orchestrates the pipeline
■■■ class-mbr-isa-rate-limiter.php	Per-IP throttling
■■■ class-mbr-isa-rest.php	REST route registration
■■■ class-mbr-isa-frontend.php	Shortcode + floating widget render
■■■ class-mbr-isa.php	Singleton orchestrator + admin page

14.4 JavaScript integration

The widget exposes a configuration object at `window.mbrAisa`, populated by `wp_localize_script`:

```

window.mbrAisa = {
  restUrl: 'https://example.com/wp-json/mbr-isa/v1/ask',
  feedbackUrl: 'https://example.com/wp-json/mbr-isa/v1/feedback',
  nonce: '...',
  strings: { sending: 'Searching...', networkErr: '...', ... }
};

```

For manual re-initialisation (for example, after an AJAX page swap in a headless theme) the widget exposes `window.MbrAisaChat.init()`.

Naming note. The JavaScript-side identifiers still use the camelCase `mbrAisa` form, retained from an earlier version of the plugin for backward compatibility with any custom front-end integration code. All PHP-side identifiers are `mbr_isa`.

15. Support and version information

Plugin version	0.3.2
Author	Robert Palmer
Distribution	littlewebshack.com
Licence	GPL-2.0-or-later
Text domain	mbr-isa

Requires	WordPress 5.8+, PHP 7.4+
-----------------	--------------------------

This plugin is free and open source. If it has saved you time, a donation at buymeacoffee.com/robertpalmer is very welcome.

For bug reports, feature suggestions, or support questions, please get in touch through littlewebshack.com or via the author's contact channels.