Chitkara

PAPER OF PT2-ACC-24CAI0104-B2024-SEM2 EXAM

Q1. ACC-24CAI0104-CODING-5MARKS-PT2-B2024-AI

Removing Duplicates

Write a C++ program to remove duplicate elements from an unsorted array. The program should take an array as input, remove all duplicate values, and output the modified array containing only unique elements. The order of elements may or may not be preserved, depending on the approach used.

Input:

- An unsorted array of integers.

Output:

- The array after removing duplicate elements.

Sample Input:

5 // size of the array

3 3 5 5 6

Sample Output:

3 5 6 // array without duplicates

ANSWER:

Test case 1 :

Input:
5
3 3 4 5 5
Output:
3 4 5

Test case 2 :

Input:
6
2 7 8 2 3 4

Output:
2 7 8 3 4

Q2. ACC-24CAI0104-CODING-5MARKS-PT2-B2024-AI

K’th Smallest Element in Unsorted Array

Given an array and a number k where k is smaller than the size of the array, we need to find the kth smallest element in the given array. It is given that all array elements are distinct.

Input Format

The first line contains the number of elements to be inserted in the array

Next, n lines contain numbers to insert in the array

The last line contains the kth smallest element to find.

Sample Input

5 // 5 element in array

12

45

11

8

9

2 //2nd smallest element

Sample Output

9 //2nd smallest element of the array

ANSWER:

Test case 1 :

Input:
5
5
6
7
8
9
3

Output:
7

Test case 2 :

Input:
5
-4
-5
-56
-33
0
1
Output:
-56

Q3. ACC-24CAI0104-CODING-5MARKS-PT2-B2024-AI

Anagrams or Not

Two strings, a and b, are called anagrams if they contain all the same characters in the same frequencies. For example, the anagrams of CAT are CAT, ACT, TAC, TCA, ATC, and CTA.

If “a” and “b” are case-insensitive anagrams, print "Anagrams"; otherwise, print "Not Anagrams" instead.

Input Format

The first line contains an integer “t” denoting the number of pairs of strings to be checked. If t=3 then total 6 strings are needed to be entered.

The next “t” lines contains t pairs of strings to be checked

Output Format

Print "Anagrams" if two strings are case-insensitive anagrams of each other; otherwise, print "Not Anagrams" instead.

Sample Input 0

3

anagram

margana

CAT

tac

xyz

xy

Sample Output 0

Anagrams

Anagrams

Not Anagrams

ANSWER:

Test case 1 :

Input:
4
Ram
Mar
Xxyy
Xxy
Abc
Abcc
Sst
tts
Output:
Anagrams
Not Anagrams
Not Anagrams
Not Anagrams

Test case 2 :

Input:
6
Ramam
Mamra
Aaaa
Aaaa
Bbb
Bbb
Ccdd
Ddcc
Q
Q
X
z
Output:
Anagrams
Anagrams
Anagrams
Anagrams
Anagrams
Not Anagrams