LINUX SYSTEMS PROGRAMMING & GLIB ARCHITECTURE

GDBus Engineering Guide

Architecture, Internals, and Practical Implementation

A comprehensive handbook covering the GLib/GIO D-Bus subsystem: GVariant type mechanics, client proxies, signal dispatching, low-level server vtables, automatic code generation with `gdbus-codegen`, async event loops, credential enforcement, and debugging tools.

Compiled by: HARDIK
LinkedIn: www.linkedin.com/in/hardikhardik

Written from hands-on systems programming notes, verified across GLib/GIO production deployments, and enriched with internal architectural diagrams.

Table of Contents

Ch.	Chapter & Topic Overview	Page
1	**What is GDBus?** (Origins, `dbus-glib` vs. GDBus, `libgio` Hierarchy, GObject Ref Counting)	2
2	**The GVariant Type System in Depth** (Type Codes, Format Strings, Tuple Rules, `&s` vs `s`)	3
3	**Containers: Builders & Iterators** (Building Arrays, `a{sv}` Dicts, `iter_loop` vs `iter_next`)	4
4	**Connecting & Error Handling** (`g_bus_get_sync`, SASL Auth Lifecycle, `GError` Discipline)	5
5	**Client-Side: Method Calls & Properties** (`GDBusProxy` Internals, Property Caching, Call Lifecycle)	6
6	**Client-Side: Signal Subscriptions** (`g_dbus_connection_signal_subscribe`, `PropertiesChanged`)	7
7	**Server-Side: Low-Level VTable Implementation** (XML Introspection, Invocations, Property Handlers)	8
8	**Server-Side: Ownership & Signal Emission** (Name Acquisition, Broadcast Signals, Manual Property Updates)	9
9	**The Code Generation Way (`gdbus-codegen`)** (Type-Safe Proxies, Skeletons, Auto PropertiesChanged)	10
10	**GMainLoop, Async Operations & Deferred Replies** (Async Calls, Slow Work Deferral, Sockets)	11
11	**Credential Checking & Security Verification** (Sender UID Validation, Polkit, End-to-End Traces)	12
12	**Memory Rules, Comparison & Quick Reference** (6 Golden Rules, `libdbus` vs `sd-bus` vs GDBus, Mental Model)	13

REFERENCE CONVENTIONS

Throughout this guide: **NOTE** highlights critical implementation contracts; **TIP** marks idiomatic GLib shortcuts; **WATCH OUT** warns against subtle memory leaks or crashes; and **EXTRA** provides deep kernel/GLib execution details.

1 What is GDBus?

1.1 Origins and Evolution

GDBus is the official GLib/GIO implementation of D-Bus. It is *not* a wrapper around `libdbus`. It is a completely independent, ground-up reimplementation developed by David Zeuthen and the GLib engineering team starting in 2008, officially released with GLib 2.26 in 2010.

Historically, GTK and GNOME applications used `dbus-glib`, an early binding that wrapped `libdbus`. That legacy binding suffered from fragile multi-threading, lacked support for structured data, and is now entirely obsolete.

Feature Aspect	Legacy `dbus-glib` (Deprecated)	Modern GDBus (GLib 2.26+ Standard)
Underlying Engine	Thin wrapper around `libdbus-1`	Independent, native socket implementation
Proxy Object	`DBusGProxy`	`GDBusProxy` (with automatic caching)
Method Invocation	`dbus_g_proxy_call()`	`g_dbus_proxy_call_sync()` / `g_dbus_proxy_call()`
Initialization	Mandatory `g_type_init()`	Not required (deprecated in GLib 2.36+)
Threading Model	Fragile; error-prone locking	Thread-safe; integrated into `GMainContext`
Type System	GValue / custom demarshallers	Native **GVariant** type system
Code Generation	`dbus-binding-tool` (limited)	`gdbus-codegen` (generates typed proxies & skeletons)

1.2 Where GDBus Lives in the System Architecture

GDBus is compiled directly into `libgio-2.0.so`. Applications access it via the single umbrella header `<gio/gio.h>` and link using `pkg-config --cflags --libs gio-2.0`.




Figure 1.1: The modular components of GDBus and its reliance on foundational GLib runtime facilities.

1.3 GObject and Reference Counting Lifecycle

Almost every primary GDBus entity is an instance of `GObject`. Constructors like `g_bus_get_sync()` and `g_dbus_proxy_new_sync()` hand out references with an initial count of 1. You must increment references with `g_object_ref()` when taking shared ownership and balance every increment with `g_object_unref()`.

> **NOTE**
> While `GDBusConnection` and `GDBusProxy` are standard `GObject` types, **GVariant** is a lightweight value-type structure that uses its own independent atomic reference counting functions: `g_variant_ref()`, `g_variant_unref()`, and `g_variant_ref_sink()`.

2 The GVariant Type System in Depth

2.1 GVariant Fundamentals & Constructors

GVariant is the serialization engine for D-Bus messages. It guarantees strong type safety, zero-copy wire parsing, and deterministic memory alignment. Values are created using explicit constructors or concise format strings:

```
// Basic explicit constructors GVariant *v_i32 = g_variant_new_int32(42); GVariant *v_u32 = g_variant_new_uint32(100); GVariant *v_str = g_variant_new_string("hello world"); GVariant *v_obj = g_variant_new_object_path("/org/example/Obj"); // Format strings: Tuples must always use parentheses ( ) GVariant *v_tup1 = g_variant_new("(ii)", 5, 7); // Valid method parameters: tuple with two int32s GVariant *v_tup2 = g_variant_new("(si)", "x", 10); // Tuple with string and int32
```

2.2 Complete Format String Reference

Char	D-Bus Type	C Data Type	Extraction / Construction Pattern
b	BOOLEAN	gboolean	0 or 1 stored in 32-bit container
y	BYTE	guchar	Unsigned 8-bit byte
n / q	INT16 / UINT16	gint16 / guint16	16-bit signed / unsigned integer
i / u	INT32 / UINT32	gint32 / guint32	Standard 32-bit integers
x / t	INT64 / UINT64	gint64 / guint64	64-bit timestamps and offsets
d	DOUBLE	gdouble	IEEE 754 64-bit floating point
s	STRING	gchar* (Allocated)	Allocates new string; **must call g_free()**
&s	STRING	const gchar* (Borrowed)	Points directly into GVariant; **do not free**
o / &o	OBJECT PATH	gchar* / const gchar*	Valid D-Bus object path (allocated vs borrowed)
g	SIGNATURE	const gchar*	Valid D-Bus signature string
h	UNIX_FD	gint32	File descriptor passed via socket ancillary data
v	VARIANT	GVariant*	Boxed polymorphic value (must g_variant_unref)
( )	STRUCT / TUPLE	Nested types	Fixed collection of heterogeneous elements
a...	ARRAY	Container	Requires GVariantIter or GVariantBuilder
@...	ANY TYPE	GVariant*	Extracts raw sub-variant without unwrapping

2.3 The Critical s vs &s Distinction

Understanding string ownership prevents crashes and memory corruption:

```
// Pattern A: Allocated copy (s) gchar *copy; g_variant_get(v, "s", &copy); g_print("Allocated: %s\n", copy); g_free(copy); // MANDATORY: failure to call leaks memory // Pattern B: Borrowed pointer (&s) const gchar *borrowed; g_variant_get(v, "&s", &borrowed); g_print("Borrowed: %s\n", borrowed); // DO NOT call g_free(borrowed); pointer is valid only while 'v' remains alive!
```

WATCH OUT: METHOD CALL TUPLE REQUIREMENT

The top-level body of every D-Bus method call or return is strictly a **STRUCT (tuple)**. When invoking a method via `g_dbus_proxy_call_sync()`, you must format parameters as `"(ii)"`. Passing `"ii"` creates two uncontained integers and will fail at runtime.

3 Containers: Builders & Iterators

3.1 Assembling Complex Types with GVariantBuilder

When creating variable-sized collections (arrays, dictionaries), use GVariantBuilder. A builder operates as a three-state machine: initialize with a container type, append entries, and finalize:

```
// 1. Constructing an array of strings ("as") GVariantBuilder str_builder;
g_variant_builder_init(&str_builder, G_VARIANT_TYPE("as")); g_variant_builder_add(&str_builder, "s",
"eth0"); g_variant_builder_add(&str_builder, "s", "wlan0"); GVariant *array_v =
g_variant_builder_end(&str_builder); // 2. Constructing an a{sv} dictionary (D-Bus Property hashmap)
GVariantBuilder dict; g_variant_builder_init(&dict, G_VARIANT_TYPE("a{sv}"));
g_variant_builder_add(&dict, "{sv}", "Volume", g_variant_new_uint32(80)); g_variant_builder_add(&dict,
"{sv}", "SpeakerName", g_variant_new_string("Front-Left")); g_variant_builder_add(&dict, "{sv}",
"Muted", g_variant_new_boolean(FALSE)); GVariant *props_dict = g_variant_builder_end(&dict);
```

3.2 Traversing Containers with GVariantIter

To deconstruct arrays or maps, initialize a GVariantIter over the container:

```
// Iterating an a{sv} dictionary with borrowed keys GVariantIter iter;
g_variant_iter_init(&iter, props_dict); const gchar *key; GVariant *value; while
(g_variant_iter_loop(&iter, "{&sv}", &key, &value)) { gchar *type_str = g_variant_print(value, TRUE);
g_print("Key: %-12s | Value: %s\n", key, type_str); g_free(type_str); // iter_loop automatically
unrefs the previous cycle's value! }
```

3.3 g_variant_iter_loop() vs. g_variant_iter_next()

g_variant_iter_loop()
- Automatically unrefs previous values each cycle.
- Frees final value when loop completes naturally.
- **Never manually unref items.**
- Cannot use early break (causes memory leaks).

g_variant_iter_next()
- Allocates fresh references for each item.
- **You must explicitly free/unref each element.**
- Safely supports early loop termination and break statements.

WATCH OUT: EARLY BREAK LEAKS IN ITER_LOOP

If you break out of a g_variant_iter_loop() before it returns FALSE, the internally cached GVariant from the active iteration is leaked, and remaining elements are never cleaned up. If you need early exits, use g_variant_iter_next() instead.

TIP: SUB-TREE OBJECT EXTRACTION

When iterating over (ao) (a tuple containing an array of object paths), use GVariantIter *iter; g_variant_get(res, "(ao)", &iter);. Remember to free heap-allocated iterators via g_variant_iter_free(iter) when finished.

4 Connecting & Error Handling

4.1 Establishing a Bus Connection

Applications connect synchronously using `g_bus_get_sync()`, passing either `G_BUS_TYPE_SYSTEM` or `G_BUS_TYPE_SESSION`:

```
GError *error = NULL; GDBusConnection *conn = g_bus_get_sync(G_BUS_TYPE_SYSTEM, NULL, &error);
if (!conn) { g_printerr("Connection failed: %s\n", error->message); g_error_free(error); return 1; }
g_print("Connected! Assigned unique bus name: %s\n", g_dbus_connection_get_unique_name(conn)); //
Perform work... g_object_unref(conn);
```

4.2 Internal Connection & SASL Handshake Sequence

When `g_bus_get_sync()` is called, GDBus executes a complete connection lifecycle behind the scenes:




Figure 4.1: The multi-step low-level authentication and initialization flow of `g_bus_get_sync()`.

4.3 Strict GError Discipline

GLib uses the `GError` structure (containing error domain quark, numeric code, and message). Follow these strict discipline rules to avoid application aborts:

> **WATCH OUT: PASSING DIRTY GERROR POINTERS**
> Always initialize error pointers to `NULL`: `GError *error = NULL;`. Never pass an already-set `GError*` to another GLib function without resetting it first. GLib will trigger a hard assertion crash if you pass a pointer pointing to existing memory. Use `g_clear_error(&error)` to cleanly free and reset.

> **TIP: ASYNC CONNECTION ALTERNATIVE**
> For UI applications where blocking the main thread during socket connection is prohibited, use `g_bus_get(G_BUS_TYPE_SESSION, cancellable, on_bus_connected, user_data)`.

5 Client-Side: Method Calls & Properties

5.1 Instantiating a GDBusProxy

GDBusProxy mirrors a remote service object. Upon instantiation, it automatically invokes Introspect() to inspect interfaces and Properties.GetAll() to prime its local property cache:

```
GError *error = NULL; GDBusProxy *proxy = g_dbus_proxy_new_sync( conn, G_DBUS_PROXY_FLAGS_NONE,
// Load introspection and cache properties NULL, // Auto-parse GDBusInterfaceInfo
"com.example.AdderService", // Destination bus name "/com/example/Adder", // Remote object path
"com.example.Adder", // Target interface NULL, &error);
```

5.2 Invoking Remote Methods via Proxy

Calling g_dbus_proxy_call_sync() serializes parameters into a METHOD_CALL frame, transmits it over the socket, and blocks the calling thread while pumping the inner context until a reply or timeout occurs:

```
// Invoke Add(5, 7) -> Returns reply tuple "(i)" GVariant *result = g_dbus_proxy_call_sync(
proxy, "Add", g_variant_new("(ii)", 5, 7), // Floating reference (consumed by call)
G_DBUS_CALL_FLAGS_NONE, -1, // Default 25-second timeout NULL, &error); if (!result) {
g_printerr("Call failed: %s\n", error->message); g_error_free(error); return 1; } gint32 sum;
g_variant_get(result, "(i)", &sum); // Unwrap return tuple g_print("Remote computation result: %d\n",
sum); g_variant_unref(result); // MANDATORY: Caller owns result
```

5.3 Reading Cached Properties

Because the proxy maintains an internal hash table of properties, reading cached attributes requires zero round-trip bus latency:

```
GVariant *prop = g_dbus_proxy_get_cached_property(proxy, "Version"); if (prop) { const gchar
*ver; g_variant_get(prop, "&s", &ver); g_print("Daemon Version: %s\n", ver); g_variant_unref(prop); //
Releases copy returned by proxy }
```

NOTE: FLOATING REFERENCES IN METHOD CALLS

g_variant_new() returns a *floating reference*. When passed to g_dbus_proxy_call_sync(), the library calls g_variant_ref_sink() to take ownership and frees it automatically. Never call g_variant_unref() on the parameters you pass into method calls.

WATCH OUT: PROXY CACHE CONSISTENCY

If the server does not emit standard PropertiesChanged signals, the proxy's local cache becomes stale. To force an authoritative read over the wire, make a direct D-Bus call to org.freedesktop.DBus.Properties.Get.

6 Client-Side: Signal Subscriptions

6.1 Connection-Level Signal Subscription

To monitor broadcast signals directly on the connection, register a match rule with `g_dbus_connection_signal_subscribe()`:

```
static void on_result_computed(GDBusConnection *c, const gchar *sender, const gchar *path, const gchar *iface, const gchar *signal_name, GVariant *params, gpointer user_data) { gint32 res; g_variant_get(params, "(i)", &res); g_print("Signal received: ResultComputed(%d) from %s\n", res, sender); } guint sub_id = g_dbus_connection_signal_subscribe( conn, "com.example.AdderService", "com.example.Adder", "ResultComputed", "/com/example/Adder", NULL, G_DBUS_SIGNAL_FLAGS_NONE, on_result_computed, NULL, NULL);
```

6.2 Handling `PropertiesChanged` Broadcasts

Standard D-Bus objects emit `PropertiesChanged` with signature `(sa{sv}as)` containing the interface name, a dictionary of updated attributes, and an array of invalidated names:

```
static void on_props_changed(GDBusConnection *c, const gchar *sender, const gchar *path, const gchar *iface, const gchar *signal_name, GVariant *params, gpointer user_data) { const gchar *target_iface; GVariant *changed_dict; const gchar **invalidated; // Extraction string: &s borrows str, @a{sv} extracts sub-variant, ^a&s parses str array g_variant_get(params, "(&s@a{sv}^a&s)", &target_iface, &changed_dict, &invalidated); GVariantIter iter; const gchar *key; GVariant *val; g_variant_iter_init(&iter, changed_dict); while (g_variant_iter_loop(&iter, "{&sv}", &key, &val)) { gchar *s = g_variant_print(val, TRUE); g_print("Property '%s' changed -> %s\n", key, s); g_free(s); } g_variant_unref(changed_dict); g_free(invalidated); // Free array pointer only; items are borrowed }
```

TIP: THE HIGH-LEVEL PROXY SHORTCUT

If you already have a `GDBusProxy`, you do not need to register low-level match rules. Simply connect to its standard GObject signal: `g_signal_connect(proxy, "g-properties-changed", G_CALLBACK(on_proxy_props), NULL);`.

WATCH OUT: MAIN LOOP REQUIREMENT FOR SIGNALS

Signal callbacks will **never fire** unless a `GMainLoop` is actively running. Synchronous calls can run internal contexts temporarily, but incoming signals rely entirely on the main event loop dispatching socket I/O events.

7 Server-Side: Low-Level VTable Implementation

7.1 Introspection XML Definition

A low-level server exports services by registering an introspection XML schema and a dispatch table:

```
static const gchar introspection_xml[] = "<node>" " <interface name='com.example.Adder'>" "
<method name='Add'>" " <arg type='i' name='a' direction='in'/>" " <arg type='i' name='b'
direction='in'/>" " <arg type='i' name='result' direction='out'/>" " </method>" " <property
name='Enabled' type='b' access='readwrite'/>" " </interface>" "</node>";
```

7.2 Method Dispatch & Invocations

The handler receives a `GDBusMethodInvocation` token that *must* be completed with either a return value or an error:

```
static void handle_method_call(GDBusConnection *c, const gchar *sender, const gchar *path, const
gchar *iface, const gchar *method, GVariant *params, GDBusMethodInvocation *invoc, gpointer udata) {
if (g_strcmp0(method, "Add") == 0) { gint32 a, b; g_variant_get(params, "(ii)", &a, &b); // Send
METHOD_RETURN frame (automatically unrefs invocation) g_dbus_method_invocation_return_value(invoc,
g_variant_new("(i)", a + b)); } else { g_dbus_method_invocation_return_error(invoc, G_DBUS_ERROR,
G_DBUS_ERROR_UNKNOWN_METHOD, "Unknown method: %s", method); } }
```

7.3 Property Get/Set Handlers

```
static GVariant *handle_get_prop(GDBusConnection *c, const gchar *s, const gchar *p, const gchar
*i, const gchar *prop, GError **err, gpointer u) { if (g_strcmp0(prop, "Enabled") == 0) return
g_variant_new_boolean(TRUE); // GDBus wraps this into a variant automatically g_set_error(err,
G_DBUS_ERROR, G_DBUS_ERROR_UNKNOWN_PROPERTY, "Unknown property"); return NULL; }
```

> **NOTE: THE INVOCATION CONTRACT**
> Every incoming method call expects an answer. You must call exactly one reply function on the `GDBusMethodInvocation`: `return_value()`, `return_error()`, or `return_dbus_error()`. Failing to reply leaves the caller hanging until their request times out.

8 Server-Side: Ownership & Signal Emission

8.1 VTable Linking & Object Registration

Combine handlers into a `GDBusInterfaceVTable` and export the object onto the active connection:

```
static const GDBusInterfaceVTable vtable = { handle_method_call, handle_get_prop, handle_set_prop }; GDBusNodeInfo *node = g_dbus_node_info_new_for_xml(introspection_xml, &error); guint reg_id = g_dbus_connection_register_object( conn, "/com/example/Adder", node->interfaces[0], &vtable, user_context, NULL, &error); g_dbus_node_info_unref(node); // Node info safe to unref after registration
```

8.2 Requesting a Well-Known Name

Acquire a service name across the bus using `g_bus_own_name_on_connection()`:

```
static void on_acquired(GDBusConnection *c, const gchar *name, gpointer u) { g_print("Successfully claimed bus name: %s\n", name); } static void on_lost(GDBusConnection *c, const gchar *name, gpointer u) { g_printerr("Lost ownership of bus name: %s (terminating)\n", name); } guint owner_id = g_bus_own_name_on_connection( conn, "com.example.AdderService", G_BUS_NAME_OWNER_FLAGS_NONE, on_acquired, on_lost, NULL, NULL);
```

8.3 Emitting Signals from the Server

Broadcast state changes to all listening clients:

```
// Broadcast ResultComputed(12) g_dbus_connection_emit_signal( conn, NULL, // Destination: NULL indicates broadcast "/com/example/Adder", // Object path "com.example.Adder", // Interface name "ResultComputed", // Signal member g_variant_new("(i)", 12), // Parameters payload &error);
```

TIP: AUTOMATIC SOCKET FLUSHING

Unlike legacy `libdbus`, GDBus queues outgoing messages directly inside its main context loop and flushes sockets automatically. You do not need to call `dbus_connection_flush()`. For immediate synchronous transmission, use `g_dbus_connection_flush_sync()`.

9 The Code Generation Way (gdbus-codegen)

9.1 Running gdbus-codegen

Writing manual vtables and GVariant packers is tedious. The official tool `gdbus-codegen` generates type-safe C proxies and server skeletons directly from XML schemas:

```
# Execute code generator from build system (Meson / Autotools / CMake) gdbus-codegen \ --
generate-c-code adder-generated \ --c-namespace Com \ --interface-prefix com.example. \ adder-
interface.xml
```

9.2 Using the Generated Type-Safe Client Proxy

Call remote methods using native C types without constructing GVariants:

```
#include "adder-generated.h" ComExampleAdder *proxy = com_example_adder_proxy_new_for_bus_sync(
G_BUS_TYPE_SYSTEM, G_DBUS_PROXY_FLAGS_NONE, "com.example.AdderService", "/com/example/Adder", NULL,
&error); gint32 sum; // Pure type-safe invocation: parameters are native integers! if
(com_example_adder_call_add_sync(proxy, 5, 7, &sum, NULL, &error)) { g_print("Type-safe Add result:
%d\n", sum); } gint32 last = com_example_adder_get_last_result(proxy); // Direct C getter
g_object_unref(proxy);
```

9.3 Exporting the Generated Server Skeleton

Implement methods by connecting to standard GObject signals:

```
static gboolean on_handle_add(ComExampleAdder *iface, GDBusMethodInvocation *invoc, gint32 a,
gint32 b, gpointer udata) { com_example_adder_complete_add(iface, invoc, a + b); // Auto-typed reply
return TRUE; } ComExampleAdder *skeleton = com_example_adder_skeleton_new();
g_signal_connect(skeleton, "handle-add", G_CALLBACK(on_handle_add), NULL);
g_dbus_interface_skeleton_export(G_DBUS_INTERFACE_SKELETON(skeleton), conn, "/com/example/Adder",
&error);
```

TIP: AUTOMATIC PROPERTIESCHANGED EMISSION
When using skeletons, calling setter functions like `com_example_adder_set_last_result(skeleton, 42);` updates internal state and **automatically emits PropertiesChanged** across the bus. You never have to build `sa{sv}as` variants by hand.

EXTRA: ASYNC CLIENT METHODS INCLUDED
The code generator automatically creates asynchronous non-blocking twins for every method: `com_example_adder_call_add()` and `com_example_adder_call_add_finish()`, making integration with GTK UI code clean and straightforward.

10 GMainLoop, Async Operations & Deferred Replies

10.1 Asynchronous Client Method Calls

To avoid blocking the UI thread or event loop during network/IPC latency, make non-blocking calls:

```
static void on_add_done(GObject *src, GAsyncResult *res, gpointer u) { GError *err = NULL;
GVariant *val = g_dbus_proxy_call_finish(G_DBUS_PROXY(src), res, &err); if (val) { gint32 sum;
g_variant_get(val, "(i)", &sum); g_print("Async returned: %d\n", sum); g_variant_unref(val); } }
g_dbus_proxy_call(proxy, "Add", g_variant_new("(ii)", 5, 7), G_DBUS_CALL_FLAGS_NONE, -1, NULL,
on_add_done, NULL);
```

10.2 Deferred Method Replies (Async Server Operations)

When fulfilling a request requires slow hardware I/O, keep the invocation alive with `g_object_ref()` and reply later:

```
static void handle_slow_op(GDBusMethodInvocation *invoc) { // Retain reference so invocation
survives returning from handler GDBusMethodInvocation *pending = g_object_ref(invoc);
start_hardware_operation(on_hardware_done, pending); // Return without replying! Caller remains
blocked waiting on bus } static void on_hardware_done(gboolean ok, gint32 val, gpointer udata) {
GDBusMethodInvocation *pending = udata; if (ok) g_dbus_method_invocation_return_value(pending,
g_variant_new("(i)", val)); else g_dbus_method_invocation_return_error(pending, G_DBUS_ERROR,
G_DBUS_ERROR_FAILED, "HW Error"); g_object_unref(pending); // Release held reference }
```



Figure 10.1: Server execution lifecycle during non-blocking deferred method execution.

WATCH OUT: FORGETTING G_OBJECT_REF ON INVOCATIONS

If you do not call `g_object_ref(invocation)` before returning from `handle_method_call`, the default dispatcher frees the invocation memory and sends a premature internal error reply to the client.

11 Credential Checking & Security Verification

11.1 Inspecting Caller UID at Runtime

For administrative operations (e.g. factory resets, power actions), verify the caller's OS credentials by querying the broker:

```
static void handle_factory_reset(GDBusMethodInvocation *invoc) { const gchar *caller = g_dbus_method_invocation_get_sender(invoc); GDBusConnection *conn = g_dbus_method_invocation_get_connection(invoc); GError *err = NULL; // Query broker for caller's POSIX UID GVariant *res = g_dbus_connection_call_sync( conn, "org.freedesktop.DBus", "/org/freedesktop/DBus", "org.freedesktop.DBus", "GetConnectionUnixUser", g_variant_new("(s)", caller), G_VARIANT_TYPE("(u)"), G_DBUS_CALL_FLAGS_NONE, -1, NULL, &err); guint32 uid; g_variant_get(res, "(u)", &uid); g_variant_unref(res); if (uid != 0) { // Reject non-root users g_dbus_method_invocation_return_error(invoc, G_DBUS_ERROR, G_DBUS_ERROR_ACCESS_DENIED, "Root required (UID=%u)", uid); return; } do_reset_sequence(); g_dbus_method_invocation_return_value(invoc, NULL); }
```

11.2 Credential Inspection Interfaces

Method / API Call	Return Type	Purpose & Security Usage
`GetConnectionUnixUser`	`uint32 (u)`	Retrieves the numeric POSIX UID of the caller.
`GetConnectionUnixProcessID`	`uint32 (u)`	Returns the PID of the calling client process.
`GetConnectionCredentials`	`a{sv}`	Returns rich dictionary (UID, PID, SELinux security context).
`g_dbus_connection_get_peer_credentials()`	`GCredentials*`	Used exclusively for peer-to-peer (P2P) connections.

WATCH OUT: TWO-TIER SECURITY ARCHITECTURE
Never rely exclusively on application-level UID checks. The primary line of defense is always the **XML policy configuration** in `/etc/dbus-1/system.d/`. The runtime check acts as an internal safeguard.

EXTRA: COMPARISON WITH SD-BUS CREDENTIALS
In `sd-bus`, inspecting credentials is significantly simpler via `sd_bus_query_sender_creds()`, which reads metadata directly from kernel socket SO_PEERCRED without an extra D-Bus round-trip query.

12 Memory Rules, Comparison & Quick Reference

12.1 The 6 Golden Memory Rules of GDBus

Entity	Allocation & Acquisition Source	Disposal & Ownership Contract
GObject	`g_bus_get_sync`, `g_dbus_proxy_new_sync`	Balance every reference with exactly one `g_object_unref()`.
GVariant Calls	`g_dbus_proxy_call_sync()` results	Caller owns the return value; **must call `g_variant_unref()`**.
Floating Ref	`g_variant_new("(ii)", 5, 7)` passed to call	Consumed by callee (floating sink). **Do NOT unref.**
Strings	`g_variant_get(v, "s", &str)` vs `"&s"`	`"s"` requires `g_free(str)`; `"&s"` is borrowed, do not free.
GError	Initialized to `NULL`, filled on failure	Free with `g_error_free()` or reset with `g_clear_error()`.
Iterators	`g_variant_iter_loop()`	Loop manages sub-items; do not manually free inside loop.

12.2 Library Comparison: `libdbus` vs. `sd-bus` vs. GDBus

Feature Metric	`libdbus-1` **(Legacy)**	`sd-bus` **(systemd)**	**GDBus (GLib / GIO)**
Header / Library	`dbus/dbus.h` (`libdbus-1`)	`systemd/sd-bus.h` (`libsystemd`)	`gio/gio.h` (`libgio-2.0`)
Main Loop	Manual socket polling	Native `sd-event` (or epoll)	`GMainLoop` / `GMainContext`
Type System	Manual message iterators	Type format strings	**GVariant** architecture
Codegen Tool	None	None	**`gdbus-codegen`**
Property Caching	No	No	**Yes** (Automatic in `GDBusProxy`)
Primary Use Case	Legacy codebases	Embedded daemons & PID 1	Modern Linux desktop & GLib daemons

12.3 Diagnostic Tooling Reference

`G_DBUS_DEBUG=all`
Environment flag that prints full protocol traces, SASL authentication states, and raw byte stream payloads directly to stderr.

`busctl` (CLI Tool)
Inspect running services: `busctl tree <dest>`, `busctl introspect <dest> <path>`, and `busctl call` to test endpoints rapidly.

Linux Systems Architecture Series: HARDIK — www.linkedin.com/in/hardikhardik