

# USB Type-C ENGINEERING CHANGE NOTICE

**Title: Remove Snubber Capacitors**

**Applied to: USB Type-C Specification Release 2.2, October 2022**

<b>Brief description of the functional changes proposed:</b>
Removes the specific recommendation for adding snubber caps in USB Type-C EPR cables used to mitigate inductive kickback induced arcing.

<b>Benefits as a result of the proposed changes:</b>
Reduces complexity of implementing USB Type-C EPR cables as there now appears no need to address inductive kickback-induced arcing given the energy associated with such arcing is very low and not harmful to the connector.

<b>An assessment of the impact to the existing revision and systems that currently conform to the USB specification:</b>
Does not impact existing cables, may lower cost of future cables.

<b>An analysis of the hardware implications:</b>
No impact to HW.

<b>An analysis of the software implications:</b>
No impact to SW.

<b>An analysis of the compliance testing implications:</b>
No impact to compliance testing.

# USB Type-C ENGINEERING CHANGE NOTICE

## Actual Change Requested

### (a) Section 3.11.1

#### Redline changes:

## 3.11 Extended Power Range (EPR) Cables

### 3.11.1 Electrical Requirements

Extended Power Range cables have additional requirements to assure that these cables can deliver the full defined voltage and current range for [USB PD](#) EPR operation.

EPR cables shall functionally support a reported 50 V and 5 A operation. The minimum functional voltage that a cable shall support is 50.9 V. The electrical components potentially in the path of VBUS in an EPR cable, e.g. bypass capacitors, should be minimally rated for 63 V.

~~To control the impact of inductive kickback and ringing that can increase the chance of arcing between a USB Type-C plug and receptacle when a cable is removed while power is still applied, an EPR cable may include a snubber capacitor within the plug at each end of the cable. See [Appendix H](#) for more information about USB PD high-voltage design and mitigating arcing damage during cable withdrawal.~~