		yte 1	Byte 2	Byte 3	Byte	e 4	Byte 5	Byt	e 6	5 5 5 5 6 6 6 6 6 6
	Type 1 Request Class, Dev8 Transport, 34-bit Addressing Packets									
Byte 0 >	ackID > 분 prio tt	ftype 0 0 0 0 1	destinationID	sourceID	transaction	rdsize	srcTID	sec_domain	secID	secTID
Byte 8 >		Address [0:28]]	ha xam sbs	xam sbs Final CRC			Logic 0 Pad		0 Pad
		Т	ype 1 Request	Class, Dev8 Tran	sport, 50	-bit Add	dressing Packets			
Byte 0 >	ackID	ftype 0 0 0 0 1	destinationID	sourceID	transaction	rdsize	srcTID	sec_domain	secID	secTID
Byte 8 >	Extended Address [0:15]		Address [0:29			9] tig xam sbs		Final CRC		I CRC
		Т	Type 1 Request	Class, Dev8 Tran	sport, 66	-bit Ado	ressing Packets			
Byte 0 >	ackID S brio tt	ftype 0 0 0 0 1	destinationID	sourceID	transaction	rdsize	srcTID	sec_domain	secID	secTID
Byte 8 >	Extended Address [0:31]						ta xam			
Byte 16 >	Final CRC		Logic 0 Pad							