Unit Tests for React

Pasted code.js
JavaScript

I have one of my files for faketube here and I would like to start writing some unit tests for it with code coverage:

Absolutely — this component is a good candidate for **React Testing Library + Vitest** unit tests with **coverage**, especially because it has a lot of UI state, timers, and event logging. The file you shared is a React component that manages simulation state, interval-driven counters, analytics unlock behavior, reset logic, toast display, and callbacks like `onStop`.

I'd start by testing these areas first:

1. **Initial render**
   - title/video render path is valid
   - stats start at 0
   - analytics starts locked
2. **Button interactions**
   - pause/resume simulation
   - dark/light mode toggle
   - unlock/lock analytics
   - reset simulation
   - stop simulation calls `onStop`
3. **Timer-driven behavior**
   - elapsed time increases while running
   - views/likes/subs increase over time
   - toast disappears after timeout
4. **Logging**
   - verify `logEvent` is called for important actions
5. **Reset correctness**
   - counters reset to zero
   - analytics resets

- comment reset trigger indirectly works through mocked child behavior

Here's a solid starting test file using **Vitest** and **React Testing Library**:

JavaScript

```
// ViralDashboard.test.jsx
import React from 'react'
import   render  screen  fireEvent  act   from '@testing-library/react'
import '@testing-library/jest-dom'
import   vi   from 'vitest'
import ViralDashboard from './ViralDashboard'

// Mock CSS import
vi.     './ViralDashboard.css'

// Mock logger
const logEventMock = vi.
vi.     '../utils/eventLogger'
                args     logEventMock    args


// Mock child components so tests stay focused on ViralDashboard logic
vi.     './CommentFeed'









    <div data-testid="comment-feed">
      <div>                </div>
      <div data-testid="comment-count-prop"> totalCommentCount </div>
      <button onClick=       onNewComment    data-testid="add-comment">

      </button>
      <button
        onClick=       onBotRaidComplete
        data-testid="complete-bot-raid"
      >

      </button>
      <div data-testid="bot-raid-count"> botRaidCount </div>
    </div>



vi.     './LiveAnalyticsChart'
```

```
    <div data-testid="analytics-chart">
                          data.
    </div>



describe 'ViralDashboard'
  const defaultProps =
           'Test Video'
              '/test-video.mp4'
            vi.


  beforeEach
    vi.
    vi.


  afterEach
    vi.
    vi.


  it 'renders initial UI state'
    render <ViralDashboard     defaultProps  />

    expect screen.          'Views'  .
    expect screen.          'Likes'  .
    expect screen.          'Subscribers'  .
    expect screen.          'Comments'  .

    expect screen.             '0'  0  .
    expect screen.          /Live Analytics Locked/i  .
    expect screen.            'analytics-chart'  .


  it 'toggles dark mode and logs event'
    render <ViralDashboard     defaultProps  />

    const modeButton = screen.          'button'          /dark mode/i
    fireEvent.      modeButton

    expect logEventMock .                      'DARK_MODE_ENABLED'
             'Test Video'


    expect
```

```
      screen.          'button'          /light mode/i
     .


  it 'pauses and resumes simulation with log events'
    render <ViralDashboard     defaultProps  />

    const pauseButton = screen.          'button'
            /pause simulation/i


    fireEvent.      pauseButton

    expect logEventMock .
      'SIMULATION_PAUSED'
      expect.
               'Test Video'



    const resumeButton = screen.          'button'
            /resume simulation/i


    fireEvent.      resumeButton

    expect logEventMock .
      'SIMULATION_RESUMED'
      expect.
               'Test Video'




  it 'calls onStop and logs event when stopping simulation'
    render <ViralDashboard     defaultProps  />

    fireEvent.      screen.          'button'          /stop simulation/i

    expect logEventMock .
      'SIMULATION_STOPPED'
      expect.
               'Test Video'



    expect defaultProps.       .                    1
```

```
  it 'unlocks analytics from paywall button'
    render <ViralDashboard     defaultProps  />

    fireEvent.      screen.          'button'          /unlock analytics/i

    expect logEventMock .
      'ANALYTICS_UNLOCKED'
      expect.
               'Test Video'



    expect
      screen.            /Live Analytics Locked/i
     .   .


  it 'locks and unlocks analytics from topbar toggle'
    render <ViralDashboard     defaultProps  />

    const toggle = screen.          'button'          /unlock analytics/i
    fireEvent.      toggle

    expect
      screen.          'button'          /lock analytics/i
     .

    fireEvent.      screen.          'button'          /lock analytics/i

    expect logEventMock .
      'ANALYTICS_LOCKED'
      expect.
               'Test Video'




  it 'increments comment count when CommentFeed reports a new comment'
    render <ViralDashboard     defaultProps  />

    fireEvent.      screen.            'add-comment'

    expect screen.          '1'  .


  it 'resets simulation counters and analytics'
    render <ViralDashboard     defaultProps  />
```

```
    fireEvent.      screen.            'add-comment'

    act
      vi.                    2500


    fireEvent.      screen.          'button'          /reset simulation/i

    expect logEventMock .
      'SIMULATION_RESET'
      expect.
               'Test Video'



    expect screen.          '🔄 Simulation reset.'  .


  it 'shows and hides toast after timeout'
    render <ViralDashboard     defaultProps  />

    fireEvent.      screen.          'button'          /viral boost/i

    expect
      screen.          /viral spike detected/i
     .

    act
      vi.                    3000


    expect
      screen.            /viral spike detected/i
     .   .


  it 'viral boost logs event'
    const mathSpy = vi.      Math  'random' .               0.5

    render <ViralDashboard     defaultProps  />

    fireEvent.      screen.          'button'          /viral boost/i

    expect logEventMock .
      'VIRAL_BOOST_TRIGGERED'
      expect.
               'Test Video'
```

```
    mathSpy.


  it 'bot raid logs event and updates mocked child prop'
    const mathSpy = vi.      Math  'random' .               0.5

    render <ViralDashboard     defaultProps  />

    fireEvent.      screen.          'button'          /bot raid/i

    expect logEventMock .
      'BOT_RAID_TRIGGERED'
      expect.
               'Test Video'



    expect screen.            'bot-raid-count'  .   .                  '0'

    mathSpy.


  it 'timer updates analytics over time while running'
    render <ViralDashboard     defaultProps  />

    act
      vi.                    4000


    expect screen.            'analytics-chart'  .
      /analytics points:/i
```

For **Vitest coverage**, add this to your `vite.config.js`:

JavaScript

```
import   defineConfig   from 'vitest/config'
import react from '@vitejs/plugin-react'

export default defineConfig
            react
```

```
                'jsdom'
            true

              'v8'
               'text'  'html'  'lcov'
              'src/**/*.{js,jsx}'
              'src/main.jsx'
```

Install what you need:

Bash

```bash
npm          -D
```

Add scripts to `package.json`:

JSON

```
          "vitest"
              "vitest run"
              "vitest run --coverage"
```

Then run:

Bash

```bash
npm
```

A few notes about this specific component:

- Because your file uses **intervals heavily**, `vi.useFakeTimers()` is the right move.
- Because `CommentFeed` and `LiveAnalyticsChart` are child components, mocking them keeps these tests focused on `ViralDashboard` behavior instead of their internals.
- `Math.random()` is used in viral boost / bot raid logic, so mocking it makes those tests deterministic.
- The biggest future improvement for testability would be extracting some logic from the component into pure helper functions, especially:
  - `algorithmConfidence`

- random boost calculations
- analytics point creation

That would let you unit test the logic without depending entirely on DOM-based tests.

A strong first coverage goal for this file would be:

- **80%+ statements**
- **70%+ branches**
- especially around button actions and timer flows

If you want, I can turn this into a version tailored to **Jest** instead of Vitest, or help you build the **next test file for CommentFeed** too.



Where do I put this test?

Perfect question — this is where a lot of people mess up structure early 👍

Based on your project layout (Vite + React), you've got **two clean options**, but one is clearly better for your setup.

✅ Best Practice (Recommended)

Put the test **right next to the component**

📁 Your structure should look like this:

```
👈
```

👉 So literally:

`src/components/ViralDashboard.test.jsx`

🔥 Why this is the best approach

- Keeps tests **close to the code they test**
- Easier to maintain as your project scales
- Standard in modern React/Vite setups
- Works perfectly with Vitest defaults

🧠 Important: Fix the import path

Since your test is in the same folder:

```javascript
import ViralDashboard from './ViralDashboard'
```

And for mocks:

```javascript
vi.     '../utils/eventLogger'
```

That path is correct because:

- test is in `components/`
- logger is in `utils/`

⚠️ Alternative (not recommended for you)

You *could* do:

```
[redacted]
```

But:

- More annoying imports
- Harder to scale
- Not how your current project is structured

🚀 After you place it

Run:

```bash
npm
```

or coverage:

```bash
npm
```

🧪 Quick sanity check

If everything is wired correctly, Vitest should:

- auto-detect `*.test.jsx`
- run without config issues
- show your component rendering tests

💡 Pro tip (very relevant for your project)

Since you're building **FakeTube + Hydra-style automation**, I'd structure ALL tests like this:

👉 This makes it super easy later when you:

- scale features
- debug automation behavior
- validate simulation logic

If you want next step, I can:

- help you write **tests for CommentFeed (super valuable for FakeTube realism)**
- or help you get **coverage to 90%+ with minimal effort**

Pasted text.txt
Document

Yeah this error is actually super clear once you know what's happening — and it's a classic Vite + Vitest gotcha.

❌ Root Problem

All your errors look like:

> `Unexpected JSX expression`
> `Unexpected token <div ...>`

👉 This means **Vitest is not transforming JSX**

So it's trying to read your React files like plain JS.

✅ The Fix (you're missing ONE thing)

You need to enable the **React plugin in Vitest/Vite config**

🔧 Fix your `vite.config.js`

Make sure it looks like this:

JavaScript

```
import   defineConfig   from 'vitest/config'
import react from '@vitejs/plugin-react'

export default defineConfig
            react     // 👈 THIS IS THE FIX

                'jsdom'
             true

               'v8'
                'text'  'html'
               'src/**/*.{js,jsx}'
```

📦 Make sure you installed it

Run:

Bash

```
npm          -D
```

🧠 Why this broke

From your logs :

Vitest internally uses Vite's transformer.

Without the React plugin:

- JSX is NOT compiled
- parser crashes
- coverage fails
- tests never run (`0 tests`)

⚠️ Bonus Issue You'll Hit Next

Your files are `.js` but contain JSX:

```javascript
ViralDashboard.
App.
```

That works in Vite dev server...

BUT for tooling (tests, coverage, linters), it's better to:

👉 Rename to `.jsx`

Not required, but **highly recommended**.

✅ After Fix

Run again:

```bash
```

```
npm
```

You should now see:

- tests actually executing
- coverage % instead of parse errors

🔥 If it STILL fails

Then I'd check:

1. `setupTests.js` exists (you already have it 👍)
2. It includes:

```javascript
import '@testing-library/jest-dom'
```

🚀 What just happened (important for you)

You basically hit:

> "Why DevOps engineers don't trust defaults" moment

Your pipeline (Vitest) didn't have:

- JSX transform
- correct plugin config

This is EXACTLY the kind of thing that breaks CI/CD pipelines later too.

If you want next step

I can:

- fix your entire test setup end-to-end
- get you to **90%+ coverage fast**
- or help you test **CommentFeed (which is way more complex than it looks)**

Pasted text.txt
Document

Good — this is actually **a really good failure**, not a bad one.
Your tests are running now ✅ (huge step), and what you're hitting is **Testing Library ambiguity**, not config issues.

🔥 Root Problem (All your failures)

From your output :

1. Multiple "Unlock Analytics" buttons

[redacted]

You have:

- Topbar button → 🔒 Unlock Analytics
- Paywall button → Unlock Analytics

👉 Testing Library doesn't know which one you mean.

---

2. Multiple "1" values

[redacted]

You have:

- Comments counter
- Mock comment feed count

---

3. Multiple "Bot Raid" buttons

🤖 [redacted]

✅ The Fix = Be More Specific

Testing Library rule:

> "Query like a user would — but precisely"

🔧 Fix 1: Unlock Analytics button

❌ Current (ambiguous)

```javascript
screen.          'button'          /unlock analytics/i
```

✅ Fix (target topbar button)

```javascript
screen.          'button'          '🔓 Unlock Analytics'
```

OR safer:

```javascript
screen.             'button'          /unlock analytics/i    0
```

🔧 Fix 2: Comment count test

❌ Current

```javascript
expect screen.          '1'  .
```

✅ Fix (target your mocked feed specifically)

```javascript
expect screen.            'comment-count-prop'  .                  '1'
```

🔧 Fix 3: Bot Raid button

❌ Current

```javascript
screen.          'button'          /bot raid/i
```

✅ Fix (target exact one)

```javascript
screen.          'button'          '🤖 Bot Raid'
```

🔧 Fix 4: Unlock toggle test (this one is key)

Replace this:

```javascript
const toggle = screen.          'button'          /unlock analytics/i
```

With:

```javascript
const toggle = screen.          'button'          '🔒 Unlock Analytics'
```

🧠 Why this is happening (important for you)

Your UI is actually **very realistic**:

- multiple buttons with same labels
- duplicated semantic meaning
- nested components

👉 This is EXACTLY what happens in real apps

Testing Library forces you to:

- think like a user
- but **target like a DevOps engineer**

💡 Pro Move (What I'd do for FakeTube long term)

Add `data-testid` to critical controls:

```javascript
<button data-testid="topbar-unlock">
```

Then in tests:

```javascript
screen.            'topbar-unlock'
```

This makes tests:

- stable
- immune to UI text changes
- way easier to maintain

🚀 Summary (your situation)

You are now:

- ✅ Vitest working
- ✅ Coverage working
- ✅ Tests executing
- ❌ Just need selector precision

This is actually **the hardest part done already**

If you want next step

I can:

- clean your entire test file so it passes 100%
- or help you push this to **90%+ coverage in like 10 mins**
- or show how to test **your algorithm simulation logic directly (way more powerful)**

Pasted text.txt
Document

Can I fix all this output?

Yes. At this point your tests are passing, and the remaining output is mostly cleanup noise from two causes shown in your run: React `act(...)` warnings and coverage parse errors for JSX living in `.js` files.

Do these two fixes.

1. Remove the coverage parse errors

Your coverage tool is still trying to parse files like `App.js`, `index.js`, `CommentFeed.js`, `LiveAnalyticsChart.js`, and `Counter.js` as plain JS even though they contain JSX. That's why you still see lines like `Unexpected JSX expression` and `Unexpected token`.

Best fix: rename JSX files from `.js` to `.jsx`

[redacted]

Then update imports accordingly.

Examples:

JavaScript
```
import App from './App.jsx'
import ViralDashboard from './ViralDashboard.jsx'
import CommentFeed from './CommentFeed.jsx'
import Counter from './Counter.jsx'
import LiveAnalyticsChart from './LiveAnalyticsChart.jsx'
```

And in `vite.config.js`, tighten coverage to JSX-bearing files:

JavaScript

```
import   defineConfig   from 'vitest/config'
import react from '@vitejs/plugin-react'

export default defineConfig
            react

                 'jsdom'
             true

                'v8'
                 'text'  'html'  'lcov'
                'src/**/*.{js,jsx}'

        'src/setupTests.js'
        'src/reportWebVitals.js'
```

If you do not want to rename files yet, the temporary workaround is to exclude those files from coverage until you rename them.

2. Remove the `act(...)` warnings

Those warnings are coming from state updates triggered by timers and async UI updates in `ViralDashboard`, even though the tests pass. Your output shows repeated `Warning: An update to ViralDashboard inside a test was not wrapped in act(...)`.

Wrap timer advances and state-triggering interactions in `act`, and prefer `userEvent` over raw `fireEvent` for clicks.

Example fixes:

JavaScript

```
import   render  screen  act   from '@testing-library/react'
import userEvent from '@testing-library/user-event'
```

For clicks:

JavaScript

```
const user = userEvent.
await user.      screen.          'button'          /stop simulation/i
```

For fake timers:

JavaScript

```
act
  vi.                    4000
```

For toast timeout:

JavaScript

```
await user.      screen.          'button'          /viral boost/i

act
  vi.                    3000
```

If you still get warnings after that, flush pending timers in `afterEach` before restoring real timers:

JavaScript

```
afterEach
  act
    vi.

  vi.
```

What your output means now

You're actually in good shape:

- 12 tests passed.
- `ViralDashboard.jsx` is already at about 88% statement coverage.
- The remaining ugly output is mostly tooling cleanup, not broken logic.

Recommended order

1. Rename JSX-containing `.js` files to `.jsx`
2. Update imports
3. Add the `coverage.exclude` entries

4. Replace `fireEvent` with `userEvent` where practical
5. Make sure every timer advance is inside `act`

After that, `npm run coverage` should be much cleaner.

If you paste your current `vite.config.js` and `ViralDashboard.test.jsx`, I'll clean both up line by line.

Pasted code.js
JavaScript

Add the changes to the test for the act I made the rest of it:

Yep — here's your test file with the `act(...)` cleanup added where it matters most, based on the version you pasted. The main changes are:

- wrap `fireEvent.click(...)` calls that trigger state updates in `act`
- wrap `afterEach` pending timers in `act`
- keep your existing selector fixes intact

Your current file is here for reference.

JavaScript

```
// ViralDashboard.test.jsx
import React from 'react'
import   render  screen  fireEvent  act   from '@testing-library/react'
import '@testing-library/jest-dom'
import   vi   from 'vitest'
import ViralDashboard from './ViralDashboard'

// Mock CSS import
vi.     './ViralDashboard.css'

// Mock logger
const logEventMock = vi.
vi.     '../utils/eventLogger'
                 args     logEventMock    args
```

```
// Mock child components so tests stay focused on ViralDashboard logic
vi.     './CommentFeed'





    <div data-testid="comment-feed">
      <div>                </div>
      <div data-testid="comment-count-prop"> totalCommentCount </div>
      <button onClick=       onNewComment    data-testid="add-comment">

      </button>
      <button
        onClick=       onBotRaidComplete
        data-testid="complete-bot-raid"
      >

      </button>
      <div data-testid="bot-raid-count"> botRaidCount </div>
    </div>



vi.     './LiveAnalyticsChart'

    <div data-testid="analytics-chart">
                          data.
    </div>



describe 'ViralDashboard'
  const defaultProps =
           'Test Video'
              '/test-video.mp4'
            vi.


  beforeEach
    vi.
    vi.


  afterEach
```

```
    act
      vi.

    vi.


  it 'renders initial UI state'
    render <ViralDashboard     defaultProps  />

    expect screen.          'Views'  .
    expect screen.          'Likes'  .
    expect screen.          'Subscribers'  .
    expect screen.          'Comments'  .

    expect screen.             '0'  0  .
    expect screen.          /Live Analytics Locked/i  .
    expect screen.            'analytics-chart'  .


  it 'toggles dark mode and logs event'
    render <ViralDashboard     defaultProps  />

    const modeButton = screen.          'button'          /dark mode/i

    act
      fireEvent.      modeButton


    expect logEventMock .                     'DARK_MODE_ENABLED'
             'Test Video'


    expect
      screen.          'button'          /light mode/i
     .


  it 'pauses and resumes simulation with log events'
    render <ViralDashboard     defaultProps  />

    const pauseButton = screen.          'button'
            /pause simulation/i


    act
      fireEvent.      pauseButton
```

```
    expect logEventMock .
      'SIMULATION_PAUSED'
      expect.
               'Test Video'



    const resumeButton = screen.          'button'
            /resume simulation/i


    act
      fireEvent.      resumeButton


    expect logEventMock .
      'SIMULATION_RESUMED'
      expect.
               'Test Video'




  it 'calls onStop and logs event when stopping simulation'
    render <ViralDashboard     defaultProps  />

    act
      fireEvent.
        screen.          'button'          /stop simulation/i



    expect logEventMock .
      'SIMULATION_STOPPED'
      expect.
               'Test Video'



    expect defaultProps.       .                    1


  it 'unlocks analytics from paywall button'
    render <ViralDashboard     defaultProps  />

    act
      fireEvent.
        screen.             'button'          /unlock analytics/i    0
```

```
  expect logEventMock .
    'ANALYTICS_UNLOCKED'
    expect.
             'Test Video'



  expect
    screen.            /Live Analytics Locked/i
   .   .


it 'locks and unlocks analytics from topbar toggle'
  render <ViralDashboard     defaultProps  />

  const toggle = screen.          'button'          '🔓 Unlock Analytics

  act
    fireEvent.      toggle


  expect
    screen.          'button'          /lock analytics/i
   .

  act
    fireEvent.      screen.          'button'          /lock analytics/i


  expect logEventMock .
    'ANALYTICS_LOCKED'
    expect.
             'Test Video'




it 'increments comment count when CommentFeed reports a new comment'
  render <ViralDashboard     defaultProps  />

  act
    fireEvent.      screen.            'add-comment'


  expect screen.            'comment-count-prop'  .                  '1'
```

```
  it 'resets simulation counters and analytics'
    render <ViralDashboard     defaultProps  />

    act
      fireEvent.      screen.            'add-comment'


    act
      vi.                    2500


    act
      fireEvent.
        screen.          'button'          /reset simulation/i



    expect logEventMock .
      'SIMULATION_RESET'
      expect.
               'Test Video'



    expect screen.          '🔄 Simulation reset.'  .


  it 'shows and hides toast after timeout'
    render <ViralDashboard     defaultProps  />

    act
      fireEvent.      screen.          'button'          /viral boost/i


    expect
      screen.          /viral spike detected/i
     .

    act
      vi.                    3000


    expect
      screen.            /viral spike detected/i
     .   .
```

```
it 'viral boost logs event'
  const mathSpy = vi.      Math  'random' .               0.5

  render <ViralDashboard     defaultProps  />

  act
    fireEvent.      screen.          'button'          /viral boost/i


  expect logEventMock .
    'VIRAL_BOOST_TRIGGERED'
    expect.
             'Test Video'



  mathSpy.


it 'bot raid logs event and updates mocked child prop'
  const mathSpy = vi.      Math  'random' .               0.5

  render <ViralDashboard     defaultProps  />

  act
    fireEvent.      screen.          'button'          '🤖 Bot Raid'


  expect logEventMock .
    'BOT_RAID_TRIGGERED'
    expect.
             'Test Video'



  expect screen.            'bot-raid-count'  .   .                  '0'

  mathSpy.


it 'timer updates analytics over time while running'
  render <ViralDashboard     defaultProps  />

  act
    vi.                    4000
```

```
    expect screen.            'analytics-chart'  .
      /analytics points:/i
```

A couple of quick notes:

- In your `"unlocks analytics from paywall button"` test, `[0]` may still be the topbar button depending on DOM order. If that test acts weird, switch it to `[1]` or target the paywall button more specifically.
- If you still get some warnings after this, the next best upgrade is replacing `fireEvent` with `userEvent`, but this should clean up most of the `act` noise first.

Run this again:

```bash
npm
```

And check whether the warnings are gone or just reduced.

Will this report my html coverage report to github as an artifact automatically?
This workflow will do a clean installation of node dependencies, cache/restore them, build the source code and run tests across different versions of node
For more information see: https://docs.github.com/en/actions/automating-builds-and-tests/building-and-testing-nodejs

name: Node.js CI

on:
  push:
    branches: ["main"]
  pull_request:
    branches: ["main"]

```
jobs:
  build:

    runs-on: ubuntu-latest

    strategy:
      matrix:
        node-version: [18.x, 20.x, 22.x]
        # See supported Node.js release schedule at
https://nodejs.org/en/about/releases/

    steps:
    - uses: actions/checkout@v4
    - name: Use Node.js ${{ matrix.node-version }}
      uses: actions/setup-node@v4
      with:
        node-version: ${{ matrix.node-version }}
        cache: 'npm'
    - run: npm ci
    - run: npm run build --if-present
    - run: npm run coverage --if-present
      env:
        CI: true
```

Short answer: **No — your current workflow does NOT upload the HTML coverage report as an artifact.**

Right now it only:

- installs deps
- builds
- runs `npm run coverage`

👉 That generates the report **inside the runner**, but then it gets discarded when the job finishes.

🔥 What you're missing

You need to explicitly upload the coverage folder using:

👉 `actions/upload-artifact`

✅ Fix: Add artifact upload step

Update your workflow like this (add at the bottom of steps):

YAML

[redacted]

📦 Full fixed workflow (clean version)

YAML

[redacted]

```
"main"

"main"
```

```
                "npm"



      # 👇 THIS is what you were missing
```

📁 What gets uploaded

Your Vitest config generates:

```
            👈
```

👉 After the run:

- Go to **GitHub → Actions → your workflow run**
- Scroll down → **Artifacts**
- Download `coverage-report-XX`
- Open `index.html`

⚠️ Important detail (matrix builds)

You're running 3 Node versions:

```yaml
</> YAML
```

So you'll get:

- `coverage-report-18.x`

- `coverage-report-20.x`
- `coverage-report-22.x`

👉 All identical (usually), just different environments.

💡 Pro upgrade (optional but 🔥)

If you want a **single coverage artifact instead of 3**, you can:

YAML

[redacted]

YAML

[redacted]

🚀 Even better (next level)

If you want:

- PR comments with coverage %
- coverage badges
- diff tracking

Then you'd use:

- Codecov
- Coveralls

🧠 Bottom line

Right now:
❌ Coverage is generated but lost
After fix:
✅ Coverage HTML downloadable from GitHub Actions

If you want next step, I can:

- add **Codecov integration (super clean for PRs)**
- or make your pipeline fail if coverage drops below X% (very DevOps-coded move)

Sure for codecov

Yep. For Codecov, add an upload step after your coverage command, and make sure Vitest is producing `lcov.info`. Codecov's current GitHub Action is `codecov/codecov-action@v5`, and v5 uses the Codecov Wrapper. Codecov also notes that tokenless uploads are not generally supported, except for PRs from forks to upstream public repos, so for a normal repo you should plan to use a `CODECOV_TOKEN` secret. GitHub +2

First, confirm your Vitest coverage config includes `lcov`:

JavaScript

```
coverage
  provider  'v8'
  reporter   'text'  'html'  'lcov'
```

Then update your workflow like this:

YAML

```
                "main"

                "main"
```

```
"npm"
```

A few important notes:

- I limited the upload to Node 22 so you do not upload the same report 3 times from the matrix. That is optional, but it keeps things clean.
- The `files: ./coverage/lcov.info` path matches the standard Vitest lcov output. Codecov's docs recommend uploading coverage reports from CI using their action/CLI flow. Codecov +2
- You'll need to add `CODECOV_TOKEN` in GitHub under **Settings → Secrets and variables → Actions** after getting the repo token from Codecov. Codecov's token docs describe this flow. Codecov +1

If your repo is public and you want to try tokenless behavior, that is mainly supported for fork PR scenarios rather than general branch uploads, so using the token is still the safer setup. GitHub +1

If you want PR comments and status checks too, add a `.codecov.yml` next.

Sources

Not doing that

That's fine. Just keep it as a GitHub Actions artifact and skip Codecov.

Use this instead:

YAML

```yaml
            "main"

            "main"



              "npm"
```

That will:

- run coverage
- keep the HTML report
- upload the `coverage/` folder as an artifact
- avoid uploading it 3 times from every Node version

Then after the workflow runs:

- open the Actions run
- scroll to Artifacts
- download `coverage-report`
- open `coverage/index.html`

If you want, I can also give you a version that fails the workflow when coverage drops below a threshold.



This would fail in mode node.js v18 env:

Yep — exactly.

Your workflow is matrixed across `18.x`, `20.x`, and `22.x`, and the failure in your screenshot is happening because one of your dependencies is using `styleText` from `node:util`, which is not available in Node 18 the way that package expects. The log shows that clearly in the `18.x` job, while `20.x` and `22.x` are green.

So the issue is not your tests. It's Node-version compatibility.

Best fix

Drop Node 18 from the matrix.

Use:

YAML

Then keep your artifact upload only on one version:

YAML

```yaml
"main"

"main"

"npm"
```

Why this is the right move

If your app and tooling already work on 20 and 22, keeping 18 in the matrix just creates noise and failed CI for an environment your current stack does not really support.

Alternative

If you really want to keep Node 18 for the build, then you'd need to pin/downgrade the offending dependency chain to versions compatible with Node 18. That is usually not worth it for a Vite/Vitest frontend app unless you have a hard requirement to support Node 18 in CI.

So yes: remove `18.x`, and your pipeline should stop failing for that reason.

Update the standard readme.md with how to trigger the tests too, ensure you return to me a fully copy pasteable markdown file:
🎨 FakeTube – Viral Video Simulator

www.fake-tube.com

FakeTube is a fun and interactive YouTube viral simulator. Upload any video and watch it rack up fake views, likes, comments, and subscribers with real-time analytics and adjustable growth rates.

🚀 Features

- 📩 Upload your own video.
- 📈 Real-time counters: views, likes, subs, comments.
- 💬 Simulated live comment feed.
- 📊 Animated analytics graph tracking growth over time.
- ⏸️ Pause and resume the simulation.
- 🎛️ Individual controls for adjusting growth speeds.

```
---

## 🛠️ Getting Started

### Clone the Repository

bash
git clone https://github.com/Hardwipe/yt-viral-sim.git
cd fake-tube


### Install Dependencies

bash
npm install


### Run Locally

bash
npm start


---

## 👥 Contributing

We welcome contributions! Here's how to help:

1. **Fork the repository.**
2. **Create a new branch** for your feature or fix:

bash
   git checkout -b feature/your-feature-name

3. **Make your changes** and commit:
```

bash
   git commit -m "Add feature: [your description]"

4. **Push to your branch**:

bash
   git push origin feature/your-feature-name

5. **Open a Pull Request** describing your change.

Please follow clear commit message guidelines and submit descriptive PRs.

📄 License

MIT License.

❤️ Support the Project

If you enjoy using FakeTube, please consider donating via the button on the site to support future development!

FakeTube is a satirical project and not affiliated with YouTube or Google.

Here's your updated, **fully copy-pasteable** `README.md` with testing + coverage + CI instructions cleanly added 👇

‹/› Markdown

🎨

🚀

📩
📈
💬
📊
⏸️
🎛️

🛠️

Install Dependencies

```bash
npm
```

Run Locally

```bash
npm
```

🧪 Running Tests

FakeTube uses **Vitest + React Testing Library** for unit testing and coverage.

Run Tests (Watch Mode)

```bash
npm
```

Run Tests Once

```bash
npm
```

Generate Coverage Report

```bash
npm
```

📊 Coverage Report

After running coverage:

- A `coverage/` folder will be generated
- Open the report locally:

```bash
```

This provides a full interactive breakdown of:

- Statements
- Branches
- Functions
- Lines

⚙️ CI / GitHub Actions

Tests and coverage automatically run on:

- Push to `main`
- Pull requests into `main`

The pipeline:

- Installs dependencies

- Builds the project
- Runs coverage tests
- Uploads the coverage report as an artifact

Viewing Coverage from CI

1. Go to **GitHub → Actions**
2. Click a workflow run
3. Scroll to **Artifacts**
4. Download `coverage-report`
5. Open `index.html`

👥 Contributing

We welcome contributions! Here's how to help:

1. **Fork the repository.**
2. **Create a new branch** for your feature or fix:

```bash
git          -b
```

3. **Make your changes** and commit:

```bash
git        -m "Add feature: [your description]"
```

4. **Push to your branch**:

```bash
git
```

5. **Open a Pull Request** describing your change.

🧠 Development Notes

- Tests are located alongside components (e.g. `Component.test.jsx`)
- Mocking is used for isolated testing of UI logic
- Timers are controlled via `vi.useFakeTimers()` for deterministic simulations

---

📄 License

MIT License.

❤️ Support the Project

If you enjoy using FakeTube, please consider donating via the button on the site to support future development!

FakeTube is a satirical project and not affiliated with YouTube or Google.

Please redo this but ensure it is in actual markdown notation in a comment block the whole way.

Markdown

👥

🧠

📄

❤️

[redacted]