

Creating and running individual threads for small applications is acceptable however if you are writing an enterprise-grade application with several dozen threads then you'll likely need to offload thread management in your application to library classes which free a developer from worrying about thread house-keeping.

Task#

A task is a logical unit of work. Usually, a task should be independent of other tasks so that it can be completed by a single thread. A task can be represented by an object of a class implementing the `Runnable` interface. We can consider HTTP requests being fielded by a web-server as tasks that need to be processed. A database server handling client queries can similarly be thought of as independent tasks.

Executor Framework#

In Java, the primary abstraction for executing logical tasks units is the Executor framework and not the Thread class. The classes in the Executor framework separate out:

- Task Submission
- Task Execution

The framework allows us to specify different policies for task execution. Java offers three interfaces, which classes can implement to manage thread lifecycle. These are:

- `Executor Interface`
- `ExecutorService`
- `ScheduledExecutorService`

The `Executor` interface forms the basis for the asynchronous task execution framework in Java.

You don't need to create your own executor class as Java's `java.util.concurrent` package offers several types of executors that are suitable for different scenarios. However, as an example, we create a dumb executor which implements the Executor Interface.

```
1  import java.util.concurrent.Executor;
2  class ThreadExecutorExample {
3
4      public static void main( String args[] ) {
5          DumbExecutor myExecutor = new DumbExecutor();
6          MyTask myTask = new MyTask();
7          myExecutor.execute(myTask);
8      }
9
10     static class DumbExecutor implements Executor {
11         // Takes in a runnable interface object
12         public void execute(Runnable runnable) {
13             Thread newThread = new Thread(runnable);
14             newThread.start();
15         }
16     }
17
18     static class MyTask implements Runnable {
19         public void run() {
20             System.out.println("Mytask is running now ...");
21         }
22     }
23
24 }
```

Run

Save

Reset

A Dumb Thread Executor

The `Executor` requires implementing classes to define a method `execute(Runnable runnable)` which takes in an object of interface `Runnable`. Fortunately, we don't need to define complex executors as Java already provides several that we'll explore in following chapters.