	Http Method	fault setting is http://{hostip}:8080/Hare	input(json)	loutout	
	<u>'</u>		Imput(Ison)	output	memo
create Connection	POST	{hostname}/connect	"zookeeperHost":"host1", "zookeeperPort":"2181", "nameNodeHostPort":"hoffs://host1:8020", "rmAddressHostPort":"host1:8032", "rmSchedulerAddressHostPort":"host1:8030", "rmResourceTrackerAddressHostPort":"host1:8031", "rmAdminAddressHostPort":"host1:8033", "mrJobhistoryAddress":"host1:10020", "hiveConnType":"LOCAL", "metaStoreConnectURL":"jdbc:mysql://10.15.1.32:3306/hare", "metaStoreConnectUrer":"nom.mysql.jdbc.Driver", "metaStoreConnectUserName":"root", "metaStoreConnectUserName":"root", "metaStoreConnectPassword":"123456", "enableKerberos":"true", "hbaseMasterPrincipal":"hbase/_HOST@ISLAND.COM", "hbaseRegionServerPrincipal":"hbase/_HOST@ISLAND.COM", "dfsDataNodePrincipal":"hdfs/_HOST@ISLAND.COM", "dfsDataNodePrincipal":"hive/_HOST@ISLAND.COM", "hiveMetaStorePrincipal":"hyarn/_HOST@ISLAND.COM", "yarnResourceMgrPrincipal":"yarn/_HOST@ISLAND.COM", "yarnResourceMgrPrincipal":"yarn/_HOST@ISLAND.COM", "yarnNodeMgrPrincipal":"yarn/_HOST@ISLAND.COM", "account":"!@#!\$%\$^", "pwd":"^\$%&%(^*") }	none	enableKerberos=enable Kerberos
create TABLE	POST	{hostname}/hbaseadmin/create	{ "tableName":"table1", "columnFamilys":["cf", "cf1"], "account":"!@#!\$%\$^", "pwd":"^\$%&%(^*") }	{ "responseTime": "391", "status": "success", "auth":"true", "exception":"exception" }	
upload data to htable	POST	{hostname}/bulkload/schema/upload	{ "schemaFilePath":"hdfs://host1:8020/schema/schema.txt", "dataPath":"hdfs://host1:8020/tmp/data.txt", "resultPath":"hdfs://host1:8020/tmp/exception.txt", "account":"!@#!\$%\$^", "pwd":"^\$%&%(^*") }	{ "jobName":"applicatid000001", "responseTime":"22334" "status": "success", "auth":"true" }	
check upload status	POST	{hostname}/bulkload/status	{ "jobName":"applicatid000001", "account":"[@#I\$%\$^", "pwd":"^\$%&%(^*") }	{ "auth": "true", "responseTime": "28", "status": "success", "bulkloadFinishTime": "30-01-2015 16:13:00", "bulkloadStartTime": "30-01-2015 16:12:29", "jobld": "job 1422588512235_0010", "jobName": "Hare_Application_1422605545249", "jobStatus": "SUCCEEDED", "mapProgress": "0.0%", "reduceProgress": "0.0%", "jobErrMessage":"error message", "auth":"true", "exception":"exception" }	

Harra Ol (a ala at alata)	Гроот	(le t) (le /	1,	1	
HareQL(select data)	POST	{hostname}/hareql/query	**tempFilePath":"/temp/ddd",	fileSize": "136485", "heads":[":key","cf:column1"], "responseTime":"123456", "results":["rk2\tvalue2",	
Scan table	POST	{hostname}/htable/scan	"tableName" = "table1", "pageSize" = "10", "limit" = "10", "account":" @#!\$%\$^", "pwd":"^\$%&%(^*") }	"auth": "true", "responseTime": "17", "status": "success", "heads":[{"columnFamily": "cf",	
HareQL(delete data)	POST	{hostname}/hareql/query	"tempFilePath":"/temp/ddd", "sql":"delete from table1 where `:key`='rowkey1'", "account":"!@#!\$%\$^", "pwd":"^\$%&%(^*") }	fileSize": "0", "responseTime":"1234", "rowSize": "0", "status":"sucess", "auth":"true", "exception":"exception" }	
drop table	POST	{hostname}/hbaseadmin/drop	{ "tableName" = "table1", "account":" @#!\$%\$^", "pwd":"^\$%&%(^*") }	{ "responseTime": "391", "status": "success", "auth":"true", "exception":"exception" }	
describe	format	1			
schemaFile format	bulkloadseparator= bulkloadfileformat=NORMAL bulkloadtablename=table100 bulkloadoutputfolder=hdfs://host1:9000/result bulkloadcolumn=:key,cf:column1,cf:column2 bulkloadcolumnrowkey=true,false,false bulkloadcolumnfamily=cf				
upload data format	:key_row1_va :key_row2_va	ilue column1_row1_value column2_ro ilue column1_row2_value column2_ro			

upload data badline forma badlineinfo: 12 :key row12 valuelcolumn1 row12 valuelcolu		
12 :key_row12_value column1_row12_value colu		