

Rajalakshmi Engineering College

Name: Haresh R
Email: 241901031@rajalakshmi.edu.in
Roll no:
Phone: null
Branch: REC
Department: CSE (CS) - Section 1
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 6_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Bob has been tasked with creating a program using CircleUtils class to calculate and display the circumference and area of the circle.

The program should allow Bob to input the radius of a circle as both an integer and a double and compute both the circumference and area of the circle using separate overloaded methods:

calculateCircumference- To calculate the circumference using the formula $2 * 3.14 * radius$
calculateArea- To calculate the area $3.14 * radius * radius$

Write a program to help Bob.

Input Format

The first line of input consists of an integer m, representing the radius of the

circle as a whole number.

The second line consists of a double value n, representing the radius of the circle as a decimal number.

Output Format

The first line of output displays two space-separated double values, rounded to two decimal places, representing the circumference of the circle with the integer radius and the double radius, respectively.

The second line displays two space-separated double values, rounded to two decimal places, representing the area of the circle with the integer radius and the double radius, respectively.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
3.50

Output: 31.40 21.98
78.50 38.47

Answer

```
import java.util.Scanner;

class CircleUtils {
    double calculateCircumference(int radius) {
        return 2 * 3.14 * radius;
    }

    double calculateCircumference(double radius) {
        return 2 * 3.14 * radius;
    }

    double calculateArea(int radius) {
        return 3.14 * radius * radius;
    }

    double calculateArea(double radius) {
```

```

        return 3.14 * radius * radius;
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        int radiusInt = scanner.nextInt();
        double radiusDouble = scanner.nextDouble();

        CircleUtils circleUtils = new CircleUtils();

        double circumferenceInt = circleUtils.calculateCircumference(radiusInt);
        double circumferenceDouble =
circleUtils.calculateCircumference(radiusDouble);
        double areaInt = circleUtils.calculateArea(radiusInt);
        double areaDouble = circleUtils.calculateArea(radiusDouble);

        System.out.format("%.2f %.2f\n", circumferenceInt, circumferenceDouble);
        System.out.format("%.2f %.2f", areaInt, areaDouble);

        scanner.close();
    }
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

Arun wants to calculate the age gap between the grandfather and the son and determine the father's age after 5 years.

Your task is to assist him in developing a program using three classes: GrandFather, Father, and Son, where the GrandFather stores the grandfather's age, the Father extends GrandFather to include the father's age and calculates his age after 5 years, and Son extends Father to include the son's age and calculate the age difference between the grandfather and the son.

Input Format

The input consists of three integers representing the ages of the grandfather, father, and son, one per line.

Output Format

The first line of output prints "Grandfather and son's age gap:" followed by an integer representing the age gap between the grandfather and the son, ending with "years".

The second line prints "Father's Age:" followed by an integer representing the father's age after 5 years, ending with "years".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 50

30

3

Output: Grandfather and son's age gap: 47 years

Father's Age: 35 years

Answer

```
import java.util.Scanner;
```

```
import java.util.*;
```

```
// Base class: GrandFather
```

```
class GrandFather {
```

```
    protected int grandfatherAge;
```

```
    public void setGrandfatherAge(int grandfatherAge) {
```

```
        this.grandfatherAge = grandfatherAge;
```

```
    }
```

```
}
```

```
// Derived class: Father extends GrandFather
```

```
class Father extends GrandFather {
```

```
    protected int fatherAge;
```

```
    public void setFatherAge(int fatherAge) {
```

```

        this.fatherAge = fatherAge;
    }

    public int calculateFatherAgeAfter5Years() {
        return fatherAge + 5;
    }
}

class Son extends Father {
    private int sonAge;

    public void setSonAge(int sonAge) {
        this.sonAge = sonAge;
    }

    public int calculateGrandfatherSonAgeDifference() {
        return grandfatherAge - sonAge;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        Son son = new Son();

        int grandfatherAge = scanner.nextInt();
        son.setGrandfatherAge(grandfatherAge);

        int fatherAge = scanner.nextInt();
        son.setFatherAge(fatherAge);

        int sonAge = scanner.nextInt();
        son.setSonAge(sonAge);

        System.out.println("Grandfather and son's age gap: "+
            son.calculateGrandfatherSonAgeDifference() + " years");

        int fatherAgeAfter5Years = son.calculateFatherAgeAfter5Years();
        System.out.println("Father's Age: " + fatherAgeAfter5Years + " years");
    }
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

Teena is launching a new airline, Boeing747, and needs to calculate the total revenue generated from ticket sales based on the ticket cost and seat availability. Teena's airline offers two types of seats: regular and premium. The ticket cost and seat availability for both types of seats need to be considered for revenue calculation.

To help with this, Teena wants to implement a system using multilevel inheritance with three classes:

Airline: This class will have the ticket cost as an attribute and defines the method `setCost(double cost)` and `double getCost()`. Indigo: This class will extend Airline and add the seat availability attribute and defines the method `getSeatAvailability()` and `setSeatAvailability(int seatAvailability)`. Boeing747: This class will extend Indigo and include a method `calculateTotalRevenue()` based on the ticket cost and seat availability.

Teena needs to calculate the total revenue using the formula:

$\text{Total Revenue} = \text{ticket cost} * \text{seat availability}$

Help Teena implement this system for calculating the revenue of her airline.

Input Format

The first line of input consists of a double value, representing the flight's ticket cost.

The second line consists of an integer, representing seat availability.

Output Format

The first line of output prints "Ticket Cost: Rs. " followed by a double value representing the ticket cost rounded to one decimal place.

The second line of output prints "Seat Availability: X seats" where X is an integer value representing the seat availability.

The third line of output prints "Total Revenue: Rs. " followed by a double value

representing the total revenue rounded to one decimal place.

Refer to the sample output for the exact text and format.

Sample Test Case

Input: 1000.0

100

Output: Ticket Cost: Rs. 1000.0

Seat Availability: 100 seats

Total Revenue: Rs. 100000.0

Answer

```
import java.util.Scanner;
```

```
class Airline {  
    private double cost;  
  
    public void setCost(double cost) {  
        this.cost = cost;  
    }  
  
    public double getCost() {  
        return cost;  
    }  
}
```

```
class Indigo extends Airline {  
    private int seatAvailability;  
  
    public void setSeatAvailability(int seatAvailability) {  
        this.seatAvailability = seatAvailability;  
    }  
  
    public int getSeatAvailability() {  
        return seatAvailability;  
    }  
}
```

```
class Boeing747 extends Indigo {
```

```

    public double calculateTotalRevenue() {
        return getCost() * getSeatAvailability();
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        Boeing747 plane = new Boeing747();

        double ticketCost = scanner.nextDouble();
        plane.setCost(ticketCost);
        int seatAvailability = scanner.nextInt();
        plane.setSeatAvailability(seatAvailability);

        System.out.printf("Ticket Cost: Rs. %.1f\n", plane.getCost());
        System.out.println("Seat Availability: " + plane.getSeatAvailability() + "
seats");
        System.out.printf("Total Revenue: Rs. %.1f\n",
plane.calculateTotalRevenue());
    }
}

```

Status : Correct

Marks : 10/10

4. Problem Statement

Mary is managing a business and wants to analyze its profitability. She operates both a regular business model and a seasonal business model. To assess profitability, she uses a program that calculates and compares the profit margins for both models based on revenue and cost.

The program defines:

BusinessUtility class with a method calculateMargin(double revenue, double cost). SeasonalBusinessUtility (inherits from BusinessUtility) and overrides calculateMargin(double revenue, double cost), adding a seasonal adjustment of 10% to the base margin. ProfitabilityChecker class with a method checkProfitability(double regularMargin), which prints "Business is profitable." if the regular margin is 10% or more, otherwise prints "Business is not profitable.".

Mary inputs revenue and cost, and the program compute and display the regular and seasonal margins using:

$$\text{Margin} = ((\text{Revenue} - \text{Cost}) / \text{Revenue}) \times 100$$

$$\text{Seasonal Margin} = \text{Margin} + 10$$

Input Format

The first line of input consists of a double value *r*, representing the revenue.

The second line consists of a double value *c*, representing the cost.

Output Format

The first line prints a double value, representing the regular profit margin, rounded to two decimal places, in the format: "Regular Margin: X. XX%", where X.XX denotes the calculated regular margin.

The second line prints a double value, representing the seasonal profit margin, rounded to two decimal places, in the format: "Seasonal Margin: X. XX%", where X.XX denotes the calculated seasonal margin.

The third line prints a string, indicating whether the business is profitable or not profitable, based on the regular margin.

If the regular margin is less than 10, print "Business is not profitable.". If it is 10 or greater, print "Business is profitable."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1000.0

800.0

Output: Regular Margin: 20.00%

Seasonal Margin: 30.00%

Business is profitable.

Answer

```
import java.util.Scanner;
```

```
class BusinessUtility {  
    public double calculateMargin(double revenue, double cost) {  
        return ((revenue - cost) / revenue) * 100;  
    }  
}
```

```
class SeasonalBusinessUtility extends BusinessUtility {  
    @Override  
    public double calculateMargin(double revenue, double cost) {  
        double baseMargin = super.calculateMargin(revenue, cost);  
        return baseMargin + 10;  
    }  
}
```

```
class ProfitabilityChecker {  
    public void checkProfitability(double regularMargin) {  
        if (regularMargin >= 10.0)  
            System.out.println("Business is profitable.");  
        else  
            System.out.println("Business is not profitable.");  
    }  
}
```

```
class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
        double revenue = scanner.nextDouble();  
        double cost = scanner.nextDouble();  
        BusinessUtility business = new BusinessUtility();  
        SeasonalBusinessUtility seasonalBusiness = new  
SeasonalBusinessUtility();  
        double regularMargin = business.calculateMargin(revenue, cost);  
        double seasonalMargin = seasonalBusiness.calculateMargin(revenue,  
cost);  
  
        System.out.printf("Regular Margin: %.2f%%\n", regularMargin);  
    }  
}
```

```
System.out.printf("Seasonal Margin: %.2f%%\n", seasonalMargin);

ProfitabilityChecker checker = new ProfitabilityChecker();
checker.checkProfitability(regularMargin);
scanner.close();
    }
}
```

Status : Correct

Marks : 10/10