

DUKE[®] Q1

FULLY AUTOMATIC TAGGING MACHINE

Automatic Tagging for Higher Efficiency

The DUKE Q1 is a fully automatic tagging machine designed for fast, reliable and precise tagging. With multiple operating modes and easy adjustment, it helps improve productivity and is widely used in apparel, textile and consumer goods industries.



**RELIABLE
TAGGING
FOR A SMARTER
PRODUCTION**



High Efficiency

Automatic operation improves productivity



Multi-Card Operation

Supports 1-6 cards in one cycle



Foot Pedal Control

Semi-automatic mode for flexible operation



Precise Adjustment

Easy adjustment for different products



Wide Application

Suitable for various industries and products

ENGINEERED FOR EFFICIENT TAGGING

A OPERATING MODES

- Before starting work, first align the card so that the center of the card hole aligns with the needle tip.
- After alignment, press the start button to begin operation.

B MULTI-CARD MODES

- Supports single card, dual cards, three cards, four cards, five cards, and six cards.

C SEMI-AUTOMATIC MODE (FOOT PEDAL)

- Controlled by a foot pedal switch.
- Suitable for precise adjustments and special requirements.

D AUTOMATIC MODE

- Press the sensor panel to automatically nail the tag.

E EASY CONTROL

- Display shows "STOP" when the emergency stop switch is activated.
- User-friendly operation panel.

F PRECISE ADJUSTMENT

- Press and hold the "S" button to test if the stapling air valve works normally; release to reset.
- Press the "P" button to perform normal adjustment operations; press again to reset.
- Press and hold the "-" button for 5 seconds to reset the needle count.
- Press and hold the "+" button for 5 seconds to view the total count.

APPLICATIONS



Plush Toy



Towel



Underwear



Clothing



Umbrella

TECHNICAL PARAMETERS

Parameter	Value	Remarks	
Operating Air Pressure	6-0.7MPa (7kg)	Factory air source output $\geq 0.55\text{MPa}$ (5.5kg)	
Tag Hole Diameter	Recommended 2mm	Needle model	Standard factory Standard factory configuration: fine needle ($\phi 0.7\text{mm}$)
Workspace	Recommended size: 300mm (W) $\times$ 200mm (D) (Depends on actual product size)		220V
Dimensions (L $\times$ W $\times$ H)	50 $\times$ 40 $\times$ 53cm	Net weight / Gross weight	14kg / 16.8kg
Tagging Barbs	10-40mm Fine needles	Tagging speed	0.3 pcs/s
Card Width	30-80mm	Card length	30-140mm
Air Source Recommendation	It is recommended to use an air source supplied through an air filter, storage tank and pressure regulator to ensure clean air.		

ELECTRICAL CONTROL PARAMETERS

Parameter ID	Value	Default	Notes
P001	Card Ejection Time	20	Unit: 10ms
P002	Needle Punching Time	10	Unit: 10ms
P003	Vacuum Feeding Time	10	Unit: 10ms
P004	Delay Staple Feeding Time	0	Unit: 10ms
P005	Card Dispensing Condition	1	1: Card is dispensed only when the needle counts to 0; 0: Card is dispensed even when the needle is not 0.
P006	Mode Selection	1	0: Pedal Mode 1: Automatic Mode
P008	Restore Factory Settings	0	After changing this parameter to 1, press the start key to restore factory parameters.



Operation Panel



Air Pressure Regulator