

DUKE

DY 438GT+LA971

Fully Automatic Button Sewing Machine



Specification :

Stitch Formation	: Single Needle Lockstitch
Sewing Speed	: 3200 rpm
Work Clamp Height	: Max. 17mm
Sewing Area (X-Y)	: Max. 40-30mm
Stitch Length	: 0.05 - 12.7mm
Thread Trimmer	: Standard Equipment.
Rotary Hook	: Shuttle Hook
Work Clamp Lifter	: Pulse Motor Drive System
Power Source	: Single Phase 100V/220V, Three
Phase	: 200V/220V/380V/400V

Product Features

1. The products are mainly aimed at the winding of button legs of high-end clothing. And the winding wire 360 degrees full hot melt. Make the buttons both strong and beautiful. There are no thread residue issues.
2. The machine is simple to operate and does not require skilled workers One buckle per second is ten times more than a manual buckle. Save time and labor.
3. Use hot melt wire to wrap the buckle. Three buckle winding patterns have a button pulling function to make the button winding wire more even. The touchscreen display interface is intuitive and easy to operate. Multi-language mode one-click switching.
4. Suitable for all kinds of high-end clothing, button wrapping, such as suits.shirts.coats.wear.T-shirts. clothing such as pants are buttoned.



HARI CHAND ANAND & CO.

Corporate Head Office:

A-94/1, Okhla Industrial Area Phase II, New Delhi - 110020


+91 8860086712 , 9313308705

enquiry@grouphca.com


> Software control system, support CorelDraw, Auto CAD and other software, support AI, PLT, DXF and other formats, support network, USB and other fast read and write file rates.



> Intelligent typesetting software can optimize the processing path, calculate the length of the material used and the cutting count, saving labor and material.



> The infrared positioning function allows the typeset materials to be quickly positioned within the effective cutting range, avoiding unnecessary waste of materials.



> Projection function: For leather proofing, replenishment or irregular materials, you need to place a pattern on the material before cutting. The projector projects the image output by the computer onto the material on the workbench, so that the computer can be used intuitively The operation discharges patterns on the material.



Specifications

Type	DY C 1510
Max cutting area	1500x1000mm
Size	2000x1760x1300mm
Max speed	1200mm/s
Accuracy	±0.1mm
Max Thickness of materials	40mm
Motor	Servo
Data format	DXF HPGL
Interface	USB or Internet Port
Dielectric adsorption	Vacuum
Overall power	5KW
Power	220V/50HZ
Weight	500Kg



HARI CHAND ANAND & CO.

Corporate Head Office:

A-94/1, Okhla Industrial Area Phase II, New Delhi - 110020

 **+91 8860086712 , 9313308705**

 **enquiry@grouphca.com**