

## JTK6-60A

智能模板机  
 SMART TEMPLATE MACHINE



### 产品简介 Product introduction

小机型、大智慧、多用途，占地少、功能多、移动便  
 Small models, great wisdom, multi-purpose, small footprint, multi-function, mobile

### 性能参数 The performance parameters

|                                    |                                                                                                                     |                                       |                                                                          |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------|---------------------------------------|--------------------------------------------------------------------------|
| 有效缝纫范围<br>Sewing range             | X轴60×Y轴40cm<br>X: 60 cm Y:40cm                                                                                      | 操作显示屏<br>Operating display            | 全液晶：触摸式液晶显示屏<br>Full liquid crystal: touch liquid crystal display screen |
| 最高缝速<br>Speed                      | 200rpm-3000rpm (需要看机型、针距、材料、缝线情况)<br>200rpm-3000rpm(depend on the machine model,needle distance, material, thread.) | 传动结构<br>Transmission structure        | 齿带导轨模组传动模式<br>Toothed belt guide module transmission mode                |
| 剪线机构<br>Trimming mechanism         | 圆刀剪线机构，适应性更广泛<br>Circular cutter wire cutting mechanism, more extensive adaptability                                | 设备占地面积<br>Machine floor space         | 150x120cm                                                                |
| 针距<br>Stitch length                | 0.5mm 至 6mm<br>0.5mm to 6mm                                                                                         | 程序记忆载体<br>Program memory carrier      | EPROM内存<br>EPROM memory                                                  |
| 可识别模板文件<br>Identify template files | 电子标签射频识别：识别数量无限<br>RFID: the identification number is unlimited                                                     | 缝纫机马达<br>Sewing motor                 | 1000W直接驱动伺服马达<br>1000W Direct drive servomotor                           |
| 缝针<br>Needle number                | DP×5(#7-#24); DP×17(#11-#24)                                                                                        | 电源规格<br>Power specification           | 200V-230V 1000W                                                          |
| 程序输入装置<br>Program input device     | 电脑USB数据线或U盘<br>Computer USB cable or USB drive                                                                      | 使用空气规格<br>Air pressure specifications | 0.5-0.6MPa(最大0.6MPa)<br>0.5-0.6MPa (max 0.6MPa)                          |