



## 1335M

### Multi-Purpose Ruffler Workstation

- Pillow-Top Gusset Ruffler
- Euro-Top Ruffler
- Continental Foundation Ruffler
- No Flip Mattress

Accomplish all of the above by simple material guide change.

- High-speed heavy-duty sewing machine
- Stepping motor drive puller
- Electronic sewing motor
- Electronic speed control
- Needle positioner - no synchronizer
- Pneumatic footlift
- Auto stop at corner
- Adjustable folder for symmetrical and offset gusset
- Gusset may be pre-flanged
- Color touch screen control system (PLC)

### Çok Amaçlı Köşe Büzgü Makinası

- Pedli yatak köşe büzme
- Euro-top tipi büzme
- Baza köşe büzme

Yukarıdaki özelliklerin tümünü basit kılavuz değişikliği ile gerçekleştirin.

- Kalın malzeme için yüksek hızlı dikiş kafası
- Step motorlu tahrik mekanizması
- Elektronik hız kontrolü
- İğne konumlandırıcı - Senkronizatör yok
- Pnömatik kumaş baskı ayağı kaldırma
- Köşelerde otomatik durma
- Simetri için ayarlanabilir kılavuz ve köşebent
- Köşebent kıvrımlı olabilir
- Renkli dokunmatik ekranlı kontrol sistemi(PLC)



# 1335M

## Technical Information

### OPTIONS

- **1337AT** - Single pneumatic flotation table
- **1337ATB** - Single air table with back drop shelf
- **1337022** - 18" Single air table extensions

### Sewing Head Preference

Model	Application	Sewing Head
<b>1335MF</b>	Drop Feed	Yamato 1804
<b>1335MG</b>	Needle Feed	Yamato 2002
<b>1335MH</b>	Walking Foot	300UX6

## Teknik Bilgiler

### SEÇENEKLER

- **1337AT** - Tek pnömatik dikiş masası
- **1337ATB** - Tek pnömatik dikiş masası - Açılır raflı
- **1337022** - 46cm'e kadar masa uzatması

### Dikiş Kafası Tercihleri

Model	Kullanım	Dikiş Kafası
<b>1335MF</b>	Altan beslemeli	Yamato 1804
<b>1335MG</b>	İğne beslemeli	Yamato 2002
<b>1335MH</b>	Alternatif ayak.	300UX6

## Method of construction / Uygulamalar



Euro-Top



Continental Foundation & Capping  
Baza köşe büzme




Pillow-Top


SPECIFICATIONS / ÖZELLİKLER	F	G	H
Max sewing speed (rpm) / Maksimum dikiş hızı (rpm)	4500	5000	3000
Factory preset speed (rpm) / Fabrika ayarlı hız (rpm)	3500	3200	2500
Max stitch length (spi) / Maksimum dikiş uzunluğu (spi)	7	4	3.3
Needle system / İğne sistemi	SN62X5721	SN62X5924	SN62X8524
Needle size / İğne ölçüsü	22/140	22/140	24/180
Weight of material / Malzeme tipi	LIGHT	MEDIUM	HEAVY
Max presser footlift (inch) / Maksimum baskı ayağı kaldırma (inch)	5/32	11/32	
Voltage (v/ph/hz) / Voltaj (v/ph/hz)	220V 1PH 60HZ		
Current (amps) / Akım (amper)	5		
Motor type / Motor tipi	EFKA DC		
Air pressure (psi) / Hava basıncı (psi)	80		
Air consumption (cfm) / Hava tüketimi (cfm)	2		
Shipping weight (lbs) / Nakliye ağırlığı (kg)	820 / 372		
Shipping dimensions (w/l/h, inch) / Nakliye boyutları (w/l/h, cm)	74x48x65 / 188x122x165		

PRODUCTION / ÜRETİM	
Pieces Per Hour / Saatte üretim adedi	25 - 30

### Footprint Makina Yerleşim



**1335MA**



**1335MA-SUAT**  
with Single Air Table  
Tek pnömatik dikiş  
masası ile

**PATENTS:** Our equipment may be covered by one or more patents. Please go to the following web page for an up-to-date patent list: [www.atlantt.com/patents](http://www.atlantt.com/patents) © 2020 Atlanta Attachment Co. 19189010120