# Dashboard / My courses / PSPP/PUP / Functions: Built-in functions, User-defined functions, Recursive functions / Week9 Coding

Started on	Wednesday, 5 June 2024, 2:39 PM
State	Finished
Completed on	Friday, 7 June 2024, 2:39 PM
Time taken	2 days
Marks	4.00/5.00
Grade	<b>80.00</b> out of 100.00

```
Question 1
Correct
Mark 1.00 out of 1.00
```

Write a code to check whether product of digits at even places is divisible by sum of digits

at odd place of a positive integer.

Input Format:

Take an input integer from stdin.

Output Format:

Print TRUE or FALSE.

Example Input:

1256

Output:

TRUE

Example Input:

1595

Output:

FALSE

## For example:

Test	Result
<pre>print(productDigits(1256))</pre>	True
<pre>print(productDigits(1595))</pre>	False

Answer: (penalty regime: 0 %)

Reset answer

```
1 ▼ def productDigits(n):
        n=str(n)
 2
 3
         e=1
4
         o=<mark>0</mark>
 5 ,
         for i,digit in enumerate(n):
 6 •
             if i%2==0:
                 o+=int(digit)
7
 8 🔻
                  e=e*int(digit)
 9
10
         return("True") if e%o==0 else("False")
```

	Test	Expected	Got	
~	print(productDigits(1256))	True	True	~
~	<pre>print(productDigits(1595))</pre>	False	False	~

Passed all tests! 🗸

Correct

Marks for this submission: 1.00/1.00.

Question **2**Correct

Mark 1.00 out of 1.00

Given a number with maximum of 100 digits as input, find the difference between the sum

of odd and even position digits.

Input Format:

Take a number in the form of String from stdin.

Output Format:

Print the difference between sum of even and odd digits

Example input:

1453

Output:

1

Explanation:

Here, sum of even digits is 4 + 3 = 7

sum of odd digits is 1 + 5 = 6.

Difference is 1.

Note that we are always taking absolute difference

Answer: (penalty regime: 0 %)

```
Reset answer
```

```
1 ⋅ def differenceSum(n):
        n=str(n)
 3
        a=0
 4
        b=0
        for i, digit in enumerate(n):
 5 .
 6 •
            if i%2==0:
 7
                a=a+int(digit)
 8 🔻
                 b=b+int(digit)
10
        return(abs(a-b))
11
```

	Test	Expected	Got	
~	<pre>print(differenceSum(1453))</pre>	1	1	~

Passed all tests! 🗸

Correct

Marks for this submission: 1.00/1.00.

```
Question 3
Correct
```

Mark 1.00 out of 1.00

complete function to implement coin change making problem i.e. finding the minimum

number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer: (penalty regime: 0 %)

Reset answer

```
1 → def coinChange(n):
        a=n//4
 2
        b=n%4
 3
4
        c=b//3
 5
        d=b%3
 6
        e=d//2
7
        f=d%2
 8
        g=f//1
        return(a+c+e+g)
10
```

	Test	Expected	Got	
<b>~</b>	<pre>print(coinChange(16))</pre>	4	4	~

Passed all tests! 🗸

Correct

Marks for this submission: 1.00/1.00.

Question **4**Not answered

Mark 0.00 out of 1.00

An automorphic number is a number whose square ends with the number itself.

For example, 5 is an automorphic number because 5\*5 =25. The last digit is 5 which same

as the given number.

If the number is not valid, it should display "Invalid input".

If it is an automorphic number display "Automorphic" else display "Not Automorphic".

Input Format:

Take a Integer from Stdin Output Format: Print Automorphic if given number is Automorphic number, otherwise Not Automorphic Example input: 5 Output: Automorphic Example input: 25 Output: Automorphic Example input: 7 Output: Not Automorphic

#### For example:

Test	Result		
<pre>print(automorphic(5))</pre>	Automorphic		

Answer: (penalty regime: 0 %)

Reset answer

	Neset allswei							
1 v d	ef automorphic(n):							
_ ,								

```
Question 5
Correct
Mark 1.00 out of 1.00
```

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

1 <= orderValue< 10e100000

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

#### For example:

Test	Result	
<pre>print(christmasDiscount(578))</pre>	12	

Answer: (penalty regime: 0 %)

```
Reset answer
```

	Test	Expected	Got		
<b>~</b>	<pre>print(christmasDiscount(578))</pre>	12	12	<b>~</b>	

Passed all tests! <

Correct

Marks for this submission: 1.00/1.00.

### ■ Week9\_MCQ

```
Jump to...
```

Searching -