

jQuery Exercises

Complete Solutions with Code

Exercise 1: jQuery Library Inclusion

Add jQuery to a page using CDN and locally, then log a paragraph to console.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>jQuery Inclusion</title>
  <!-- Method 1: CDN -->
  <script src="https://code.jquery.com/jquery-3.7.1.min.js"></script>
  <!-- Method 2: Local (uncomment to use downloaded copy) -->
  <!-- <script src="js/jquery-3.7.1.min.js"></script> -->
</head>
<body>
  <p id="msg">Hello World!</p>

  <script>
    $(document).ready(function() {
      // Log the paragraph text via jQuery
      console.log($('#msg').text());

      // Bonus: Change color to confirm jQuery is working
      $('#msg').css('color', 'blue');
    });
  </script>
</body>
</html>
```

Exercise 2: The \$() Function — Selecting Elements

Use \$() to change h1 text and hide a paragraph on button click.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>jQuery Selectors</title>
  <script src="https://code.jquery.com/jquery-3.7.1.min.js"></script>
</head>
<body>
  <h1 id="heading">Original Heading</h1>
  <p id="p1">Paragraph One – I will be hidden.</p>
  <p id="p2">Paragraph Two – I stay visible.</p>
  <button id="btnChange">Change Heading & Hide Para</button>

  <script>
    $(document).ready(function() {
      // Change h1 text immediately
      $('#h1').text('Updated via jQuery!');

      // Hide first paragraph on button click
      $('#btnChange').click(function() {
```

```

        $('#p1').hide();
    });
});
</script>
</body>
</html>

```

Exercise 3: jQuery Methods — hide, show, fade, toggle

Apply *hide*, *show*, *fadeOut*, *fadeIn*, and *toggle* on *.box* elements; chain *slideUp* and *slideDown*.

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>jQuery Methods</title>
  <script src="https://code.jquery.com/jquery-3.7.1.min.js"></script>
  <style>
    .box {
      width: 150px; height: 80px; margin: 8px;
      display: inline-block; background: #9c27b0;
      color: white; text-align: center; line-height: 80px;
      border-radius: 6px; font-weight: bold;
    }
    button { margin: 6px; padding: 8px 14px; cursor: pointer; }
  </style>
</head>
<body>
  <div class="box" id="b1">Box 1</div>
  <div class="box" id="b2">Box 2</div>
  <div class="box" id="b3">Box 3</div>
  <br>
  <button onclick="$(' .box').hide()">Hide All</button>
  <button onclick="$(' .box').show()">Show All</button>
  <button onclick="$(' .box').fadeOut(600)">Fade Out</button>
  <button onclick="$(' .box').fadeIn(600)">Fade In</button>
  <button onclick="$(' .box').toggle()">Toggle</button>
  <button id="slideBtn">Slide Up then Down</button>

  <script>
    $(document).ready(function() {
      // Bonus: chained slide with delay
      $('#slideBtn').click(function() {
        $(' .box').slideUp(500).delay(1000).slideDown(500);
      });
    });
  </script>
</body>
</html>

```

Exercise 4: DOM Manipulation — Creating and Modifying Elements

Take input value, create a new , append to , and remove all on 'Remove All'.

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">

```

```

<title>DOM Manipulation</title>
<script src="https://code.jquery.com/jquery-3.7.1.min.js"></script>
<style>
  body { font-family: Arial, sans-serif; max-width: 400px; margin: 40px auto; }
  input { padding: 8px; width: 70%; }
  button { padding: 8px 14px; cursor: pointer; margin-left: 4px; }
  #itemList { margin-top: 14px; padding-left: 20px; }
  #itemList li {
    background: #e1bee7; padding: 6px 10px;
    margin: 4px 0; border-radius: 4px; list-style: disc;
  }
  #removeAll { background: #c62828; color: white;
    border: none; border-radius: 4px; margin-top: 10px; }
</style>
</head>
<body>
  <h2>Event Item List</h2>
  <input type="text" id="itemInput" placeholder="Enter event name...">
  <button id="addBtn">Add</button>
  <ul id="itemList"></ul>
  <button id="removeAll">Remove All</button>

  <script>
    $(document).ready(function() {
      $('#addBtn').click(function() {
        const val = $('#itemInput').val().trim();
        if (val) {
          $('#itemList').append('<li>' + val + '</li>');
          $('#itemInput').val('');
        }
      });

      $('#removeAll').click(function() {
        $('#itemList').empty();
      });
    });
  </script>
</body>
</html>

```

Exercise 5: Working with Events — Color Box

Change #colorBox background to red on click, back to white on double-click.

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Color Box Events</title>
  <script src="https://code.jquery.com/jquery-3.7.1.min.js"></script>
  <style>
    body { font-family: Arial, sans-serif; text-align: center; padding: 40px; }
    #colorBox {
      width: 200px; height: 200px; margin: 20px auto;
      background-color: white;
      border: 3px solid #333;
      border-radius: 8px;
      line-height: 200px; font-size: 1.1em;
    }
  </style>

```

```

        #colorBtn { padding: 10px 22px; font-size: 1em; cursor: pointer; }
    </style>
</head>
<body>
    <h2>Event Color Box</h2>
    <button id="colorBtn">Click to change color</button>
    <div id="colorBox">Click the button!</div>

    <script>
        $(document).ready(function() {
            $('#colorBtn').click(function() {
                $('#colorBox').css('background-color', 'red').text('Red!');
            });

            $('#colorBox').dblclick(function() {
                $(this).css('background-color', 'white').text('Reset!');
            });
        });
    </script>
</body>
</html>

```

Exercise 6: Event Helpers — Mouse and Keyboard Events

Use `.click()`, `.dblclick()`, `.mouseenter()`, `.mouseleave()`, and `.keypress()` on a and input.

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>jQuery Event Helpers</title>
    <script src="https://code.jquery.com/jquery-3.7.1.min.js"></script>
    <style>
        body { font-family: Arial, sans-serif; max-width: 480px; margin: 40px auto; }
        #eventBox {
            padding: 30px; background: #e8eaf6; border: 2px solid #5c6bc0;
            border-radius: 8px; text-align: center; cursor: pointer;
            font-size: 1em; transition: background 0.2s;
        }
        #log { margin-top: 12px; color: #333; font-size: 0.95em; min-height: 24px; }
        input { width: 100%; padding: 8px; margin-top: 12px; box-sizing: border-box; }
        #keyLog { color: purple; margin-top: 6px; }
    </style>
</head>
<body>
    <h2>jQuery Event Helpers</h2>
    <div id="eventBox">Interact with me!</div>
    <div id="log">Status: waiting...</div>

    <input type="text" id="typeBox" placeholder="Type here to test keypress...">
    <div id="keyLog">Key pressed: —</div>

    <script>
        $(document).ready(function() {
            const log = $('#log');

            $('#eventBox').click(function() {
                $(this).css('background', '#c5cae9');
                log.text('Single click detected!');
            });
        });
    </script>

```

```
});

$('#eventBox').dblclick(function() {
    $(this).css('background', '#ff8a65');
    log.text('Double-click detected!');
});

$('#eventBox').mouseenter(function() {
    $(this).css('border-color', '#e91e63');
    log.text('Mouse entered the box.');
```

```
});

$('#eventBox').mouseleave(function() {
    $(this).css('border-color', '#5c6bc0').css('background', '#e8eaf6');
    log.text('Mouse left the box.');
```

```
});

$('#typeBox').keypress(function(e) {
    $('#keyLog').text('Key pressed: ' + String.fromCharCode(e.which) +
        ' (code: ' + e.which + ')');
```

```
});
});
</script>
</body>
</html>
```