

eNoah Coding Standards - C Language

Table of Contents

1. NAMING CONVENTIONS

1.1 File Names

1.2 Function Names

1.3 Variable Names

1.4 Constant Names

1.5 Type Definitions

1.6 Macro Names

2. CODE ORGANIZATION

2.1 Header Files (.h)

2.2 Source Files (.c)

2.3 Include Guards

2.4 Include Order

3. FORMATTING STANDARDS

3.1 Braces Placement

3.2 Indentation

3.3 Line Length

3.4 Spacing

4. COMMENTING STANDARDS

4.1 File Headers

4.2 Function Comments

4.3 Inline Comments

5. DATA TYPES AND DECLARATIONS

5.1 Variable Declarations

5.2 Type Definitions

5.3 Structure Definitions

6. FUNCTION STANDARDS

6.1 Function Length

6.2 Parameter Passing

6.3 Return Values

7. PREPROCESSOR DIRECTIVES

7.1 Macro Definitions

7.2 Conditional Compilation

8. ERROR HANDLING

8.1 Return Code Standards

8.2 Error Reporting

9. MEMORY MANAGEMENT

9.1 Dynamic Allocation

9.2 Pointer Usage

10. SECURITY GUIDELINES

10.1 Buffer Management

10.2 Input Validation

1. Naming Conventions

1.1 File Names

Use lowercase with underscores for file names.

c

// Good

file_operations.c

database_manager.h

network_utils.c

// Bad

FileOperations.c *// PascalCase*

fileoperations.c *// no underscores*

FILE_OPS.C *// uppercase*

1.2 Function Names

Use snake_case for function names.

c

// Good void calculate_user_score(void); int validate_input_data
(const char* data);

FILE* open_log_file(const char* filename);

// Bad void CalculateUserScore(void); *// PascalCase* void calcu
lateUserScore(void); *// camelCase* void CALCULATE_USER_SCORE(v
oid); *// uppercase*

1.3 Variable Names

Use snake_case for variables. Prefix pointers with 'p', arrays with 'arr'.

c

```
// Goodint user_count;char* p_filename;int arr_user_ids[MAX_USERS];float temperature_celsius;
```

```
// Badint userCount;           // camelCasechar* Filename;
// PascalCaseint user_ids_array[]; // redundant
```

1.4 Constant Names

Use UPPER_SNAKE_CASE for constants and macros.

c

```
// Good#define MAX_BUFFER_SIZE 1024#define DEFAULT_TIMEOUT 30const int MAX_USERS = 100;
```

```
// Bad#define maxBufferSize 1024 // camelCase#define DefaultTimeout 30 // PascalCaseconst int max_users = 100; // snake_case
```

1.5 Type Definitions

Use typedef with _t suffix for custom types.

c

```
// Goodtypedef unsigned int user_id_t;typedef struct node_s node_t;typedef enum status_e status_t;
```

```
// Badtypedef unsigned int USER_ID; // uppercasetypedef struct node Node; // no suffix
```

1.6 Macro Names

Use UPPER_SNAKE_CASE for macros. Parenthesize macro parameters.

c

```
// Good#define MIN(x, y) ((x) < (y) ? (x) : (y))#define ARRAY_SIZE(arr) (sizeof(arr) / sizeof((arr)[0]))
```

```
// Bad#define min(x, y) x < y ? x : y // no parentheses#define ARRAY_SIZE(arr) sizeof(arr)/sizeof(arr[0]) // no spacing
```

2. Code Organization

2.1 Header Files (.h)

Header files should contain declarations only.

c

```
// database_manager.h#ifndef DATABASE_MANAGER_H#define DATABASE_MANAGER_H
```

```
#include <stdint.h>#include <stdbool.h>
```

```
#define DB_MAX_CONNECTIONS 10#define DB_TIMEOUT_MS 5000
```

```
typedef struct database_s database_t;
```

```
typedef enum {
```

```
    DB_SUCCESS = 0,
```

```
    DB_ERROR_CONNECTION,
```

```
    DB_ERROR_TIMEOUT} db_status_t;
```

```
db_status_t database_connect(const char* connection_string);db_status_t database_execute_query(database_t* db, const char* query);void database_disconnect(database_t* db);
```

```
#endif /* DATABASE_MANAGER_H */
```

2.2 Source Files (.c)

Source files should contain implementations.

c

```
// database_manager.c#include "database_manager.h"#include <stdlib.h>#include <string.h>
```

```
struct database_s {
```

```
    char connection_string[256];
```

```
    bool is_connected;
```

```
    uint32_t timeout_ms;};
```

```
db_status_t database_connect(const char* connection_string){
```

```
    if (connection_string == NULL || strlen(connection_string) == 0) {
```

```
        return DB_ERROR_CONNECTION;
```

```
    }
```

```
    // Implementation
```

```
    return DB_SUCCESS;}
```

2.3 Include Guards

Use `#ifndef` guards with file-specific names.

c

```
// Good
#ifndef NETWORK_UTILS_H
#define NETWORK_UTILS_H // content
#endif /* NETWORK_UTILS_H */
```

```
// Bad
#pragma once // Not all compilers support this
#ifndef UTILS_H // Too generic
```

2.4 Include Order

Group includes in logical order.

c

```
// System headers first
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
```

```
// Third-party headers
#include <openssl/ssl.h>
```

```
// Project headers
#include "database_manager.h"
#include "network_utils.h"
```

3. Formatting Standards

3.1 Braces Placement

Use K&R style braces.

c

```
// Good
int calculate_sum(int a, int b){
```

```
    if (a > 0 && b > 0) {
```

```
        return a + b;
```

```
    } else {
```

```
        return 0;
```



```
}}
```

```
// Bad - Allman styleint calculate_sum(int a, int b){
```

```
    if (a > 0 && b > 0)
```

```
    {
```

```
        return a + b;
```

```
    }
```

```
    else
```

```
    {
```

```
        return 0;
```

```
}}
```

3.2 Indentation

Use 4 spaces for indentation (no tabs).

c

```
// Goodvoid process_data(const char* data, size_t length){
```

```
    if (data != NULL && length > 0) {
```

```
        for (size_t i = 0; i < length; i++) {
```

```
            if (is_valid_character(data[i])) {
```

```
                handle_character(data[i]);
```

```
            }
```

```

    }

}}

// Bad - mixed tabs and spaces
void process_data(const char* data,
size_t length){

    if (data != NULL) { // 2 spaces

        for (int i = 0; i < length; i++) { // tab

            // inconsistent

        }

    }

}}

```

3.3 Line Length

Maximum 80 characters per line.

```

c

// Good - break long lines logically
if (user_is_authenticated
&& user_has_permission(PERM_READ) &&

    data_is_available() && !system_is_locked()) {

    display_content();}

// Bad - too long
if (user_is_authenticated && user_has_permission(PERM_READ) && data_is_available() && !system_is_locked())
{

    display_content();}

```

3.4 Spacing

Use consistent spacing around operators.

c

```
// Good
int result = (a * b) + (c / d);
if (count > MAX_ITEMS ||
    flag == true) {
```

```
    process_items();
}
```

```
// Bad
int result=(a*b)+(c/d);
if (count>MAX_ITEMS||flag==true){
```

```
    process_items();
}
```

4. Commenting Standards

4.1 File Headers

Include descriptive file headers.

c

```
/**
```

```
 * @file network_utils.c
```

```
 * @brief Network utility functions for TCP/IP communication
```

```
 *
```

```
 * This module provides utility functions for network operations including
```

```
 * socket creation, connection management, and data transmission.
```

```
 *
```

```
 * @author Developer Name
```

```
* @date 2024-01-15
```

```
* @version 1.0
```

```
*
```

```
* Updated By: Developer Name
```

```
* Updated Date: 2024-02-20
```

```
* Description: Added IPv6 support, fixed memory leak in socket creation
```

```
*/
```

```
#include "network_utils.h"
```

4.2 Function Comments

Use Doxygen-style function comments.

```
c
```

```
/**
```

```
 * @brief Establishes a TCP connection to the specified host and port
```

```
*
```

```
 * This function creates a TCP socket and attempts to connect to the
```

```
 * specified hostname and port. It handles DNS resolution and timeout.
```

```
*
```

```
 * @param hostname The target hostname or IP address
```

```

* @param port The target port number

* @param timeout_ms Connection timeout in milliseconds

*

* @return socket_fd_t File descriptor of the connected socket
on success,

*          INVALID_SOCKET on failure

*

* @note The caller is responsible for closing the socket using
close_socket()

*/socket_fd_t tcp_connect(const char* hostname, uint16_t port,
uint32_t timeout_ms){

    // Implementation}

```

4.3 Inline Comments

Comment complex logic, but avoid stating the obvious.

c

```

// Good// Calculate CRC32 checksum for data validationuint32_t
crc = calculate_crc32(buffer, length);if (crc != expected_crc)
{

    // Data corruption detected, request retransmission

    request_retransmission();}

// Badint x = 5; // Set x to 5

x++; // Increment x by 1

```

5. Data Types and Declarations

5.1 Variable Declarations

Declare variables at the beginning of blocks.

c

```
// Good
void process_user_data(user_t* user){

    int error_code = 0;

    char buffer[MAX_BUFFER_SIZE];

    size_t bytes_read = 0;


    // Rest of function}

// Bad - mixed declarations and code
void process_user_data(user_t* user){

    int error_code = 0;

    process_something();

    char buffer[MAX_BUFFER_SIZE]; // Declaration after code}
```

5.2 Type Definitions

Use meaningful type names with `_t` suffix.

c

```
// Good
typedef uint32_t user_id_t;
typedef int64_t timestamp_t;
typedef enum {
```

```

STATE_IDLE,

STATE_ACTIVE,

STATE_ERROR} system_state_t;

// Badtypedef uint32_t U32; // Not descriptive
// Too generictypedef int ID;

```

5.3 Structure Definitions

Use forward declarations when needed.

```

c

// Good - forward declarationtypedef struct list_node_s list_n
ode_t;

struct list_node_s {

    void* data;

    list_node_t* next;

    list_node_t* prev;};

// Self-referential structuretypedef struct tree_node_s {

    int value;

    struct tree_node_s* left;

    struct tree_node_s* right;} tree_node_t;

```

6. Function Standards

6.1 Function Length

Keep functions focused and under 50 lines.

c

```
// Good - focused functiondb_status_t validate_connection_params(const db_config_t* config){
```

```
    if (config == NULL) {
```

```
        return DB_ERROR_INVALID_PARAM;
```

```
    }
```

```
    if (strlen(config->hostname) == 0) {
```

```
        return DB_ERROR_INVALID_HOST;
```

```
    }
```

```
    if (config->port == 0 || config->port > 65535) {
```

```
        return DB_ERROR_INVALID_PORT;
```

```
    }
```

```
    return DB_SUCCESS;}
```

```
// Bad - function does too muchdb_status_t setup_database_connection(void){
```



```
// 100+ lines of mixed responsibilities}
```

6.2 Parameter Passing

Pass large structures by pointer, small types by value.

c

```
// Good - large structure by pointervoid update_user_profile(u  
ser_profile_t* profile, const update_data_t* update){
```

```
// Modify profile through pointer}
```

```
// Good - small types by valueint calculate_sum(int a, int b){
```

```
    return a + b;}
```

```
// Bad - large structure by valuevoid process_large_data(large  
_struct_t data) // Inefficient{
```

```
// Makes copy of entire structure}
```

6.3 Return Values

Use consistent return codes.

c

```
typedef enum {
```

```
    SUCCESS = 0,
```

```
    ERROR_INVALID_PARAM = -1,
```

```
    ERROR_MEMORY_ALLOC = -2,
```

```
    ERROR_IO_OPERATION = -3,
```

```

        ERROR_NETWORK_TIMEOUT = -4} result_code_t;

result_code_t initialize_system(system_config_t* config){

    if (config == NULL) {

        return ERROR_INVALID_PARAM;

    }

    // Initialization logic

    return SUCCESS;}

```

7. Preprocessor Directives

7.1 Macro Definitions

Parenthesize macro parameters and expressions.

c

```

// Good#define MAX(a, b) ((a) > (b) ? (a) : (b))#define ARRAY_
SIZE(arr) (sizeof(arr) / sizeof((arr)[0]))#define IS_VALID_POI
NTER(ptr) ((ptr) != NULL)

// Bad - missing parentheses#define MAX(a, b) a > b ? a : b#de
fine SQUARE(x) x * x // SQUARE(2+3) becomes 2+3*2+3 = 11, not
25

```

7.2 Conditional Compilation

Use `#if` for feature flags, avoid complex nested conditions.

c

```
// Good
#ifdef DEBUG

#define LOG_DEBUG(msg) printf("DEBUG: %s\n", msg)
#else

#define LOG_DEBUG(msg) // Nothing in release
#endif

#if VERSION_MAJOR > 2

#define USE_NEW_API 1
#else

#define USE_NEW_API 0
#endif

// Bad - complex nested conditions
#ifdef LINUX

#ifdef DEBUG

    #if VERSION > 2

        // Hard to follow

    #endif

#endif
#endif
```

8. Error Handling

8.1 Return Code Standards

Use consistent error reporting.

c

```
typedef enum {
```

```
FILE_OPERATION_SUCCESS = 0,
```

```
FILE_ERROR_NOT_FOUND = -1,
```

```
FILE_ERROR_PERMISSION_DENIED = -2,
```

```
FILE_ERROR_IO = -3,
```

```
FILE_ERROR_INVALID_FORMAT = -4} file_status_t;
```

```
file_status_t read_config_file(const char* filename, config_t*  
config){
```

```
    if (filename == NULL || config == NULL) {
```

```
        return FILE_ERROR_INVALID_PARAM;
```

```
    }
```

```
    FILE* file = fopen(filename, "r");
```

```
    if (file == NULL) {
```

```
        if (errno == ENOENT) {
```

```
            return FILE_ERROR_NOT_FOUND;
```

```
        } else if (errno == EACCES) {
```

```
            return FILE_ERROR_PERMISSION_DENIED;
```

```
        } else {
```

```
            return FILE_ERROR_IO;
```

```

    }

}

// Read file contents

fclose(file);

return FILE_OPERATION_SUCCESS;}

```

8.2 Error Reporting

Use consistent error logging.

```

c

#define LOG_ERROR(format, ...) \

    fprintf(stderr, "ERROR [%s:%d]: " format "\n", \

        __FILE__, __LINE__, ##__VA_ARGS__)

#define LOG_WARNING(format, ...) \

    fprintf(stderr, "WARNING [%s:%d]: " format "\n", \

        __FILE__, __LINE__, ##__VA_ARGS__)

result_code_t safe_memory_copy(void* dest, const void* src, si
ze_t size){

    if (dest == NULL || src == NULL) {

```

```

        LOG_ERROR("Invalid parameters for memory copy");

        return ERROR_INVALID_PARAM;

    }

    if (size == 0) {

        LOG_WARNING("Zero-size memory copy requested");

        return SUCCESS; // Nothing to do

    }

    memcpy(dest, src, size);

    return SUCCESS;}

```

9. Memory Management

9.1 Dynamic Allocation

Always check allocation results, pair alloc/free calls.

c

```

// Good
int* create_int_array(size_t size){

    if (size == 0) {

        return NULL;
    }
}

```

```

    }

    int* array = (int*)malloc(size * sizeof(int));

    if (array == NULL) {

        LOG_ERROR("Failed to allocate memory for %zu integers",
size);

        return NULL;

    }

    // Initialize array

    memset(array, 0, size * sizeof(int));

    return array;}

void cleanup_int_array(int** array){

    if (array != NULL && *array != NULL) {

        free(*array);

        *array = NULL; // Prevent dangling pointer

    }}

```

9.2 Pointer Usage

Use `const` appropriately, avoid pointer arithmetic when possible.

c

```
// Good - const correctnesssize_t string_length(const char* str) // Input won't be modified{
```

```
    if (str == NULL) {
```

```
        return 0;
```

```
    }
```

```
    const char* p = str; // Pointer to const data
```

```
    while (*p != '\\0') {
```

```
        p++;
```

```
    }
```

```
    return p - str;}
```

```
// Bad - unnecessary pointer arithmeticvoid dangerous_pointer_use(void){
```

```
    int array[10];
```

```
    int* p = array;
```

```
    // Hard to read and error-prone
```

```
    *(p + 5) = 100; // Instead use array[5] = 100;}
```


10. Security Guidelines

10.1 Buffer Management

Always check buffer bounds.

c

```
// Good - safe string copyresult_code_t safe_string_copy(char*  
dest, size_t dest_size, const char* src){
```

```
    if (dest == NULL || src == NULL || dest_size == 0) {
```

```
        return ERROR_INVALID_PARAM;
```

```
    }
```

```
    size_t src_len = strlen(src);
```

```
    if (src_len >= dest_size) {
```

```
        // Truncate but ensure null termination
```

```
        strncpy(dest, src, dest_size - 1);
```

```
        dest[dest_size - 1] = '\0';
```

```
        return ERROR_TRUNCATED;
```

```
    }
```

```
    strcpy(dest, src);
```

```

    return SUCCESS;}

// Bad - unsafe buffer operations
void unsafe_buffer_operation(
char* input){

    char buffer[64];

    strcpy(buffer, input); // Potential buffer overflow}

```

10.2 Input Validation

Validate all external inputs.

```

c

result_code_t validate_user_input(const user_input_t* input){

    if (input == NULL) {

        return ERROR_INVALID_PARAM;

    }

    // Validate string inputs

    if (input->username != NULL) {

        size_t username_len = strlen(input->username);

        if (username_len < MIN_USERNAME_LENGTH ||

            username_len > MAX_USERNAME_LENGTH) {

            return ERROR_INVALID_USERNAME;

```

```

    }

    // Check for valid characters

    if (!contains_only_alphanumeric(input->username)) {

        return ERROR_INVALID_CHARACTERS;

    }

}

// Validate numerical ranges

if (input->age < MIN_AGE || input->age > MAX_AGE) {

    return ERROR_INVALID_AGE;

}

return SUCCESS;}

```

12. Compiler Flags and Warnings

Recommended compiler flags for GCC/Clang:

makefile

```

CFLAGS = -Wall -Wextra -Wpedantic -Werror \

        -Wmissing-prototypes -Wstrict-prototypes \

```

`-Wold-style-definition -Wmissing-declarations \`

`-Wredundant-decls -Wnested-externs \`

`-Wpointer-arith -Wcast-qual -Wcast-align \`

`-Wwrite-strings -Wswitch-default \`

`-Wunreachable-code -Wundef -Wshadow \`

`-O2 -g -std=c99`

These C language coding standards ensure consistent, secure, and maintainable code across all C projects at eNoah, following the same professional structure as your PHP and Python standards documents.

QMS/SDM/UG/CODING STANDARDS-C