



Data Science Cheat Sheet

NumPy

KEY

We'll use shorthand in this cheat sheet

`arr` - A numpy Array object

IMPORTS

Import these to start

`import numpy as np`

IMPORTING/EXPORTING

`np.loadtxt('file.txt')` - From a text file

`np.genfromtxt('file.csv', delimiter=',')`
- From a CSV file

`np.savetxt('file.txt', arr, delimiter=' ')`
- Writes to a text file

`np.savetxt('file.csv', arr, delimiter=',')`
- Writes to a CSV file

CREATING ARRAYS

`np.array([1, 2, 3])` - One dimensional array

`np.array([(1, 2, 3), (4, 5, 6)])` - Two dimensional array

`np.zeros(3)` - 1D array of length 3 all values 0

`np.ones((3, 4))` - 3x4 array with all values 1

`np.eye(5)` - 5x5 array of 0 with 1 on diagonal (Identity matrix)

`np.linspace(0, 100, 6)` - Array of 6 evenly divided values from 0 to 100

`np.arange(0, 10, 3)` - Array of values from 0 to less than 10 with step 3 (eg [0, 3, 6, 9])

`np.full((2, 3), 8)` - 2x3 array with all values 8

`np.random.rand(4, 5)` - 4x5 array of random floats between 0-1

`np.random.rand(6, 7)*100` - 6x7 array of random floats between 0-100

`np.random.randint(5, size=(2, 3))` - 2x3 array with random ints between 0-4

INSPECTING PROPERTIES

`arr.size` - Returns number of elements in `arr`

`arr.shape` - Returns dimensions of `arr` (rows, columns)

`arr.dtype` - Returns type of elements in `arr`

`arr.astype(dtype)` - Convert `arr` elements to type `dtype`

`arr.tolist()` - Convert `arr` to a Python list

`np.info(np.eye)` - View documentation for `np.eye`

COPYING/SORTING/RESHAPING

`np.copy(arr)` - Copies `arr` to new memory

`arr.view(dtype)` - Creates view of `arr` elements with type `dtype`

`arr.sort()` - Sorts `arr`

`arr.sort(axis=0)` - Sorts specific axis of `arr`

`two_d_arr.flatten()` - Flattens 2D array `two_d_arr` to 1D

`arr.T` - Transposes `arr` (rows become columns and vice versa)

`arr.reshape(3, 4)` - Reshapes `arr` to 3 rows, 4 columns without changing data

`arr.resize((5, 6))` - Changes `arr` shape to 5x6 and fills new values with 0

ADDING/REMOVING ELEMENTS

`np.append(arr, values)` - Appends `values` to end of `arr`

`np.insert(arr, 2, values)` - Inserts `values` into `arr` before index 2

`np.delete(arr, 3, axis=0)` - Deletes row on index 3 of `arr`

`np.delete(arr, 4, axis=1)` - Deletes column on index 4 of `arr`

COMBINING/SPLITTING

`np.concatenate((arr1, arr2), axis=0)` - Adds `arr2` as rows to the end of `arr1`

`np.concatenate((arr1, arr2), axis=1)` - Adds `arr2` as columns to end of `arr1`

`np.split(arr, 3)` - Splits `arr` into 3 sub-arrays

`np.hsplit(arr, 5)` - Splits `arr` horizontally on the 5th index

INDEXING/SLICING/SUBSETTING

`arr[5]` - Returns the element at index 5

`arr[2, 5]` - Returns the 2D array element on index [2][5]

`arr[1]=4` - Assigns array element on index 1 the value 4

`arr[1, 3]=10` - Assigns array element on index [1][3] the value 10

`arr[0:3]` - Returns the elements at indices 0, 1, 2 (On a 2D array: returns rows 0, 1, 2)

`arr[0:3, 4]` - Returns the elements on rows 0, 1, 2 at column 4

`arr[:2]` - Returns the elements at indices 0, 1 (On a 2D array: returns rows 0, 1)

`arr[:, 1]` - Returns the elements at index 1 on all rows

`arr<5` - Returns an array with boolean values

`(arr1<3) & (arr2>5)` - Returns an array with boolean values

`~arr` - Inverts a boolean array

`arr[arr<5]` - Returns array elements smaller than 5

SCALAR MATH

`np.add(arr, 1)` - Add 1 to each array element

`np.subtract(arr, 2)` - Subtract 2 from each array element

`np.multiply(arr, 3)` - Multiply each array element by 3

`np.divide(arr, 4)` - Divide each array element by 4 (returns `np.nan` for division by zero)

`np.power(arr, 5)` - Raise each array element to the 5th power

VECTOR MATH

`np.add(arr1, arr2)` - Elementwise add `arr2` to `arr1`

`np.subtract(arr1, arr2)` - Elementwise subtract `arr2` from `arr1`

`np.multiply(arr1, arr2)` - Elementwise multiply `arr1` by `arr2`

`np.divide(arr1, arr2)` - Elementwise divide `arr1` by `arr2`

`np.power(arr1, arr2)` - Elementwise raise `arr1` raised to the power of `arr2`

`np.array_equal(arr1, arr2)` - Returns True if the arrays have the same elements and shape

`np.sqrt(arr)` - Square root of each element in the array

`np.sin(arr)` - Sine of each element in the array

`np.log(arr)` - Natural log of each element in the array

`np.abs(arr)` - Absolute value of each element in the array

`np.ceil(arr)` - Rounds up to the nearest int

`np.floor(arr)` - Rounds down to the nearest int

`np.round(arr)` - Rounds to the nearest int

STATISTICS

`np.mean(arr, axis=0)` - Returns mean along specific axis

`arr.sum()` - Returns sum of `arr`

`arr.min()` - Returns minimum value of `arr`

`arr.max(axis=0)` - Returns maximum value of specific axis

`np.var(arr)` - Returns the variance of array

`np.std(arr, axis=1)` - Returns the standard deviation of specific axis

`arr.corrcoef()` - Returns correlation coefficient of array