

Summarize Data

df['w'].value_counts()

Count number of rows with each unique value of variable

len(df)

of rows in DataFrame.

df['w'].nunique()

of distinct values in a column.

df.describe()

Basic descriptive statistics for each column (or GroupBy)



pandas provides a large set of **summary functions** that operate on different kinds of pandas objects (DataFrame columns, Series, GroupBy, Expanding and Rolling (see below)) and produce single values for each of the groups. When applied to a DataFrame, the result is returned as a pandas Series for each column. Examples:

sum()

Sum values of each object.

count()

Count non-NA/null values of each object.

median()

Median value of each object.

quantile([0.25,0.75])

Quantiles of each object.

apply(function)

Apply function to each object.

min()

Minimum value in each object.

max()

Maximum value in each object.

mean()

Mean value of each object.


var()

Variance of each object.

std()

Standard deviation of each object.

Group Data



df.groupby(by="col")

Return a GroupBy object, grouped by values in column named "col".

df.groupby(level="ind")

Return a GroupBy object, grouped by values in index level named "ind".

All of the summary functions listed above can be applied to a group. Additional GroupBy functions:

size()

Size of each group.

agg(function)

Aggregate group using function.

Windows

df.expanding()

Return an Expanding object allowing summary functions to be applied cumulatively.

df.rolling(n)

Return a Rolling object allowing summary functions to be applied to windows of length n.

Handling Missing Data

df.dropna()

Drop rows with any column having NA/null data.

df.fillna(value)

Replace all NA/null data with value.

Make New Columns



df.assign(Area=lambda df: df.Length*df.Height)

Compute and append one or more new columns.

df['Volume'] = df.Length*df.Height*df.Depth

Add single column.

pd.qcut(df.col, n, labels=False)

Bin column into n buckets.



pandas provides a large set of **vector functions** that operate on all columns of a DataFrame or a single selected column (a pandas Series). These functions produce vectors of values for each of the columns, or a single Series for the individual Series. Examples:

max(axis=1)

Element-wise max.

min(axis=1)

Element-wise min.

clip(lower=-10,upper=10) abs()

Trim values at input thresholds Absolute value.

The examples below can also be applied to groups. In this case, the function is applied on a per-group basis, and the returned vectors are of the length of the original DataFrame.

shift(1)

Copy with values shifted by 1.

rank(method='dense')

Ranks with no gaps.

rank(method='min')

Ranks. Ties get min rank.

rank(pct=True)

Ranks rescaled to interval [0, 1].

rank(method='first')

Ranks. Ties go to first value.

shift(-1)

Copy with values lagged by 1.

cumsum()

Cumulative sum.

cummax()

Cumulative max.

cummin()

Cumulative min.


cumprod()

Cumulative product.

Plotting


df.plot.hist()

Histogram for each column



df.plot.scatter(x='w',y='h')

Scatter chart using pairs of points



Combine Data Sets

adf		bdf		
x1	x2	x1	x3	
A	1	A	T	+
B	2	B	F	
C	3	D	T	
				=

Standard Joins

pd.merge(adf, bdf, how='left', on='x1')
Join matching rows from bdf to adf.

pd.merge(adf, bdf, how='right', on='x1')
Join matching rows from adf to bdf.

pd.merge(adf, bdf, how='inner', on='x1')
Join data. Retain only rows in both sets.

pd.merge(adf, bdf, how='outer', on='x1')
Join data. Retain all values, all rows.

Filtering Joins

adf[adf.x1.isin(bdf.x1)]
All rows in adf that have a match in bdf.

adf[~adf.x1.isin(bdf.x1)]
All rows in adf that do not have a match in bdf.

ydf		zdf		
x1	x2	x1	x2	
A	1	B	2	+
B	2	C	3	
C	3	D	4	
				=

Set-like Operations

pd.merge(ydf, zdf)
Rows that appear in both ydf and zdf (Intersection).

pd.merge(ydf, zdf, how='outer')
Rows that appear in either or both ydf and zdf (Union).

pd.merge(ydf, zdf, how='outer', indicator=True)
.query('_merge == "left_only"')
.drop(['_merge'],axis=1)
Rows that appear in ydf but not zdf (Setdiff).