


Data Visualization with ggplot2 Cheat Sheet




Basics

ggplot2 is based on the **grammar of graphics**, the idea that you can build every graph from the same few components: a **data** set, a set of **geoms**—visual marks that represent data points, and a **coordinate system**.



To display data values, map variables in the data set to aesthetic properties of the geom like **size**, **color**, and **x** and **y** locations.



Build a graph with **qplot()** or **ggplot()**

qplot(x = cty, y = hwy, color = cyl, data = mpg, geom = "point")
Creates a complete plot with given data, geom, and mappings. Supplies many useful defaults.

ggplot(data = mpg, aes(x = cty, y = hwy))

Begins a plot that you finish by adding layers to. No defaults, but provides more control than **qplot()**.

ggplot(mpg, aes(hwy, cty)) +
geom_point(aes(color = cyl)) +
geom_smooth(method = "lm") +
coord_cartesian() +
scale_color_gradient() +
theme_bw()

add layers, elements with +
layer = geom + default stat + layer specific mappings
additional elements

Add a new layer to a plot with a **geom_*()** or **stat_*()** function. Each provides a geom, a set of aesthetic mappings, and a default stat and position adjustment.

last_plot()
Returns the last plot

ggsave("plot.png", width = 5, height = 5)
Saves last plot as 5' x 5' file named "plot.png" in working directory. Matches file type to file extension.

Geoms - Use a geom to represent data points, use the geom's aesthetic properties to represent variables. Each function returns a layer.

One Variable

Continuous

a <- ggplot(mpg, aes(hwy))



a + geom_area(stat = "bin")
x, y, alpha, color, fill, linetype, size
b + geom_area(aes(y = ..density..), stat = "bin")



a + geom_density(kernel = "gaussian")
x, y, alpha, color, fill, linetype, size, weight
b + geom_density(aes(y = ..county..))



a + geom_dotplot()
x, y, alpha, color, fill



a + geom_freqpoly()
x, y, alpha, color, linetype, size
b + geom_freqpoly(aes(y = ..density..))



a + geom_histogram(binwidth = 5)
x, y, alpha, color, fill, linetype, size, weight
b + geom_histogram(aes(y = ..density..))

Discrete

b <- ggplot(mpg, aes(flr))



b + geom_bar()
x, alpha, color, fill, linetype, size, weight

Graphical Primitives

c <- ggplot(map, aes(long, lat))



c + geom_polygon(aes(group = group))
x, y, alpha, color, fill, linetype, size

d <- ggplot(economics, aes(date, unemploy))



d + geom_path(lineend = "butt", linejoin = "round", linemitre = 1)
x, y, alpha, color, linetype, size



d + geom_ribbon(aes(ymin = unemploy - 900, ymax = unemploy + 900))
x, ymax, ymin, alpha, color, fill, linetype, size

e <- ggplot(seals, aes(x = long, y = lat))



e + geom_segment(aes(xend = long + delta_long, yend = lat + delta_lat))
x, xend, y, yend, alpha, color, linetype, size



e + geom_rect(aes(xmin = long, ymin = lat, xmax = long + delta_long, ymax = lat + delta_lat))
xmax, xmin, ymax, ymin, alpha, color, fill, linetype, size

Two Variables

Continuous X, Continuous Y

f <- ggplot(mpg, aes(cty, hwy))



f + geom_blank()



f + geom_jitter()
x, y, alpha, color, fill, shape, size



f + geom_point()
x, y, alpha, color, fill, shape, size



f + geom_quantile()
x, y, alpha, color, linetype, size, weight



f + geom_rug(sides = "bl")
alpha, color, linetype, size



f + geom_smooth(model = lm)
x, y, alpha, color, fill, linetype, size, weight



f + geom_text(aes(label = cty))
x, y, label, alpha, angle, color, family, fontface, hjust, lineheight, size, vjust

Discrete X, Continuous Y

g <- ggplot(mpg, aes(class, hwy))



g + geom_bar(stat = "identity")
x, y, alpha, color, fill, linetype, size, weight



g + geom_boxplot()
lower, middle, upper, x, ymax, ymin, alpha, color, fill, linetype, shape, size, weight



g + geom_dotplot(binaxis = "y", stackdir = "center")
x, y, alpha, color, fill



g + geom_violin(scale = "area")
x, y, alpha, color, fill, linetype, size, weight

Discrete X, Discrete Y

h <- ggplot(diamonds, aes(cut, color))



h + geom_jitter()
x, y, alpha, color, fill, shape, size

Continuous Bivariate Distribution

i <- ggplot(movies, aes(year, rating))



i + geom_bin2d(binwidth = c(5, 0.5))
xmax, xmin, ymax, ymin, alpha, color, fill, linetype, size, weight



i + geom_density2d()
x, y, alpha, colour, linetype, size



i + geom_hex()
x, y, alpha, colour, fill, size

Continuous Function

j <- ggplot(economics, aes(date, unemploy))



j + geom_area()
x, y, alpha, color, fill, linetype, size



j + geom_line()
x, y, alpha, color, linetype, size



j + geom_step(direction = "hv")
x, y, alpha, color, linetype, size

Visualizing error

df <- data.frame(grp = c("A", "B"), fit = 4:5, se = 1:2)
k <- ggplot(df, aes(grp, fit, ymin = fit-se, ymax = fit+se))



k + geom_crossbar(fatten = 2)
x, y, ymax, ymin, alpha, color, fill, linetype, size



k + geom_errorbar()
x, ymax, ymin, alpha, color, linetype, size, width (also **geom_errorbarh()**)



k + geom_linerange()
x, ymin, ymax, alpha, color, linetype, size



k + geom_pointrange()
x, y, ymin, ymax, alpha, color, fill, linetype, size

Maps

data <- data.frame(murder = USArrests\$Murder, state = tolower(rownames(USArrests)))
map <- map_data("state")
l <- ggplot(data, aes(fill = murder))



l + geom_map(aes(map_id = state, map = map) +
expand_limits(x = map\$long, y = map\$lat)
map_id, alpha, color, fill, linetype, size

Three Variables

sealsSz <- with(seals, sqrt(delta_long^2 + delta_lat^2))
m <- ggplot(seals, aes(long, lat))



m + geom_raster(aes(fill = z), hjust = 0.5, vjust = 0.5, interpolate = FALSE)
x, y, alpha, fill



m + geom_contour(aes(z = z))
x, y, z, alpha, colour, linetype, size, weight



m + geom_tile(aes(fill = z))
x, y, alpha, color, fill, linetype, size