Achieving 100% Throughput in an Input-Queued Switch

Haricharan

IITM

Jan 31, 2024

Problem Statement

- Discrete Time
- ullet Consider M input switches, each with some Bernoulli arrival rate λ_i
- ullet Each packet has a destination output (N)
- FIFO is not obeyed in an input queue!
- Given rates λ_{ij} , best way to route flow?

Virtual Output Queues

- ullet We construct N VOQs (Virtual Output Queues) at each input queue
- We can, of course, know the length of each of the queues
- As long as we're guaranteed $\sum_i \lambda_{ij} < 1$ and $\sum_j \lambda_{ij} < 1$, we can achieve 100% throughput!
- We have to find a graph matching at each timestep

Inefficient Algorithms

- Constructing the maximum size matching doesn't work and routing flow as per that doesn't work!
- Among maximum size matchings, even if we pick one at random each time, that also doesn't work!




Figure 1: Alt text

Efficient Algorithms

Both achieve 100% throughput

LQF: Longest Queue First

- ullet Weight the edges by L_{ij} (Length of jth VOQ at ith input)
- Find max weight matching in this
- (Can lead to starvation: not getting rid of initial conditions)

OCF: Oldest Cell First

- ullet Weight the edges by W_{ij} (Waiting time of head of jth VOQ at ith input)
- Find max weight matching in this

MAB Version?

- Input as unknowns (not practical, as we can measure it anyways)
- ullet Try to solve a weighted version, with regrets like (for instance) $R(t) = \sum_{ij} E[c_{ij}L_{ij}]$
- This can be interpreted as "power" in some sense:

Dynamic Power Allocation and Routing for Time Varying Wireless Networks

Michael J. Neely http://web.mit.edu/mjneely/www MIT—LIDS: mjneely@mit.edu Eytan Modiano http://web.mit.edu/modiano/www MIT—LIDS: modiano@mit.edu Charles E. Rohrs MIT—LIDS crohrs@mit.edu

(Again Lyapunov drift calculation is used)

Other ideas:

• MAB on Erasure channel with unknown erasure rates (idea of "min-cuts")

Capacity of Wireless Erasure Networks

Amir F. Dana, Student Member, IEEE, Radhika Gowaikar, Student Member, IEEE, Ravi Palanki, Babak Hassibi, and Michelle Effros, Senior Member, IEEE

Simple Deletion Channel