

WEEK 14

Problem Statement:

You are transporting some boxes through a tunnel, where each box is a parallelepiped, and is characterized by its length, width and height.

The height of the tunnel 41 feet and the width can be assumed to be infinite. A box can be carried through the tunnel only if its height is strictly less than the tunnel's height. Find the volume of each box that can be successfully transported to the other end of the tunnel.

Note: Boxes cannot be rotated.

Input Format

The first line contains a single integer n , denoting the number of boxes.

n lines follow with three integers on each separated by single spaces - length_i , width_i and height_i which are length, width and height in feet of the i -th box.

Constraints

$$1 \leq n \leq 100$$

$$1 \leq \text{length}_i, \text{width}_i, \text{height}_i \leq 100$$

Output Format

For every box from the input which has a height lesser than 41 feet, print its volume in a separate line.

Sample Input

```
4
5 5 5
1 2 40
10 5 41
7 2 42
```

Sample Output

```
125
80
```

Explanation

The first box is really low, only 5 feet tall, so it can pass through the tunnel and its volume is $5 \times 5 \times 5 = 125$.

The second box is sufficiently low, its volume is $1 \times 2 \times 4 = 80$.

The third box is exactly 41 feet tall, so it cannot pass. The same can be said about the fourth box.

Program

REC-CIS

Week-14-Structures and Unions: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=156218&cmid=405

REC-CIS

```
1 #include<stdio.h>
2 struct box{
3     int l,w,h;
4 };
5 int main(){
6     int n;
7     scanf("%d",&n);
8     struct box arr[n];
9     for(int i=0;i<n;i++){
10         scanf("%d %d %d",&arr[i].l,&arr[i].w,&arr[i].h);
11     }
12     for(int i=0;i<n;i++){
13         if(arr[i].h<41){
14             printf("%d\n",arr[i].l*arr[i].w*arr[i].h);
15         }
16     }
17     return 0;
18 }
```

Output

	Input	Expected	Got	
✓	4	125	125	✓
	5 5 5	80	80	
	1 2 40			
	10 5 41			
	7 2 42			

Passed all tests! ✓

Problem Statement:

You are given n triangles, specifically, their sides a_i , b_i and c_i . Print them in the same style but sorted by their areas from the smallest one to the largest one. It is guaranteed that all the areas are different.

The best way to calculate a volume of the triangle with sides a , b and c is Heron's formula:

$$S = \sqrt{p * (p - a) * (p - b) * (p - c)} \text{ where } p = (a + b + c) / 2.$$

Input Format

First line of each test file contains single integer n . n lines follow with a_i , b_i and c_i on each separated by single spaces.

Constraints

$$1 \leq n \leq 100$$

$$1 \leq a_i, b_i, c_i \leq 70$$

$$a_i + b_i > c_i, a_i + c_i > b_i \text{ and } b_i + c_i > a_i$$

Output Format

Print exactly n lines. On each line print 3 integers separated by single spaces, which are a_i , b_i and c_i of the corresponding triangle.

Sample Input

```
3
7 24 25
5 12 13
3 4 5
```

Sample Output

```
3 4 5
5 12 13
7 24 25
```

Explanation

The square of the first triangle is 84. The square of the second triangle is 30. The square of the third triangle is 6. So, the sorted order is the reverse one.

Program

Click to go back, hold to see history

HARIHARAN N 2024-CSBS H2

Week-14-Structures and Unions: Attempt review | REC-CIS - Google Chrome

Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=156218&cmid=405

REC-CIS

```
1 //C program to find area of triangle
2
3 struct sides{
4     int a,b,c;
5 };
6 int vol(int a,int b,int c){
7     float p=(a+b+c)/2;
8     return sqrt(p*(p-a)*(p-b)*(p-c));
9 }
10
11 int main(){
12     int n;
13     scanf("%d",&n);
14     struct sides s[n];
15     for(int i=0;i<n;i++){
16         scanf("%d %d %d",&s[i].a,&s[i].b,&s[i].c);
17     }
18     for(int i=0;i<n;i++){
19         for(int j=i;j<n;j++){
20             if(i!=j){
21                 if(vol(s[i].a,s[i].b,s[i].c)>vol(s[j].a,s[j].b,s[j].c)){
22                     struct sides temp=s[j];
23                     s[j]=s[i];
24                     s[i]=temp;
25                 }
26             }
27         }
28     }
29     for(int i=0;i<n;i++){
30         printf("%d %d %d\n",s[i].a,s[i].b,s[i].c);
31     }
32     return 0;
33 }
```

Output

	Input	Expected	Got	
✓	3	3 4 5	3 4 5	✓
	7 24 25	5 12 13	5 12 13	
	5 12 13	7 24 25	7 24 25	
	3 4 5			

Passed all tests! ✓